Agilent HDSP-301x/303x Series
HDSP-561x/563x Series
10 mm and 13 mm Slim Font Seven Segment Displays

Data Sheet



Description

These slim font seven segment displays incorporate a new slim font character design. This slim font features narrow width, specially mitered segments to give a fuller appearance to the illuminated character. Faces of these displays are painted a neutral gray for enhanced on/off contrast.

All devices are available in either common anode or common cathode configuration with right hand decimal point.

Features


- **Excellent appearance**
- **Slim font design**
- **Mitered corners, evenly illuminated segments**
- **Gray face for optimum on/off contrast**
- **Choice of colors: HER, green, yellow, and AlGaAs**
- **Choice of character size: 10 mm and 13 mm**
- **Characterized for luminous intensity**

Devices

HER HDSP-	Green HDSP-	Yellow HDSP-	AlGaAs HDSP-	Description
301E	301G	301Y	301A	Common Anode, 10 mm Display
303E	303G	303Y	303A	Common Cathode, 10 mm Display
561E	561G	561Y	561A	Common Anode, 13 mm Display
563E	563G	563Y	563A	Common Cathode, 13 mm Display


Part Numbering System

5082 - x xx x - x x x xx
HDSP - x xx x - x x x xx




Notes:

1. For codes not listed in the figure above, please refer to the respective data sheet or contact your nearest Agilent representative for details.
2. Bin options refer to shippable bins for a part-number. Color and Intensity Binbs are typically restricted to 1 bin per tube (exceptions may apply). Please refer to respective data sheet for specific bin limit information.



NOTE: QDSP-399G DOES NOT HAVE PIN 6.

Pin	Function
1	G
2	F
3	Common A/C
4	E
5	D
6	DP
7	C
8	Common A/C
9	B
10	A



NOTES:
1. ALL DIMENSIONS ARE IN MILLIMETERS (INCHES).
2. UNLESS OTHERWISE STATED, TOLERANCES ARE ±0.25 mm.

Pin	Function
1	E
2	D
3	Common A/C
4	C
5	DP
6	B
7	A
8	Common A/C
9	F
10	G

Absolute Maximum Ratings

Description	HER	Green	Yellow	AlGaAs	Units
Average Power per Segment or DP	105	105	105	37	mW
Peak Forward Current per Segment or DP	90	90	90	45	mA
DC Forward Current per Segment or DP	30	30	30	15	mA
Operating Temperature Range	–40 to +80	–40 to +80	–40 to +80	–20 to +80	°C
Storage Temperature Range	–40 to +80	–40 to +80	–40 to +80	–40 to +80	°C
Reverse Voltage per Segment or DP	5	5	5	5	V
Wavesoldering Temperature for 3 Seconds 1.59 mm below body	250	250	250	250	°C

Notes:
1. Derate above 33°C at 0.34 mA/°C for HER.
2. Derate above 27°C at 0.32 mA/°C for Green.
3. Derate above 30°C at 0.33 mA/°C for Yellow.
4. Derate above 60°C at 0.25 mA/°C for AlGaAs.

Electrical/Optical Characteristics at T_A = 25°C

HER

Device Series HDSP-	Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
301/303E	Luminous Intensity/Segment (Digit Average)	I_V	1.251	2.000		mcd	I_F = 10 mA
	Forward Voltage/Segment or DP	V_F		1.90	2.50	V	I_F = 20 mA
	Peak Wavelength	λ_{PEAK}		635		nm	I_F = 20 mA
	Dominant Wavelength	λ_d		625		nm	I_F = 20 mA
	Reverse Current	I_R			100	µA	V_R = 5 V
	Thermal Resistance LED Junction-to-Pin	$R\theta_{J-PIN}$		351.5		°C/W/Seg.	

HER

Device Series HDSP-	Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
561/563E	Luminous Intensity/Segment (Digit Average)	I_V	2.001	3.526		mcd	I_F = 10 mA
	Forward Voltage/Segment or DP	V_F		1.90	2.50	V	I_F = 20 mA
	Peak Wavelength	λ_{PEAK}		635		nm	I_F = 20 mA
	Dominant Wavelength	λ_d		625		nm	I_F = 20 mA
	Reverse Current	I_R			100	µA	V_R = 5 V
	Thermal Resistance LED Junction-to-Pin	$R\theta_{J-PIN}$		351.5		°C/W/Seg.	

Green

Device Series HDSP-	Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
301/303G	Luminous Intensity/Segment (digit average)	I_V	2.001	3.200		mcd	I_F = 10 mA
	Forward Voltage/Segment or DP	V_F		2.25	2.50	V	I_F = 20 mA
	Peak Wavelength	λ_{PEAK}		568		nm	I_F = 20 mA
	Dominant Wavelength	λ_d		573		nm	I_F = 20 mA
	Reverse Current	I_R			100	μA	V_R = 5 V
	Thermal Resistance LED Junction-to-Pin	$R\theta_{J-PIN}$		351.5		°C/W/Seg.	

Green

Device Series HDSP-	Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
561/563G	Luminous Intensity/Segment (Digit Average)	I_V	3.201	5.601		mcd	I_F = 10 mA
	Forward Voltage/Segment or DP	V_F		2.25	2.50	V	I_F = 20 mA
	Peak Wavelength	λ_{PEAK}		568		nm	I_F = 20 mA
	Dominant Wavelength	λ_d		573		nm	I_F = 20 mA
	Reverse Current	I_R			100	μA	V_R = 5 V
	Thermal Resistance LED Junction-to-Pin	$R\theta_{J-PIN}$		351.5		°C/W/Seg.	

Yellow

Device Series HDSP-	Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
301/303Y	Luminous Intensity/Segment (Digit Average)	I_V	1.251	2.000		mcd	I_F = 10 mA
	Forward Voltage/Segment or DP	V_F		2.15	2.50	V	I_F = 20 mA
	Peak Wavelength	λ_{PEAK}		589		nm	I_F = 20 mA
	Dominant Wavelength	λ_d		590		nm	I_F = 20 mA
	Reverse Current	I_R			100	μA	V_R = 5 V
	Thermal Resistance LED Junction-to-Pin	$R\theta_{J-PIN}$		351.5		°C/W/Seg.	

Yellow

Device Series HDSP-	Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
561/563Y	Luminous Intensity/Segment (Digit Average)	I_V	2.00	3.526		mcd	I_F = 10 mA
	Forward Voltage/Segment or DP	V_F		2.15	2.50	V	I_F = 20 mA
	Peak Wavelength	λ_{PEAK}		589		nm	I_F = 20 mA
	Dominant Wavelength	λ_d		590		nm	I_F = 20 mA
	Reverse Current	I_R			100	µA	V_R = 5 V
	Thermal Resistance LED Junction-to-Pin	$R\theta_{J-PIN}$		351.5		°C/W/Seg.	

Notes:
1. Typical specification for reference only. Do not exceed absolute maximum ratings.
2. The dominant wavelength, λ, is derived from the CIE chromaticity diagram and is that single wavelength which defines the color of the device.

AlGaAs

Device Series HDSP-	Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
301/303A	Luminous Intensity/Segment (Digit Average)	I_V	0.320	0.505		mcd	I_F = 1 mA
	Forward Voltage/Segment or DP	V_F		1.80	2.20	V	I_F = 20 mA
	Peak Wavelength	λ_{PEAK}		660		nm	I_F = 20 mA
	Dominant Wavelength	λ_d		643		nm	I_F = 20 mA
	Reverse Current	I_R			100	µA	V_R = 5 V
	Thermal Resistance LED Junction-to-Pin	$R\theta_{J-PIN}$		351.5		°C/W/Seg.	

AlGaAs

Device Series HDSP-	Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
561/563A	Luminous Intensity/Segment (Digit Average)	I_V	0.506	0.878		mcd	I_F = 1 mA
	Forward Voltage/Segment or DP	V_F		1.80	2.20	V	I_F = 20 mA
	Peak Wavelength	λ_{PEAK}		660		nm	I_F = 20 mA
	Dominant Wavelength	λ_d		643		nm	I_F = 20 mA
	Reverse Current	I_R			100	µA	V_R = 5 V
	Thermal Resistance LED Junction-to-Pin	$R\theta_{J-PIN}$		351.5		°C/W/Seg.	

Notes:
1. Typical specification for reference only. Do not exceed absolute maximum ratings.
2. The dominant wavelength, λ, is derived from the CIE chromaticity diagram and is that single wavelength which defines the color of the device.

Intensity Bin Limits (mcd)

Green

HDSP-301G/303G/561G/563G		
IV Bin Category	**Min.**	**Max.**
K	1.800	3.600
L	2.800	5.600

Yellow

HDSP-301Y/303Y		
IV Bin Category	**Min.**	**Max.**
I	1.100	2.200
K	1.800	3.600

Yellow

HDSP-561Y/563Y		
IV Bin Category	**Min.**	**Max.**
K	1.800	3.600
L	2.800	5.600

HER

HDSP-301E/303E/561E/563E		
IV Bin Category	**Min.**	**Max.**
I	1.100	2.200
K	1.800	3.600

AlGaAs Red

HDSP-301A/303A/561A/563A		
IV Bin Category	**Min.**	**Max.**
F	0.280	0.560
G	0.450	0.900

Color Categories

		Dominant Wavelength (nm)	
Color	**Bin**	**Min.**	**Max.**
Green	3	570.00	574.50
	4	567.00	571.50
Yellow	2	586.50	590.00
	3	584.00	587.50

Note:

1. All categories are established for classification of products. Products may not be available in all categories. Please contact your Agilent representatives for further clarification/information.

HDSP-301x/303x Series




Figure 1. Maximum allowable DC current vs. ambient temperature.




Figure 2. Forward current vs. forward voltage.




Figure 3. Relative luminous intensity vs. DC forward current.

HDSP-561x/563x Series




Figure 4. Maximum allowable DC current vs. ambient temperature.




Figure 5. Forward current vs. forward voltage.




Figure 6. Relative luminous intensity vs. DC forward current.

Contrast Enhancement

For information on contrast enhancement, please see Application Note 1015.

Soldering/Cleaning

Cleaning agents from the ketone family (acetone, methyl ethyl ketone, etc.) and from the chlorinated hydrocarbon family (methylene chloride, trichloroethylene, carbon tetrachloride, etc.) are not recommended for cleaning LED parts. All of these various solvents attack or dissolve the encapsulating epoxies used to form the package of plastic LED parts.

For information on soldering LEDs, please refer to Application Note 1027.

www.agilent.com/semiconductors

For product information and a complete list of distributors, please go to our web site.

For technical assistance call:

Americas/Canada: +1 (800) 235-0312 or (916) 788-6763

Europe: +49 (0) 6441 92460

China: 10800 650 0017

Hong Kong: (+65) 6756 2394

India, Australia, New Zealand: (+65) 6755 1939

Japan: (+81 3) 3335-8152(Domestic/ International), or 0120-61-1280(Domestic Only)

Korea: (+65) 6755 1989

Singapore, Malaysia, Vietnam, Thailand, Philippines, Indonesia: (+65) 6755 2044

Taiwan: (+65) 6755 1843

Data subject to change.

Obsoletes 5980-2919EN
July 11, 2004
5988-4352EN



Agilent Technologies


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.