


Optocoupler, Phototransistor Output (Dual, Quad Channel)


Dual Channel



Quad Channel



H79054



FEATURES

- Alternate source to TLP621-2/-4 and TLP621GB-2/-4
- High collector emitter voltage, $BV_{CEO} = 70\text{ V}$
- Dual and quad packages feature:
 - Lower pin and parts count
 - Better channel to channel CTR match
 - Improved common mode rejection
- Isolation test voltage, 5300 V_{RMS}
- Lead (Pb)-free component
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



RoHS
COMPLIANT

AGENCY APPROVALS

- UL1577, file no. E52744 system code H or J, double protection
- DIN EN 60747-5-2 (VDE 0884)/DIN EN 60747-5-5 pending available with option 1
- BSI IEC 60950; IEC 60065
- FIMKO

DESCRIPTION

The ILD621/ILQ621 and ILD621GB/ILQ621GB are multi-channel phototransistor optocouplers that use GaAs IRLED emitters and high gain NPN silicon phototransistors. These devices are constructed using double molded insulation technology. This assembly process offers a withstand test voltage of 7500 VDC.

The ILD621/ILQ621GB is well suited for CMOS interfacing given the CTR_{CEsat} of 30 % minimum at I_F of 1.0 mA. High gain linear operation is guaranteed by a minimum CTR_{CE} of 100 % at 5.0 mA. The ILD/Q621 has a guaranteed CTR_{CE} 50 % minimum at 5.0 mA. The transparent ion shield insures stable DC gain in applications such as power supply feedback circuits, where constant DC V_{IO} voltages are present.

ORDER INFORMATION

| PART | REMARKS |
|-------------|---------------------------------|
| ILD621 | CTR > 50 %, dual, DIP-8 |
| ILD621GB | CTR > 100 %, dual, DIP-8 |
| ILQ621 | CTR > 50 %, quad, DIP-16 |
| ILQ621GB | CTR > 100 %, quad, DIP-16 |
| ILD621-X006 | CTR > 50 %, dual, DIP-8 400 mil |

ILD621/ILD621GB/ILQ621/ILQ621GB



Vishay Semiconductors

Optocoupler, Phototransistor Output
(Dual, Quad Channel)

| ORDER INFORMATION | |
|-------------------|--------------------------------------|
| PART | REMARKS |
| ILD621-X007 | CTR > 50 %, dual, SMD-8 (option 7) |
| ILD621-X009 | CTR > 50 %, dual, SMD-8 (option 9) |
| ILD621GB-X007 | CTR > 100 %, dual, SMD-8 (option 7) |
| ILQ621-X006 | CTR > 50 %, quad, DIP-16 400 mil |
| ILQ621-X007 | CTR > 50 %, quad, SMD-16 (option 7) |
| ILQ621-X009 | CTR > 50 %, quad, SMD-16 (option 9) |
| ILQ621GB-X006 | CTR > 100 %, quad, DIP-16 400 mil |
| ILQ621GB-X007 | CTR > 100 %, quad, SMD-16 (option 7) |
| ILQ621GB-X009 | CTR > 100 %, quad, SMD-16 (option 9) |

Note

For additional information on the available options refer to option information.

| ABSOLUTE MAXIMUM RATINGS (1) | | | | | |
|-----------------------------------|--------------------------------------|----------|------------|----------------|-----------|
| PARAMETER | TEST CONDITION | PART | SYMBOL | VALUE | UNIT |
| INPUT | | | | | |
| Reverse voltage | | | V_R | 6.0 | V |
| Forward current | | | I_F | 60 | mA |
| Surge current | | | I_{FSM} | 1.5 | A |
| Power dissipation | | | P_{diss} | 100 | mW |
| Derate from 25 °C | | | | 1.33 | mW/°C |
| OUTPUT | | | | | |
| Collector emitter reverse voltage | | | V_{ECO} | 70 | V |
| Collector current | | | I_C | 50 | mA |
| | $t < 1.0$ ms | | I_C | 100 | mA |
| Power dissipation | | | P_{diss} | 150 | mW |
| Derate from 25 °C | | | | - 2.0 | mW/°C |
| COUPLER | | | | | |
| Isolation test voltage | $t = 1.0$ s | | V_{ISO} | 5300 | V_{RMS} |
| Package dissipation | | ILD621 | | 400 | mW |
| | | ILD621GB | | 400 | mW |
| Derate from 25 °C | | | | 5.33 | mW/°C |
| Package dissipation | | ILQ621 | | 500 | mW |
| | | ILQ621GB | | 500 | mW |
| Derate from 25 °C | | | | 6.67 | mW/°C |
| Creepage distance | | | | ≥ 7.0 | mm |
| Clearance distance | | | | ≥ 7.0 | mm |
| Isolation resistance | $V_{IO} = 500$ V, $T_{amb} = 25$ °C | | R_{IO} | $\geq 10^{12}$ | Ω |
| | $V_{IO} = 500$ V, $T_{amb} = 100$ °C | | R_{IO} | $\geq 10^{11}$ | Ω |
| Storage temperature | | | T_{stg} | - 55 to + 150 | °C |
| Operating temperature | | | T_{amb} | - 55 to + 100 | °C |
| Junction temperature | | | T_j | 100 | °C |
| Soldering temperature (2) | 2.0 mm from case bottom | | T_{sld} | 260 | °C |

Notes

(1) $T_{amb} = 25$ °C, unless otherwise specified.

Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.

(2) Refer to reflow profile for soldering conditions for surface mounted devices (SMD). Refer to wave profile for soldering conditions for through hole devices (DIP).



ILD621/ILD621GB/ILQ621/ILQ621GB

Optocoupler, Phototransistor Output Vishay Semiconductors
(Dual, Quad Channel)

| ELECTRICAL CHARACTERISTICS | | | | | | | |
|--------------------------------------|-------------------------------------------------|----------|-------------|-----------|------|------|---------------|
| PARAMETER | TEST CONDITION | PART | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| INPUT | | | | | | | |
| Forward voltage | $I_F = 10 \text{ mA}$ | | V_F | 1.0 | 1.15 | 1.3 | V |
| Reverse current | $V_R = 6.0 \text{ V}$ | | I_R | | 0.01 | 10 | μA |
| Capacitance | $V_R = 0 \text{ V}, f = 1.0 \text{ MHz}$ | | C_O | | 40 | | pF |
| Thermal resistance, junction to lead | | | R_{THJL} | | 750 | | K/W |
| OUTPUT | | | | | | | |
| Collector emitter capacitance | $V_{CE} = 5.0 \text{ V}, f = 1.0 \text{ MHz}$ | | C_{CE} | | 6.8 | | pF |
| Collector emitter leakage current | $V_{CE} = 24 \text{ V}$ | | I_{CEO} | | 10 | 100 | nA |
| | | | I_{CEO} | | 20 | 50 | μA |
| Thermal resistance, junction to lead | | | R_{THJL} | | 500 | | K/W |
| COUPLER | | | | | | | |
| Capacitance (input to output) | $V_{IO} = 0 \text{ V}, f = 1.0 \text{ MHz}$ | | C_{IO} | 0.8 | | | pF |
| Insulation resistance | $V_{IO} = 500 \text{ V}$ | | | 10^{12} | | | Ω |
| Channel to channel insulation | | | | 500 | | | VAC |
| Collector emitter saturation voltage | $I_F = 8.0 \text{ mA}, I_{CE} = 2.4 \text{ mA}$ | ILD621 | V_{CEsat} | | | 0.4 | V |
| | | ILQ621 | | | | | |
| Collector emitter saturation voltage | $I_F = 1.0 \text{ mA}, I_{CE} = 0.2 \text{ mA}$ | ILD621GB | V_{CEsat} | | | 0.4 | V |
| | | ILQ621GB | | | | | |

Note

$T_{amb} = 25 \text{ }^\circ\text{C}$, unless otherwise specified.

Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements.

| CURRENT TRANSFER RATIO | | | | | | | |
|------------------------------------------------------|------------------------------------------------|----------|----------------------------------------|--------|------|--------|------|
| PARAMETER | TEST CONDITION | PART | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Channel/channel CTR match | $I_F = 5.0 \text{ mA}, V_{CE} = 5.0 \text{ V}$ | | CTR _X / CTR _Y | 1 to 1 | | 3 to 1 | % |
| Current transfer ratio (collector emitter saturated) | $I_F = 1.0 \text{ mA}, V_{CE} = 0.4 \text{ V}$ | ILD621 | CTR _{CEsat} | | 60 | | % |
| | | ILQ621 | CTR _{CEsat} | | 60 | | % |
| | | ILD621GB | CTR _{CEsat} | 30 | | | % |
| | | ILQ621GB | CTR _{CEsat} | 30 | | | % |
| Current transfer ratio (collector emitter) | $I_F = 5.0 \text{ mA}, V_{CE} = 5.0 \text{ V}$ | ILD621 | CTR _{CE} | 50 | 80 | 600 | % |
| | | ILQ621 | CTR _{CE} | 50 | 80 | 600 | % |
| | | ILD621GB | CTR _{CE} | 100 | 200 | 600 | % |
| | | ILQ621GB | CTR _{CE} | 100 | 200 | 600 | % |

| SWITCHING CHARACTERISTICS | | | | | | | |
|---------------------------|----------------------------------------------------------------------------------------------|-----------|------|------|------|---------------|--|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT | |
| NON-SATURATED | | | | | | | |
| On time | $I_F = \pm 10 \text{ mA}, V_{CC} = 5.0 \text{ V}, R_L = 75 \Omega, 50 \% \text{ of } V_{PP}$ | t_{on} | | 3.0 | | μs | |
| Rise time | $I_F = \pm 10 \text{ mA}, V_{CC} = 5.0 \text{ V}, R_L = 75 \Omega, 50 \% \text{ of } V_{PP}$ | t_r | | 2.0 | | μs | |
| Off time | $I_F = \pm 10 \text{ mA}, V_{CC} = 5.0 \text{ V}, R_L = 75 \Omega, 50 \% \text{ of } V_{PP}$ | t_{off} | | 2.3 | | μs | |
| Fall time | $I_F = \pm 10 \text{ mA}, V_{CC} = 5.0 \text{ V}, R_L = 75 \Omega, 50 \% \text{ of } V_{PP}$ | t_f | | 2.0 | | μs | |
| Propagation H to L | $I_F = \pm 10 \text{ mA}, V_{CC} = 5.0 \text{ V}, R_L = 75 \Omega, 50 \% \text{ of } V_{PP}$ | t_{PHL} | | 1.1 | | μs | |
| Propagation L to H | $I_F = \pm 10 \text{ mA}, V_{CC} = 5.0 \text{ V}, R_L = 75 \Omega, 50 \% \text{ of } V_{PP}$ | t_{PLH} | | 2.5 | | μs | |

| SWITCHING CHARACTERISTICS | | | | | | |
|---------------------------|-------------------------------------------------------------------------------------------------------------|-----------|------|------|------|---------------|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| SATURATED | | | | | | |
| On time | $I_F = \pm 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 1 \text{ k}\Omega$, $V_{TH} = 1.5 \text{ V}$ | t_{on} | | 4.3 | | μs |
| Rise time | $I_F = \pm 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 1 \text{ k}\Omega$, $V_{TH} = 1.5 \text{ V}$ | t_r | | 2.8 | | μs |
| Off time | $I_F = \pm 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 1 \text{ k}\Omega$, $V_{TH} = 1.5 \text{ V}$ | t_{off} | | 2.5 | | μs |
| Fall time | $I_F = \pm 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 1 \text{ k}\Omega$, $V_{TH} = 1.5 \text{ V}$ | t_f | | 11 | | μs |
| Propagation H to L | $I_F = \pm 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 1 \text{ k}\Omega$, $V_{TH} = 1.5 \text{ V}$ | t_{PHL} | | 2.6 | | μs |
| Propagation L to H | $I_F = \pm 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 1 \text{ k}\Omega$, $V_{TH} = 1.5 \text{ V}$ | t_{PLH} | | 7.2 | | μs |

| COMMON MODE TRANSIENT IMMUNITY | | | | | | |
|------------------------------------|-------------------------------------------------------------------------------------|--------|------|------|------|------------------------|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Common mode rejection, output high | $V_{CM} = 50 \text{ V}_{P-P}$, $R_L = 1.0 \text{ k}\Omega$, $I_F = 0 \text{ mA}$ | CM_H | | 5000 | | $\text{V}/\mu\text{s}$ |
| Common mode rejection, output low | $V_{CM} = 50 \text{ V}_{P-P}$, $R_L = 1.0 \text{ k}\Omega$, $I_F = 10 \text{ mA}$ | CM_L | | 5000 | | $\text{V}/\mu\text{s}$ |

TYPICAL CHARACTERISTICS

$T_{amb} = 25 \text{ }^\circ\text{C}$, unless otherwise specified



Fig. 1 - Non-Saturated Switching Timing




Fig. 3 - Saturated Switching Timing



Fig. 2 - Non-Saturated Switching Timing



Fig. 4 - Saturated Switching Timing



ILD621/ILD621GB/ILQ621/ILQ621GB

Optocoupler, Phototransistor Output
(Dual, Quad Channel)

Vishay Semiconductors



Fig. 5 - Maximum LED Current vs. Ambient Temperature



Fig. 8 - Collector Emitter Current vs. Temperature and LED Current



Fig. 6 - Maximum LED Power Dissipation



Fig. 9 - Collector Emitter Leakage vs. Temperature



Fig. 7 - Forward Voltage vs. Forward Current



Fig. 10 - Propagation Delay vs. Collector Load Resistor



Fig. 11 - Maximum Detector Power Dissipation




Fig. 14 - Normalization Factor for Non-Saturated and Saturated CTR vs. I_F



Fig. 12 - Maximum Collector Current vs. Collector Voltage



Fig. 15 - Normalization Factor for Non-Saturated and Saturated CTR vs. I_F



Fig. 13 - Normalization Factor for Non-Saturated and Saturated CTR vs. I_F







ILD621/ILD621GB/ILQ621/ILQ621GB





Optocoupler, Phototransistor Output
(Dual, Quad Channel)

Vishay Semiconductors

PACKAGE DIMENSIONS in inches (millimeters)



i178006



i178007

ILD621/ILD621GB/ILQ621/ILQ621GB



Vishay Semiconductors

Optocoupler, Phototransistor Output
(Dual, Quad Channel)



18450

**OZONE DEPLETING SUBSTANCES POLICY STATEMENT**

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively.
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA.
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design
and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.