# Film Capacitors

## Metallized Polyester Film Capacitors (MKT)

**Series/Type:** **B32560 ... B32564**

Date: June 2018

© EPCOS AG 2018. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

EPCOS AG is a TDK Group Company.

### Typical applications
- SMPS, converter
- Electronic ballasts
- Compact fluorescent lamps (CFL)
- Ignition

### Climatic
- Max. operating temperature: 125 °C
- Climatic category (IEC 60068-1:2013): 55/125/56

### Features
- Special dimensions available on request
- High pulse strength
- Small dimensions
- RoHS-compatible

### Construction
- Dielectric: polyethylene terephthalate (polyester, PET)
- Stacked-film technology
- Uncoated

### Terminals
- Parallel wire leads, lead-free tinned
- Special lead lengths available on request

### Marking
Rated capacitance (coded),
rated DC voltage

### Dimensional drawing




Dimensions in mm

| Lead spacing $e$ ±0.4 | Lead diameter $d_1$ ±0.05 | Type |
|---|---|---|
| 7.5 | 0.5 | B32560 |
| 10.0 | 0.5 | B32561 |
| 15.0 | 0.6 | B32562J |
| | 0.8 | B32562H |
| 22.5 | 0.8 | B32563 |
| 27.5 | 0.8 | B32564 |

### Delivery mode
Bulk (untaped)
Taped (Ammo pack or reel) for lead spacing ≤15.0 mm.
For notes on taping, refer to chapter "Taping and packing".

### Notes on mounting
When mounting these capacitors, take into account creepage distances and clearances to adjacent live parts. The insulating strength of the cut surfaces to other live parts of the circuit is 1.5 times the capacitors rated DC voltage, but is always at least 300 V DC.

Capacitors with 7.5 mm lead spacing are only suitable for use with single-clad printed circuit boards.

## Overview of available types

| Lead spacing | 7.5 mm | | | | | | 10.0 mm | | | | | 15.0 mm | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Type | B32560 | | | | | | B32561 | | | | | B32562 | | | |
| Page | 5 | | | | | | 7 | | | | | 9 | | | |
| $V_R$ (V DC) | 63 | 100 | 250 | 400 | 630 | 1000 | 63 | 100 | 250 | 400 | 630 | 100 | 250 | 400 | 630 |
| $V_{RMS}$ (V AC) | 40 | 63 | 160 | 200 | 400 | 500 | 40 | 63 | 160 | 200 | 350 | 63 | 160 | 200 | 350 |
| $C_R$ (µF) | | | | | | | | | | | | | | | |
| 0.0010 | | | | | ■ | | | | | | | | | | |
| 0.0015 | | | | | ■ | | | | | | | | | | |
| 0.0022 | | | | | ■ | ■ | | | | | | | | | |
| 0.0033 | | | | | ■ | ■ | | | | | | | | | |
| 0.0047 | | | | | ■ | ■ | | | | | | | | | |
| 0.0068 | | | | ■ | ■ | | | | | | | | | | |
| 0.010 | | | | ■ | ■ | | | | | | | | | | |
| 0.015 | | | | ■ | ■ | | | | | | ■ | | | | |
| 0.022 | | | | ■ | ■ | | | | | | ■ | | | | |
| 0.033 | | | | ■ | | | | | | ■ | ■ | | | | |
| 0.047 | | | ■ | ■ | | | | | | ■ | ■ | | | | |
| 0.068 | | | ■ | ■ | | | | | | ■ | ■ | | | | |
| 0.10 | | | ■ | ■ | | | | | ■ | ■ | ■ | | | | |
| 0.15 | | | ■ | ■ | | | | | ■ | ■ | ■ | | | | |
| 0.22 | | ■ | ■ | ■ | | | | | ■ | ■ | | | | ■ | ■ |
| 0.33 | | ■ | ■ | | | | | | ■ | ■ | | | | ■ | ■ |
| 0.47 | | ■ | ■ | | | | | | ■ | ■ | | | ■ | ■ | ■ |
| 0.68 | | ■ | ■ | | | | | ■ | ■ | | | | ■ | ■ | |
| 1.0 | ■ | ■ | | | | | ■ | ■ | ■ | | | | ■ | ■ | |
| 1.5 | ■ | ■ | | | | | ■ | ■ | | | | | ■ | ■ | |
| 2.2 | ■ | ■ | | | | | ■ | ■ | | | | ■ | ■ | | |
| 3.3 | ■ | ■ | | | | | ■ | ■ | | | | ■ | ■ | | |
| 4.7 | ■ | | | | | | ■ | | | | | ■ | | | |
| 6.8 | | | | | | | ■ | | | | | ■ | | | |
| 10 | | | | | | | | | | | | ■ | | | |

## Overview of available types

| Lead spacing | 22.5 mm | | | 27.5 mm | | | |
|---|---|---|---|---|---|---|---|
| Type | B32563 | | | B32564 | | | |
| Page | 10 | | | 11 | | | |
| $V_R$ (V DC) | 100 | 250 | 400 | 100 | 250 | 400 | 420 |
| $V_{RMS}$ (V AC) | 63 | 160 | 200 | 63 | 160 | 200 | 200 |
| $C_R$ (µF) | | | | | | | |
| 1.0 | | | | | | | |
| 1.5 | | | | | | | |
| 2.2 | | | | | | | |
| 3.3 | | | | | | | |
| 4.7 | | | | | | | |
| 6.8 | | | | | | | |
| 10 | | | | | | | |
| 15 | | | | | | | |
| 22 | | | | | | | |
| 33 | | | | | | | |




## Ordering codes and packing units (lead spacing 7.5 mm)

| $V_R$ V DC | $V_{RMS}$ f ≤60 Hz V AC | $C_R$ µF | Max. dimensions w × h × l mm | Ordering code (composition see below) | Ammo pack pcs./MOQ | Reel pcs./MOQ | Untaped pcs./MOQ |
|---|---|---|---|---|---|---|---|
| 63 | 40 | 1.0 | 4.0 × 6.8 × 9.0 | B32560J0105+*** | 8800 | 7200 | 4000 |
| | | 1.5 | 5.1 × 7.6 × 9.0 | B32560J0155+*** | 6800 | 5600 | 2000 |
| | | 2.2 | 6.5 × 8.2 × 9.0 | B32560J0225+*** | 6000 | 4800 | 2000 |
| | | 3.3 | 8.5 × 9.1 × 9.0 | B32560J0335+000 | – | – | 1400 |
| | | 4.7 | 9.8 × 11.0 × 9.0 | B32560J0475+000 | – | – | 1000 |
| 100 | 63 | 0.22 | 2.5 × 5.1 × 9.0 | B32560J1224+*** | 12400 | 10000 | 7600 |
| | | 0.33 | 2.7 × 5.7 × 9.0 | B32560J1334+*** | 12000 | 9600 | 6000 |
| | | 0.47 | 3.4 × 6.1 × 9.0 | B32560J1474+*** | 9600 | 8000 | 4800 |
| | | 0.68 | 4.2 × 6.5 × 9.0 | B32560J1684+*** | 8000 | 6400 | 3600 |
| | | 1.0 | 5.5 × 7.0 × 9.0 | B32560J1105+*** | 6000 | 4800 | 2000 |
| | | 1.5 | 6.7 × 8.2 × 9.0 | B32560J1155+*** | 5000 | 4000 | 1600 |
| | | 2.2 | 8.5 × 9.2 × 9.0 | B32560J1225+000 | – | – | 1200 |
| | | 3.3 | 9.5 × 11.0 × 9.0 | B32560J1335+000 | – | – | 800 |
| 250 | 160 | 0.047 | 2.5 × 5.2 × 9.0 | B32560J3473+*** | 13000 | 10400 | 7600 |
| | | 0.068 | 2.6 × 5.7 × 9.0 | B32560J3683+*** | 12400 | 10000 | 6800 |
| | | 0.10 | 3.2 × 6.1 × 9.0 | B32560J3104+*** | 12400 | 8000 | 4800 |
| | | 0.15 | 3.9 × 7.0 × 9.0 | B32560J3154+*** | 8200 | 6800 | 3600 |
| | | 0.22 | 4.9 × 7.5 × 9.0 | B32560J3224+*** | 6800 | 5200 | 2600 |
| | | 0.33 | 6.4 × 8.2 × 9.0 | B32560J3334+*** | 5200 | 4400 | 1800 |
| | | 0.47 | 7.4 × 9.8 × 9.0 | B32560J3474+000 | – | – | 1200 |
| | | 0.68 | 9.5 × 11.0 × 9.0 | B32560J3684+000 | – | – | 800 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Special dimensions available on request.
For corresponding design rules, refer to chapter "General technical information", section 1.3.2.

**Composition of ordering code**

+ = Capacitance tolerance code:
- M = ±20%
- K = ±10%
- J = ±5%

*** = Packaging code:
- 289 = Ammo pack
- 189 = Reel
- 000 = Untaped (lead length 5 −1 mm)




**B32560**

**General purpose (stacked) SilverCap™**

## Ordering codes and packing units (lead spacing 7.5 mm)

| $V_R$ V DC | $V_{RMS}$ f ≤60 Hz V AC | $C_R$ µF | Max. dimensions w × h × l mm | Ordering code (composition see below) | Ammo pack pcs./MOQ | Reel pcs./MOQ | Untaped pcs./MOQ |
|---|---|---|---|---|---|---|---|
| 400 | 200 | 0.0068 | 2.5 × 5.5 × 9.0 | B32560J6682+*** | 14000 | 11200 | 7600 |
| | | 0.010 | 2.5 × 5.5 × 9.0 | B32560J6103+*** | 12800 | 10400 | 7200 |
| | | 0.015 | 2.5 × 5.5 × 9.0 | B32560J6153+*** | 13000 | 10400 | 7200 |
| | | 0.022 | 2.5 × 5.5 × 9.0 | B32560J6223+*** | 12400 | 10000 | 6800 |
| | | 0.033 | 2.6 × 6.0 × 9.0 | B32560J6333+*** | 12400 | 10000 | 6400 |
| | | 0.047 | 3.2 × 6.5 × 9.0 | B32560J6473+*** | 10400 | 8400 | 4800 |
| | | 0.068 | 3.8 × 7.3 × 9.0 | B32560J6683+*** | 8600 | 7200 | 3600 |
| | | 0.10 | 4.9 × 7.7 × 9.0 | B32560J6104+*** | 6800 | 5600 | 2000 |
| | | 0.15 | 6.5 × 8.2 × 9.0 | B32560J6154+*** | 5400 | 4000 | 1800 |
| | | 0.22 | 7.7 × 9.8 × 9.0 | B32560J6224+000 | – | – | 1200 |
| 630 | 400 | 0.0010 | 2.5 × 5.5 × 9.0 | B32560J8102+*** | 14800 | 12000 | 9200 |
| | | 0.0015 | 2.5 × 5.5 × 9.0 | B32560J8152+*** | 13000 | 2600 | 7200 |
| | | 0.0022 | 2.5 × 5.5 × 9.0 | B32560J8222+*** | 13400 | 10800 | 7200 |
| | | 0.0033 | 2.5 × 5.5 × 9.0 | B32560J8332+*** | 14000 | 11200 | 7600 |
| | | 0.0047 | 2.5 × 5.5 × 9.0 | B32560J8472+*** | 13600 | 10800 | 7200 |
| | | 0.0068 | 3.2 × 6.5 × 9.0 | B32560J8682+*** | 15000 | 9200 | 5200 |
| | | 0.010 | 3.8 × 7.5 × 9.0 | B32560J8103+*** | 9000 | 9200 | 4000 |
| | | 0.015 | 4.6 × 8.3 × 9.0 | B32560J8153+000 | – | – | 2400 |
| | | 0.022 | 5.7 × 8.6 × 9.0 | B32560J8223+000 | – | – | 1600 |
| 1000 | 500 | 0.0022 | 2.5 × 6.0 × 9.0 | B32560J9222+*** | 13000 | 10400 | 6800 |
| | | 0.0033 | 3.3 × 6.5 × 9.0 | B32560J9332+*** | 10000 | 8000 | 4800 |
| | | 0.0047 | 3.6 × 7.4 × 9.0 | B32560J9472+*** | 9000 | 7600 | 3600 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Special dimensions available on request.
For corresponding design rules, refer to chapter "General technical information", section 1.3.2.

**Composition of ordering code**

+ = Capacitance tolerance code:
- M = ±20%
- K = ±10%
- J = ±5%

*** = Packaging code:
- 289 = Ammo pack
- 189 = Reel
- 000 = Untaped (lead length 5 −1 mm)

## Ordering codes and packing units (lead spacing 10 mm)

| $V_R$ V DC | $V_{RMS}$ f ≤60 Hz V AC | $C_R$ µF | Max. dimensions w × h × l mm | Ordering code (composition see below) | Ammo pack pcs./MOQ | Reel pcs./MOQ | Untaped pcs./MOQ |
|---|---|---|---|---|---|---|---|
| 63 | 40 | 1.0 | 3.5 × 6.2 × 11.0 | B32561J0105+*** | 4960 | 7600 | 4000 |
| | | 1.5 | 4.3 × 6.9 × 11.0 | B32561J0155+*** | 4200 | 6000 | 2800 |
| | | 2.2 | 5.1 × 7.9 × 11.0 | B32561J0225+*** | 3400 | 5000 | 2000 |
| | | 3.3 | 6.4 × 9.1 × 11.0 | B32561J0335+000 | – | – | 1200 |
| | | 4.7 | 7.3 × 11.0 × 11.0 | B32561J0475+000 | – | – | 800 |
| | | 6.8 | 8.8 × 12.7 × 11.0 | B32561J0685+000 | – | – | 600 |
| 100 | 63 | 0.68 | 3.6 × 6.3 × 11.5 | B32561J1684+*** | 5040 | 8000 | 4000 |
| | | 1.0 | 4.5 × 6.9 × 11.5 | B32561J1105+*** | 4200 | 6000 | 2000 |
| | | 1.5 | 5.6 × 7.8 × 11.5 | B32561J1155+*** | 3240 | 4800 | 2000 |
| | | 2.2 | 6.9 × 9.0 × 11.5 | B32561J1225+000 | – | – | 1400 |
| | | 3.3 | 7.8 × 10.5 × 11.5 | B32561J1335+000 | – | – | 800 |
| 250 | 160 | 0.10 | 2.8 × 5.3 × 11.5 | B32561J3104+*** | 6160 | 9200 | 5200 |
| | | 0.15 | 3.3 × 6.0 × 11.5 | B32561J3154+*** | 5040 | 8000 | 4000 |
| | | 0.22 | 4.2 × 6.6 × 11.5 | B32561J3224+*** | 4160 | 6000 | 2800 |
| | | 0.33 | 5.2 × 7.5 × 11.5 | B32561J3334+*** | 3360 | 5200 | 2000 |
| | | 0.47 | 6.3 × 8.5 × 11.5 | B32561J3474+*** | 2720 | 4400 | 1400 |
| | | 0.68 | 7.5 × 9.7 × 11.5 | B32561J3684+000 | – | – | 800 |
| | | 1.0 | 9.5 × 11.0 × 11.5 | B32561J3105+000 | – | – | 600 |
| 400 | 200 | 0.033 | 2.5 × 5.1 × 11.5 | B32561J6333+*** | 6480 | 9200 | 6000 |
| | | 0.047 | 2.6 × 6.0 × 11.5 | B32561J6473+*** | 6240 | 9200 | 5200 |
| | | 0.068 | 3.2 × 6.6 × 11.5 | B32561J6683+*** | 5560 | 8400 | 4000 |
| | | 0.10 | 4.0 × 6.9 × 11.5 | B32561J6104+*** | 4360 | 6800 | 2800 |
| | | 0.15 | 5.2 × 7.7 × 11.5 | B32561J6154+*** | 3400 | 5200 | 2000 |
| | | 0.22 | 6.6 × 8.5 × 11.5 | B32561J6224+*** | 2720 | 4000 | 1400 |
| | | 0.33 | 8.0 × 9.5 × 11.5 | B32561J6334+000 | – | – | 800 |
| | | 0.47 | 9.8 × 11.0 × 11.5 | B32561J6474+000 | – | – | 600 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Special dimensions available on request.
For corresponding design rules, refer to chapter "General technical information", section 1.3.2.

**Composition of ordering code**

+ = Capacitance tolerance code:
- M = ±20%
- K = ±10%
- J = ±5%

*** = Packaging code:
- 289 = Ammo pack
- 189 = Reel
- 000 = Untaped (lead length 5 −1 mm)




**B32561**

**General purpose (stacked) SilverCap™**

## Ordering codes and packing units (lead spacing 10 mm)

| $V_R$ V DC | $V_{RMS}$ f ≤60 Hz V AC | $C_R$ µF | Max. dimensions w × h × l mm | Ordering code (composition see below) | Ammo pack pcs./MOQ | Reel pcs./MOQ | Untaped pcs./MOQ |
|---|---|---|---|---|---|---|---|
| 630 | 350 | 0.015 | 2.8 × 6.3 × 11.0 | B32561J8153+*** | 6320 | 9200 | 4800 |
| | | 0.022 | 3.4 × 6.9 × 11.0 | B32561J8223+*** | 5200 | 8000 | 3600 |
| | | 0.033 | 4.2 × 7.6 × 11.0 | B32561J8333+*** | 4080 | 6400 | 2400 |
| | | 0.047 | 5.3 × 8.0 × 11.0 | B32561J8473+*** | 3360 | 5000 | 1800 |
| | | 0.068 | 6.3 × 9.0 × 11.0 | B32561J8683+000 | – | – | 1400 |
| | | 0.10 | 7.3 × 11.4 × 11.0 | B32561J8104+000 | – | – | 800 |
| | | 0.15 | 8.8 × 13.3 × 11.0 | B32561J8154+000 | – | – | 600 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Special dimensions available on request.
For corresponding design rules, refer to chapter "General technical information", section 1.3.2.

**Composition of ordering code**

+ = Capacitance tolerance code:
- M = ±20%
- K = ±10%
- J = ±5%

*** = Packaging code:
- 289 = Ammo pack
- 189 = Reel
- 000 = Untaped (lead length 5 −1 mm)

## Ordering codes and packing units (lead spacing 15 mm)

| $V_R$ V DC | $V_{RMS}$ f ≤60 Hz V AC | $C_R$ µF | Max. dimensions w × h × l mm | Ordering code (composition see below) | Ammo pack pcs./MOQ | Reel pcs./ MOQ | Untaped pcs./ MOQ |
|---|---|---|---|---|---|---|---|
| 100 | 63 | 2.2 | 4.9 × 8.0 × 16.5 | B32562J1225+*** | 4760 | 5200 | 3200 |
| | | 3.3 | 6.0 × 9.3 × 16.5 | B32562J1335+*** | 3840 | 4000 | 2000 |
| | | 4.7 | 7.3 × 10.6 × 16.5 | B32562H1475+*** | 3160 | 3600 | 1600 |
| | | 6.8 | 9.0 × 11.8 × 16.5 | B32562H1685+*** | 2560 | 2800 | 1160 |
| | | 10 | 11.8 × 13.0 × 16.5 | B32562H1106+000 | – | – | 800 |
| 250 | 160 | 0.47 | 5.0 × 6.7 × 16.5 | B32562J3474+*** | 4760 | 5200 | 3800 |
| | | 0.68 | 6.0 × 7.8 × 16.5 | B32562J3684+*** | 3840 | 4000 | 2000 |
| | | 1.0 | 7.0 × 9.3 × 16.5 | B32562J3105+*** | 3320 | 3600 | 2000 |
| | | 1.5 | 8.7 × 11.0 × 16.5 | B32562H3155+*** | 2640 | 2800 | 1200 |
| | | 2.2 | 10.7 × 12.8 × 16.5 | B32562H3225+000 | – | – | 800 |
| | | 3.3 | 13.9 × 14.5 × 16.5 | B32562H3335+000 | – | – | 600 |
| 400 | 200 | 0.22 | 4.7 × 7.5 × 16.5 | B32562J6224+*** | 4960 | 5200 | 3400 |
| | | 0.33 | 6.0 × 8.3 × 16.5 | B32562J6334+*** | 3840 | 4000 | 2000 |
| | | 0.47 | 7.3 × 9.3 × 16.5 | B32562J6474+*** | 3160 | 3600 | 1800 |
| | | 0.68 | 8.9 × 10.8 × 16.5 | B32562H6684+*** | 2560 | 2800 | 1200 |
| | | 1.0 | 10.9 × 12.5 × 16.5 | B32562H6105+000 | – | – | 800 |
| | | 1.5 | 13.7 × 15.2 × 16.5 | B32562H6155+000 | – | – | 400 |
| 630 | 350 | 0.22 | 9.2 × 12.2 × 16.5 | B32562H8224+000 | – | – | 1400 |
| | | 0.33 | 11.2 × 14.2 × 16.5 | B32562H8334+000 | – | – | 1000 |
| | | 0.47 | 13.5 × 16.3 × 16.5 | B32562H8474+000 | – | – | 720 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Special dimensions available on request.
For corresponding design rules, refer to chapter "General technical information", section 1.3.2.

**Composition of ordering code**

+ = Capacitance tolerance code:
- M = ±20%
- K = ±10%
- J = ±5%

*** = Packaging code:
- 289 = Ammo pack
- 189 = Reel
- 000 = Untaped (lead length 5 −1 mm)




**B32563**

**General purpose (stacked) SilverCap™**

## Ordering codes and packing units (lead spacing 22.5 mm)

| $V_R$ | $V_{RMS}$ f ≤60 Hz | $C_R$ | Max. dimensions w × h × l | Ordering code (composition see below) | Untaped |
|---|---|---|---|---|---|
| V DC | V AC | µF | mm | | pcs./MOQ |
| 100 | 63 | 6.8 | 7.0 × 10.5 × 24.0 | B32563J1685+000 | 3680 |
| | | 10 | 8.6 × 12.2 × 24.0 | B32563J1106+000 | 3840 |
| | | 15 | 10.9 × 14.0 × 24.0 | B32563J1156+000 | 2480 |
| | | 22 | 12.8 × 17.2 × 24.0 | B32563J1226+000 | 1440 |
| 250 | 160 | 2.2 | 8.3 × 11.2 × 24.0 | B32563J3225+000 | 2960 |
| | | 3.3 | 10.1 × 13.5 × 24.0 | B32563J3335+000 | 2800 |
| | | 4.7 | 12.2 × 15.5 × 24.0 | B32563J3475+000 | 1560 |
| 400 | 200 | 1.0 | 8.3 × 11.2 × 24.0 | B32563J6105+000 | 3400 |
| | | 1.5 | 10.3 × 13.2 × 24.0 | B32563J6155+000 | 2640 |
| | | 2.2 | 12.6 × 15.5 × 24.0 | B32563J6225+000 | 1440 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Special dimensions available on request.
For corresponding design rules, refer to chapter "General technical information", section 1.3.2.

**Composition of ordering code**

+ = Capacitance tolerance code:
M = ±20%
K = ±10%
J = ±5%

Packaging code:
000 = Untaped (lead length 5 − 1 mm)




## Ordering codes and packing units (lead spacing 27.5 mm)

| $V_R$ | $V_{RMS}$ f ≤60 Hz | $C_R$ | Max. dimensions w × h × l | Ordering code (composition see below) | Untaped |
|---|---|---|---|---|---|
| V DC | V AC | µF | mm | | pcs./MOQ |
| 100 | 63 | 10 | 7.6 × 11.0 × 29.0 | B32564J1106+000 | 2720 |
| | | 15 | 9.1 × 13.5 × 29.0 | B32564J1156+000 | 1720 |
| | | 22 | 11.0 × 16.0 × 29.0 | B32564J1226+000 | 1280 |
| | | 33 | 13.0 × 19.8 × 29.0 | B32564J1336+000 | 1440 |
| 250 | 160 | 3.3 | 7.9 × 14.0 × 29.0 | B32564J3335+000 | 3000 |
| | | 4.7 | 9.6 × 15.8 × 29.0 | B32564J3475+000 | 1600 |
| | | 6.8 | 11.9 × 18.0 × 29.0 | B32564J3685+000 | 1200 |
| | | 10 | 13.8 × 22.5 × 29.0 | B32564J3106+000 | 1120 |
| 400 | 200 | 1.5 | 7.8 × 14.2 × 29.0 | B32564J6155+000 | 3000 |
| | | 2.2 | 9.6 × 16.4 × 29.0 | B32564J6225+000 | 1600 |
| | | 3.3 | 12.2 × 18.8 × 29.0 | B32564J6335+000 | 1320 |
| | | 4.7 | 14.2 × 22.8 × 29.0 | B32564J6475+000 | 1040 |
| 420 | 200 | 4.7 | 16.0 × 20.0 × 29.0 | B32564T6475K000 | 1160 |
| | | 6.8 | 16.0 × 20.0 × 29.0 | B32564T6685K000 | 1160 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Special dimensions available on request.
For corresponding design rules, refer to chapter "General technical information", section 1.3.2.
The technical data given on page 12 do not apply to 420 V series. Please contact your nearest EPCOS representative if you need further information.

**Composition of ordering code**

+ = Capacitance tolerance code:
M = ±20%
K = ±10%
J = ±5%

Packaging code:
000 = Untaped (lead length 5 − 1 mm)

## Technical data

Reference standard: IEC 60384-2:2005. All data given at T = 20 ºC, unless otherwise specified.

| | | | | |
|---|---|---|---|---|
| Operating temperature range | Max. operating temperature $T_{op,max}$ | +125 °C | | |
| | Upper category temperature $T_{max}$ | +125 °C | | |
| | Lower category temperature $T_{min}$ | −55 °C | | |
| | Rated temperature $T_R$ | +85 °C | | |
| Dissipation factor tan δ (in $10^{-3}$) at 20 °C (upper limit values) | at | $C_R \leq 0.1$ µF | 0.1 µF < $C_R \leq 1$ µF | $C_R > 1$ µF |
| | 1 kHz | 8 | 8 | 10 |
| | 10 kHz | 15 | 15 | – |
| | 100 kHz | 30 | – | – |
| Insulation resistance $R_{ins}$ or time constant $\tau = C_R \cdot R_{ins}$ at 20 °C, rel. humidity ≤ 65% (minimum as-delivered values) | $V_R$ | $C_R \leq 0.33$ µF | $C_R > 0.33$ µF | |
| | ≤ 100 V DC | 3750 MΩ | 1250 s | |
| | ≥ 250 V DC | 7500 MΩ | 2500 s | |
| DC test voltage | 1.4 · $V_R$, 2 s | | | |
| Category voltage $V_C$ (continuous operation with $V_{DC}$ or $V_{AC}$ at f ≤ 60 Hz) | $T_{op}$ (°C) | DC voltage derating | AC voltage derating | |
| | $T_{op} \leq 85$ | $V_C = V_R$ | $V_{C,RMS}=V_{RMS}$ | |
| | $85<T_{op}\leq125$ | $V_C = V_R \cdot (165-T_{op})/80$ | $V_{C,RMS}=V_{RMS} \cdot (165-T_{op})/80$ | |
| Operating voltage $V_{op}$ for short operating periods ($V_{DC}$ or $V_{AC}$ at f ≤ 60 Hz) | $T_{op}$ (°C) | DC voltage (max. hours) | AC voltage (max. hours) | |
| | $T_{op} \leq 100$ | $V_{op} = 1.25 \cdot V_C$ (2000 h) | $V_{op} = 1.0 \cdot V_{C,RMS}$ (2000 h) | |
| | $100<T_{op}\leq125$ | $V_{op} = 1.25 \cdot V_C$ (1000 h) | $V_{op} = 1.0 \cdot V_{C,RMS}$ (1000 h) | |
| Reliability: | | | | |
| Failure rate λ | 2 fit (≤ 1 · $10^{-9}$ /h) at 0.5 · $V_R$, 40 °C | | | |
| Service life $t_{SL}$ | 100 000 h at 1.0 · $V_R$, 85 °C | | | |
| | For conversion to other operating conditions and temperatures, refer to chapter "Reliability". | | | |
| Failure criteria: | | | | |
| Total failure | Short circuit or open circuit | | | |
| Failure due to variation of parameters | Capacitance change $\lvert\Delta C/C\rvert$ | > 10% | | |
| | Dissipation factor tan δ | > 2 · upper limit value | | |
| | Insulation resistance $R_{ins}$ | < 150 MΩ ($C_R \leq 0.33$ µF) | | |
| | or time constant $\tau = C_R \cdot R_{ins}$ | < 50 s ($C_R > 0.33$ µF) | | |

## Pulse handling capability

"dV/dt" represents the maximum permissible voltage change per unit of time for non-sinusoidal voltages, expressed in V/µs.

"$k_0$" represents the maximum permissible pulse characteristic of the waveform applied to the capacitor, expressed in $V^2/\mu s$.

*Note:*
*The values of dV/dt and $k_0$ provided below must not be exceeded in order to avoid damaging the capacitor. These parameters are given for isolated pulses in such a way that the heat generated by one pulse will be completely dissipated before applying the next pulse. For a train of pulses, please refer to the curves of permissible AC voltage-current versus frequency.*

### dV/dt values

| Lead spacing | | 7.5 mm | 10 mm | 15 mm | 22.5 mm | 27.5 mm |
|---|---|---|---|---|---|---|
| $V_R$ V DC | $V_{RMS}$ V AC | dV/dt in V/µs | | | | |
| 63 | 40 | 120 | 60 | – | – | – |
| 100 | 63 | 150 | 75 | 50 | 50 | 25 |
| 250 | 160 | 200 | 150 | 100 | 100 | 50 |
| 400 | 200 | 275 | 175 | 125 | 125 | 60 |
| 420 | 200 | – | – | – | – | 60 |
| 630 | 350 | – | 320 | 150 | – | – |
| 630 | 400 | 320 | – | – | – | – |
| 1000 | 500 | 360 | – | – | – | – |

### $k_0$ values

| Lead spacing | | 7.5 mm | 10 mm | 15 mm | 22.5 mm | 27.5 mm |
|---|---|---|---|---|---|---|
| $V_R$ V DC | $V_{RMS}$ V AC | $k_0$ in $V^2/\mu s$ | | | | |
| 63 | 40 | 15 000 | 7500 | – | – | – |
| 100 | 63 | 30 000 | 15 000 | 10 000 | 10 000 | 5 000 |
| 250 | 160 | 100 000 | 75 000 | 50 000 | 50 000 | 25 000 |
| 400 | 200 | 220 000 | 140 000 | 100 000 | 100 000 | 50 000 |
| 420 | 200 | – | – | – | – | 50 000 |
| 630 | 350 | – | 400 000 | 190 000 | – | – |
| 630 | 400 | 400 000 | – | – | – | – |
| 1000 | 500 | 720 000 | – | – | – | – |

**Impedance Z versus frequency f**

(typical values)



## Permissible AC voltage $V_{RMS}$ versus frequency f (for sinusoidal waveforms, $T_A \leq 55$ °C)

For $T_A$ >55 °C, please refer to "General technical information", section 3.2.3.

### Lead spacing 7.5 mm

63 V DC/40 V AC




100 V DC/63 V AC




250 V DC/160 V AC




400 V DC/200 V AC



**Permissible AC voltage $V_{RMS}$ versus frequency f (for sinusoidal waveforms, $T_A \leq 55$ °C)**

For $T_A$ >55 °C, please refer to "General technical information", section 3.2.3.

**Lead spacing 7.5 mm**

630 V DC/400 V AC




1000 V DC/500 V AC



## Permissible AC voltage $V_{RMS}$ versus frequency f (for sinusoidal waveforms, $T_A \leq 55$ °C)

For $T_A$ >55 °C, please refer to "General technical information", section 3.2.3.

### Lead spacing 10 mm

63 V DC/40 V AC




100 V DC/63 V AC




250 V DC/160 V AC




400 V DC/200 V AC



**Permissible AC voltage $V_{RMS}$ versus frequency f (for sinusoidal waveforms, $T_A \leq 55$ °C)**

For $T_A$ >55 °C, please refer to "General technical information", section 3.2.3.

**Lead spacing 10 mm**

630 V DC/350 V AC



**Permissible AC voltage $V_{RMS}$ versus frequency f (for sinusoidal waveforms, $T_A \leq 55$ °C)**

For $T_A$ >55 °C, please refer to "General technical information", section 3.2.3.

**Lead spacing 15 mm**

100 V DC/63 V AC




250 V DC/160 V AC




400 V DC/200 V AC




630 V DC/350 V AC








**Permissible AC voltage $V_{RMS}$ versus frequency f (for sinusoidal waveforms, $T_A \leq 55$ °C)**

For $T_A$ >55 °C, please refer to "General technical information", section 3.2.3.

**Lead spacing 22.5 mm**

100 V DC/63 V AC




250 V DC/160 V AC




400 V DC/200 V AC



**Permissible AC voltage $V_{RMS}$ versus frequency f (for sinusoidal waveforms, $T_A \leq 55$ °C)**

For $T_A$ >55 °C, please refer to "General technical information", section 3.2.3.

**Lead spacing 27.5 mm**

100 V DC/63 V AC




250 V DC/160 V AC




400 V DC/200 V AC




420 V DC/200 V AC



## Permissible current $I_{RMS}$ versus frequency f (for sinusoidal waveforms, $T_A \leq 55$ °C)

### Lead spacing 7.5 mm

63 V DC/40 V AC




100 V DC/63 V AC




250 V DC/160 V AC




400 V DC/200 V AC



## Permissible current $I_{RMS}$ versus frequency f (for sinusoidal waveforms, $T_A \leq 55$ °C)

### Lead spacing 7.5 mm

630 V DC/400 V AC




1000 V DC/500 V AC



## Permissible current $I_{RMS}$ versus frequency f (for sinusoidal waveforms, $T_A \leq 55$ °C)

### Lead spacing 10 mm

63 V DC/40 V AC




100 V DC/63 V AC




250 V DC/160 V AC




400 V DC/200 V AC



## Permissible current $I_{RMS}$ versus frequency f (for sinusoidal waveforms, $T_A \leq 55$ °C)

### Lead spacing 10 mm

630 V DC/350 V AC



## Permissible current $I_{RMS}$ versus frequency f (for sinusoidal waveforms, $T_A \leq 55$ °C)

### Lead spacing 15 mm

100 V DC/63 V AC




250 V DC/160 V AC




400 V DC/200 V AC




630 V DC/350 V AC



## Permissible current $I_{RMS}$ versus frequency f (for sinusoidal waveforms, $T_A \leq 55$ °C)

### Lead spacing 22.5 mm

100 V DC/63 V AC




250 V DC/160 V AC




400 V DC/200 V AC








## Permissible current $I_{RMS}$ versus frequency f (for sinusoidal waveforms, $T_A \leq 55$ °C)

### Lead spacing 27.5 mm

100 V DC/63 V AC




250 V DC/160 V AC




400 V DC/200 V AC




420 V DC/200 V AC



## Testing and Standards

| Test | Reference | Conditions of test | Performance requirements |
|---|---|---|---|
| Electrical parameters | IEC 60384-2:2005 | Voltage proof, 1.4 $V_R$, 1 minute<br>Insulation resistance, $R_{ins}$<br>Capacitance, C<br>Dissipation factor, tan δ | Within specified limits |
| Robustness of terminations | IEC 60068-2-21:2006 | Tensile strength (test Ua1)<br>Wire diameter / Tensile force<br>0.3 <$d_1$ ≤0.5 mm / 5 N<br>0.5 <$d_1$ ≤0.8 mm / 10 N | No visible damage<br>Capacitance and tan δ within specified limits |
| Resistance to soldering heat | IEC 60068-2-20:2008, test Tb, method 1A | Solder bath temperature at 260 ±5 °C, immersion for<br>4 seconds (lead spacing ≤10mm)<br>10 seconds (lead spacing > 10mm) | $\Delta C/C_0$ ≤2%<br>$\lvert\Delta \tan\delta\rvert$ ≤0.003 for C ≤ 1 µF<br>$\lvert\Delta \tan\delta\rvert$ ≤0.002 for C > 1 µF |
| Rapid change of temperature | IEC 60384-2:2005 | $T_A$ = lower category temperature<br>$T_B$ = upper category temperature<br>Five cycles, duration t = 30 min. | $\Delta C/C_0$ ≤5%<br>$\lvert\Delta \tan\delta\rvert$ ≤0.003 for C ≤ 1 µF<br>$\lvert\Delta \tan\delta\rvert$ ≤0.002 for C > 1 µF<br>$R_{ins}$ ≥50% of initial limit |
| Vibration | IEC 60384-2:2005 | Test Fc: vibration sinusoidal<br>Displacement: 0.75 mm<br>Accleration: 98 m/s²<br>Frequency: 10 Hz ... 500 Hz<br>Test duration: 3 orthogonal axes, 2 hours each axe | No visible damage |
| Bump | IEC 60384-2:2005 | Test Eb: Total 4000 bumps with 390 m/s² mounted on PCB<br>Duration: 6 ms | $\Delta C/C_0$ ≤5%<br>$\lvert\Delta \tan\delta\rvert$ ≤0.003 for C ≤1 µF<br>$\lvert\Delta \tan\delta\rvert$ ≤0.002 for C > 1 µF<br>$R_{ins}$ ≥50% of initial limit |
| Climatic sequence | IEC 60384-2:2005 | Dry heat Tb / 16 h<br>Damp heat cyclic, 1st cycle<br>+55 °C / 24 h / 95% ... 100% RH<br>Cold Ta / 2 h<br>Damp heat cyclic, 5 cycles<br>+55 °C / 24 h / 95% ... 100% RH | $\Delta C/C_0$ ≤5%<br>$\lvert\Delta \tan\delta\rvert$ ≤ 0.005 for C ≤ 1 µF<br>$\lvert\Delta \tan\delta\rvert$ ≤ 0.003 for C > 1 µF<br>$R_{ins}$ ≥50% of initial limit |
| Damp heat, steady state | IEC 60384-2:2005 | Test Ca<br>40 °C / 93% RH / 56 days | No visible damage<br>$\lvert\Delta C/C_0\rvert$ ≤5%<br>$\lvert\Delta \tan\delta\rvert$ ≤ 0.005<br>$R_{ins}$ ≥50% of initial limit |

| Test | Reference | Conditions of test | Performance requirements |
|---|---|---|---|
| Endurance A | IEC 60384-2:2005 | 85 °C / 1.25 $V_R$ / 2000 hours | No visible damage<br>$\|\Delta C/C_0\| \leq 5\%$<br>$\|\Delta \tan\delta\| \leq 0.003$ for $C \leq 1$ µF<br>$\|\Delta \tan\delta\| \leq 0.002$ for $C > 1$ µF<br>$R_{ins}$ ≥50% of initial limit |
| Endurance B | IEC 60384-2:2005 | 125 °C / 1.25 $V_C$ / 2000 hours | No visible damage<br>$\|\Delta C/C_0\| \leq 5\%$<br>$\|\Delta \tan\delta\| \leq 0.003$ for $C \leq 1$ µF<br>$\|\Delta \tan\delta\| \leq 0.002$ for $C > 1$ µF<br>$R_{ins}$ ≥50% of initial limit |

## Mounting guidelines

### 1 Soldering

### 1.1 Solderability of leads

The solderability of terminal leads is tested to IEC 60068-2-20, test Ta, method 1.

Before a solderability test is carried out, terminals are subjected to accelerated ageing (to IEC 60068-2-2, test Ba: 4 h exposure to dry heat at 155 °C). Since the ageing temperature is far higher than the upper category temperature of the capacitors, the terminal wires should be cut off from the capacitor before the ageing procedure to prevent the solderability being impaired by the products of any capacitor decomposition that might occur.

| | |
|---|---|
| Solder bath temperature | 235 ±5 °C |
| Soldering time | 2.0 ±0.5 s |
| Immersion depth | 2.0 +0/−0.5 mm from capacitor body or seating plane |
| Evaluation criteria:<br>Visual inspection | Wetting of wire surface by new solder ≥90%, free-flowing solder |

### 1.2 Resistance to soldering heat

Resistance to soldering heat is tested to IEC 60068-2-20, test Tb, method 1.
Conditions:

| Series | | Solder bath temperature | Soldering time |
|---|---|---|---|
| MKT | boxed (except 2.5 × 6.5 × 7.2 mm)<br>coated<br>uncoated (lead spacing >10 mm) | 260 ±5 °C | 10 ±1 s |
| MFP<br>MKP | (lead spacing >7.5 mm) | | |
| MKT | boxed (case 2.5 × 6.5 × 7.2 mm) | | 5 ±1 s |
| MKP<br>MKT | (lead spacing ≤7.5 mm)<br>uncoated (lead spacing ≤10 mm)<br>insulated (B32559) | | <4 s<br>recommended soldering profile for MKT uncoated (lead spacing ≤ 10 mm) and insulated (B32559) |




| | |
|---|---|
| Immersion depth | 2.0 +0/−0.5 mm from capacitor body or seating plane |
| Shield | Heat-absorbing board, (1.5 ±0.5) mm thick, between capacitor body and liquid solder |
| Evaluation criteria: | |
| Visual inspection | No visible damage |
| $\Delta C/C_0$ | 2% for MKT/MKP/MFP<br>5% for EMI suppression capacitors |
| tan $\delta$ | As specified in sectional specification |

## 1.3 General notes on soldering

Permissible heat exposure loads on film capacitors are primarily characterized by the upper category temperature $T_{max}$. Long exposure to temperatures above this type-related temperature limit can lead to changes in the plastic dielectric and thus change irreversibly a capacitor's electrical characteristics. For short exposures (as in practical soldering processes) the heat load (and thus the possible effects on a capacitor) will also depend on other factors like:

- Pre-heating temperature and time
- Forced cooling immediately after soldering
- Terminal characteristics:
  diameter, length, thermal resistance, special configurations (e.g. crimping)
- Height of capacitor above solder bath
- Shadowing by neighboring components
- Additional heating due to heat dissipation by neighboring components
- Use of solder-resist coatings

The overheating associated with some of these factors can usually be reduced by suitable countermeasures. For example, if a pre-heating step cannot be avoided, an additional or reinforced cooling process may possibly have to be included.

### EPCOS recommendations

As a reference, the recommended wave soldering profile for our film capacitors is as follows:




$T_s$: Capacitor body maximum temperature at wave soldering
$T_p$: Capacitor body maximum temperature at pre-heating

KMK1745-A-E




Body temperature should follow the description below:

- MKP capacitor
  During pre-heating: $T_p \leq 110$ °C
  During soldering: $T_s \leq 120$ °C, $t_s \leq 45$ s
- MKT capacitor
  During pre-heating: $T_p \leq 125$ °C
  During soldering: $T_s \leq 160$ °C, $t_s \leq 45$ s

When SMD components are used together with leaded ones, the film capacitors should not pass into the SMD adhesive curing oven. The leaded components should be assembled after the SMD curing step.

Leaded film capacitors are not suitable for reflow soldering.

In order to ensure proper conditions for manual or selective soldering, the body temperature of the capacitor ($T_s$) must be ≤120 °C.

One recommended condition for manual soldering is that the tip of the soldering iron should be <360 °C and the soldering contact time should be no longer than 3 seconds.

For uncoated MKT capacitors with lead spacings ≤10 mm (B32560/B32561) the following measures are recommended:

- pre-heating to not more than 110 °C in the preheater phase
- rapid cooling after soldering

Please refer to EPCOS Film Capacitor Data Book in case more details are needed.

## Cautions and warnings

- Do not exceed the upper category temperature (UCT).
- Do not apply any mechanical stress to the capacitor terminals.
- Avoid any compressive, tensile or flexural stress.
- Do not move the capacitor after it has been soldered to the PC board.
- Do not pick up the PC board by the soldered capacitor.
- Do not place the capacitor on a PC board whose PTH hole spacing differs from the specified lead spacing.
- Do not exceed the specified time or temperature limits during soldering.
- Avoid external energy inputs, such as fire or electricity.
- Avoid overload of the capacitors.
- Consult us if application is with severe temperature and humidity condition.
- There are no serviceable or repairable parts inside the capacitor. Opening the capacitor or any attempts to open or repair the capacitor will void the warranty and liability of EPCOS.
- Please note that the standards referred to in this publication may have been revised in the meantime.

The table below summarizes the safety instructions that must always be observed. A detailed description can be found in the relevant sections of the chapters "General technical information" and "Mounting guidelines".

| Topic | Safety information | Reference chapter "General technical information" |
|---|---|---|
| Storage conditions | Make sure that capacitors are stored within the specified range of time, temperature and humidity conditions. | 4.5 "Storage conditions" |
| Flammability | Avoid external energy, such as fire or electricity (passive flammability), avoid overload of the capacitors (active flammability) and consider the flammability of materials. | 5.3 "Flammability" |
| Resistance to vibration | Do not exceed the tested ability to withstand vibration. The capacitors are tested to IEC 60068-2-6:2007. EPCOS offers film capacitors specially designed for operation under more severe vibration regimes such as those found in automotive applications. Consult our catalog "Film Capacitors for Automotive Electronics". | 5.2 "Resistance to vibration" |

| Topic | Safety information | Reference chapter "Mounting guidelines" |
|---|---|---|
| Soldering | Do not exceed the specified time or temperature limits during soldering. | 1 "Soldering" |
| Cleaning | Use only suitable solvents for cleaning capacitors. | 2 "Cleaning" |

| Topic | Safety information | Reference chapter "Mounting guidelines" |
|---|---|---|
| Embedding of capacitors in finished assemblies | When embedding finished circuit assemblies in plastic resins, chemical and thermal influences must be taken into account.<br>Caution: Consult us first, if you also wish to embed other uncoated component types! | 3 "Embedding of capacitors in finished assemblies" |

**Display of ordering codes for EPCOS products**

The ordering code for one and the same product can be represented differently in data sheets, data books, other publications and the website of EPCOS, or in order-related documents such as shipping notes, order confirmations and product labels. **The varying representations of the ordering codes are due to different processes employed and do not affect the specifications of the respective products**. Detailed information can be found on the Internet under www.epcos.com/orderingcodes.

## Symbols and terms

| Symbol | English | German |
|---|---|---|
| $\alpha$ | Heat transfer coefficient | Wärmeübergangszahl |
| $\alpha_C$ | Temperature coefficient of capacitance | Temperaturkoeffizient der Kapazität |
| A | Capacitor surface area | Kondensatoroberfläche |
| $\beta_C$ | Humidity coefficient of capacitance | Feuchtekoeffizient der Kapazität |
| C | Capacitance | Kapazität |
| $C_R$ | Rated capacitance | Nennkapazität |
| $\Delta C$ | Absolute capacitance change | Absolute Kapazitätsänderung |
| $\Delta C/C$ | Relative capacitance change (relative deviation of actual value) | Relative Kapazitätsänderung (relative Abweichung vom Ist-Wert) |
| $\Delta C/C_R$ | Capacitance tolerance (relative deviation from rated capacitance) | Kapazitätstoleranz (relative Abweichung vom Nennwert) |
| dt | Time differential | Differentielle Zeit |
| $\Delta t$ | Time interval | Zeitintervall |
| $\Delta T$ | Absolute temperature change (self-heating) | Absolute Temperaturänderung (Selbsterwärmung) |
| $\Delta \tan \delta$ | Absolute change of dissipation factor | Absolute Änderung des Verlustfaktors |
| $\Delta V$ | Absolute voltage change | Absolute Spannungsänderung |
| dV/dt | Time differential of voltage function (rate of voltage rise) | Differentielle Spannungsänderung (Spannungsflankensteilheit) |
| $\Delta V/\Delta t$ | Voltage change per time interval | Spannungsänderung pro Zeitintervall |
| E | Activation energy for diffusion | Aktivierungsenergie zur Diffusion |
| ESL | Self-inductance | Eigeninduktivität |
| ESR | Equivalent series resistance | Ersatz-Serienwiderstand |
| f | Frequency | Frequenz |
| $f_1$ | Frequency limit for reducing permissible AC voltage due to thermal limits | Grenzfrequenz für thermisch bedingte Reduzierung der zulässigen Wechselspannung |
| $f_2$ | Frequency limit for reducing permissible AC voltage due to current limit | Grenzfrequenz für strombedingte Reduzierung der zulässigen Wechselspannung |
| $f_r$ | Resonant frequency | Resonanzfrequenz |
| $F_D$ | Thermal acceleration factor for diffusion | Therm. Beschleunigungsfaktor zur Diffusion |
| $F_T$ | Derating factor | Deratingfaktor |
| i | Current (peak) | Stromspitze |
| $I_C$ | Category current (max. continuous current) | Kategoriestrom (max. Dauerstrom) |

| Symbol | English | German |
|---|---|---|
| $I_{RMS}$ | (Sinusoidal) alternating current, root-mean-square value | (Sinusförmiger) Wechselstrom |
| $i_z$ | Capacitance drift | Inkonstanz der Kapazität |
| $k_0$ | Pulse characteristic | Impulskennwert |
| $L_S$ | Series inductance | Serieninduktivität |
| $\lambda$ | Failure rate | Ausfallrate |
| $\lambda_0$ | Constant failure rate during useful service life | Konstante Ausfallrate in der Nutzungsphase |
| $\lambda_{test}$ | Failure rate, determined by tests | Experimentell ermittelte Ausfallrate |
| $P_{diss}$ | Dissipated power | Abgegebene Verlustleistung |
| $P_{gen}$ | Generated power | Erzeugte Verlustleistung |
| Q | Heat energy | Wärmeenergie |
| $\rho$ | Density of water vapor in air | Dichte von Wasserdampf in Luft |
| R | Universal molar constant for gases | Allg. Molarkonstante für Gas |
| R | Ohmic resistance of discharge circuit | Ohmscher Widerstand des Entladekreises |
| $R_i$ | Internal resistance | Innenwiderstand |
| $R_{ins}$ | Insulation resistance | Isolationswiderstand |
| $R_P$ | Parallel resistance | Parallelwiderstand |
| $R_S$ | Series resistance | Serienwiderstand |
| S | severity (humidity test) | Schärfegrad (Feuchtetest) |
| t | Time | Zeit |
| T | Temperature | Temperatur |
| $\tau$ | Time constant | Zeitkonstante |
| tan $\delta$ | Dissipation factor | Verlustfaktor |
| tan $\delta_D$ | Dielectric component of dissipation factor | Dielektrischer Anteil des Verlustfaktors |
| tan $\delta_P$ | Parallel component of dissipation factor | Parallelanteil des Verlfustfaktors |
| tan $\delta_S$ | Series component of dissipation factor | Serienanteil des Verlustfaktors |
| $T_A$ | Temperature of the air surrounding the component | Temperatur der Luft, die das Bauteil umgibt |
| $T_{max}$ | Upper category temperature | Obere Kategorietemperatur |
| $T_{min}$ | Lower category temperature | Untere Kategorietemperatur |
| $t_{OL}$ | Operating life at operating temperature and voltage | Betriebszeit bei Betriebstemperatur und -spannung |
| $T_{op}$ | Operating temperature, $T_A + \Delta T$ | Beriebstemperatur, $T_A + \Delta T$ |
| $T_R$ | Rated temperature | Nenntemperatur |
| $T_{ref}$ | Reference temperature | Referenztemperatur |
| $t_{SL}$ | Reference service life | Referenz-Lebensdauer |






| Symbol | English | German |
|---|---|---|
| $V_{AC}$ | AC voltage | Wechselspannung |
| $V_C$ | Category voltage | Kategoriespannung |
| $V_{C,RMS}$ | Category AC voltage | (Sinusförmige) Kategorie-Wechselspannung |
| $V_{CD}$ | Corona-discharge onset voltage | Teilentlade-Einsatzspannung |
| $V_{ch}$ | Charging voltage | Ladespannung |
| $V_{DC}$ | DC voltage | Gleichspannung |
| $V_{FB}$ | Fly-back capacitor voltage | Spannung (Flyback) |
| $V_i$ | Input voltage | Eingangsspannung |
| $V_o$ | Output voltage | Ausgangsspannung |
| $V_{op}$ | Operating voltage | Betriebsspannung |
| $V_p$ | Peak pulse voltage | Impuls-Spitzenspannung |
| $V_{pp}$ | Peak-to-peak voltage Impedance | Spannungshub |
| $V_R$ | Rated voltage | Nennspannung |
| $\hat{v}_R$ | Amplitude of rated AC voltage | Amplitude der Nenn-Wechselspannung |
| $V_{RMS}$ | (Sinusoidal) alternating voltage, root-mean-square value | (Sinusförmige) Wechselspannung |
| $V_{SC}$ | S-correction voltage | Spannung bei Anwendung "S-correction" |
| $V_{sn}$ | Snubber capacitor voltage | Spannung bei Anwendung "Beschaltung" |
| Z | Impedance | Scheinwiderstand |
| $e$ | Lead spacing | Rastermaß |

## Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or lifesaving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.

7. **Our manufacturing sites serving the automotive business apply the IATF 16949 standard.** The IATF certifications confirm our compliance with requirements regarding the quality management system in the automotive industry. Referring to customer requirements and customer specific requirements (“CSR”) TDK always has and will continue to have the policy of respecting individual agreements. Even if IATF 16949 may appear to support the acceptance of unilateral requirements, we hereby like to emphasize that **only requirements mutually agreed upon can and will be implemented in our Quality Management System.** For clarification purposes we like to point out that obligations from IATF 16949 shall only become legally binding if individually agreed upon.
8. The trade names EPCOS, CeraCharge, CeraDiode, CeraLink, CeraPad, CeraPlas, CSMP, CTVS, DeltaCap, DigiSiMic, ExoCore, FilterCap, FormFit, LeaXield, MiniBlue, MiniCell, MKD, MKK, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, PowerHap, PQSine, PQvar, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.

Release 2018-06

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

EPCOS / TDK:

B32564T6475K000 B32564T6685K000 B32560J0335K000 B32560J1155K000 B32560J1335K000
B32560J3154K000 B32560J3334K000 B32560J3474K000 B32560J3684K000 B32560J6333K000
B32560J6683K000 B32560J6154K000 B32560J8102K000 B32560J8152K000 B32560J8222K000
B32560J8332K000 B32560J8472K000 B32560J8682K000 B32560J8103K000 B32560J8223K000
B32560J9222K000 B32560J9332K000 B32561J0225K000 B32561J0335K000 B32561J0685K000
B32561J1155K000 B32561J3334K000 B32561J3105K000 B32561J6333K000 B32561J6683K000
B32561J6154K000 B32561J6334K000 B32561J6474K000 B32561J8223K000 B32561J8104K000
B32561J8154K000 B32562H1475K000 B32562H1685K000 B32562H1106K000 B32562H3155K000
B32562H3225K000 B32562H3335K000 B32562H6684K000 B32562H6105K000 B32562H6155K000
B32562H8224K000 B32562H8334K000 B32562H8474K000 B32563J1685K000 B32563J1106K000
B32563J1156K000 B32563J1226K000 B32563J3225K000 B32563J3335K000 B32563J3475K000
B32563J6105K000 B32563J6155K000 B32563J6225K000 B32564J1106K000 B32564J1226K000
B32564J1336K000 B32564J3475K000 B32564J3685K000 B32564J3106K000 B32564J6155K000
B32564J6225K000 B32564J6335K000 B32564J6475K000 B32560J0225K289 B32560J1155K289
B32560J3334K289 B32560J6152K289 B32560J6222K289 B32560J6472K289 B32560J6103K289
B32560J6333K289 B32560J8102K289 B32560J8103K289 B32561J0225K289 B32561J1684K289
B32561J3104K289 B32561J3334K289 B32562H6684K289 B32560J0225K189 B32560J1684K189
B32560J6223K189 B32560J8102K189 B32561J3474K189 B32562H1475K189 B32562H1685K189
B32562J6474K189 B32562H6684K189 B32560J0105J000 B32560J0225J000 B32560J0335J000 B32560J0475J000
B32560J1224J000 B32560J1334J000 B32560J1474J000 B32560J1684J000

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.




**Как с нами связаться**

**Телефон:** 8 (812) 309 58 32 (многоканальный)
**Факс:** 8 (812) 320-02-42
**Электронная почта:** org@eplast1.ru
**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.