

# NR01 Series Process Sealed Rotaries



**Subminiature Rotaries with  
Positive, Distinctive Detent**

# General Specifications

## Electrical Capacity (Resistive Load)

**Logic Level:** 0.4VA maximum @ 28V AC/DC maximum  
(Applicable Range 0.1mA ~ 0.1A @ 20mV ~ 28V)  
Note: Find additional explanation of operating range in Supplement section

## Other Ratings

**Contact Resistance:** 100 milliohms maximum  
**Insulation Resistance:** 100 megohms minimum @ 500V DC  
**Dielectric Strength:** 500V AC minimum for 1 minute minimum  
**Mechanical Life:** 30,000 cycles minimum  
**Electrical Life:** 10,000 cycles minimum  
**Nominal Operating Torque:** 0.02Nm (0.177 lb•in)  
**Contact Timing:** Nonshorting  
**Indexing:** 45° for 3-position, 4-position & 5-position

## Materials & Finishes

**Housing:** Glass fiber reinforced polyester (PBT)  
**Base:** Glass fiber reinforced polyamide  
**Rotor:** Polyacetal  
**Movable Contactor:** Beryllium copper with gold plating  
**Stationary Contacts:** Phosphor bronze with gold plating  
**Terminals:** Phosphor bronze with gold plating  
**Mounting Bracket:** Steel with tin plating

## Environmental Data

**Operating Temperature Range:** -25°C through +70°C (-13°F through +158°F)  
**Humidity:** 90 ~ 95% humidity for 96 hours @ 40°C (104°F)  
**Vibration:** 10 ~ 55Hz with peak-to-peak amplitude of 1.5mm traversing the frequency range & returning in 1 minute; 3 right angled directions for 2 hours  
**Shock:** 50G (490m/s<sup>2</sup>) acceleration (tested in 6 right angled directions, with 5 shocks in each direction)

## PCB Processing

**Soldering:** Wave Soldering Recommended: Preheat temperature 110°C; Preheat time 40 seconds; Peak Temperature 270°C; Peak Time 6 seconds; Thickness of PCB 1.6mm; 2 Cycles.  
 Manual Soldering Recommended: Temperature 390°C for 4 seconds, 2 cycles.  
**Cleaning:** Automated cleaning. See Cleaning Specifications in Supplement section.

## Standards & Certifications

The NR01 Series rotaries have not been tested for UL recognition or CSA certification. These switches are designed for use in a low-voltage, low-current, logic-level circuit. When used as intended in a logic-level circuit, the results do not produce hazardous energy.

Note: Values are determined by NKK's individual specification tests in a controlled environment, and do not certify that the product supports simultaneous multiple conditions.

# Distinctive Characteristics

Totally sealed construction with internal o-ring, gasket between base and housing, and insert-molded terminals, gives protection for automated processing techniques.

Detent mechanism, with its spring-operated steel ball, gives distinct feel and crisp actuation for accurate switch setting.

Subminiature size and compact body contributes to high density mounting.

Bifurcated, self-wiping contact mechanism provides unequalled logic-level reliability and smoother, positive detent actuation.

Crimped bracket legs ensure secure PCB mounting and prevent dislodging during automated wave soldering.

Molded-in terminals prevent entry of flux and other contaminants.

.100" x .100" (2.54mm x 2.54mm) terminal spacing conforms to standard PC board grid spacing.





## Applications

- Power Control Equipment
- Measuring Devices
- Telecommunication Equipment
- Medical Equipment
- Teaching Pendant

## Actual Size



### TYPICAL SWITCH ORDERING EXAMPLE



### POLES & CIRCUITS

| Pole | Model   | Actuator Positions |       |       |       |       | Connected Terminals |       |       |       |       | Throw & Schematics |
|------|---------|--------------------|-------|-------|-------|-------|---------------------|-------|-------|-------|-------|--------------------|
|      |         | Pos 1              | Pos 2 | Pos 3 | Pos 4 | Pos 5 | Pos 1               | Pos 2 | Pos 3 | Pos 4 | Pos 5 |                    |
| SP3T | NR01103 | ON                 | ON    | ON    | —     | —     | C-2                 | C-3   | C-4   | —     | —     |                    |
| SP4T | NR01104 | ON                 | ON    | ON    | ON    | —     | C-2                 | C-3   | C-4   | C-5   | —     |                    |
| SP5T | NR01105 | ON                 | ON    | ON    | ON    | ON    | C-1                 | C-2   | C-3   | C-4   | C-5   |                    |


Note: Terminal numbers are not actually on switch

### CONTACT MATERIAL & RATING

**G** Gold over Bronze or Copper  
Logic Level  
0.4VA @ 28V AC/DC maximum


### TERMINALS

**13** Straight PC with Bracket




## TYPICAL SWITCH DIMENSIONS



### 45° Indexing • SP3T • Straight PC



Actuator shown in Position 1




Terminals 1 & 5 are support pins




NR01103ANG13-1C



### 45° Indexing • SP4T • Straight PC



Actuator shown in Position 1




Terminal 1 is a support pin






NR01104ANG13-2C

### 45° Indexing • SP5T • Straight PC



Actuator shown in Position 1



NR01105ANG13-2C


## KNOBS

**No Code**

Without Knob


**1** AT3008 Without Flange

Material:  
Glass fiber reinforced polyamide



**2** AT3009 With Flange

Material:  
Glass fiber reinforced polyamide




Knob Colors

- A** Black
- C** Red
- H** Gray


## MOUNTING & INSTALLATION

### Knob Installation

To prevent knob from disassembling from the switch, it is recommended to use the type with a flange. Mount the knob with the flange (AT3009, assembled to switch) beneath the panel, as shown in illustration.



Ideal for Applications that Require Small Sizes with Precision & Reliability



### Advantages

- Simplified soldering and automated cleaning processes enhance production efficiency
- Reinforced bracket with crimped legs improves mounting stability and strength
- Easy, straightforward functionality
- Small, subminiature size with precise detent and crisp actuation

### Typical Applications



Switching Function

F1, F2, F3, F4

Handheld Automation Devices



Input Switching

AC, DC, GND

Signal Mode Selection

CH1, CH2, DUAL


Measuring Devices

A Comprehensive Line of Rotary Switches Meets a Variety of Applications

| PCB Mount Rotaries    | NR01  | MRB   | MRA112  | FR01  |
|-----------------------|---|---|---|---|
| Specifications        |  |  |  |  |
| Number of Poles       | 1   | 1   | 1, 2, 4   | —   |
| Positions             | 3, 4, 5   | 2, 3  | 2 ~ 12  | —   |
| Electrical Capacity   | 0.4VA Max @ 28V AC/DC Max   | 0.4VA Max @ 28V AC/DC Max   | 250mA @ 125V AC   | 100mA @ 5V DC   |
| Electrical Life       | 10,000 Operations Min   | 10,000 Operations Min   | 10,000 Operations Min   | 10,000 Detent Operations Min  |
| Operating Temperature | -25 ~ +70°C (-13 ~ +158°F)  | -10 ~ +70°C (+14 ~ +158°F)  | -10 ~ +70°C (+14 ~ +158°F)  | -25 ~ +85°C (-13 ~ +185°F)  |
| External Dimensions   | 10.7 x 10.7mm (.421 x .421")  | 14.5 x 15.74mm (.571 x .620")   | 16mm Dia (.630" Dia)  | 10.0 x 10.0mm (.394 x .394")  |
| Process Sealed        | Yes   | Yes   | Yes   | No  |


**Subminiature & Ultra-Miniature DIP Rotaries**

**FR01**



- 10mm
- Ultra-Thin
- 100mA @ 5/50V DC
- Subminiature


**ND**



- 8mm
- Process Sealed
- 100mA @ 5/50V DC
- Ultra-Miniature


**SMT DIP Rotaries**

**FR02**



- 10mm
- Ultra-Thin
- 100mA @ 5/50V DC
- Subminiature


**ND3**



- 8mm
- Process Sealed
- 100mA @ 5/50V DC
- Ultra-Miniature


**Miniature & Subminiature Rotaries**

**NR01**




- Process Sealed
- Positive Detent
- 0.4VA @ 28V AC/DC
- Subminiature

**MRX**



- Positive Detent
- Metal Bushing & Housing
- 1A @ 30V DC
- Miniature


**MRB**



- Process Sealed
- IP67 Rated
- 0.4VA @ 28V AC/DC
- Miniature


**Standard Rotaries with Multiple Positions & Poles**

**HS13**




- 6A @ 125V AC
- 10mm Bushing

**TS**




- 6A @ 125/250V AC
- 10mm Bushing

**HS16**



- 12A @ 125V AC
- 10mm Bushing

**PS**



- 30A @ 125/250V AC
- 10mm Bushing

NKK offers optional knobs for Rotary Switches. See Accessories or contact our Sales Department.

Effective Date July 2017



7850 East Gelding Drive • Scottsdale, AZ 85260 • Telephone 480.991.0942 • Fax 480.998.1435





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.