

E D C B A						8 9 10																											
DIMENSIONS IN INCHES (MILLIMETERS) DO NOT SCALE DRAWING Dwg. No. CWR-181-XX-0000 NOTES: 1. Dimensions are in inches; dimensions in () are millimeters. 2. Metric equivalents are given for general information only, and are based upon 1.00 inches equals (25.4) millimeters. 3. Unless otherwise specified, tolerances are ±.005 (.13) for three place decimals, and ±.01 (.3) for two place decimals. MATERIALS: PLASTIC PARTS — UL94V-0 thermoplastic (blue, standard) flame retardant. CONTACTS — Phosphor bronze. CONTACT PLATING— Selective gold plating, .000010 (min.) gold in mating area and .000100(min.) Tin Plating on the termination end, All over .000050 (min.) nickel. OPERATING STANDARDS: TEMPERATURE RATING — 120° C CONTACT RATING — 1 ampere. DIELECTRIC STRENGTH — Over 500V.D.C. at sea level. CONDUCTORS ACCEPTED — 28-30 AWG solid or stranded. INSULATION RESISTANCE — Greater than 5 x 10⁹ ohms. <table border="1" style="display: inline-table; border-collapse: collapse; text-align: center;"> <thead> <tr> <th>NO. CONTS.</th> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>9</td> <td>.984 (24.99)</td> <td>.434 (11.02)</td> <td>.640 (16.26)</td> </tr> <tr> <td>15</td> <td>1.312 (33.32)</td> <td>.760 (19.30)</td> <td>.966 (24.54)</td> </tr> <tr> <td>25</td> <td>1.852 (47.04)</td> <td>1.303 (33.10)</td> <td>1.510 (38.35)</td> </tr> <tr> <td>37</td> <td>2.500 (63.50)</td> <td>1.955 (49.66)</td> <td>2.162 (54.91)</td> </tr> </tbody> </table>										NO. CONTS.	A	B	C	9	.984 (24.99)	.434 (11.02)	.640 (16.26)	15	1.312 (33.32)	.760 (19.30)	.966 (24.54)	25	1.852 (47.04)	1.303 (33.10)	1.510 (38.35)	37	2.500 (63.50)	1.955 (49.66)	2.162 (54.91)	CUSTOMER DRAWING			
NO. CONTS.	A	B	C																														
9	.984 (24.99)	.434 (11.02)	.640 (16.26)																														
15	1.312 (33.32)	.760 (19.30)	.966 (24.54)																														
25	1.852 (47.04)	1.303 (33.10)	1.510 (38.35)																														
37	2.500 (63.50)	1.955 (49.66)	2.162 (54.91)																														
REVISIONS <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>REV.</th> <th>DATE</th> <th>DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>12-04-96</td> <td>RELEASED.</td> </tr> <tr> <td>1</td> <td>12-04-96</td> <td>TIN-LEAD WAS REMOVED & TIN-PLATING WAS ADDED IN CONTACT PLATING.</td> </tr> </tbody> </table> APR 03 2006 ATTENTION THIS DRAWING AND ITS ATTACHMENTS, IF ANY, ARE PROPRIETARY TO CW INDUSTRIES AND DESCRIBE DESIGNS THAT ARE CONFIDENTIAL AND MUST NOT BE DISCLOSED UNLESS AUTHORIZED, IN WRITING, BY AN OFFICER OF CW INDUSTRIES..... CW INDUSTRIES Southampton, Pa. 18966 TOLERANCES UNLESS OTHERWISE SPECIFIED <table style="width: 100%;"> <tr> <td>2 Place Decimal ±.010</td> <td>METRIC</td> </tr> <tr> <td>3 Place Decimal ±.005</td> <td>1 Place Dec. ±.25mm</td> </tr> <tr> <td>Angles ±1°</td> <td>2 Place Dec. ±.13mm</td> </tr> </table> Made for: CW IND. Drawn by: DGW 12-04-96 Checked by: G. GUL 12-9-96 Approval: A. HOSFELD 12-7-96										REV.	DATE	DESCRIPTION	0	12-04-96	RELEASED.	1	12-04-96	TIN-LEAD WAS REMOVED & TIN-PLATING WAS ADDED IN CONTACT PLATING.	2 Place Decimal ±.010	METRIC	3 Place Decimal ±.005	1 Place Dec. ±.25mm	Angles ±1°	2 Place Dec. ±.13mm	Title: PLASTIC "D" CONNECTOR (PLUG) FEMALE CONTACTS Division: CONNECTOR Dwg. No. CWR-181-XX-0000								
REV.	DATE	DESCRIPTION																															
0	12-04-96	RELEASED.																															
1	12-04-96	TIN-LEAD WAS REMOVED & TIN-PLATING WAS ADDED IN CONTACT PLATING.																															
2 Place Decimal ±.010	METRIC																																
3 Place Decimal ±.005	1 Place Dec. ±.25mm																																
Angles ±1°	2 Place Dec. ±.13mm																																

MASTER



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.