3.3V Low Power EIA/TIA562 Transceiver

FEATURES

- **Operates from a Single 3.3V Supply**
- **Low Supply Current: I_{CC} = 200μA**
- ESD Protection Over ±10kV
- Available in 16-Pin SOIC Narrow Package
- Uses Small Capacitors: 0.1μF
- Operates to 120kBaud
- Output Overvoltage Does Not Force Current Back into Supplies
- EIA/TIA562 I/O Lines Can Be Forced to ±25V Without Damage
- Pin Compatible with LT1181A

APPLICATIONS

- Notebook Computers
- Palmtop Computers

DESCRIPTION

The LTC®1386 is an ultra-low power 2-driver/2-receiver EIA/TIA562 transceiver that operates from a single 3.3V supply. The charge pump requires only four space-saving 0.1μF capacitors. The supply current (I_{CC}) of the transceiver is only 200μA with driver outputs unloaded.

The LTC1386 is fully compliant with all data rate and overvoltage EIA/TIA562 specifications. The transceiver can operate up to 120kbaud with a 1000pF, 3kΩ load. Both driver outputs and receiver inputs can be forced to ±25V without damage and can survive multiple ±10kV ESD strikes.

, LTC and LT are registered trademarks of Linear Technology Corporation.

TYPICAL APPLICATION



Quiescent Supply Current vs Temperature



ABSOLUTE MAXIMUM RATINGS

Supply Voltage (V_{CC}) 5V
Input Voltage
  Driver ..... $-0.3V$ to $V_{CC} + 0.3V$
  Receiver ..... $-25V$ to $25V$
  Digital Input ..... $-0.3V$ to $V_{CC} + 0.3V$
Output Voltage
  Driver ..... $-25V$ to $25V$
  Receiver ..... $-0.3V$ to $V_{CC} + 0.3V$
Short-Circuit Duration
  V^+ ..... 30 sec
  V^- ..... 30 sec
  Driver Output ..... Indefinite
  Receiver Output ..... Indefinite
Operating Temperature Range
  LTC1386C ..... 0°C to 70°C
  LTC1386I ..... $-40°C$ to 85°C
Storage Temperature Range ..... $-65°C$ to 150°C
Lead Temperature (Soldering, 10 sec) ..... 300°C

PACKAGE/ORDER INFORMATION



S PACKAGE
16-LEAD PLASTIC SO

$T_{JMAX} = 125°C$, $\theta_{JA} = 95°C/W$

ORDER PART NUMBER
LTC1386CS
LTC1386IS

Consult LTC Marketing for parts specified with wider operating temperature ranges.

DC ELECTRICAL CHARACTERISTICS

The ● denotes specifications which apply over the full operating temperature range. V_{CC} = 3.3V, C1 = C2 = C3 = C4 = 0.1µF, unless otherwise noted.

PARAMETER	CONDITIONS			MIN	TYP	MAX	UNITS
Any Driver							
Output Voltage Swing	3k to GND	Positive	●	3.7	4.5		V
		Negative	●	–3.7	–4.5		V
Logic Input Voltage Level	Input Low Level (V_{OUT} = High)		●		1.4	0.8	V
	Input High Level (V_{OUT} = Low)		●	2.0	1.4		V
Logic Input Current	$V_{IN} = V_{CC}$		●			5	µA
	V_{IN} = 0V		●		–20	–40	µA
Output Short-Circuit Current	V_{OUT} = 0V			±9	±10		mA
Any Receiver							
Input Voltage Thresholds	Input Low Threshold		●	0.8	1.3		V
	Input High Threshold		●		1.7	2.4	V
Hysteresis			●	0.1	0.4	1	V
Input Resistance	$-10V \le V_{IN} \le 10V$			3	5	7	kΩ
Output Voltage	Output Low, $I_{OUT} = -1.6mA$ (V_{CC} = 3.3V)		●		0.2	0.4	V
	Output High, $I_{OUT} = 160µA$ (V_{CC} = 3.3V)		●	3.0	3.2		V
Output Short-Circuit Current	Sinking Current, $V_{OUT} = V_{CC}$			–5	–20		mA
	Sourcing Current, V_{OUT} = GND			2	7		mA
Power Supply Generator							
V^+ Output Voltage	I_{OUT} = 0mA				5.7		V
	I_{OUT} = 5mA				5.5		V
V^- Output Voltage	I_{OUT} = 0mA				–5.3		V
	$I_{OUT} = -5mA$				–5.0		V
Power Supply							
V_{CC} Supply Current	No Load (Note 2), 0°C to 70°C		●		0.2	0.5	mA
	No Load (Note 2), –40°C to 85°C		●		0.35	1.0	mA

AC CHARACTERISTICS

The ● denotes specifications which apply over the full operating temperature range.
V_{CC} = 3.3V, C1 = C2 = C3 = C4 = 0.1µF, unless otherwise noted.

PARAMETER	CONDITIONS		MIN	TYP	MAX	UNITS
Slew Rate	R_L = 3k, C_L = 51pF			8	30	V/µs
	R_L = 3k, C_L = 1000pF		3	5		V/µs
Driver Propagation Delay (TTL to EIA/TIA562)	t_{HLD} (Figure 1)	●		2	3.5	µs
	t_{LHD} (Figure 1)	●		2	3.5	µs
Receiver Propagation Delay (EIA/TIA562 to TTL)	t_{HLR} (Figure 2)	●		0.3	0.8	µs
	t_{LHR} (Figure 2)	●		0.3	0.8	µs

Note 1: Absolute Maximum Ratings are those values beyond which the life of the device may be impaired.

Note 2: Supply current is measured with driver and receiver outputs unloaded.

Note 3: Measurements made in the shutdown mode are performed with $V_{ON/\overline{OFF}}$=0V.

TYPICAL PERFORMANCE CHARACTERISTICS

Driver Output Voltage vs Temperature



Receiver Input Thresholds vs Temperature



Supply Current vs Data Rate



V_{CC} Supply Current vs Temperature



Driver Output Waveforms



Receiver Output Waveforms



PIN FUNCTIONS

V_{CC}: 3.3V Input Supply Pin. This pin should be decoupled with a 0.1μF ceramic capacitor.

GND: Ground Pin.

V^+: Positive Supply Output (EIA/TIA562 Drivers). $V^+ \cong 2V_{CC} - 1V$. This pin requires an external capacitor C = 0.1μF for charge storage. The capacitor may be tied to ground or V_{CC}. With multiple devices, the V^+ and V^- pins may share a common capacitor. For large numbers of devices, increasing the size of the shared common storage capacitors is recommended to reduce ripple.

V^-: Negative Supply Output (RS232 Drivers). $V^- \cong -(2V_{CC} - 1.3V)$. This pin requires an external capacitor C = 0.1μF for charge storage.

$C1^+$, $C1^-$, $C2^+$, $C2^-$: Commutating Capacitor Inputs. These pins require two external capacitors C = 0.1μF: one from $C1^+$ to $C1^-$ and another from $C2^+$ to $C2^-$. To maintain charge pump efficiency, the capacitor's effective series resistance should be less than 2Ω.

TR IN: EIA/TIA562 Driver Input Pins. Inputs are TTL/CMOS compatible. The inputs of unused drivers can be left unconnected since 300k input pull-up resistors to V_{CC} are included on chip.

TR OUT: Driver Outputs at EIA/TIA562 Voltage Levels. The driver outputs are protected against ESD to ±10kV for human body model discharges.

RX IN: Receiver Inputs. These pins can be forced to ±25V without damage. The receiver inputs are protected against ESD to ±10kV for human body model discharges. Each receiver provides 0.4V of hysteresis for noise immunity.

RX OUT: Receiver Outputs with TTL/CMOS Voltage Levels.

SWITCHING TIME WAVEFORMS



Figure 1. Driver Propagation Delay Timing



Figure 2. Receiver Propagation Delay Timing

TEST CIRCUITS

Driver Timing Test Load



LTC1386 • TA03

Receiver Timing Test Load



LTC1386 • TA04

ESD Test Circuit



1386 TA05

TYPICAL APPLICATIONS

Paralleling Power Supply Generator with Common Storage Capacitors



PACKAGE DESCRIPTION

S Package
16-Lead Plastic Small Outline (Narrow .150 Inch)
(Reference LTC DWG # 05-08-1610)



NOTE:
1. DIMENSIONS IN $\frac{\text{INCHES}}{(\text{MILLIMETERS})}$
2. DRAWING NOT TO SCALE
3. THESE DIMENSIONS DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS.
   MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED .006" (0.15mm)

Information furnished by Linear Technology Corporation is believed to be accurate and reliable. However, no responsibility is assumed for its use. Linear Technology Corporation makes no representation that the interconnection of its circuits as described herein will not infringe on existing patent rights.

RELATED PARTS

PART NUMBER	DESCRIPTION	COMMENTS
LT1780/LT1781	5V, 2 Driver, 2 Receiver RS232 Transeivers	±15kV ESD per IEC 1000-4
LTC1327	3.3V, 3 Driver, 5 Receiver RS562 Transceiver	300μA Supply Current, 0.2μA in Shutdown
LTC1348	3.3V to 5V, 3 Driver, 5 Receiver RS232 Transceiver	True RS232 on 3.3V, 5 Receivers Active in Shutdown
LTC1382	5V, 2 Driver, 2 Receiver RS232 Transceiver	220μA Supply Current, 0.2μA in Shutdown
LTC1383	5V, 2 Driver, 2 Receiver RS232 Transceiver	220μA Supply Current, Narrow 16-pin SO
LTC1384	5V, 2 Driver, 2 Receiver RS232 Transceiver	220μA Supply Current, 2 Receivers Active in Shutdown
LTC1385	3.3V, 2 Driver, 2 Receiver RS562 Transceiver	220μA Supply Current, 2 Receivers Active in Shutdown

Linear Technology Corporation
1630 McCarthy Blvd., Milpitas, CA 95035-7487
(408) 432-1900 • FAX: (408) 434-0507 • linear.com

LW/TP 1002 1K REV A • PRINTED IN USA

© LINEAR TECHNOLOGY CORPORATION 1994

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.