

#### Is Now Part of



## ON Semiconductor®

## To learn more about ON Semiconductor, please visit our website at www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (\_), the underscore (\_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (\_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at <a href="www.onsemi.com">www.onsemi.com</a>. Please email any questions regarding the system integration to Fairchild <a href="guestions@onsemi.com">guestions@onsemi.com</a>.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any EDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officer



August 2010

# **2N6517 NPN Epitaxial Silicon Transistor**

#### **Features**

- · High Voltage Transistor
- Collector Dissipation: P<sub>C</sub>(max) = 625mW
- Complement to 2N6520
- Suffix "-C" means Center Collector (1. Emitter 2. Collector 3. Base)



## **Absolute Maximum Ratings** $T_a = 25$ °C unless otherwise noted

Symbol	Parameter		Value	Units
V <sub>CBO</sub>	Collector-Base Voltage	2N6517 2N6517C	350 400	V V
V <sub>CEO</sub>	Collector-Emitter Voltage	2N6517 2N6517C	350 400	V V
V <sub>EBO</sub>	Emitter-Base Voltage		6	V
I <sub>C</sub>	Collector Current		500	mA
P <sub>C</sub>	Collector Power Dissipation		625	mW
T <sub>J</sub>	Junction Temperature		150	°C
T <sub>STG</sub>	Storage Temperature		-55 ~ 150	°C

## **Electrical Characteristics** $T_a = 25^{\circ}C$ unless otherwise noted

Symbol	Parameter	Conditions	Min.	Max.	Units
BV <sub>CBO</sub>		$I_{C} = 100\mu A, I_{E} = 0$ $I_{C} = 100\mu A, I_{E} = 0$	350 400		V V
BV <sub>CEO</sub>		I <sub>C</sub> = 1mA, I <sub>B</sub> = 0 I <sub>C</sub> = 1mA, I <sub>B</sub> = 0	350 400		V V
BV <sub>EBO</sub>	Emitter-Base Breakdown Voltage	$I_E = 10\mu A, I_C = 0$	6		V
I <sub>CBO</sub>	Collector Cut-off Current	V <sub>CB</sub> = 250V, I <sub>E</sub> = 0		50	nA
I <sub>EBO</sub>	Emitter Cut-off Current	$V_{EB} = 5V, I_{C} = 0$		50	nA
h <sub>FE</sub>	2N6517/2N6517C 2N6517/2N6517C 2N6517/2N6517C 2N6517/2N6517C	$V_{CE} = 10V, I_{C} = 1mA$ $V_{CE} = 10V, I_{C} = 10mA$ $V_{CE} = 10V, I_{C} = 30mA$ $V_{CE} = 10V, I_{C} = 50mA$ $V_{CE} = 10V, I_{C} = 100mA$ $V_{CE} = 10V, I_{C} = 5mA$	20 30 30 20 15 50	200 200 200	

## **Electrical Characteristics** (Continued) $T_a = 25$ °C unless otherwise noted

Symbol	Parameter	Conditions	Min.	Max.	Units
V <sub>CE(sat)</sub>	Collector-Emitter Saturation Voltage	I <sub>C</sub> = 10mA, I <sub>B</sub> = 1mA		0.3	V
(3.3.3)		$I_{C} = 20 \text{mA}, I_{B} = 2 \text{mA}$		0.35	V
		$I_{C} = 30 \text{mA}, I_{B} = 3 \text{mA}$		0.5	V
		$I_C = 50$ mA, $I_B = 5$ mA		1	V
V <sub>BE(sat)</sub>	Base-Emitter Saturation Voltage	I <sub>C</sub> = 10mA, I <sub>B</sub> = 1mA		0.75	V
(;;;)		$I_{C} = 20 \text{mA}, I_{B} = 2 \text{mA}$		0.85	V
		$I_C = 30\text{mA}, I_B = 3\text{mA}$		0.9	V
C <sub>ob</sub>	Output Capatitance	V <sub>CB</sub> = 20V, I <sub>E</sub> = 0, f = 1MHz		6	pF
f <sub>T</sub>	Current Gain Bandwidth Product *	$I_C = 10 \text{mA}, V_{CE} = 20 \text{V}, f = 20 \text{MHz}$	40	200	MHz
V <sub>BE(on)</sub>	Base-Emitter On Voltage	I <sub>C</sub> = 100mA, V <sub>CE</sub> = 10V		2	V

<sup>\*</sup> Pulse Test: Pulse Width  $\leq 300 \mu s,$  Duty Cycle  $\leq 2\%$ 

## **Typical Performance Characteristics**




Figure 1. DC Current Gain




Figure 2. Saturation Voltage




Figure 3. Saturation Voltage




Figure 4. Emitter Cut Off Current




Figure 5. Collector CutOff Current




Figure 6. Base-Emitter On Voltage

### **Typical Performance Characteristics** (Continued)




Figure 7. Output Capacitance




Figure 8. Input Capacitance




Figure 9. Current Gain Bandwidth Product




Figure 10. Resistive Load Switching





Figure 11. Resistive Load Switching

## **Physical Dimensions**

TO-92





Dimensions in Millimeters

(R2.29)





#### **TRADEMARKS**

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

Green FPS™ e-Series™

CROSSVOLT™

Gmax™

CTL™ GTO™

CTL™ GTO™

Current Transfer Logic™ IntelliMAX™

DEUXPEED® ISOPLANAR™

Dual Cool™ MegaBuck™

EcoSPARK® MICROCOUPLER™

EfficientMax™

ESBC™

MicroPak™

MicroPak™

MicroPak²™

MicroPak²™

MicroPak²™

MillerDrive™

MotionMax™

MotionMax™

Motion-SPM™

OptoHiT™

OPTOLOGIC®

PAST®

OPTOLOGIC®

FETBench™ FlashWriter®\* PDP SPM™ Power-SPM™ PowerTrench® PowerXS™

Programmable Active Droop™

QFĔT<sup>®</sup>
QS™
Quiet Series™
RapidConfigure™

**○**TM

Saving our world, 1mW/W/kW at a time™ SignalWise™

SmartMax™
SMART START™
SPM®
STEALTH™
SuperFET™
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SupreMOS®
SyncFET™
Sync-Lock™

SYSTEM ®\*

GENERAL

The Power Franchise®

Franchise

TinyBoost™

TinyBoost™

TinyCalc™

TinyCalc™

TinyCopTo™

TinyPower™

TinyPower™

TinyWMre™

TinyWire™

TriFault Detect™

TRUECURRENT™\*

µSerDes™

SerDes\*
UHC®
Ultra FRFET™
UniFET™
VCX™
VisualMax™
XS™

OPTOPLANAR®

#### DISCLAIMER

FastvCore™

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

#### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

#### As used herein:

- Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
- A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

#### ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

#### PRODUCT STATUS DEFINITIONS

#### **Definition of Terms**

ive / In Design	Datasheet contains the design specifications for product development. Specifications may change in
	any manner without notice.
oduction	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
oduction	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.
	oduction  Production

Rev. I49

<sup>\*</sup> Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

ON Semiconductor and in are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at <a href="www.onsemi.com/site/pdt/Patent-Marking.pdf">www.onsemi.com/site/pdt/Patent-Marking.pdf</a>. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and exp

#### **PUBLICATION ORDERING INFORMATION**

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com N. American Technical Support: 800-282-9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## **ON Semiconductor:**

2N6517CBU 2N6517TA 2N6517CTA 2N6517BU 2N6517TA\_Q 2N6517CTA\_Q



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

#### Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов:
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001:
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: <u>org@eplast1.ru</u>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина,

дом 2, корпус 4, литера А.