

For more Information  
please call

1-800-Belden1



## Description:

Tinned copper conductor, rubber insulated.

## Physical Characteristics (Overall)

### Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
1	18	65x36	TC - Tinned Copper

### Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
Rubber	1.143

### Overall Insulation

### Overall Cabling

Overall Nominal Diameter: 3.658 mm

## Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +90°C

Bulk Cable Weight: 22.323 Kg/Km

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

EU CE Mark:	No
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

### Plenum/Non-Plenum

Plenum (Y/N): No

## Electrical Characteristics (Overall)

Breakdown Voltage: 20000 V

Suggested Working Voltage: 5000 V

## Related Documents:

No related documents are available for this product

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8899 002U1000	305 MT	7.258 KG	RED		18 STR EPDM RED
8899 002U500	152 MT	3.856 KG	RED		18 STR EPDM RED
8899 002100	30 MT	0.998 KG	RED		#18 STR EPDM RED
8899 0021000	305 MT	6.804 KG	RED	C	#18 STR EPDM RED
8899 00225	8 MT	0.272 KG	RED		#18 STR EPDM RED
8899 002500	152 MT	3.856 KG	RED		#18 STR EPDM RED
8899 004100	30 MT	0.998 KG	YELLOW		#18 STR EPDM YEL
8899 004500	152 MT	3.629 KG	YELLOW		#18 STR EPDM YEL
8899 005100	30 MT	0.998 KG	GREEN, DARK		#18 STR EPDM DGRN
8899 005500	152 MT	3.856 KG	GREEN, DARK		#18 STR EPDM DGRN
8899 006100	30 MT	0.998 KG	BLUE, LIGHT		#18 STR EPDM LBLU
8899 006500	152 MT	3.856 KG	BLUE, LIGHT		#18 STR EPDM LBLU
8899 009100	30 MT	1.043 KG	WHITE		#18 STR EPDM WHT
8899 009500	152 MT	3.856 KG	WHITE		#18 STR EPDM WHT
8899 010U1000	305 MT	7.258 KG	BLACK		#18 STR EPDM BLK
8899 010U500	152 MT	3.856 KG	BLACK		18 STR EPDM BLK
8899 010100	30 MT	1.043 KG	BLACK		18 STR EPDM BLK
8899 0101000	305 MT	6.804 KG	BLACK	C	#18 STR EPDM BLK
8899 01025	8 MT	0.272 KG	BLACK		18 STR EPDM BLK
8899 010500	152 MT	3.856 KG	BLACK		#18 STR EPDM BLK

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 06-30-2010

© 2011 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.