

**Product:** [9740MN](#) 



SpaceMaker™, 2 C #18 Str TC, PO Ins, PVC Jkt, AWM 2937

 [Request Sample](#)

## Product Description

SpaceMaker™, 2 Conductor 18AWG (41x34) Tinned Copper, PO Insulation, PVC Outer Jacket, AWM 2937

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Pairs
18	41x34	TC - Tinned Copper	1

Conductor Count:

#### Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.010 in

#### Color Chart

Number	Color
1	Black & White
2	White
3	Red
4	Dark Green
5	Brown
6	Dark Blue
7	Orange
8	Yellow
9	Purple

#### Outer Shield Material

Material
No Shield

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.166 in	0.016 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
6.5 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor
15.3 pF/ft

#### Inductance

**Nominal Inductance**

0.170 µH/ft

**Impedance****Nominal Characteristic Impedance**

39 Ohm

**Voltage****UL Voltage Rating**

300 V RMS

**Temperature Range**

UL Temp Rating:	80°C
Operating Temp Range:	-20°C To +80°C

**Mechanical Characteristics**

Bulk Cable Weight:	16 lbs/1000ft
Max. Pull Tension:	45 lbs
Min Bend Radius During Installation:	0.660 in
Min Bend Radius (Continuous Flexing):	1.660 in

**Standards**

UL AWM Style Compliance:	AWM 2937 (300 V 80°C), NFPA 79
--------------------------	--------------------------------

**Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01

**Suitability**

Suitability - Indoor:	Yes
-----------------------	-----

**Flammability, LSOH, Toxicity Testing**

CSA Flammability:	FT2
UL voltage rating:	300 V RMS

**Part Number****Variants**

Item #	Color	Putup Type	Length	UPC
9740MN 006100	Blue, Light	Reel	100 ft	612825385578
9740MN 0061000	Blue, Light	Reel	1,000 ft	612825385608
9740MN 008100	Gray	Reel	100 ft	612825385585
9740MN 0081000	Gray	Reel	1,000 ft	612825382713
9740MN 004100	Yellow	Reel	100 ft	612825385561
9740MN 0041000	Yellow	Reel	1,000 ft	612825385592

**History**

Update and Revision:	Revision Number: 0.161 Revision Date: 04-28-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.