



NETWORK-ATTACHED
USB HUB



ANYWHEREUSB®

Network-attached USB hub connects USB peripheral devices anywhere on a LAN – without a locally-attached host PC

AnywhereUSB products are network-attached USB hubs that connect USB peripheral devices to a PC over a Local Area Network. The AnywhereUSB TS model also adds four RS-232 serial ports, enabling the mixing of USB and serial ports over the same network connection.

The AnywhereUSB software drivers are loaded onto a host PC or server so that USB devices attached to the AnywhereUSB hub may communicate with the host PC without changing existing device application software. AnywhereUSB drivers work equally well on physical servers or virtual machines in virtualized environments. Peripheral USB devices can be

centrally managed and monitored from a remote server or PC. The Multi-Host Connections feature allows multiple host PCs to establish connections with the AnywhereUSB hub concurrently, where each PC takes ownership of a group of USB ports on the AnywhereUSB hub.

Relocating the host PC to a remote location translates to smaller workstations, enabling deployment without a local PC in kiosks, ATMs, restaurant kitchens, manufacturing lines or any hostile or non-secure area where having a local PC is not practical.

USB storage devices and USB modems are not supported.
Digi's Edgeport/1 USB-to-serial converter may be used to connect a serial modem.

BENEFITS

- Network-attached USB hub easily connects remote USB devices to a LAN
- Ideal for connecting USB devices over the network in virtualized environments such as VMware®
- AnywhereUSB/14 rack mountable product has two built-in power supplies and two Ethernet connections for redundancy
- Access and monitor USB and serial devices over a TCP/IP connection
- Compatible with bulk or interrupt type USB devices
- Multi-Host connections (on select models)

RELATED PRODUCTS



Watchport®
Camera



Watchport®
Sensors



Hubport®




Edgeport®
Family




TransPort®
WR21

APPLICATION EXAMPLE




SPECIFICATIONS	AnywhereUSB®/2 AnywhereUSB®/5 AnywhereUSB®/5M AnywhereUSB® TS AnywhereUSB®/14				
INTERFACES					
10/100BASE-T ETHERNET	1 RJ-45	1 RJ-45	1 RJ-45	1 RJ-45	2 RJ-45
USB	2	5	5	4	14
SERIAL	N/A	N/A	N/A	4 RS-232 RJ-45	1 RS-232 DB9
FEATURES					
IP ADDRESS	1 static (fixed) address per unit				
LEDS	System and Port status				
POWER SUPPLY	Ships with 120-240 VAC 50-60 Hz at 5 VDC @ 3 amps max w/ locking barrel	Ships with 120-240 VAC 50-60 Hz at 5 VDC @ 3 amps max w/ locking barrel	Ships with 120-240 VAC 50-60 Hz at 5 VDC @ 3 amps max w/ locking barrel	Ships with 120-240 VAC 50-60 Hz at 5 VDC @ 3 amps max w/ locking barrel	Includes 2 120-230 VAC 50-60 Hz @ 8 amps max
MANAGEMENT	CLI and AnywhereUSB web configuration tool				
SECURITY	OpenSSL w/ AES-128				
OTHER SHARED FEATURES	Remote configuration utility; Multiple units supported per server; Field-upgradable software and firmware; Patented RealPort® (serial over IP) and RealPort USB (USB over IP)				
SERIAL DATA RATES	N/A	N/A	N/A	Up to 230 Kbps per port	Up to 230 Kbps per port
USB DOWNSTREAM POWER	500 mA per USB device				
USB COMPATIBILITY	USB 2.0, 1.1, 1.0 Note: USB storage devices and USB modems are not supported. Digi's Edgeport®/1 USB-to-serial converter may be used to connect a serial modem.				
OPERATING SYSTEMS	Windows® 10, Windows® 8, Windows® 7, Windows Vista®, Windows Server® 2012 R2, Windows® Server 2008 R2, Windows® Server 2003, Windows XP®, Windows XP® Embedded				
MULTI-HOST CONNECTIONS	N/A	N/A	Yes	N/A	Yes
DIMENSIONS (L X W X H)	2.38 in x 3.9 in x 1.0 in (6.04 cm x 10.0 cm x 2.54 cm)	4.35 in x 7.20 in x 1.03 in (11.05 cm x 18.29 cm x 2.61 cm)	4.35 in x 7.20 in x 1.03 in (11.05 cm x 18.29 cm x 2.61 cm)	4.35 in x 7.20 in x 1.03 in (11.05 cm x 18.29 cm x 2.61 cm)	4.97 in x 17.00 in x 1.74 in (12.62 cm x 43.18 cm x 4.42 cm), Rack mountable 1U
WEIGHT	5.0 oz (141.8 g)	10.0 oz (283.5 g)	10.0 oz (283.5 g)	10.0 oz (283.5 g)	40 oz (1134 g)
ENVIRONMENTAL					
OPERATING TEMPERATURE	32° F to 140° F (0° C to 60° C)	32° F to 140° F (0° C to 60° C)	32° F to 140° F (0° C to 60° C)	32° F to 140° F (0° C to 60° C)	32° F to 131° F (0° C to 55° C)
STORAGE TEMPERATURE	-40° F to +185° F (-40° C to +85° C)				
RELATIVE HUMIDITY	0% to 95% (non-condensing)				
NETWORK AND DEVICE RECOMMENDATIONS					
NETWORK TYPE	10/100 Mb switched Ethernet	10/100 Mb switched Ethernet	10/100 Mb switched Ethernet	10/100 Mb switched Ethernet	Dual 10/100 Mb switched Ethernet
USB DEVICE TYPES	Compatible with bulk or interrupt type USB devices; Isochronous devices not supported				
REGULATORY APPROVALS					
SAFETY	UL 1950/CSA 2.2 No. 950, EN60950, IEC-950				
EMISSIONS/IMMUNITY	CE, FCC Part 15 (Class B), EN55022, EN55024				


AnywhereUSB/5 AnywhereUSB/5M - Front




AnywhereUSB/2 - Front




AnywhereUSB TS - Front




AnywhereUSB/14 - Front




AnywhereUSB/5 AnywhereUSB/5M - Back




AnywhereUSB TS - Front



AnywhereUSB TS - Back



AnywhereUSB/14 - Front



PART NUMBERS	DESCRIPTION
14-PORT MODEL	
AW-USB-14	AnywhereUSB/14 with Multi-Host Connections
AW-USB-14-W	AnywhereUSB/14 with Multi-Host Connections (International)
2-PORT MODEL	
AW-USB-2	AnywhereUSB/2
AW-USB-2-W	AnywhereUSB/2 (International)
5-PORT MODEL	
AW-USB-5	AnywhereUSB/5 Gen 2
AW-USB-5M	AnywhereUSB/5 with Multi-Host Connections
AW-USB-5M-W	AnywhereUSB/5 with Multi-Host Connections (International)
AW-USB-5-W	AnywhereUSB/5 Gen 2 (International)
TS MODEL	
AW-TS-44	AnywhereUSB TS - 4 serial and 4 USB ports
AW-TS-44-W	AnywhereUSB TS - 4 serial and 4 USB ports (International)

FOR MORE INFORMATION
PLEASE VISIT WWW.DIGI.COM

DIGI SERVICE AND SUPPORT / You can purchase with confidence knowing that Digi is always available to serve you with expert technical support and our industry leading warranty. For detailed information visit www.digi.com/support.

© 1996-2015 Digi International Inc. All rights reserved.
All trademarks are the property of their respective owners.

91001219
F1/915

DIGI INTERNATIONAL WORLDWIDE HQ
877-912-3444 / 952-912-3444 / www.digi.com

DIGI INTERNATIONAL FRANCE
+33-1-55-61-98-98 / www.digi.fr

DIGI INTERNATIONAL JAPAN
+81-3-5428-0261 / www.digi-intl.co.jp

DIGI INTERNATIONAL SINGAPORE
+65-6213-5380

DIGI INTERNATIONAL CHINA
+86-21-50492199 / www.digi.com.cn





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.