




Differential LVPECL Voltage Controlled Crystal Oscillator

CVPD-920 Model 9X14 mm SMD, 3.3V, LVPECL


Frequency Range:	50MHz to 125MHz
Frequency Pulling:	±20ppm APR Min
Temperature Range:	0°C to 70°C
	(Option X)
	-40°C to 85°C
Storage:	-55°C to 120°C
Input Voltage:	3.3V ±0.3V
Control Voltage:	1.65V ±1.65V
Input Current:	88mA Max
Output:	Differential LVPECL
	Symmetry: 45/55% Max @ 50% Vcc
	Rise/Fall Time: 1ns Max @ 20% to 80% Vcc
	Linearity: ±10% Max
	Logic: Terminated to Vcc-2V into 50 ohms
	"0" = Vcc-1.85V Min, Vcc-1.62V Max
	"1" = Vcc-1.02V Min, Vcc-0.81V Max
	200ns
	Disable Time: 1ms Typ., 2ms Max
Phase Jitter:	12KHz to 80MHz 0.5psec Typ., 1psec RMS Max
Phase Noise:	10Hz -65dBc/Hz Typical
	100Hz -98dBc/Hz Typical
	1KHz -125dBc/Hz Typical
	10KHz -140dBc/Hz Typical
	100KHz -145dBc/Hz Typical
Aging:	<3ppm 1st/yr, <1ppm every year thereafter




Designed to meet today's requirements for 3.3V Differential LVPECL applications. The CVPD-920 is produced using our cost saving FR5 PCB and UM-1 overtone crystal technology. This design offers considerable cost savings over other HFF VCXO products when broad frequency pulling is not required. Also available in 14 pin dip fully hermetic package.



SUGGESTED PAD LAYOUT



RECOMMENDED REFLOW SOLDERING PROFILE



NOTE: Reflow Profile with 240°C peak also acceptable.

PIN	Function
1	Control Volt
2	E/D
3	GND
4	OUT
5	COU
6	Vcc

Crystek Part Number Guide

CVPD-920 X - 100.000

#1 #2 #3 #4

#1 Crystek 9x14 SMD PECL VCXO
#2 Model 920
#3 Temp. Range: Blank = 0/70°C, X=-40/85°C
#4 Frequency in MHz: 3 or 6 decimal places

Example:
CVPD-920X-25-100.000 = 3.3V, 45/55, -40/85°C, 25ppm, 100.000 MHz

Enable/Disable Function

Pin 2	Output Pin
Open	Active
"0" level Vcc-1.620V Max	Active
"1" level Vcc-1.025V Min	Disabled
Disabled State: Pin 4 will assume a fixed level of logic "0" Pin 5 will assume a fixed level of logic "1"	

Specifications subject to change without notice.

TD-030701 Rev. D



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.