



### Main

|                           |   |
|---------------------------|---|
| Range of product          | Preventa XY2  |
| Product or component type | Latching emergency stop rope pull switch                                |
| Device short name         | XY2CE   |
| Housing colour            | Red RAL 3000  |
| Overtoltage category      | Class I conforming to EN/IEC 61140<br>Class I conforming to NF C 20-030 |

### Complementary

|  |   |
|--|---|
| Local signalling                             | Without pilot light   |
| Number of cables                             | 1   |
| Trigger cable maximum length                 | 229.66 ft (70 m)  |
| Body material                                | Zamak   |
| Cover material                               | Stainless steel   |
| Reset  | By key-release push-button  |
| Trigger cable anchor point                   | RH side   |
| Connections - terminals                      | Screw clamp terminal 1 x 0.5...2 x 1.5 mm <sup>2</sup>  |
| Tightening torque                            | 7.08...10.62 lbf.in (0.8...1.2 N.m)   |
| Cable entry number                           | 3   |
| Safety level                                 | Can reach category 4 with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1<br>Can reach PL = e with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1<br>Can reach SIL 3 with the appropriate monitoring system and correctly wired conforming to EN/IEC 61508 |
| Safety reliability data                      | B10d = 300000 with value given for a life time of 20 years limited by mechanical or contact wear conforming to IEC 60947-5-5  |
| Marking                                      | CE  |
| Mechanical durability                        | 60000 cycles  |
| Distance between cable supports              | 16.4 ft (5 m)   |
| [Ie] rated operational current               | 3 A at 240 V AC-15, A300 conforming to EN/IEC 60947-5-1 appendix A<br>0.27 A at 250 V DC-13, Q300 conforming to EN/IEC 60947-5-1 appendix A   |
| [Ithe] conventional enclosed thermal current | 10 A  |
| [Ui] rated insulation voltage                | 500 V (degree of pollution: 3) conforming to EN/IEC 60947-1<br>300 V (degree of pollution: conforming to UL 508<br>300 V (degree of pollution: conforming to CSA C22.2 No 14  |
| [Uimp] rated impulse withstand voltage       | 6 kV conforming to EN/IEC 60947-1   |
| Positive opening                             | With conforming to EN/IEC 60947-5-1   |
| Resistance across terminals                  | <= 25 MOhm conforming to NF C 93-050 method A<br><= 25 MOhm conforming to EN/IEC 60255-7 category 3   |
| Short-circuit protection                     | 10 A by gG cartridge fuse conforming to EN/IEC 60269  |
| Terminals description ISO n°1                | (21-22)NC<br>(11-22)NC  |
| Product weight                               | 3.24 lb(US) (1.47 kg)   |

### Environment

|           |                                    |
|-----------|------------------------------------|
| standards | EN/IEC 60204-1<br>EN/IEC 60947-5-1 |
|-----------|------------------------------------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

EN/IEC 60947-5-5  
 EN/ISO 13850  
 UL 508  
 Machinery directive 2006/42/EC  
 CSA C22.2 No 14  
 Work equipment directive 2009/104/EC

|                                       |  |
|---------------------------------------|--|
| product certifications                | UL category NISD emergency stop devices<br>CSA<br>CCC  |
| protective treatment                  | TC   |
| ambient air temperature for operation | -40...158 °F (-40...70 °C)                             |
| ambient air temperature for storage   | -40...158 °F (-40...70 °C)                             |
| vibration resistance                  | 10 gn (f = 10...300 Hz) conforming to EN/IEC 60068-2-6 |
| shock resistance                      | 50 gn 11 ms conforming to EN/IEC 60068-2-27            |
| IP degree of protection               | IP65 conforming to IEC 60529                           |

### Offer Sustainability

|  |  |
|--|--|
| Green Premium product  | Green Premium product  |
| Compliant - since 1618 - Schneider Electric declaration of conformity  | Compliant - since 1618 - Schneider Electric declaration of conformity  |
| Reference not containing SVHC above the threshold  | Reference not containing SVHC above the threshold  |
| Available  | Available  |
| Need no specific recycling operations  | Need no specific recycling operations  |
| WARNING: This product can expose you to chemicals including:   | WARNING: This product can expose you to chemicals including:   |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.