

For more Information
please call

1-800-Belden1



Description:

Stranded silver-coated copper conductor insulation with extruded TFE Teflon.

Physical Characteristics (Overall)

Conductor

AWG:

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|----------------------------|
| 1 | 16 | 19x29 | SPC - Silver Plated Copper |

Insulation

Insulation Material:

| Insulation Material | Wall Thickness (mm) |
|---------------------------|---------------------|
| TFE - Tetrafluoroethylene | 0.3048 |

Overall Insulation

Overall Cabling

Overall Nominal Diameter: 1.956 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|--------------------------------------|
| UL AWM Style: | 1371 |
| UL Rating: | 105°C |
| EU CE Mark: | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 04/01/2005 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |
| Military Specification: | MIL-W-16878/4 (Except For Stranding) |
| MIL Spec Rating: | 600 V, 200°C |

Flame Test

UL Flame Test: VW-1

Plenum/Non-Plenum

Plenum (Y/N): No

Related Documents:

No related documents are available for this product

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|--------------|-------|-------------|-------|-------|-----------------|
| 83010 001100 | 30 MT | 0.544 KG | BROWN | | #16 STR TFE BRN |

METRIC MEASUREMENT VERSION

83010 Hook-up/Lead - UL AWM Style 1371

| | | | | | |
|---------------|--------|----------|-------------|-------|-------------------|
| 83010 0011000 | 305 MT | 4.990 KG | BROWN | S W Z | #16 STR TFE BRN |
| 83010 001500 | 152 MT | 2.722 KG | BROWN | S W | #16 STR TFE BRN |
| 83010 002100 | 30 MT | 0.544 KG | RED | | #16 STR TFE RED |
| 83010 0021000 | 305 MT | 4.990 KG | RED | S W | #16 STR TFE RED |
| 83010 002500 | 152 MT | 2.722 KG | RED | S W | #16 STR TFE RED |
| 83010 003100 | 30 MT | 0.544 KG | ORANGE | | #16 STR TFE ORG |
| 83010 0031000 | 305 MT | 4.990 KG | ORANGE | S W | #16 STR TFE ORG |
| 83010 003500 | 152 MT | 2.722 KG | ORANGE | S W | #16 STR TFE ORG |
| 83010 004100 | 30 MT | 0.544 KG | YELLOW | | #16 STR TFE YEL |
| 83010 0041000 | 305 MT | 4.990 KG | YELLOW | S W | #16 STR TFE YEL |
| 83010 004500 | 152 MT | 2.722 KG | YELLOW | S W | #16 STR TFE YEL |
| 83010 005100 | 30 MT | 0.544 KG | GREEN, DARK | | #16 STR TFE GRNDK |
| 83010 0051000 | 305 MT | 4.990 KG | GREEN, DARK | S W | #16 STR TFE GRNDK |
| 83010 005500 | 152 MT | 2.722 KG | GREEN, DARK | S W | #16 STR TFE GRNDK |
| 83010 006100 | 30 MT | 0.544 KG | BLUE, LIGHT | | #16 STR TFE BLULT |
| 83010 0061000 | 305 MT | 4.990 KG | BLUE, LIGHT | S W | #16 STR TFE BLULT |
| 83010 006500 | 152 MT | 2.722 KG | BLUE, LIGHT | S W | #16 STR TFE BLULT |
| 83010 007100 | 30 MT | 0.544 KG | VIOLET | | #16 STR TFE VIO |
| 83010 007500 | 152 MT | 2.722 KG | VIOLET | S W | #16 STR TFE VIO |
| 83010 008100 | 30 MT | 0.544 KG | GRAY | | #16 STR TFE GRY |
| 83010 0081000 | 305 MT | 4.990 KG | GRAY | S W | #16 STR TFE GRY |
| 83010 008500 | 152 MT | 2.722 KG | GRAY | S W | #16 STR TFE GRY |
| 83010 009100 | 30 MT | 0.544 KG | WHITE | | #16 STR TFE WHT |
| 83010 0091000 | 305 MT | 4.990 KG | WHITE | S W | #16 STR TFE WHT |
| 83010 009500 | 152 MT | 2.722 KG | WHITE | S W | #16 STR TFE WHT |
| 83010 010100 | 30 MT | 0.544 KG | BLACK | | #16 STR TFE BLK |
| 83010 0101000 | 305 MT | 4.990 KG | BLACK | S W | #16 STR TFE BLK |
| 83010 010500 | 152 MT | 2.722 KG | BLACK | S W | #16 STR TFE BLK |

Notes:

S = STRIPING ADDERS FOR TYPES E AND EE: 123 STRIPES. MINIMUM ORDER 10

W = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 75'

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 1 Revision Date: 05-14-2007

© 2011 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.