Pneumatic logic components



Operating fluid
- Compressed air or inert gas.

Conditions of use
- Operating pressure 2 at 8 bars (except for special conditions).
- Fluid: Filtered air to 50 microns - non lubricated.
- Operating temperature from - 5° C to + 50° C (under + 5° C the dew point must be below 10° C for the application).
- For optimum performance, the elements should be inter-connected by air supply tubing with an internal diameter ≥ at 2.5 mm.

Mounting recommendations
- The elements should be mounted and piped in a clean atmosphere in order to prevent any form of pollution entering the system.
- Minimum torque for element fixing screws: 5 cm/kg.
- maximum torque for element fixing screws: 10 cm/kg.

Characteristics common to all elements in the modular system
- The characteristics have been obtained with a supply pressure at 6 bars.
- The flow in NI/min is the number of litres of air at normal atmospheric pressure obtained with the output open to atmophere and the supply pressure at 4 bars
- The consumption in NI/min is the number of litres of free air necessary for the unit to function.
- kV = the flow coefficient of the equipment.
- Mechanical life > 10^7 operations.

flow graphs



Sequencer modules

Operation results from the combination of a sequential cycle. A system comprises individual modules which are joined together by means of a sub-base. Each module has a memory which delivers an output signal and receives an input signal.

An indicator on each module allows the operator to monitor the progress of the cycle and identity quickly and easily any fault which may occur.



Operation results from the combination of three functions (memory, AND and OR) which constitute each module.

The memory activates the output and gives priority to the reset signal. The AND element ensures the transition to the next module but only if an input signal is present.
The OR element ensures the resetting of all previously operated modules

Function diagram



sequencer module with maintained reset

Brake

This maintains the memory spool in position only when the supply is lost.

Module with auto reset



Brake

This returns the memory spool to the reset condition only when the supply is lost

Shift register

The general principle is to advance the sequencer step by command impulses to the inputs of the even steps, alternating with the command impulses to the inputs of the odd steps.

Used for example on a transfer machine to shift the information "bad component" collected at a test-test "n" steps further along the machine to a reject station.

Function diagram



Auto reset sequencer module



Sequencer modules

- **100 % pneumatic**
- **Ideal for a simple pneumatic sequence**

Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive





		81 550 001	81 550 201	81 550 401	81 550 601
Versions	sequencer	with 'maintain'	Reset to zero	—	—
	shift register	—	—	with 'maintain'	Reset to zero

Symbol



Characteristics

Operating pressure	bar	2 → 8	2 → 8	2 → 8	2 → 8
Orifice diameter	mm	2.7	2.7	2.7	2.7
Flow at 6 bars	Nl/min	150	150	150	150
Operating temperature	°C	-5 → +50	-5 → +50	-5 → +50	-5 → +50
Mechanical life 5 x 10^6 at 6 bars		●	●	●	●
Connection - Sub-base page 26		●	●	●	●
Weight	g	70	70	70	70



Principle of operation

(supplied without logic element. For choice of units see pages 46/47)

Sequencer module with maintained reset



1 - Input signal
2 - Supply
3 - Output signal
4 - Start signal
5 - In cycle signal
6 - End of cycle signal
7 - Reset to zero signal

Shif register with maintained reset



1 - Input signal
2 - Supply
3 - Output signal
4 - Start signal
5 - In cycle signal
6 - End of cycle signal
7 - Reset to zero signal

Dimensions



Mounting plan for sequencer



ATEX version products are available in the following catologues: **Pneumatic products for explosive atmospheres** or on our website **www.crouzet.com**

Sequencer sub-bases

Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive







		81 551 101	81 552 101	81 552 601
Versions	Front connecting (DIN-omega)	Sub-base (DIN oméga)	End bases - one pair	Diversion base
	Rear connecting (with clips)	—	—	—

Characteristics

Sub-bases (fitted)	Rotatable connectors		●	●	●
	Pressure indicators		●	●	●
Operating temperature		°C	-5 → +50	-5 → +50	-5 → +50
Weight		g	55	135	60

Sequencer connections

Front connecting









1 - Input port (green port 1) Ø 4
2 - Output port (red port 1) Ø 4
3 - Input port, cycle start (green port 1) Ø 4
4 - Output port, in-cycle signal (red port 1) Ø 4
5 - Output port, cycle end (red port 6) Ø 4
6 - Output port, cycle end (red port 6) Ø 4
7 - Input port, reset to zero (green port 7) Ø 4
8 - Output indicator (red)
9 - Input indicator (green)
10 - Cycle start indicator at port 4 (green)
11 - In-cycle indicator at port 5 (red)
12 - Input indicator at port 7 (green)
13 - End of cycle indicator at port 6 (red)
14 - Supply indicator at port 2 (yellow)
15 - Interconnecting ports
16 - Fixing screws
17 - Engraved arrow to indicate direction of sequence
18 - Marking tag
19 - Marking tag position
20 - Marking tag position
21 - Mounting tongue
22 - Mounting groove
23 - Sub-base
24 - End bases

Dimensions

Front connecting







81 551 001	81 552 001
—	—
Sub-base (with clips)	End bases - one pair

—	—
—	●
-5 → +50	-5 → +50
40	120

Rear connecting



1 - Input port (marked port 1)
2 - Supply port (Port 2)
3 - Output port (Port 3)
4 - Cycle start signal port (Port 4)
5 - In-cycle signal port (Port 5)
6 - End of cycle signal port (Port 6)
7 - Reset to zero signal port (Port 7)
8 - Indicator at supply port
9 - Marking area

Rear connecting



ATEX version products are available in the following catologues: **Pneumatic products for explosive atmospheres** or on our website **www.crouzet.com**

Logic elements

- **Performs "combined" Pneumatic**
- **Easy to use**

Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



Functions	OR	81 521 501	81 540 001	81 540 005	81 522 501
	AND	—	—	—	—
	YES	—	—	—	—
	NO	—	—	—	—
Version		On Sub-base page 4/14-4/15	Plug-in Ø 4	Plug-in Ø 6	On Sub-base page 4/14-4/15

Symbol





Characteristics

Push-in connection for semi-rigid tubing (NFE 49100)	Male/Female/Female	—	Ø 4 mm	—	—
	Female/Female/Female	—	—	Ø 6 mm	—
Colour		Blue	Blue	Blue	Green
Operating pressure	bar	2 → 8	2 → 8	2 → 8	2 → 8
Orifice diameter	mm	2.7	2.7	4	2.7
Flow at 6 bars	Nl/min	170	170	200	170
Pressure indicator		●	—	—	●
Switching time	ms	—	—	—	—
Operating temperature	°C	-5 → +50	-5 → +50	-5 → +50	-5 → +50
Mechanical life	operations	$>10^7$	$>10^7$	$>10^7$	$>10^7$
Weight	g	25	12	25	25

Pilot/pressure curves

P.p : Pilot pressure
P.a : Supply pressure

4

Principle of operation



Cellule OR

The output signal "S" is present when a signal at "a" OR "b" is present:

S = a OR b S = a + b



Cellule AND

The output signal "S" is present only when signals "a" AND "b" are present simultaneously:

S = a AND b S = a . b

Dimensions

81 521 501 - 81 522 501



81 540 005 - 81 541 005



81 540 001 - 81 541 001



Other information

See pages 54/55 for mounting plan for logic elements.

					
—	—	—	—	—	—
81 541 001	81 541 005	—	—	—	—
—	—	81 501 025	81 503 025	—	—
—	—	—	—	81 504 025	81 506 025
Plug-in Ø 4	Plug-in Ø 6	On sub-base page 36-37	Threshold On sub-base page 4/14-4/15	Threshold On sub-base page 4/14-4/15	Threshold On sub-base page 4/14-4/15
					
Ø 4 mm	—	—	—	—	—
—	Ø 6 mm	—	—	—	—
Green	Green	Yellow	Orange	Light grey	Dark grey
2 → 8	2 → 8	2 → 8	2 → 8	2 → 8	2 → 8
2.7	4	2.7	2.7	2.7	2.7
150	200	170	170	170	170
—	●	●	●	●	●
—	—	< 4	< 4	< 4	< 4
-5 → +50	-5 → +50	-5 → +50	-5 → +50	-5 → +50	-5 → +50
$>10^7$	$>10^7$	$>10^7$	$>10^7$	$>10^7$	$>10^7$
13	25	30	30	30	30
					



YES element

The output signal "S" is only present when the pilot is present "a" is present:

S = a YES b S = a



NOT element

The output signal "s" is present only if the input signal "a" is NOT present. The output signal is therefore the inverse of the pilot signal:

S= NOT a $S = \overline{a}$

If the supply port is connected to a 2nd input "b", the function obtained is called inhibition:

S = NOT a AND b $S = \overline{a} \cdot b$

81 501 025 - 81 503 025
81 504 025 - 81 506 025



ATEX version products are available in the following catologues: **Pneumatic products for explosive atmospheres** or on our website **www.crouzet.com**

Memory element

- **100 % pneumatic**
- **Bistable pneumatic**

Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



Version	81 523 201 With pressure indicator	81 523 601 With pressure indicator and manual override

Symbol



Characteristics

Colour		Black	Black
Operating pressure	bar	2 → 8	2 → 8
Orifice diameter	mm	2.7	2.7
Minimum memory pilot pressure	bar	2.5	2.5
Operating temperature	°C	-5 → +50	-5 → +50
Flow at 6 bars	Nl/min	200	200
Connection - On sub-base page 4/14-4/15		●	●
Weight	g	90	90

Principle of operation

The function is that of a 4/2 valves. The appearence of signal "X1" causes the displacement of the slide valve. The output port "x" is then put under pressure. This state is remembered until the arrival of signal "X0". This signal reverses the slide valve, the output "x" is put under pressure. This state is likewise remembered. The output:

- "x" under pressure indicates that the information in the MEMORY is "X1",
- "x" under pressure indicates that the information in the MEMORY is "X0".



Dimensions

81 523 201 - 81 523 601



Dimensions of logic and memory elements



Viewed from above

ATEX version products are available in the following catologues: **Pneumatic products for explosive atmospheres** or on our website **www.crouzet.com**

Timers fixed timing

■ Fixed 0.4 s

Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



	81 503 540
Version	Positive output

Symbol



Characteristics

Timing	s	0.4
Operating pressure	bar	2 → 8
Flow at 6 bars	Nl/min	170
Orifice diameter	mm	2.7
Accuracy	%	± 5
Min. reset time	s	<0.1
Connection - On sub-base page 36-37		●
Operating temperature	°C	-5 → +50
Mechanical life	operations	$>10^7$
Weight	g	106

Principle of operation
with positive output



Dimensions
81 503 540



ATEX version products are available in the following catologues: **Pneumatic products for explosive atmospheres** or on our website **www.crouzet.com**

Timers (with adjustable timing)

■ 60 s adjustable (60 s max.)

Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive





		81 503 710	81 506 710	81 503 720	81 506 720	81 503 725	81 506 725
Function	positive	●	—	●	—	●	—
	negative	—	●	—	●	—	●

Symbol



Characteristics

Timing	s	0.1 → 15	0.1 → 15	0.1 → 30	0.1 → 30	0.1 → 60	0.1 → 60
Operating pressure	bar	2 → 8	2 → 8	2 → 8	2 → 8	2 → 8	2 → 8
Flow at 6 bars	Nl/min	170	170	170	170	170	170
Orifice diameter	mm	2.7	2.7	2.7	2.7	2.7	2.7
Accuracy	%	± 5	± 5	± 5	± 5	± 5	± 5
Min. reset time	s	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1
Connection - On sub-base page 4/14-4/15		●	●	●	●	●	●
Operating temperature	°C	-5 → +50	-5 → +50	-5 → +50	-5 → +50	-5 → +50	-5 → +50
Mechanical life	operations	$>10^7$	$>10^7$	$>10^7$	$>10^7$	$>10^7$	$>10^7$
Weight	g	90	90	100	100	120	120

Accessories

Panel mounting adaptator		79 451 698	79 451 698	79 451 903	79 451 903	—	—
Weight	g	53	53	53	53	—	—

Principle

The operation of these pneumatic timers is similar to that of electronic timers (circuit with capacitor/resistor)

Timing by charging of reservoir



The reservoir fills via the flow restrictor until the switching point of the timer output is reached (positive or negative).
The non-return valve allows the reservoir to be emptied rapidly for the next timing.

Principle of operation

with positive output



with negative output



Dimensions



	L (mm)
81 503 710 - 81 506 710	78
81 503 720 - 81 506 720	92
81 503 725 - 81 506 725	125

Adaptator 79 451 . . .





For panel mounting, a pre-drilled hole Ø 10.5 mm si required

ATEX version products are available in the following catologues: **Pneumatic products for explosive atmospheres** or on our website **www.crouzet.com**

Timers

■ Fixed and adjustable

Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive





Single impulse generator	Fixed	81 507 540	—	—
	Adjustable	—	81 507 720	—
Adjustable frequency generator		—	—	81 506 940

Symbol





Characteristics

Timing	s	0.4	0.1 → 30	—
Frequency	Hz	—	—	0.02 → 8
Operating pressure	bar	2 → 8	2 → 8	2 → 8
Flow at 6 bars	Nl/min	170	170	170
Orifice diameter	mm	2.7	2.7	2.7
Accuracy	%	± 5	± 5	± 5
Min. reset time	s	<0.1	<0.1	<0.1
Connection - On sub-base page 4/14-4/15		●	●	●
Operating temperature	°C	-5 → +50	-5 → +50	-5 → +50
Mechanical life	operations	$>10^7$	$>10^7$	$>10^7$
Weight	g	106	180	85

Accessories

Panel mounting adaptators	—	79 451 904	79 451 905
Weight (g)	—	53	53

Principle of operation

Single impulse generator



Adjustable impulse generator



Frequency generator





Dimensions



79 451



Part numbers	L (mm)
81 507 540	73
81 507 720	99
81 506 940	72



For panel mounting, a pre-drilled hole Ø 10.5 mm si required

ATEX version products are available in the following catologues: **Pneumatic products for explosive atmospheres** or on our website **www.crouzet.com**

Timing Accessories

Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



One-way in-line fixed flow restritors	Flow at 4 bars Nm³/h	Ø orifice (mm)					
	0.18 → 0.30	0.3	white	81 529 003	—	—	—
	0.35 → 0.50	0.4	yellow	81 529 004	—	—	—
	0.58 → 0.77	0.5	red	81 529 005	—	—	—
	0.80 → 1.06	0.6	green	81 529 006	—	—	—
	1.10 → 1.39	0.7	blue	81 529 007	—	—	—
	1.45 → 1.65	0.8	grey	81 529 008	—	—	—
	2.30 → 2.80	1	black	81 529 010	—	—	—
	0.08 → 0.12	0.25	white	81 529 025	—	—	—
One-way adjustable flow restritor				—	81 525 101	81 526 001	—
Capacity for timing	10 • 60 s			—	—	—	79 458 808

Symbol

Characteristics

Free flow		Nl/min	Depending on orifice	30	200	—
Orifice diameter		mm	Depending on orifice	0 → 0.5	0 → 1.7	—
Operating pressure		bars	1 → 8	1 → 8	2 → 8	—
Timing		s	—	—	—	10 → 60
Capacity		cm³	—	—	—	30
Connection	Sub-base page 4/14-4/15		—	•	•	—
	Push-in connection for semi-rigid tubing (NFE 49100)	mm	Ø 4	—	—	Ø 4
Operating temperature		°C	-5 → +50	-5 → +50	-5 → +50	-5 → +50
Weight		g	8	60	70	40

Connections

For timing circuit
- One-way flow restrictor 81 525 1 - 81 529 0 (1)
- Reservoir 79 458 018 (2)
- Relay element 81 503 0 - 81 506 0 (3) page 4/6-4/7

Sub-base page 4/14-4/15



Principle of operation

One-way
with fixed flow



One-way
with adjustable flow



Dimensions

81 529



81 525 101





81 526 001



79 452 808



ATEX version products are available in the following catologues: **Pneumatic products for explosive atmospheres** or on our website **www.crouzet.com**

Regulator accessories

Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive





Part numbers

Mini-détenteur	**81 527 001**	—	—
Plug element	—	**81 520 601**	—
In-line non-return	—	—	**81 529 901**

Symbol





Characteristics

Operating pressure	bars	2 → 8	—	2 → 8
Flow at 6 bars	Nl/min	200	—	200
Adjustable output pressure	bar	0,1 → 8	—	—
Connection: Sub-base		●	●	
Connection: Push-in connection for semi-rigid tubing (NFE 49100)	mm			Ø 4
Weight	g	150	70	70

Dimensions

81 529 901



81 520 601



4

ATEX version products are available in the following catologues: **Pneumatic products for explosive atmospheres** or on our website **www.crouzet.com**

Sub-bases for logic elements

Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive





	81 532 104	81 532 102
Two-hand start module	● 1	● 1
Manostats - vacuostats	● 1	● 1
Leak sensor and amplifier relays	● 1	● 1
Logic elements AND Timers	● 1	● 1
Regulator accessories	● 1	● 1
Memory element	—	—
Operating temperature °C	-5 → +50	-5 → +50
Electro-pneumatic miniature solenoid	● 1	● 1

NB: The number indicates the number of components mounted on the sub-base

Characteristics

Push-in connection for semi-rigid tubing Ø 4 mm (NFE 49100)	rotatable	rotatable	
Fixation	DIN rail 35 mm	DIN rail 35 mm	
Weight g	56	52	

Connections elements and relays

Front connecting



A - Single sub-base or end base
B - Associable sub-base
1 - Input port (green port 1)
2 - Output port (red port 3)
3 - Input/supply port (yellow port 2) Ø 4
4 - Input port integral to sub-base
5 - Input indicator (green)
6 - Output indicator (red)
7 - 1/4 turn screws
8 - Marking tag
9 - Arrow indicating flow direction
10 - Mounting tongue
11 - Mounting groove
12 - Selector

Dimensions

81 532 104 **3 x 81532102**



ATEX version products are available in the following catologues: **Pneumatic products for explosive atmospheres** or on our website **www.crouzet.com**





	81 542 002	81 532 001	81 531 001
Two-hand start module	—	● 1	● 2
Manostats - vacuostats	—	● 1	● 2
Leak sensor and amplifier relays	—	● 1	● 2
Logic elements AND Timers	—	● 1	● 2
Regulator accessories	—	● 1	● 2
Memory element	● 1	—	● 1
Operating temperature °C	-5 → +50	-5 → +50	-5 → +50
Electro-pneumatic miniature solenoid	—	● 1	● 2

Caractéristiques

Push-in connection for semi-rigid tubing Ø 4 mm (NFE 49100)	rotatable	rear	rear
Fixation	DIN rail 35 mm	2 M4 screws	Clips for rails Ø 8 mm
Weight g	95	10	35

Memory element sub-base, front and rear connecting



1 - Input port X1 (green port 1)
2 - Input port X0 (green port 1)
3 - Output port X (red port 3)
4 - Output port X (red port 3)
5 - Supply port (brass port 2)
7 - 1/4 turn screws
8 - Input indicator
9 - Output indicator
10 - Marking tag
11 - Arrow indicating the flow direction

Rear connection



The modular system elements are fixed with two screws on the sub-base.

A locating device on each logic element prevents incorrect assembly.

The logic element is connected via the sub-base. This sub-base has 3 instant connections for connecting semi-rigid tubes with outer Ø 4.

1 - Input signal
2 - Signal port for passive logic elements, air supply for active logic elements.
3 - Output signal

81 542 002 (for memory 81523201/601)



81 531 001



81 532 001



ATEX version products are available in the following catologues: **Pneumatic products for explosive atmospheres** or on our website **www.crouzet.com**

Mounting accessories

Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive






Mounting equipment	81 533 501 Hole domino	81 533 001 Clip domino	79 450 609 Bar clips Ø 8		— —
Supply manifold 13 outputs	—	—	—		81 536 801

Characteristics

Weight (g)	8	4	80		80
	For mounting on the end of a zinc-coated mild steel rod Ø 8 mm on an asymmetrical DIN rail	For adjustable mounting on a zinc-coated mild steel rod Ø 8 mm on an asymmetrical DIN rail	Packet of 100 pieces		
Operating temperature °C	-5 → +50	-5 → +50	-5 → +50		-5 → +50

Dimensions
81 536 804



4

Other information

Use Weidmuller plastic labels for marking components part number FW 4734-6.

ATEX version products are available in the following catologues: **Pneumatic products for explosive atmospheres** or on our website **www.crouzet.com**

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.

Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.