








SD71175



REV.	DATE	REVISION DESCRIPTION	BY	C'D.
1	12-24-76	SEE REV. REF. PRINT SHEET 2 (ECB1291)	RWD.	RWD.
2	2-8-71	SEE REV. REF. PRINT SHS 142 (ECB1341)	PJR	RWD.
3	2-22-71	SHEET 1, BLACK STRIP ADDED TO FIG. I - III (ECB1357)	PJB	RWD.
4	4-26-71	SEE REV. REF. PRINT SH. 1 (ECB1399)	RWD.	RWD.
5	9-20-71	SEE REV. REF. PRINT SH. 1 (ECB1496)	P.G.P.	RWD.
6	30-MAY-72	SEE REV. REF. PRINT (ECB1695)	POP	RWD.
7	7-17-72	PLATING TABLE REMOVED (ECB1703)	RWD.	RWD.
REVISIONS CONTINUED ON SHEET 2				



DOUGLAS CONTACT CATALOG NO.	PIN OR SOCKET	MATING END		WIRE BARREL				TOOLING					FIG.	FIG.								WEIGHT LBS./M.	BURNDY CATALOG NUMBER	L1 ±.002	L2 ±.005		
		SIZE	COLOR CODE	SIZE	COLOR CODE	ACCOMMODATES		CRIMP TOOL	DIE SET	STOP BUSHING	INSERTION TOOL	EXTRACTION TOOL		A ±.010	B DIA. ±.001	C DIA.	D STRIP LENGTH	E DIA.	F DIA.	G DIA.	H DIA. ±.001						
						CONDUCTOR MIN.	CONDUCTOR MAX.																			INSULATION MIN. DIA.	INSULATION MAX. DIA.
LRM12Z-5DE5	P	12	YELLOW	12	YELLOW	(#14)	(#12)	.112	.146	S-8	SL-4	RTM12-5	RX12-7	I	.905	.094	9/32	202/198	102/098	153/147	3.4	LRM12Z-5DE5	.296	.220			
LRC12Z-5DE5	S	12	YELLOW	12	YELLOW	(#14)	(#12)							III	.844		161/158	9/32	202/198	102/098	153/147	3.5	LRC12Z-5DE5	.296	.220		
LRM16M-5DE5	P	16	BLUE	16	BLUE	(#20)	(#16)	.074	.110	S-7	SL-2	RTM16-2V2	RX16-7V1	I	.905	.0625	9/32	148/144	068/066	108/101	1.6	LRM16M-5DE5	.296	.220			
LRC16M-5DE5	S	16	BLUE	16	BLUE	(#20)	(#16)			III	.844		113/110	9/32	148/144	068/066	108/101	1.7	LRC16M-5DE5	.296	.220						
LRM16M-6DE5	P	16	BLUE	16	BLUE	(#20)	(#16)			I	1.093	.0625	9/32	148/144	068/066	108/101	2.1	LRM16M-6DE5	.296	.220							
LRC16M-6DE5	S	16	BLUE	16	BLUE	(#20)	(#16)			III	1.091		113/110	9/32	148/144	068/066	108/101	2.2	LRC16M-6DE5	.296	.220						
LRM16W-2DE5	P	20	RED	16	BLUE	(#20)	(#16)			S-7	SL-44	RTM16-2	RX20-24V3	V	.905	.040	9/32		068/066	108/101	.9	LRM16W-2DE5	.296	.220			
LRC16W-2DE5	S	20	RED	16	BLUE	(#20)	(#16)			VI	.844		078/076	9/32		068/066	108/101	1.0	LRC16W-2DE5	.296	.220						
LRM20M-1DE5	P	16	BLUE	20	RED	(#24)	(#20)			S-6A	SL-64	RTM20-5 OR RTM20-14	RX16-8	II	.915	.0625	7/32	148/144	050/048	078/076	.105	1.5	LRM20M-1DE5	.306	.246		
LRC20M-1DE5	S	16	BLUE	20	RED	(#24)	(#20)			IV	.854		113/110	7/32	148/144	050/048	078/076	.105	1.6	LRC20M-1DE5	.306	.246					
LRM20M-2DE5	P	16	BLUE	20	RED	(#24)	(#20)			S-6A	SL-64	RTM20-5 OR RTM20-14	RX16-8	II	1.103	.0625	7/32	148/144	050/048	078/076	.105	2.0	LRM20M-2DE5	.306	.246		
LRC20M-2DE5	S	16	BLUE	20	RED	(#24)	(#20)			IV	1.101		113/110	7/32	148/144	050/048	078/076	.105	2.1	LRC20M-2DE5	.306	.246					
LRM20W-5DE5	P	20	RED	20	RED	(#24)	(#20)			S-6A	SL-3A	RTM20-5 OR RTM20-14	RX20-24V3	II	.915	.040	7/32	103/100	050/048	078/076	.105	.8	LRM20W-5DE5	.306	.246		
LRC20W-5DE5	S	20	RED	20	RED	(#24)	(#20)			IV	.854		078/076	7/32	103/100	050/048	078/076	.105	.9	LRC20W-5DE5	.306	.246					
LRM22M-1DE5	P	16	BLUE	22	GREEN	(#24)	(#22)			S-6A	SL-64	RTM16-2	RX16-7	II	.915	.0625	7/32	148/144	038/036	066/064	.105	1.7	LRM22M-1DE5	.306	.246		
LRC22M-1DE5	S	16	BLUE	22	GREEN	(#24)	(#22)			IV	.854		113/110	7/32	148/144	038/036	066/064	.105	1.8	LRC22M-1DE5	.306	.246					
LRM22M-2DE5	P	16	BLUE	22	GREEN	(#24)	(#22)			S-6A	SL-64	RTM16-2	RX16-8	II	1.103	.0625	7/32	148/144	038/036	066/064	.105	1.8	LRM22M-2DE5	.306	.246		
LRC22M-2DE5	S	16	BLUE	22	GREEN	(#24)	(#22)			IV	1.101		113/110	7/32	148/144	038/036	066/064	.105	2.2	LRC22M-2DE5	.306	.246					

NOTES:

DENOTES WIRE BARREL.
 DENOTES MATING END.
 BLACK DENOTES 5015 TYPE CONTACT AND IS ONLY APPLICABLE IF APPEARS TO LEFT OF CATALOG NUMBER.

IDENTIFICATION STRIPES IN ACCORDANCE WITH:
 MIL-C-23216
 MS 3190
 MS 3192C
 MS 3193B

TO ORDER REEL MOUNTED CONTACTS, PRECEDE CONTACT CATALOG NO. WITH "C" - EXAMPLE - CLRC16M-5DE5 INDICATES LRC16M-5DE5 CONTACTS MOUNTED IN REELED CARRY STRIP FOR BANDOMATIC ASSEMBLY.
 REF. ASTM B33-63 AIRCRAFT WIRE ONLY.

FOR NEW CONTACTS REPLACING SUPERSEDED CONTACTS SEE DWG. SDW1119

MATERIAL: BRASS

PLATING TABLE	
SUFFIX	PLATING
DE5	GOLD OVER COPPER

FSCM NO. 09922

BANTAM PIN AND SOCKET CONTACTS		SCALE	
CAT. NO. LRM/LRC (TABLE)		1/4" = 1"	
DRAWN	CHECKED	DATE	
RJR2	10-29-70	11-13-70 C.B.	
DES. APPROV.		PROD. APPROV.	
11-13-70		11/13/70	
DRAWING NO.		REV.	
B. SD71175		13	
SHEET 1 OF 2			

SD7117S

REV.	DATE	REVISION DESCRIPTION	BY	C.K.D.
12	11-21-83	SHT. 1, NOTE 3, ADDED. AND IS ONLY APPLICABLE TO LEFT OF CAT. NO. (DC11095)	DA	C.B.
13	3/24/79	REMOVED BR FROM DRAWING # MATERIAL: BRASS PER ECN 4328	DAF	SAF

REV.	DATE	REVISION DESCRIPTION	BY	C.K.D.
8	3-23-74	REVISIONS CONTINUED FROM SHEET 1 SHEET 2, NOTE 'A' WAS NOTE '4' NOTE 'B' ADDED. (ECB1968 & ADD.)	D.L.	P.J.B.
9	4-29-81	SHTS. 1 & 2, SEE REV. REF. (ECC4269) PRINT.	L.H.	SFP
10	9-15-81	SHTS. 1 & 2 SEE REV. REF. (DC10,666) PRINTS	L.H.	SFP
11	9/9/83	ADDED NOTE 6, SUPERSEDED CAT. NO'S. LRM12Z23DES, LRC12Z23DES, LRM16M23DES, LRC16M23DES, LRM20W23DES, LRC20W23DES PER ECW1395	S.E.	CEB




FIGURE I




FIGURE II




FIGURE III




FIGURE IV

CONTACT CATALOG NO.	PIN OR SOCKET	MATING END		WIRE BARREL				TOOLING					FIG.	DIMENSIONS								MATERIAL	WEIGHT LBS/M	FINISH		LEAD					
		SIZE	COLOR CODE	SIZE	COLOR CODE	ACCOMMODATES			CRIMP TOOL	DIE SET	STOP BUSHING	INSERTION TOOL		EXTRACTION TOOL	A ±.010	B DIA. ±.001	C DIA.	D STRIP LENGTH	E DIA.	F DIA. ±.001	G DIA.					H DIA. ±.001	±.002	±.005			
						MIN.	MAX.	PER																							
LRM16M-9	P	16	BLUE	16	BLUE	.038	.057	REGULAR GRADE THERMOCOUPLE	M10S-1	S7	SL 2	RTM16-2	RX16-7	I	.905	.0625	—	9/32	.148/.144	.067	.105/.101	—	ALUMEL	1.7	NONE	.296	.220				
LRC16M-9	S	16	BLUE	16	BLUE	#20	#16	WIRE PER MIL-W-5846 TYPE I, CLASS D,E						III	.844	—	.113/.110	9/32		.067				—	—	NONE	.296	.220			
LRM16M-10	P	16	BLUE	16	BLUE	.038	.057	—						I	.905	.0625	—	9/32		.067				—	—	CHROMEL	1.7	NONE	.296	.220	
LRC16M-10	S	16	BLUE	16	BLUE	#20	#16							III	.844	—	.113/.110	9/32		.067				—	—	NONE	.296	.220			
LRM16M-11	P	16	BLUE	16	BLUE	.038	.057	THERMOCOUPLE						I	.905	.0625	—	9/32		.067				—	—	IRON	1.4	CAD. PLATE	.296	.220	
LRC16M-11	S	16	BLUE	16	BLUE	#20	#16	WIRE PER MIL-W-5845						III	.844	—	.113/.110	9/32		.067				—	—		1.5	CAD. PLATE	.296	.220	
LRM16M-12	P	16	BLUE	16	BLUE	.038	.057	TYPE I, CLASS D,E						I	.905	.0625	—	9/32		.067				—	—	CONSTANTAN	1.7	NONE	.296	.220	
LRC16M-12	S	16	BLUE	16	BLUE	#20	#16	III						.844	—	.113/.110	9/32	.067		—				—	1.8		NONE	.296	.220		
LRM20W-9	P	20	RED	20	RED	.024	.038	REGULAR GRADE THERMOCOUPLE			S6A	SL-3A	RTM20-5	RX20-24V3	II	.915	.040	—	7/32	.103/.100	.049	.078/.076	.105	ALUMEL	.8	NONE	.306	.246			
LRC20W-9	S	20	RED	20	RED	#24	#20	WIRE PER MIL-W-5846 TYPE I, CLASS D,E							IV	.854	—	.078/.076	7/32		.049				—	—	NONE	.306	.246		
LRM20W-10	P	20	RED	20	RED	.024	.038	—							II	.915	.040	—	7/32		.049				—	—	CHROMEL	.8	NONE	.306	.246
LRC20W-10	S	20	RED	20	RED	#24	#20								IV	.854	—	.078/.076	7/32		.049				—	—	NONE	.306	.246		
LRM20W-11	P	20	RED	20	RED	.024	.038	THERMOCOUPLE							II	.915	.040	—	7/32		.049				—	—	IRON	.7	CAD. PLATE	.306	.246
LRC20W-11	S	20	RED	20	RED	#24	#20	WIRE PER MIL-W-5845							IV	.854	—	.078/.076	7/32		.049				—	—		.8	CAD. PLATE	.306	.246
LRM20W-12	P	20	RED	20	RED	.024	.038	TYPE I, CLASS D,E							II	.915	.040	—	7/32		.049				—	—	CONSTANTAN	.8	NONE	.306	.246
LRC20W-12	S	20	RED	20	RED	#24	#20	III							.854	—	.078/.076	7/32	.049		—				—	.9		NONE	.306	.246	

NOTES:

GREEN DENOTES ALUMEL
WHITE DENOTES CHROMEL
YELLOW DENOTES CONSTANTAN
BLACK DENOTES IRON

THERMOCOUPLE CONTACTS ONLY

WEEP HOLE ON LRC16M-11 AND
LRC20W-11 ONLY.

CONSULT FACTORY FOR
AVAILABILITY.

FSCM NO. 09922

THERMOCOUPLE CONTACTS	
BANTAM PIN AND SOCKET CONTACTS	
CAT. NO. LRM/LRC	(TABLE)
DRAWN RJR2	CHECKED RJR2 11-6-70
10-29-70	DES. APPROV. 11-13-70 C.B.
PROD. APPROV. 11-13-70	
DRAWING NO. SD7117S13	
SHEET 2 OF 2	
DOB-1069	



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.