


SPECIFICATION CONTROL DRAWING		44A123X	
TITLE	THREE CONDUCTOR CABLE, SHIELDED, JACKETED, GENERAL PURPOSE, 1000 VOLT	Date	5-5-08
		Revision	E
This specification sheet forms a part of the latest issue of Raychem Specification 44.			



PART NUMBER 1/	CONDUCTOR SIZE (AWG)	SHIELD SIZE (AWG)	JACKET THICKNESS (in.)		OUTSIDE DIAMETER (in.)		MAXIMUM WEIGHT (lbs/1000 ft.)
			MINIMUM	NOMINAL	NOMINAL	MAXIMUM	
44A123X-26-*	26	36	.006	.008	.123	.130	13.3
44A123X-24-*	24	36	.006	.008	.136	.143	16.8
44A123X-22-*	22	36	.006	.008	.154	.161	21.6
44A123X-20-*	20	36	.007	.009	.173	.182	28.4
44A123X-18-*	18	36	.007	.009	.197	.207	38.4
44A123X-16-*	16	36	.007	.009	.214	.225	46.3
44A123X-14-*	14	36	.007	.009	.251	.263	64.4
44A123X-12-*	12	36	.008	.010	.294	.308	91.4
44A123X-10-*	10	36	.008	.010	.356	.374	138.
44A123X- 8-*	8	34	.010	.012	.495	.520	240.
44A123X- 6-*	6	34	.010	.012	.599	.629	351.

NOTE: Nominal values are for information only.
Nominal values are not requirements.


Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.			
1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.			
Page 1 of 2	The TE logo, Tyco Electronics and Raychem are trademarks.		 Raychem Wire & Cable 501 Oakside Avenue Redwood City, CA 94063-3800 Phone: 1-800-227-8816 Fax: 1-650-361-6297
	DIMENSIONS ARE IN INCHES, AND UNLESS OTHERWISE DESIGNATED ARE NOMINAL.		
	THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.		

TABLE II. CABLE PERFORMANCE DETAILS

PART NUMBER 1/	BEND TESTING			
	MANDREL DIAMETER (inch) (±3%)		WEIGHT (lb) (±3%)	
	LIFE CYCLE, IMMERSION AND ACCELERATED AGING	COLD BEND	LIFE CYCLE, IMMERSION AND ACCELERATED AGING	COLD BEND
44A123X-26-*	3.00	3.00	.563	4.50
44A123X-24-*	6.00	6.00	.563	9.00
44A123X-22-*	6.00	6.00	.563	9.00
44A123X-20-*	6.00	6.00	.750	13.5
44A123X-18-*	6.00	6.00	.750	13.5
44A123X-16-*	6.00	6.00	1.50	18.0
44A123X-14-*	10.0	10.0	1.50	18.0
44A123X-12-*	10.0	10.0	2.25	18.0
44A123X-10-*	10.0	10.0	3.00	18.0
44A123X- 8-*	18.0	18.0	4.50	22.5
44A123X- 6-*	18.0	18.0	4.50	36.0

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 150°C

Maximum continuous conductor temperature

VOLTAGE RATING: 1000 volts (rms) at sea level
ACCELERATED AGING: 300 ± 3°C for 6 hours
BLOCKING: 150 ± 3°C for 6 hours
DIELECTRIC WITHSTAND: 3000 volts (rms), 60 Hz, 1 minute
FLAMMABILITY:

30 seconds (maximum); 3 in. (maximum); no flaming of facial tissue

IMMERSION: Diameter increase 5% (maximum),

no cracking, no dielectric breakdown

JACKET COLOR: White preferred
JACKET CONCENTRICITY: 70% (minimum)
JACKET ELONGATION AND TENSILE STRENGTH:

Elongation, 200% (minimum)

 Tensile Strength, 4000 lbf/in² (minimum)

JACKET FLAWS:

Spark Test, 1.5 kV (rms)

Impulse Dielectric Test, 6.0 kV (peak)

LIFE CYCLE: 200 ± 3°C for 168 hours
LOW TEMPERATURE-COLD BEND: -65 ± 2°C for 4 hours
SHIELD COVERAGE: 85% (minimum)
VOLTAGE WITHSTAND TEST (Post Environmental):

1000 volts (rms), 60 Hz, 1 minute

PART NUMBER:

The "X" in the part numbers on page 1 shall be replaced by the applicable conductor material designator as follows:

- 1 tin-coated copper
- 2 silver-coated copper
- 3 nickel-coated copper
- 4 silver-coated high strength copper alloy (AWG's 26 -20 only)

The "*" in the part numbers on page 1 shall be replaced by color code designators with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color. Colors shown do not necessarily reflect the sequence of manufacturing.

1/ Example: AWG 20, tin-coated copper wires, black, brown and red component wires; white jacket: 44A1231-20-0/1/2-9

1/ See footer section on page 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

[44A1231-16-9/93/96-9](#) [44A1231-22-1/2/3-9](#) [44A1231-6-9/95/96-9](#) [44A1231-0-ST3-9CS3030](#) [44A1231-14-0/5/9-9](#)
[44A1231-18-0/2/9-9](#) [44A1231-4-ST3-9CS3030](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.