

Hybrid Conductive Polymer Aluminum Capacitors SMD (Chip), Low Impedance




Fig. 1

| QUICK REFERENCE DATA | |
|---|---------------------------------------|
| DESCRIPTION | VALUE |
| Nominal case sizes (L x W x H in mm) | 5.0 x 5.0 x 5.8 to 10.0 x 10.0 x 10.5 |
| Rated capacitance range, C _R | 10 µF to 330 µF |
| Tolerance on C _R | ± 20 % |
| Rated voltage range, U _R | 25 V to 80 V |
| Category temperature range | -55 °C to +105 °C |
| Endurance test at 105 °C | 10 000 h |
| Useful life at 105 °C | 10 000 h |
| Shelf life at 0 V, 105 °C | 1000 h |
| Based on sectional specification | IEC 60384-25 / CECC 32300 |
| Climatic category IEC 60068 | 55 / 105 / 56 |

FEATURES

- Long useful life: up to 10 000 h at 105 °C
- Very low ESR and high ripple current
- High voltages up to 80 V
- SMD-version with base plate, lead (Pb)-free reflow solderable
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912


**RoHS
COMPLIANT**

APPLICATIONS

- Automotive electronics
- Industrial and professional applications
- Telecommunications and IT
- Portable and mobile equipment

MARKING

- Rated capacitance (in µF)
- Rated voltage (in V)
- Date code, in accordance with IEC 60062
- Black mark or “-” sign indicating the cathode (the anode is identified by beveled edges)
- Code indicating group number (82)

PACKAGING

Supplied in blister tape on reel

| SELECTION CHART FOR C _R , U _R , AND RELEVANT NOMINAL CASE SIZES (L x W x H in mm) | | | | | |
|---|--------------------|--------------------|--------------------|--------------------|--------------------|
| C _R (µF) | U _R (V) | | | | |
| | 25 | 35 | 50 | 63 | 80 |
| 10 | → | → | 5.0 x 5.0 x 5.8 | 6.3 x 6.3 x 5.8 | - |
| 22 | → | 5.0 x 5.0 x 5.8 | 6.3 x 6.3 x 5.8 | 6.3 x 6.3 x 7.7 | 8.0 x 8.0 x 10.5 |
| 27 | → | 6.3 x 6.3 x 5.8 | - | - | - |
| 33 | 5.0 x 5.0 x 5.8 | → | 6.3 x 6.3 x 7.7 | 8.0 x 8.0 x 10.5 | 10.0 x 10.0 x 10.5 |
| 47 | → | 6.3 x 6.3 x 5.8 | - | - | - |
| 56 | 6.3 x 6.3 x 5.8 | → | → | 10.0 x 10.0 x 10.5 | - |
| 68 | → | 6.3 x 6.3 x 7.7 | 8.0 x 8.0 x 10.5 | - | - |
| 100 | 6.3 x 6.3 x 7.7 | → | 10.0 x 10.0 x 10.5 | - | - |
| 150 | → | 8.0 x 8.0 x 10.5 | - | - | - |
| 220 | 8.0 x 8.0 x 10.5 | - | - | - | - |
| 270 | → | 10.0 x 10.0 x 10.5 | - | - | - |
| 330 | 10.0 x 10.0 x 10.5 | - | - | - | - |




Fig. 2 - Dimensional outline

Table 1

| DIMENSIONS in millimeters AND MASS | | | | | | | | | |
|---|--------------|-------------------|-------------------|-------------------|------|-------------------|-----|--------------------|-------------|
| NOMINAL CASE SIZE L x W x H | CASE CODE | L _{MAX.} | W _{MAX.} | H _{MAX.} | Ø D | B _{MAX.} | S | L1 _{MAX.} | MASS (g) |
| 5.0 x 5.0 x 5.8 | 0506 | 5.5 | 5.5 | 6.1 | 5.0 | 0.8 | 1.4 | 6.1 | 0.2 |
| 6.3 x 6.3 x 5.8 | 0606 | 6.7 | 6.7 | 6.1 | 6.3 | 0.8 | 2.2 | 7.4 | 0.3 |
| 6.3 x 6.3 x 7.7 | 0608 | 6.7 | 6.7 | 8.0 | 6.3 | 0.8 | 2.2 | 7.4 | 0.4 |
| 8.0 x 8.0 x 10.5 | 0810 | 8.5 | 8.5 | 10.8 | 8.0 | 1.1 | 3.1 | 9.2 | 0.9 |
| 10.0 x 10.0 x 10.5 | 1010 | 10.5 | 10.5 | 10.8 | 10.0 | 1.1 | 4.5 | 11.2 | 1.2 |

Table 2

| TAPE AND REEL DIMENSIONS in millimeters, PACKAGING QUANTITIES | | | | | | |
|--|--------------|-------------------------|-----------------|-------------------------------------|---------------|-----------------------------------|
| NOMINAL CASE SIZE L x W x H | CASE CODE | PITCH P ₁ | TAPE WIDTH W | TAPE THICKNESS T ₂ | REEL DIAMETER | PACKAGING QUANTITY PER REEL |
| 5.0 x 5.0 x 5.8 | 0506 | 12 | 12 | 6.1 | 380 | 1000 |
| 6.3 x 6.3 x 5.8 | 0606 | 12 | 16 | 5.7 | 380 | 1000 |
| 6.3 x 6.3 x 7.7 | 0608 | 12 | 16 | 8.0 | 380 | 900 |
| 8.0 x 8.0 x 10.5 | 0810 | 16 | 24 | 11.0 | 380 | 500 |
| 10.0 x 10.0 x 10.5 | 1010 | 16 | 24 | 11.0 | 380 | 500 |

MOUNTING

The capacitors are designed for automatic placement on to printed-circuit boards.

Optimum dimensions of soldering pads depend amongst others on soldering method, mounting accuracy, print layout and / or adjacent components.

For recommended soldering pad dimensions, refer to Fig. 3 and Table 3.

SOLDERING

Soldering conditions are defined by the curve, temperature versus time, where the temperature is that measured on the component during processing.

For maximum conditions refer to Fig. 4.

Any temperature versus time curve which does not exceed the specified maximum curves may be applied.

As a general principle, temperature and duration shall be the **minimum** necessary required to ensure good soldering connections. However, the specified maximum curves should never be exceeded.




Fig. 3 - Recommended soldering pad dimensions

Table 3

| RECOMMENDED SOLDERING PAD DIMENSIONS in millimeters | | | | |
|--|-----------|-----|-----|-----|
| NOMINAL CASE SIZE L x W x H | CASE CODE | a | b | c |
| 5.0 x 5.0 x 5.8 | 0506 | 3.0 | 1.6 | 1.4 |
| 6.3 x 6.3 x 5.8 | 0606 | 3.5 | 1.6 | 2.1 |
| 6.3 x 6.3 x 7.7 | 0608 | 3.5 | 1.6 | 2.1 |
| 8.0 x 8.0 x 10.5 | 0810 | 4.2 | 1.9 | 2.8 |
| 10.0 x 10.0 x 10.5 | 1010 | 4.4 | 1.9 | 4.3 |


SOLDERING PROFILE FOR LEAD (Pb)-FREE REFLOW PROCESS


Fig. 4 - Maximum temperature load during reflow soldering

Table 4

| REFLOW SOLDERING CONDITIONS for MAL2182xxxxE3 | | |
|--|--------|--------------|
| PROFILE FEATURES | 25 V | 35 V TO 80 V |
| Maximum time between 150 °C to 180 °C (t_1) | 120 s | 120 s |
| Maximum time above 200 °C (t_2) | 80 s | 70 s |
| Maximum time above 230 °C (t_3) | 50 s | 30 s |
| Peak temperature T_{Peak} | 240 °C | 240 °C |
| Maximum reflow cycles | 2 | 1 |

Note

- Temperature measuring point on top of the case and on terminals



| ELECTRICAL DATA | |
|-----------------|---|
| SYMBOL | DESCRIPTION |
| C_R | Rated capacitance at 120 Hz, tolerance $\pm 20\%$ |
| I_R 105 °C | Rated RMS ripple current at 100 kHz |
| I_{L2} | Max. leakage current after 2 min at U_R |
| $\tan \delta$ | Max. dissipation factor at 120 Hz |
| ESR | Max. ESR at 100 kHz |

Note

- Unless otherwise specified, all electrical values in Table 5 apply at $T_{amb} = 20\text{ °C}$, $P = 86\text{ kPa}$ to 106 kPa , $RH = 45\%$ to 75%

Table 5

| ELECTRICAL DATA AND ORDERING INFORMATION | | | | | | | |
|--|----------------------------|---|------------------------------------|--|-------------------------|--|-----------------------------|
| U_R (V) | C_R (μF) | NOMINAL CASE SIZE L x W x H (mm) | I_R 105 °C 100 kHz (mA) | I_{L2} 2 min (μA) | $\tan \delta$ 120 Hz | ESR 100 kHz 20 °C (m Ω) | ORDERING CODE MAL2182... |
| 25 | 33 | 5.0 x 5.0 x 5.8 | 900 | 8.3 | 0.14 | 80 | 97601E3 |
| | 56 | 6.3 x 6.3 x 5.8 | 1300 | 14 | 0.14 | 50 | 97602E3 |
| | 100 | 6.3 x 6.3 x 7.7 | 2000 | 25 | 0.14 | 30 | 97603E3 |
| | 220 | 8.0 x 8.0 x 10.5 | 2300 | 55 | 0.14 | 27 | 97604E3 |
| | 330 | 10.0 x 10.0 x 10.5 | 2500 | 82.5 | 0.14 | 20 | 97605E3 |
| 35 | 22 | 5.0 x 5.0 x 5.8 | 900 | 7.7 | 0.12 | 100 | 97001E3 |
| | 27 | 6.3 x 6.3 x 5.8 | 1300 | 9.5 | 0.12 | 60 | 97002E3 |
| | 47 | 6.3 x 6.3 x 5.8 | 1300 | 16.5 | 0.12 | 60 | 97003E3 |
| | 68 | 6.3 x 6.3 x 7.7 | 2000 | 23.8 | 0.12 | 35 | 97004E3 |
| | 150 | 8.0 x 8.0 x 10.5 | 2300 | 52.5 | 0.12 | 27 | 97005E3 |
| | 270 | 10.0 x 10.0 x 10.5 | 2500 | 94.5 | 0.12 | 20 | 97006E3 |
| 50 | 10 | 5.0 x 5.0 x 5.8 | 750 | 5 | 0.1 | 120 | 97101E3 |
| | 22 | 6.3 x 6.3 x 5.8 | 1100 | 11 | 0.1 | 80 | 97102E3 |
| | 33 | 6.3 x 6.3 x 7.7 | 1600 | 16.5 | 0.1 | 40 | 97103E3 |
| | 68 | 8.0 x 8.0 x 10.5 | 1800 | 34 | 0.1 | 30 | 97104E3 |
| | 100 | 10.0 x 10.0 x 10.5 | 2000 | 50 | 0.1 | 28 | 97105E3 |
| 63 | 10 | 6.3 x 6.3 x 5.8 | 1000 | 6.3 | 0.08 | 120 | 97801E3 |
| | 22 | 6.3 x 6.3 x 7.7 | 1500 | 13.9 | 0.08 | 80 | 97802E3 |
| | 33 | 8.0 x 8.0 x 10.5 | 1700 | 20.8 | 0.08 | 40 | 97803E3 |
| | 56 | 10.0 x 10.0 x 10.5 | 1800 | 35.3 | 0.08 | 30 | 97804E3 |
| 80 | 22 | 8.0 x 8.0 x 10.5 | 1550 | 17.6 | 0.08 | 45 | 97701E3 |
| | 33 | 10.0 x 10.0 x 10.5 | 1700 | 26.4 | 0.08 | 36 | 97702E3 |

Table 6

| ADDITIONAL ELECTRICAL DATA | | |
|---------------------------------|------------------------------|----------------------------|
| PARAMETER | CONDITIONS | VALUE |
| Voltage | | |
| Surge voltage for short periods | IEC 60384-25, subclause 4.14 | $U_s \leq 1.15 \times U_R$ |

USEFUL LIFE AND ENDURANCE

Table 7

| ENDURANCE TEST AND USEFUL LIFE | | | | | | | |
|--------------------------------|--------------|--|-------------------------|------------------------|------------------------|------------------------|------------------------|
| SERIES | CASE CODE | USEFUL LIFE AT 105 °C (h) ⁽¹⁾ | ENDURANCE AT 105 °C (h) | ENDURANCE AT 95 °C (h) | ENDURANCE AT 85 °C (h) | ENDURANCE AT 75 °C (h) | ENDURANCE AT 65 °C (h) |
| 182 CPHZ | 0506 to 1010 | 10 000 | 10 000 | 20 000 | 40 000 | 80 000 | 160 000 |

Note

⁽¹⁾ Identical with endurance for this series

Endurance can be calculated by formula below:

$$L = L_{T_{max.}} \times 2^{\frac{T_{max.} - T_a}{10}}$$

L: estimated lifetime (h)

$L_{T_{max.}}$: base lifetime specified at maximum operating temperature with applied DC voltage (h)

$T_{max.}$: rated maximum operating temperature (°C)

T_a : actual ambient temperature (°C)

Table 8

| MULTIPLIER OF RIPPLE CURRENT (I_R) AS A FUNCTION OF FREQUENCY | | | |
|---|------|--------|-----------|
| FREQUENCY (Hz) | | | |
| 120 | 1000 | 10 000 | ≥ 100 000 |
| I_R MULTIPLIER | | | |
| 0.1 | 0.3 | 0.6 | 1 |

Table 9

| TEST PROCEDURES AND REQUIREMENTS | | | |
|--|---|---|---|
| TEST | | PROCEDURE (quick reference) | REQUIREMENTS |
| NAME OF TEST | REFERENCE | | |
| Mounting | IEC 60384-25, subclause 4.3 | Shall be performed prior to tests mentioned below; reflow soldering; for maximum temperature load refer to chapter "Mounting" | $\Delta C/C: \pm 5 \%$ $\tan \delta \leq \text{spec. limit}$ $I_{L2} \leq \text{spec. limit}$ |
| Endurance | IEC 60384-25 / CECC 32300, subclause 4.15 | $T_{amb} = 105 \text{ °C}$; U_R applied; for test duration see Table 7 | $\Delta C/C: \pm 30 \%$ $\tan \delta \leq 2 \times \text{spec. limit}$ $I_{L2} \leq \text{spec. limit}$ $ESR \leq 2 \times \text{spec. limit}$ |
| Useful life | CECC 30301, subclause 1.8.1 | $T_{amb} = 105 \text{ °C}$; U_R and I_R applied; for test duration see Table 7 | $\Delta C/C: \pm 30 \%$ $\tan \delta \leq 2 \times \text{spec. limit}$ $I_{L2} \leq \text{spec. limit}$ $ESR \leq 2 \times \text{spec. limit}$ |
| Shelf life (storage at high temperature) | IEC 60384-25 / CECC 32300, subclause 4.16 | $T_{amb} = 105 \text{ °C}$; no voltage applied; 1000 h after test: U_R to be applied for 30 min, 24 h to 48 h before measurement | For requirements see "Endurance test" above |

Statements about product lifetime are based on calculations and internal testing. They should only be interpreted as estimations. Also due to external factors, the lifetime in the field application may deviate from the calculated lifetime. In general, nothing stated herein shall be construed as a guarantee of durability.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.