

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0458450001

Status:

Active

Overview:

edge_card_connectors

Description:

2.50mm (.098") Pitch EXTreme PowerEdge™, Signal Connector, Double Sided, 2 Segments, 8 Signal Contacts per Segment, Press-Fit

Documents:

3D Model

Drawing (PDF)

Product Specification PS-45719-001 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA

LR19980

TUV

30482572

General

Product Family

Edge Card Connectors

Series

45845

Component Type

Edgecard to PCB

Overview

edge_card_connectors

Product Name

EXTreme PowerEdge™

Physical

Circuits (Loaded)

16

Circuits (maximum)

16

Circuits Detail

All Signal

Color - Resin

Black

Durability (mating cycles max)

250

Entry Angle

Vertical (Top Entry)

Flammability

94V-0

Keying to Mating Part

N/A

Material - Metal

Phosphor Bronze

Material - Plating Mating

Gold

Material - Plating Termination

Tin

Material - Resin

High Temperature Thermoplastic

PC Tail Length (in)

0.177 In

PC Tail Length (mm)

4.50 mm

PCB Thickness Recommended (in)

0.093 In

PCB Thickness Recommended (mm)

2.40 mm

Packaging Type

Tray

Pitch - Mating Interface (in)

0.098 In

Pitch - Mating Interface (mm)

2.50 mm

Plating min: Mating (µin)

30

Plating min: Mating (µm)

0.75

Plating min: Termination (µin)

150

Plating min: Termination (µm)

3.75

Temperature Range - Operating

-40°C to +105°C

Termination Interface: Style

Through Hole - Compliant Pin

Electrical

Current - Maximum per Contact

3A

Voltage - Maximum

250V

Material Info


Reference - Drawing Numbers

Packaging Specification

PK-45714-001

Product Specification

PS-45719-001



EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Contains SVHC: No

Halogen-Free

Status

Halogen-Free

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

45845Series

Mates With

1.58mm (.062") double sided card edge

This document was generated on 06/04/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

D

C

B




A

D

C


B

A



- NOTES:
1. MATERIAL: HOUSING 30% GF LCP, UL94V-0, BLACK
MATERIAL: TERMINAL C5210 ALLOY
 2. FINISH: SEE SHT 2 FOR FINISH SPECIFICATIONS
 3. PRODUCT SPECIFICATION: PS-45719-001.
 4. PACKAGING SPECIFICATION: PK-45714-001.
 5. THIS PART MATES WITH 1.60±0.16 THICK PCB OR BUSBAR
 6. DIMENSIONS GIVEN ACROSS CENTERLINES ARE SYMMETRICAL ABOUT THOSE CENTERLINES WITHIN HALF THE TOTAL TOLERANCE.
 7. PCB THICKNESS: 2.36 MIN
EDGE CARD THICKNESS: 1.57±0.15
 8. PCB HOLE SPECIFICATION: SEE PS-45719-001.
 9. 0.50 X 45° CHAMFER ON LEADING EDGE, TYP 4 SIDES.
 10. THIS PART IS RoHS COMPLIANT. SEE ES-45482-999 FOR LABEL REQUIREMENTS.

MATERIAL NUMBER	SEGMENTS	FINISH (SHT 2)	VOID LOCATIONS
45845-0001	2	1	NONE
45845-0002	3	1	NONE
45845-0003	4	1	NONE
45845-1001	2	1	SEG 1 CKT 7, 8
45845-1003	3	1	SEGS 1, 2 CKTS 5,6,15,16
45845-2001	2	2	SEG 1 CKT 7, 8
45845-3001	2	1	SEG 1 CKTS 3,4,7,8
45845-9001	2	3	NONE
45845-9003	4	3	NONE



ADD -1002	2008/04/16
EC NO: UCP2008-2498	DRWN: SCHAFER
CHKD: 2008/04/22	APPR: APATEL
2008/04/25	DESCRIPTION
H	REV

GENERAL TOLERANCES (UNLESS SPECIFIED)		
	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± 0.25	± ---
1 PLACE	± ---	± ---
ANGULAR ± 1/2°		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		

DIMENSION STYLE	
MM ONLY	
DRAWN BY	DATE
MARGULIS	2004/08/05
CHECKED BY	DATE
MARGULIS	2004/08/05
APPROVED BY	DATE
MARGULIS	2004/08/05
MATERIAL NUMBER	
SEE CHART	
SIZE	
A	

SCALE 2:1	DESIGN UNITS METRIC	 THIRD ANGLE PROJECTION
TITLE POWER EDGE ASSEMBLY SIGNAL VERTICAL CPI		
 MOLEX INCORPORATED		
DOCUMENT NO. SD-45845-001		SHEET NO. 1 OF 3
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		

6



5

4


3

2

1



5.40
TYP





PCB LAYOUT: COMPONENT SIDE

SEGMENT 1
CIRCUIT 1

NOTES

1. FOR NOTES AND DIMENSIONS NOT SHOWN SEE SHEET 1

2. FINISH:

FINISH 1- SELECT GOLD 30 M.I.MIN IN CONTACT AREA
SELECT TIN 100 M.I.MIN IN PC TAIL AREA
BOTH OVER NICKEL 50 M.I.MIN OVERALLFINISH 2- SELECT GOLD PLATE OVER 100-200 M.I.
Pd/Ni IN MATING AREA OVER
NICKEL 15-50 M.I. IN MATING AREA.
TIN 15-60 M.I. IN TAIL AREA OVER
NICKEL 30-60 M.I. IN TAIL AREA.FINISH 3- SELECT GOLD 30 M.I.MIN IN CONTACT AREA
SELECT TIN/LEAD 100 M.I.MIN IN PC TAIL AREA
BOTH OVER NICKEL 50 M.I.MIN OVERALLRECOMMENDED EDGE CARD LAYOUT
TOLERANCE: ± 0.05 SEGMENT 1
CIRCUIT 1

EC NO: UCP2008-2498	2008/04/16
DRWN: JSCHAFER	2008/04/22
CHKD: APATTEL	2008/04/25
APPR: APATTEL	2008/04/25
DESCRIPTION	
REV	

GENERAL TOLERANCES
(UNLESS SPECIFIED)

	mm	INCH
4 PLACES	$\pm$ ---	$\pm$ ---
3 PLACES	$\pm$ ---	$\pm$ ---
2 PLACES	± 0.25	$\pm$ ---
1 PLACE	$\pm$ ---	$\pm$ ---

ANGULAR $\pm 1/2^\circ$ DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONSDIMENSION STYLE
MM ONLY

DRAWN BY	DATE
MARGULIS	2004/08/05
CHECKED BY	DATE
MARGULIS	2004/08/05
APPROVED BY	DATE
MARGULIS	2004/08/05

MATERIAL NUMBER
SEE CHARTSIZE
ASCALE
2:1DESIGN UNITS
METRICTHIRD ANGLE
PROJECTIONTITLE
POWER EDGE ASSEMBLY
SIGNAL VERTICAL
CPI

MOLEX INCORPORATED

DOCUMENT NO.
SD-45845-001SHEET NO.
2 OF 3

5

4

3

2

1



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.