



preliminary

# Sonic Fast Recovery Diode


|           |   |              |
|-----------|---|--------------|
| $V_{RRM}$ | = | <b>600 V</b> |
| $I_{FAV}$ | = | <b>30 A</b>  |
| $t_{rr}$  | = | <b>35 ns</b> |

High Performance Fast Recovery Diode  
Low Loss and Soft Recovery  
Single Diode


Part number

**DHG30IM600PC**

Marking on Product: *DHG30IM600PC*



Backside: cathode



**Features / Advantages:**

- Planar passivated chips
- Very low leakage current
- Very short recovery time
- Improved thermal behaviour
- Very low  $I_{rm}$ -values
- Very soft recovery behaviour
- Avalanche voltage rated for reliable operation
- Soft reverse recovery for low EMI/RFI
- Low  $I_{rm}$  reduces:
  - Power dissipation within the diode
  - Turn-on loss in the commutating switch

**Applications:**

- Antiparallel diode for high frequency switching devices
- Antisaturation diode
- Snubber diode
- Free wheeling diode
- Rectifiers in switch mode power supplies (SMPS)
- Uninterruptible power supplies (UPS)

**Package:** TO-263 (D2Pak)

- Industry standard outline
- RoHS compliant
- Epoxy meets UL 94V-0

**Disclaimer Notice**

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).




| Fast Diode |  |   |                              | Ratings |      |            |  |
|------------|--|---|------------------------------|---------|------|------------|--|
| Symbol     | Definition                                   | Conditions  | min.                         | typ.    | max. | Unit       |  |
| $V_{RSM}$  | max. non-repetitive reverse blocking voltage | $T_{VJ} = 25^{\circ}C$                                    |                              |         | 600  | V          |  |
| $V_{RRM}$  | max. repetitive reverse blocking voltage     | $T_{VJ} = 25^{\circ}C$                                    |                              |         | 600  | V          |  |
| $I_R$      | reverse current, drain current               | $V_R = 600 V$   | $T_{VJ} = 25^{\circ}C$       |         | 50   | $\mu A$    |  |
|            |  | $V_R = 600 V$   | $T_{VJ} = 125^{\circ}C$      |         | 4    | mA         |  |
| $V_F$      | forward voltage drop                         | $I_F = 30 A$  | $T_{VJ} = 25^{\circ}C$       |         | 2.26 | V          |  |
|            |  | $I_F = 60 A$  |                              |         | 3.11 | V          |  |
|            |  | $I_F = 30 A$  | $T_{VJ} = 125^{\circ}C$      |         | 2.22 | V          |  |
|            |  | $I_F = 60 A$  |                              |         | 3.20 | V          |  |
| $I_{FAV}$  | average forward current                      | $T_C = 95^{\circ}C$<br>rectangular $d = 0.5$              | $T_{VJ} = 150^{\circ}C$      |         | 30   | A          |  |
| $V_{FO}$   | threshold voltage                            | } for power loss calculation only                         | $T_{VJ} = 150^{\circ}C$      |         | 1.17 | V          |  |
| $r_F$      | slope resistance                             |   |                              |         | 32   | m $\Omega$ |  |
| $R_{thJC}$ | thermal resistance junction to case          |   |                              |         | 0.6  | K/W        |  |
| $R_{thCH}$ | thermal resistance case to heatsink          |   |                              | 0.25    |      | K/W        |  |
| $P_{tot}$  | total power dissipation                      |   | $T_C = 25^{\circ}C$          |         | 210  | W          |  |
| $I_{FSM}$  | max. forward surge current                   | $t = 10 ms; (50 Hz), sine; V_R = 0 V$                     | $T_{VJ} = 45^{\circ}C$       |         | 200  | A          |  |
| $C_J$      | junction capacitance                         | $V_R = 400 V f = 1 MHz$                                   | $T_{VJ} = 25^{\circ}C$       |         | 16   | pF         |  |
| $I_{RM}$   | max. reverse recovery current                | } $I_F = 35 A; V_R = 400 V$<br>$-di_F / dt = 600 A/\mu s$ | $T_{VJ} = 25^{\circ}C$       |         | 12   | A          |  |
|            |  |   | $T_{VJ} = \text{ }^{\circ}C$ |         | tbd  | A          |  |
| $t_{rr}$   | reverse recovery time                        |   | $T_{VJ} = 25^{\circ}C$       |         | 35   | ns         |  |
|            |  |   | $T_{VJ} = \text{ }^{\circ}C$ |         | tbd  | ns         |  |



preliminary

| Package TO-263 (D2Pak) |                              |                            | Ratings |      |      |      |
|------------------------|------------------------------|----------------------------|---------|------|------|------|
| Symbol                 | Definition                   | Conditions                 | min.    | typ. | max. | Unit |
| $I_{RMS}$              | RMS current                  | per terminal <sup>1)</sup> |         |      | 35   | A    |
| $T_{VJ}$               | virtual junction temperature |                            | -55     |      | 150  | °C   |
| $T_{op}$               | operation temperature        |                            | -55     |      | 125  | °C   |
| $T_{stg}$              | storage temperature          |                            | -55     |      | 150  | °C   |
| <b>Weight</b>          | <b>Product Marking</b>       | <b>Part description</b>    |         | 2    |      | g    |
| $F_C$                  | mounting force with clip     | D = Diode                  | 20      |      | 60   | N    |



H = Sonic Fast Recovery Diode  
 G = extreme fast  
 30 = Current Rating [A]  
 IM = Single Diode  
 600 = Reverse Voltage [V]  
 PC = TO-263AB (D2Pak) (2)

| Ordering    | Ordering Number  | Marking on Product | Delivery Mode | Quantity | Code No. |
|-------------|------------------|--------------------|---------------|----------|----------|
| Standard    | DHG30IM600PC-TRL | DHG30IM600PC       | Tape & Reel   | 800      | 503501   |
| Alternative | DHG30IM600PC-TUB | DHG30IM600PC       | Tube          | 50       | 525078   |


| Similar Part | Package      | Voltage class |
|--------------|--------------|---------------|
| DHG30I600PA  | TO-220AC (2) | 600           |
| DHG30I600HA  | TO-247AD (2) | 600           |

**Equivalent Circuits for Simulation** \* on die level  $T_{VJ} = 150\text{ }^\circ\text{C}$

|                    |                    |      |    |
|--------------------|--------------------|------|----|
| $V_{0\text{ max}}$ | threshold voltage  | 1.17 | V  |
| $R_{0\text{ max}}$ | slope resistance * | 29   | mΩ |




**Outlines TO-263 (D2Pak)**



| Dim. | Millimeter |       | Inches      |       |
|------|------------|-------|-------------|-------|
|      | min        | max   | min         | max   |
| A    | 4.06       | 4.83  | 0.160       | 0.190 |
| A1   | typ. 0.10  |       | typ. 0.004  |       |
| A2   | 2.41       |       | 0.095       |       |
| b    | 0.51       | 0.99  | 0.020       | 0.039 |
| b2   | 1.14       | 1.40  | 0.045       | 0.055 |
| c    | 0.40       | 0.74  | 0.016       | 0.029 |
| c2   | 1.14       | 1.40  | 0.045       | 0.055 |
| D    | 8.38       | 9.40  | 0.330       | 0.370 |
| D1   | 8.00       | 8.89  | 0.315       | 0.350 |
| D2   | 2.5        |       | 0.098       |       |
| E    | 9.65       | 10.41 | 0.380       | 0.410 |
| E1   | 6.22       | 8.50  | 0.245       | 0.335 |
| e    | 2.54 BSC   |       | 0.100 BSC   |       |
| e1   | 4.28       |       | 0.169       |       |
| H    | 14.61      | 15.88 | 0.575       | 0.625 |
| L    | 1.78       | 2.79  | 0.070       | 0.110 |
| L1   | 1.02       | 1.68  | 0.040       | 0.066 |
| W    | typ. 0.02  | 0.040 | typ. 0.0008 | 0.002 |

*All dimensions conform with and/or within JEDEC standard.*





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.