

1000W, 10V - 100V Surface Mount Transient Voltage Suppressor

FEATURES FEATURES

- Low profile package
- Ideal for automated placement
- Glass passivated junction
- Built-in strain relief
- Excellent clamping capability
- Fast response time: Typically less than 1.0ps from 0 volt to BV min
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21

APPLICATIONS

- Switching mode power supply (SMPS)
- Adapters
- TV
- Monitor

MECHANICAL DATA

- Case: DO-214AA (SMB)
- Molding compound meets UL 94V-0 flammability rating
- Moisture sensitivity level: level 1, per J-STD-020
- Part no. with suffix "H" means AEC-Q101 qualified
- Packing code with suffix "G" means green compound (halogen-free)
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 2 whisker test
- Polarity: As marked
- Weight: 0.11 g (approximately)

| KEY PARAMETERS | | |
|----------------------------|----------------|------|
| PARAMETER | VALUE | UNIT |
| V_{WM} | 8.55 – 85.5 | V |
| V_{BR} (uni-directional) | 9.5 - 105 | V |
| V_{BR} (bi-directional) | 9.5 - 105 | V |
| P_{PPSM} | 1000 | W |
| T_{JMAX} | 175 | °C |
| Package | DO-214AA (SMB) | |
| Configuration | Single die | |



DO-214AA (SMB)

| ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted) | | | |
|---|------------|-------------|------|
| PARAMETER | SYMBOL | PART NUMBER | UNIT |
| Non-repetitive peak impulse power dissipation with 10/1000us waveform | P_{PPSM} | 1000 | W |
| Steady state power dissipation at $T_A=25^\circ\text{C}$ ⁽¹⁾ | P_{tot} | 5 | W |
| Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load | I_{FSM} | 100 | A |
| Forward Voltage @ $I_F=50\text{A}$ for Uni-directional only ⁽²⁾ | V_F | 3.5/5.0 | V |
| Junction temperature | T_J | -55 to +175 | °C |
| Storage temperature | T_{STG} | -55 to +175 | °C |

Notes:

1. Non-repetitive Current Pulse Per Fig. 3 and Derated above $T_A=25^\circ\text{C}$ Per Fig. 2
2. $V_F=3.5\text{V}$ for Devices of $V_{BR} \leq 50\text{V}$ and $V_F=5.0\text{V}$ Max. for Devices $V_{BR} > 50\text{V}$

Devices for Bipolar Applications

1. For Bidirectional use CA suffix

| THERMAL PERFORMANCE | | | |
|--|-----------------|--------------|-------------|
| PARAMETER | SYMBOL | LIMIT | UNIT |
| Junction-to-lead thermal resistance | $R_{\theta JL}$ | 20 | °C/W |
| Junction-to-ambient thermal resistance | $R_{\theta JA}$ | 100 | °C/W |

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

| Device | Device Marking Code | Breakdown Voltage $V_{BR@I_T}$ (V) | | Test Current I_T (mA) | Stand-Off Voltage @ V_{WM} (V) | Maximum Reverse Leakage @ V_{WM} (μA) | Maximum Peak imp current I_{PP} (A) (Note 2) | Maximum Clamping Voltage $V_C@I_{PP}$ (V) |
|-----------|---------------------|------------------------------------|------|-------------------------|----------------------------------|--|--|---|
| | | Min. | Max. | | | | | |
| 1KSMB10A | A10E | 9.5 | 10.5 | 1.0 | 8.55 | 10.0 | 69.0 | 14.5 |
| 1KSMB10CA | N10E | | | | | | | |
| 1KSMB11A | A10F | 10.5 | 11.6 | 1.0 | 9.40 | 5.0 | 64.1 | 15.6 |
| 1KSMB11CA | N10F | | | | | | | |
| 1KSMB12A | A10G | 11.4 | 12.6 | 1.0 | 10.2 | 5.0 | 59.9 | 16.7 |
| 1KSMB12CA | N10G | | | | | | | |
| 1KSMB13A | A10H | 12.4 | 13.7 | 1.0 | 11.1 | 5.0 | 54.9 | 18.2 |
| 1KSMB13CA | N10H | | | | | | | |
| 1KSMB15A | A10I | 14.3 | 15.8 | 1.0 | 12.8 | 5.0 | 47.2 | 21.2 |
| 1KSMB15CA | N10I | | | | | | | |
| 1KSMB16A | A10J | 15.2 | 16.8 | 1.0 | 13.6 | 1.0 | 44.4 | 22.5 |
| 1KSMB16CA | N10J | | | | | | | |
| 1KSMB18A | A10K | 17.1 | 18.9 | 1.0 | 15.3 | 1.0 | 39.2 | 25.5 |
| 1KSMB18CA | N10K | | | | | | | |
| 1KSMB20A | A10L | 19.0 | 21.0 | 1.0 | 17.1 | 1.0 | 36.1 | 27.7 |
| 1KSMB20CA | N10L | | | | | | | |
| 1KSMB22A | A10M | 20.9 | 23.1 | 1.0 | 18.8 | 1.0 | 32.7 | 30.6 |
| 1KSMB22CA | N10M | | | | | | | |
| 1KSMB24A | A10N | 22.8 | 25.2 | 1.0 | 20.5 | 1.0 | 30.1 | 33.2 |
| 1KSMB24CA | N10N | | | | | | | |
| 1KSMB27A | A10O | 25.7 | 28.4 | 1.0 | 23.1 | 1.0 | 26.7 | 37.5 |
| 1KSMB27CA | N10O | | | | | | | |
| 1KSMB30A | A10P | 28.5 | 31.5 | 1.0 | 25.6 | 1.0 | 24.2 | 41.4 |
| 1KSMB30CA | N10P | | | | | | | |
| 1KSMB33A | A10Q | 31.4 | 34.7 | 1.0 | 28.2 | 1.0 | 21.9 | 45.7 |
| 1KSMB33CA | N10Q | | | | | | | |
| 1KSMB36A | A10R | 34.2 | 37.8 | 1.0 | 30.8 | 1.0 | 20.0 | 49.9 |
| 1KSMB36CA | N10R | | | | | | | |
| 1KSMB39A | A10S | 37.1 | 41.0 | 1.0 | 33.3 | 1.0 | 18.6 | 53.9 |
| 1KSMB39CA | N10S | | | | | | | |
| 1KSMB43A | A10T | 40.9 | 45.2 | 1.0 | 36.8 | 1.0 | 16.9 | 59.3 |
| 1KSMB43CA | N10T | | | | | | | |
| 1KSMB47A | A10U | 44.7 | 49.4 | 1.0 | 40.2 | 1.0 | 15.4 | 64.8 |
| 1KSMB47CA | N10U | | | | | | | |
| 1KSMB51A | A10V | 48.5 | 53.6 | 1.0 | 43.6 | 1.0 | 14.3 | 70.1 |
| 1KSMB51CA | N10V | | | | | | | |
| 1KSMB56A | A10W | 53.2 | 58.8 | 1.0 | 47.8 | 1.0 | 13.0 | 77.0 |
| 1KSMB56CA | N10W | | | | | | | |
| 1KSMB62A | A10X | 58.9 | 65.1 | 1.0 | 53.0 | 1.0 | 11.8 | 85.0 |
| 1KSMB62CA | N10X | | | | | | | |
| 1KSMB68A | A10Y | 64.6 | 71.4 | 1.0 | 58.1 | 1.0 | 10.9 | 92.0 |
| 1KSMB68CA | N10Y | | | | | | | |

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

| Device | Device Marking Code | Breakdown voltage $V_{BR}@I_T$ (V) (Note 1) | | Test current I_T (mA) | Stand-Off Voltage @ V_{WM} (V) | Maximum Reverse leakage @ V_{WM} (μA) | Maximum peak impulse current I_{PP} (A) (Note 2) | Maximum clamping voltage $V_C@I_{PP}$ (V) |
|------------|---------------------|---|------|-------------------------|----------------------------------|--|--|---|
| | | Min. | Max. | | | | | |
| 1KSMB75A | A10Z | 71.3 | 78.8 | 1.0 | 64.1 | 1.0 | 9.7 | 103 |
| 1KSMB75CA | N10Z | | | | | | | |
| 1KSMB82A | B10A | 77.9 | 86.1 | 1.0 | 70.1 | 1.0 | 8.8 | 113 |
| 1KSMB82CA | O10A | | | | | | | |
| 1KSMB91A | B10B | 86.5 | 95.5 | 1.0 | 77.8 | 1.0 | 8.0 | 125 |
| 1KSMB91CA | O10B | | | | | | | |
| 1KSMB100A | B10C | 95 | 105 | 1.0 | 85.5 | 1.0 | 7.3 | 137 |
| 1KSMB100CA | O10C | | | | | | | |

Notes:

- V_{BR} measure after I_T applied for $300\mu\text{s}$, I_T =square wave pulse or equivalent.
- All terms and symbols are consistent with ANSI/IEEE C62.35.
- For Bidirectional use CA suffix

ORDERING INFORMATION

| PART NO. | PART NO. SUFFIX | PACKING CODE | PACKING CODE SUFFIX(*) | PACKAGE | PACKING |
|-----------------------|-----------------|--------------|------------------------|---------|--------------------------|
| 1KSMBxxxx (Note 1) | H | R5 | G | SMB | 850 / 7" Plastic reel |
| | | R4 | | SMB | 3,000 / 13" Paper reel |
| | | M4 | | SMB | 3,000 / 13" Plastic reel |

Note :

- "xxxx" defines voltage from 10V (1KSMB10A) to 100V (1KSMB100CA)
- *: Optional available

EXAMPLE P/N

| EXAMPLE P/N | PART NO. | PART NO. SUFFIX | PACKING CODE | PACKING CODE SUFFIX | DESCRIPTION |
|--------------|----------|-----------------|--------------|---------------------|--------------------------------------|
| 1KSMB39AHR5G | 1KSMB39A | H | R5 | G | AEC-Q101 qualified Green compound |

CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig1. Peak Pulse Power Rating Curve



Fig2. Pulse Derating Curve



Fig3. Clamping Power Pulse Waveform



Fig4. Maximum Non-Repetitive Forward Surge Current Unidirectional Only



Fig5. Typical Junction Capacitance



PACKAGE OUTLINE DIMENSIONS

DO-214AA (SMB)



| DIM. | Unit (mm) | | Unit (inch) | |
|------|-----------|------|-------------|-------|
| | Min | Max | Min | Max |
| A | 1.95 | 2.20 | 0.077 | 0.087 |
| B | 4.05 | 4.60 | 0.159 | 0.181 |
| C | 3.30 | 3.95 | 0.130 | 0.156 |
| D | 1.95 | 2.65 | 0.077 | 0.104 |
| E | 0.75 | 1.60 | 0.030 | 0.063 |
| F | 5.10 | 5.60 | 0.201 | 0.220 |
| G | 0.05 | 0.20 | 0.002 | 0.008 |
| H | 0.15 | 0.31 | 0.006 | 0.012 |

SUGGESTED PAD LAYOUT



| Symbol | Unit (mm) | Unit (inch) |
|--------|-----------|-------------|
| A | 2.3 | 0.091 |
| B | 2.5 | 0.098 |
| C | 4.3 | 0.169 |
| D | 1.8 | 0.071 |
| E | 6.8 | 0.268 |

MARKING DIAGRAM



- P/N = Marking Code
- G = Green Compound
- YW = Date Code
- F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.