


Full-HD-Flatpanel-Controller

CRTtoLCD-51-pro

- DVI-I incl. Analog-RGB and DisplayPort (DP) inputs up to WUXGA
- Display resolution up to WUXGA (1920x1200)
- Highest picture quality due to improved scaling algorithms
- Powerful software tools including Panel-Editor and Serial-API
- Scripting support

Full-HD-Flatpanel-Controller CRTtoLCD-51-pro



Description

The CRTtoLCD-51-pro is a highly integrated Full-HD-Flatpanel-Controller that allows connection of standard Analog RGB, DVI and DisplayPort sources to TFT-LCD flatpanels.

It includes all the necessary functionality to design a full featured LCD monitor.

From a single +12V DC power supply, the CRTtoLCD-51-pro generates all required supply voltages and power sequencing. LED or CCFL backlight dimming is supported and can be controlled by PWM or absolute voltage level.

Typical Verticals

Point of Sales (POS):	Check-in terminals
Point of Information (POI):	Public displays
Industrial Automation & Medical:	Panel-PCs, Industrial monitors
Test & Measurement:	Smart displays
Transportation:	Rugged displays
Gaming Machines:	Casino slot machines, Lottery systems, Open frame monitors

Full-HD-Flatpanel-Controller CRTtoLCD-51-pro

Technical Information

DVI Input	<ul style="list-style-type: none"> • Highest quality up to WUXGA@60Hz (with full zoom & shrink capabilities)
Analog Input	<ul style="list-style-type: none"> • Analog-RGB-Interface via DVI-I up to WUXGA@60Hz, All color depths up to 24 bits/pixel
DisplayPort Input	<ul style="list-style-type: none"> • Integrated DisplayPort 1.1 compliant receiver up to WUXGA
High Quality Advanced Scaling	<ul style="list-style-type: none"> • Horizontal & Vertical Zoom
Specials	<ul style="list-style-type: none"> • Two separate onboard power supplies for flatpanel (up to 3A) • High power connector for backlight (up to 3.5A) • Ambient Light Sensor support to control backlight brightness via ADC input • PWM or voltage controlled backlight dimming • Scripting support • DDC2Bi / VCP (also accessible via script) • Serial-API for full access to various functions and features • Serial-OSD for keypad-less OSD control
Integrated On-Screen-Display	<ul style="list-style-type: none"> • On Screen Display (OSD) for full control of all configured features
Display-Interface	<ul style="list-style-type: none"> • JLI30 (up to 2x24Bit dual channel LVDS) Output up to WUXGA@60Hz (1920x1200)
Form Factor	<ul style="list-style-type: none"> • 179.07 mm x 119.50 mm x 16.5 mm (L/W/H)
Optional	<ul style="list-style-type: none"> • Inverter and display cable-kits for various flatpanels

Ordering Information

Article	Part.-No.	Description
CRTtoLCD-51-pro	21029E	Full-HD-Flatpanel-Controller with Analog-RGB(VGA) via DVI-I and DisplayPort inputs , Dual channel LVDS output
KAB-COMtoTTL	61021E	Serial-RS232 to TTL converter cable for CRTtoLCD-51-pro/-61-pro/-71-LP/-61-LP
OSD-Panel-Set	22010	5-button On-Screen-Display(OSD)-Keypad incl. cable



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.