








3M™ Shrouded Board Mount Header 2 mm X 2 mm Pitch 159 Series, Standard Length [3] and Extended Length [4]



RECOMMENDED PCB HOLE PATTERN
TOLERANCE = 0.05 [.002]

PERFORMANCE [5] [7]	
CURRENT:	1.25 A, ALL LINES ENERGIZED 2.75 A, 6 LINES ENERGIZED 4.75 A, 1 LINE ENERGIZED
INSULATION RESISTANCE:	>1 X 10 ⁹ OHMS AT 500 VDC
WITHSTANDING VOLTAGE:	500 VACrms AT SEA LEVEL
TEMPERATURE RATING:	-55° C TO +105° C
SOLDER PROCESS TEMPERATURE:	260° C MAX PER IPC/JEDEC J-STD-020D

REFERENCE TABLE ON SHEET 5
FOR AVAILABLE POSITIONS AND
SOLDER TAIL LENGTHS

METRIC [ENGLISH]

- NOTES
- 1

MATERIAL:
BODY: HIGH TEMPERATURE
GLASS FILLED LCP, BLACK
UL94V-0
CONTACTS: COPPER ALLOY
- 2

PLATING:
2.03-3.81 μ m [80-150 μ in]
NICKEL UNDERPLATE.
0.38 μ m [15 μ in] OR
0.76 μ m [30 μ in] AVG GOLD
ON WIPING AREA.
5.08 μ m [200 μ in] MIN
MATTE TIN ON SOLDER TAILS.
- 3

STANDARD LENGTH HEADERS
MATE WITH 3M™ SOCKETS,
158 SERIES (REFERENCE 3M
DRAWING 78-5100-2358-9).
- 4

EXTENDED LENGTH HEADERS
MATE WITH 3M™ SOCKETS,
870 SERIES.
- 5

FOR PRODUCT
SPECIFICATIONS AND
WARRANTY INFORMATION SEE
3M 78-5102-0078-1.
- 6





SEE THE REGULATORY
INFORMATION APPENDIX (RIA)
IN THE "RoHS COMPLIANCE"
SECTION OF
WWW.3MCONNECTOR.COM FOR
COMPLIANCE INFORMATION
(RIA E1 & C1 APPLY).
- 7

IN THE EVENT OF CONFLICT
BETWEEN THIS DATA AND
THAT CONTAINED IN THE
PRODUCT SPECIFICATION,
THE PRODUCT SPECIFICATION
TAKES PRECEDENT.


D	41488	JUN 20,2012	LDS	SAN
		REVISED CURRENT RATING IN PERFORMANCE TABLE		
C	39876	APR 18,2012	LDS	SAN
		REMOVED 32 POS FROM TABLE ON SHT 5		
B	34080	MAY 18,2011	LDS	SF
		ADDED 6.19 DIM ON SHT 2; REVISED & MOVED TABLE TO SHT 5		
A	30741	OCT 28,2010	LDS	SF
		INITIAL RELEASE		
REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
DRP	L. SCHMIDT	DATE JUL 29,2010	MFG	DATE
CHKD		DATE	APPRV	DATE
			S FELDMAN	AUG 09,2010

DO NOT SCALE DRAWING		SCALE 6 1	TOLERANCES EXCEPT AS NOTED	INCHES 0 0.00 0.008 0.000 0.000		MILLIMETERS 0 0 0.00 0.00 0.000		INTERPRET PER ASME Y14.5 - 1994		MAX SURFACE ROUGHNESS 125 ALL SURFACES MARKED ONLY		ANGLES ±1°	
THIRD ANGLE PROJECTION													
TITLE		3M SHROUDED BOARD MOUNT HEADER 2 MM X 2 MM PITCH 159 SERIES		CAGE NUMBER		DRAWING NO.		REV.		MODEL		SHT 1 OF 5	
		D		78-5100-2359-7		D							


3M™ Shrouded Board Mount Header 2 mm X 2 mm Pitch 159 Series, Standard Length [3] and Extended Length [4]




RECOMMENDED PCB HOLE PATTERN
TOLERANCE = ±0.05 [.002]



POLARIZATION SLOT
RIGHT ANGLE HEADER
6-12 POSITIONS ONLY



POLARIZATION SLOT AND
DUAL FRICTION LATCHES
RIGHT ANGLE HEADER
14-50 POSITIONS






SINGLE FRICTION LATCH
RIGHT ANGLE HEADER
6-12 POSITIONS ONLY

REFERENCE TABLE ON SHEET 5
FOR AVAILABLE POSITIONS AND
SOLDER TAIL LENGTHS



METRIC [ENGLISH]

DESIGN REFERENCE		NEXT ASSEMBLY		REV	ECO	ISSUE DATE AND DESCRIPTION		DRFT	CHKD
DISTRIBUTION CODES				DRFT	L. SCHMIDT	DATE	JUL 29, 2010	MRG	DATE
				CHKD	C. W.	DATE		S FELDMAN	DATE
									AUG 09, 2010
DIVISION		DIVISION CODE		3M 3M Center St. Paul, MN 55144		© 3M COPYRIGHT 2010 This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.			
DO NOT SCALE DRAWING	SCALE 4 1	TOLERANCES EXCEPT AS NOTED							
		INCHES							
THIRD ANGLE PROJECTION		MILLIMETERS							
INTERPRET PER ASME Y14.5 - 1994				TITLE		3M SHROUDED BOARD MOUNT HEADER 2 MM X 2 MM PITCH 159 SERIES			
MAX SURFACE ROUGHNESS				CAGE NUMBER		DRAWING NO.			
125 ✓		□ ALL SURFACES ☒ MARKED ONLY		D		78-5100-2359-7			
		ANGLES ± 1°		MODEL		REV.			
						DET. LISTS YES ☐ NO ☒ SHT 2 OF 5			


3M™ Shrouded Board Mount Header 2 mm X 2 mm Pitch 159 Series, Standard Length 3 and Extended Length 4




RECOMMENDED PCB PAD PATTERN
TOLERANCE = ±0.08 [0.003]



POLARIZATION SLOT
SURFACE MOUNT HEADER
6-12 POSITIONS ONLY



POLARIZATION SLOT AND
DUAL FRICTION LATCHES
SURFACE MOUNT HEADER
14-50 POSITIONS



SINGLE FRICTION LATCH
SURFACE MOUNT HEADER
6-12 POSITIONS ONLY


REFERENCE TABLE ON SHEET 5
FOR AVAILABLE POSITIONS

METRIC [ENGLISH]

DESIGN REFERENCE		NEXT ASSEMBLY		REV	ECO	ISSUE DATE AND DESCRIPTION		DRFT	CHKD
DISTANCE		DISTANCE		DRFT	CHKD	DATE	DATE	DATE	DATE
L. SCHMIDT		JUL 29, 2010		DRFT	CHKD	DATE	DATE	DATE	DATE
DIVISION		DIVISION CODE		APPROVAL		DATE		DATE	
DO NOT SCALE DRAWING		SCALE 4/1		TOLERANCES EXCEPT AS NOTED		INCHES		MILLIMETERS	
THIRD ANGLE PROJECTION		INTERPRET PER ASME Y14.5 - 1994		MAX SURFACE ROUGHNESS		ALL SURFACES		MARKED ONLY	
125		125		125		125		125	
ANGLES ±1°		ANGLES ±1°		ANGLES ±1°		ANGLES ±1°		ANGLES ±1°	
CAGE NUMBER		DRAWING NO.		REV.		MODEL		SHEET	
125		D 78-5100-2359-7		D		SHEET 3 OF 5		SHEET 3 OF 5	


3M™ Shrouded Board Mount Header 2 mm X 2 mm Pitch 159 Series, Standard Length 3

STANDARD LENGTH HEADERS
ARE AVAILABLE



3M™ Shrouded Board Mount Header 2 mm X 2 mm Pitch 159 Series, Extended Length 4

CALL 3M INTERCONNECT SOLUTIONS
AT 800-225-5373 FOR AVAILABILITY
OF EXTENDED LENGTH HEADERS



ORDERING INFORMATION

TIER 1 - BEST
1591XX-XXXX

TIER
1 = BEST 0.76 μm
[30 μin] GOLD

POSITION COUNT
(SEE TABLE)

PART CONFIGURATION
2 = VERTICAL SMT
5 = RIGHT ANGLE THRU HOLE
6 = VERTICAL THRU HOLE

BODY LENGTH
0 = STANDARD LENGTH
(MATES TO 158 SERIES)
1 = EXTENDED LENGTH
(MATES TO 870 SERIES)

CONTACT TAIL LENGTH
2 = 2.84 mm [.112]
3 = 3.94 mm [.155]

POLARIZATION/LATCHING
0 = POLARIZATION SLOT AND
DUAL FRICTION LATCHES
(14-50 POSITIONS ONLY)
1 = POLARIZATION SLOT
(6-12 POSITIONS ONLY)
2 = SINGLE FRICTION LATCH
(6-12 POSITIONS ONLY)

TIER 2 - BETTER
1592XX-XXXX

TIER
2 = BETTER 0.38 μm
[15 μin] GOLD

POSITION COUNT
(SEE TABLE)


PART CONFIGURATION
2 = VERTICAL SMT
5 = RIGHT ANGLE THRU HOLE
6 = VERTICAL THRU HOLE

BODY LENGTH
0 = STANDARD LENGTH
(MATES TO 158 SERIES)
1 = EXTENDED LENGTH
(MATES TO 870 SERIES)

CONTACT TAIL LENGTH
2 = 2.84 mm [.112]
3 = 3.94 mm [.155]

POLARIZATION/LATCHING
0 = POLARIZATION SLOT AND
DUAL FRICTION LATCHES
(14-50 POSITIONS ONLY)
1 = POLARIZATION SLOT
(6-12 POSITIONS ONLY)
2 = SINGLE FRICTION LATCH
(6-12 POSITIONS ONLY)

METRIC [ENGLISH]

DESIGN REFERENCE		NEXT ASSEMBLY		REV	ECO	ISSUE DATE AND DESCRIPTION		DRFT	CHKD
DISTRIBUTION CODES				DRFT	L. SCHMIDT	DATE	JUL 29, 2010	MFG	DATE
				CHKD		DATE		APPROV	DATE
								S. FELDMAN	AUG 09, 2010
DIVISION		DIVISION CODE		© 3M COPYRIGHT 2010					
DO NOT SCALE DRAWING		SCALE 4 1		TOLERANCES EXCEPT AS NOTED		This document and the information it contains are 3M property and may not be reproduced or further distributed without the express permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.			
		THIRD ANGLE PROJECTION		INCHES		3M 3M Center St. Paul, MN 55144			
				.00 ±		TITLE			
				.00 ±		3M SHROUDED BOARD			
				.000 ±		MOUNT HEADER 2 MM X 2			
				.0000 ±		MM PITCH 159 SERIES			
				MILLIMETERS		CAGE NUMBER			
				.00 ±		SIZE			
				.00 ±		DRAWING NO.			
				.000 ±		D 78-5100-2359-7			
				.000 ±		REV.			
				.000 ±		D			
				.000 ±		MODEL			
				.000 ±		DET.			
				.000 ±		LISTS			
				.000 ±		YES			
				.000 ±		NO			
				.000 ±		SHT			
				.000 ±		4 OF			
				.000 ±		B			
				.000 ±		C			
				.000 ±		D			
				.000 ±		E			
				.000 ±		F			
				.000 ±		G			
				.000 ±		H			
				.000 ±		J			
				.000 ±		K			
				.000 ±		L			
				.000 ±		M			
				.000 ±		N			
				.000 ±		P			
				.000 ±		Q			
				.000 ±		R			
				.000 ±		S			
				.000 ±		T			
				.000 ±		U			
				.000 ±		V			
				.000 ±		W			
				.000 ±		X			
				.000 ±		Y			
				.000 ±		Z			
				.000 ±		AA			
				.000 ±		AB			
				.000 ±		AC			
				.000 ±		AD			
				.000 ±		AE			
				.000 ±		AF			
				.000 ±		AG			
				.000 ±		AH			
				.000 ±		AI			
				.000 ±		AJ			
				.000 ±		AK			
				.000 ±		AL			
				.000 ±		AM			
				.000 ±		AN			
				.000 ±		AO			
				.000 ±		AP			
				.000 ±		AQ			
				.000 ±		AR			
				.000 ±		AS			
				.000 ±		AT			
				.000 ±		AU			
				.000 ±		AV			
				.000 ±		AW			
				.000 ±		AX			
				.000 ±		AY			
				.000 ±		AZ			
				.000 ±		BA			
				.000 ±		BB			
				.000 ±		BC			
				.000 ±		BD			
				.000 ±		BE			
				.000 ±		BF			
				.000 ±		BG			
				.000 ±		BH			
				.000 ±		BI			
				.000 ±		BJ			
				.000 ±		BK			
				.000 ±		BL			
				.000 ±		BM			
				.000 ±		BN			
				.000 ±		BO			
				.000 ±		BP			
				.000 ±		BQ			
				.000 ±		BR			
				.000 ±		BS			
				.000 ±		BT			
				.000 ±		BU			
				.000 ±		BV			
				.000 ±		BW			
				.000 ±		BX			
				.000 ±		BY			
				.000 ±		BZ			
				.000 ±		CA			
				.000 ±		CB			
				.000 ±		CC			
				.000 ±		CD			
				.000 ±		CE			
				.000 ±		CF			
				.000 ±		CG			
				.000 ±		CH			
				.000 ±		CI			
				.000 ±		CJ			
				.000 ±		CK			
				.000 ±		CL			
				.000 ±		CM			
				.000 ±		CN			
				.000 ±		CO			
				.000 ±		CP			
				.000 ±		CQ			
				.000 ±		CR			
				.000 ±		CS			
				.000 ±		CT			
				.000 ±		CU			
				.000 ±		CV			
				.000 ±		CW			
				.000 ±		CX			
				.000 ±		CY			
				.000 ±		CZ			
				.000 ±		DA			
				.000 ±		DB			
				.000 ±		DC			
				.000 ±		DD			
				.000 ±		DE			
				.000 ±		DF			
				.000 ±		DG			
				.000 ±		DH			
				.000 ±		DI			
				.000 ±		DJ			
				.000 ±		DK			
				.000 ±		DL			
				.000 ±		DM			
				.000 ±		DN			
				.000 ±		DO			
				.000 ±		DP			
				.000 ±		DQ			
				.000 ±		DR			
				.000 ±		DS			
				.000 ±		DT			
				.000 ±		DU			
				.000 ±		DV			
				.000 ±		DW			
				.000 ±		DX			
				.000 ±		DY			
				.000 ±		DZ			
				.000 ±		EA			
				.000 ±		EB			
				.000 ±		EC			
				.000 ±		ED			
				.000 ±		EE			
				.000 ±		EF			
				.000 ±		EG			
				.000 ±		EH			
				.000 ±		EI			
				.000 ±		EJ			
				.000 ±		EK			
				.000 ±		EL			
				.000 ±		EM			
				.000 ±		EN			
				.000 ±		EO			
				.000 ±		EP			
				.000 ±		EQ			
				.000 ±		ER			
				.000 ±		ES			
				.000 ±		ET			
				.000 ±		EU			
				.000 ±		EV			
				.000 ±		EW			
				.000 ±		EX			
				.000 ±		EY			
				.000 ±		EZ			
				.000 ±		FA			
				.000 ±		FB			
				.000 ±		FC			
				.000 ±		FD			
				.000 ±		FE			
				.000 ±		FF			
				.000 ±		FG			
				.000 ±		FH			
				.000 ±		FI			
				.000 ±		FJ			
				.000 ±		FK			
				.000 ±		FL			
				.000 ±		FM			
				.000 ±		FN			
				.000 ±		FO			
				.000 ±		FP			
				.000 ±		FQ			
				.000 ±		FR			
				.000 ±		FS			
				.000 ±		FT			
				.000 ±		FU			
				.000 ±		FV			
				.000 ±		FW			
				.000 ±		FX			
				.000 ±		FY			
				.000 ±		FZ			
				.000 ±		GA			
				.000 ±		GB			
				.000 ±		GC			
				.000 ±		GD			
				.000 ±		GE			
				.000 ±		GF			
				.000 ±		GG			
				.000 ±		GH			
				.000 ±		GI			
				.000 ±		GJ			
				.000 ±		GK			
				.000 ±		GL			
				.000 ±		GM			
				.000 ±		GN			
				.000 ±		GO			
				.000 ±		GP			
				.000 ±		GQ			
				.000 ±		GR			
				.000 ±		GS			
				.000 ±		GT			
				.000 ±		GU			
				.000 ±		GV			
				.000 ±		GW			
				.000 ±		GX			
				.000 ±		GY			
				.000 ±		GZ			
				.000 ±		HA			
				.000 ±		HB			
				.000 ±		HC			
				.000 ±		HD			
				.000 ±		HE			
				.000 ±		HF			
				.000 ±		HG			
				.000 ±		HH			
				.000 ±		HI			
				.000 ±		HJ			
				.000 ±		HK			
				.000 ±		HL			
				.000 ±		HM			
				.000 ±		HN			
				.000 ±		HO			
				.000 ±		HP			
				.000 ±		HQ			
				.000 ±		HR			
				.000 ±		HS			
				.000 ±		HT			
				.000 ±		HU			
				.000 ±		HV			
				.000 ±		HW			
				.000 ±		HX			
				.000 ±		HY			
				.000 ±		HZ			
				.000 ±		IA			
				.000 ±		IB			
				.000 ±		IC			
				.000 ±		ID			
				.000 ±		IE			
				.000 ±		IF			
				.000 ±		IG			
				.000 ±		IH			
				.000 ±		II			
				.000 ±		IJ			
				.000 ±		IK			
				.000 ±		IL			
				.000 ±		IM			
				.000 ±		IN			
				.000 ±		IO			
				.000 ±		IP			
				.000 ±		IQ			
				.000 ±		IR			
				.000 ±		IS			
				.000 ±		IT			
				.000 ±		IU			
				.000 ±		IV			
				.000 ±		IW			
				.000 ±		IX			
				.000 ±		IY			
				.000 ±		IZ			
				.000 ±		JA			
				.000 ±		JB			
				.000 ±		JC			
				.000 ±		JD			
				.000 ±		JE			
				.000 ±		JF			
				.000 ±		JG			
				.000 ±		JH			
				.000 ±		JI			
				.000 ±		JJ			
				.000 ±		JK			
				.000 ±		JL			
				.000 ±		JM			
				.000 ±		JN			
				.000 ±		JO			
				.000 ±		JP			
				.000 ±		JQ			
				.000 ±		JR			
				.000 ±		JS			
				.000 ±		JT			
				.000 ±		JU			
				.000 ±		JV			

3M™ Shrouded Board Mount Header 2 mm X 2 mm Pitch 159 Series, Standard Length and Extended Length

SHROUDED BOX HEADER							
NUMBER OF POSITIONS	DIM A		DIM B	DIM C		DIM D	
	STANDARD	EXTENDED		STANDARD	EXTENDED		
6	8.35 [.329]	9.52 [.375]	4.00 [.157]	6.83 [.269]	7.99 [.315]	2.84 [.112]	3.94 [.155]
8	10.35 [.407]	11.52 [.453]	6.00 [.236]	8.83 [.347]	9.99 [.393]	2.84 [.112]	3.94 [.155]
10	12.35 [.486]	13.52 [.532]	8.00 [.315]	10.83 [.426]	11.99 [.472]	2.84 [.112]	3.94 [.155]
12	14.35 [.565]	15.52 [.611]	10.00 [.394]	12.83 [.505]	13.99 [.551]	2.84 [.112]	3.94 [.155]
14	16.35 [.644]	17.52 [.690]	12.00 [.472]	14.83 [.584]	15.99 [.630]	2.84 [.112]	3.94 [.155]
16	18.35 [.722]	19.52 [.768]	14.00 [.551]	16.83 [.662]	17.99 [.708]	2.84 [.112]	3.94 [.155]
20	22.35 [.880]	23.52 [.926]	18.00 [.709]	20.83 [.820]	21.99 [.866]	2.84 [.112]	3.94 [.155]
22	24.35 [.959]	25.52 [1.005]	20.00 [.787]	22.83 [.899]	23.99 [.945]	2.84 [.112]	3.94 [.155]
24	26.35 [1.037]	27.52 [1.083]	22.00 [.866]	24.83 [.977]	25.99 [1.023]	2.84 [.112]	3.94 [.155]
26	28.35 [1.116]	29.52 [1.162]	24.00 [.945]	26.83 [1.056]	27.99 [1.102]	2.84 [.112]	3.94 [.155]
30	32.35 [1.274]	33.52 [1.320]	28.00 [1.102]	30.83 [1.214]	31.99 [1.260]	2.84 [.112]	3.94 [.155]
34	36.35 [1.431]	37.52 [1.477]	32.00 [1.260]	34.83 [1.371]	35.99 [1.417]	2.84 [.112]	3.94 [.155]
40	42.35 [1.667]	43.52 [1.713]	38.00 [1.496]	40.83 [1.607]	41.99 [1.653]	2.84 [.112]	3.94 [.155]
44	46.35 [1.825]	47.52 [1.871]	42.00 [1.654]	44.83 [1.765]	45.99 [1.811]	2.84 [.112]	3.94 [.155]
50	52.35 [2.061]	53.52 [2.107]	48.00 [1.890]	50.83 [2.001]	51.99 [2.047]	2.84 [.112]	3.94 [.155]

D	41488	JUN 20,2012	LDS	SAN
		REVISED CURRENT RATING IN PERFORMANCE TABLE		
C	39876	APR 18,2012	LDS	SAN
		REMOVED 32 POS FROM TABLE ON SHT 5		
B	34080	MAY 18,2011	LDS	SF
		ADDED 6.19 DIM ON SHT 2; REVISED & MOVED TABLE TO SHT 5		
A	30741	OCT 28,2010	LDS	SF
		INITIAL RELEASE		
REV	ECO	ISSUE DATE AND DESCRIPTION		
DRFT		DATE	MFG	DATE
L	SCHMIDT	JUL 29,2010		
CHKD		DATE	APPROV	DATE
			S FELDMAN	AUG 09,2010

DESIGN REFERENCE		NEXT ASSEMBLY		REV		ECO		ISSUE DATE AND DESCRIPTION		DRFT		CHKD	
DISTRIBUTION CODES				DRFT L. SCHMIDT		DATE JUL 29, 2010		MFG		DATE			
				CHKD		DATE		PRP S. FELDMAN		DATE		AUG 09, 2010	
DIVISION				DIVISION CODE				 3M Center St. Paul, MN 55144 © 3M COPYRIGHT 2010 This document and the information it contains are 3M property and may not be reproduced or further distributed without the 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.					
DO NOT SCALE DRAWING		SCALE 1		TOLERANCES EXCEPT AS NOTED									
		INCHES		.00 .008 .0000		3M SHROUDED BOARD MOUNT HEADER 2 MM X 2 MM PITCH 159 SERIES							
THIRD ANGLE PROJECTION		MILLIMETERS		.00 .008 .000		CAGE NUMBER SIZE DRAWING NO. REV.							
INTERPRET PER ASME Y14.5 - 1994		MAX SURFACE ROUGHNESS 125 ALL SURFACES MARKED ONLY		ANGLES ± 1°		D 78-500-2359-7 D							
						DET. LISTS YES NO SHT 5 OF 5							

METRIC [ENGLISH]



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.