

# 74ALVC32

## Quad 2-input OR gate

Rev. 3 — 20 January 2014

Product data sheet

## 1. General description

The 74ALVC32 is a quad 2-input OR gate.

Schmitt trigger action on all inputs makes the device tolerant of slow rise and fall times.

## 2. Features and benefits

- Wide supply voltage range from 1.65 V to 3.6 V
- 3.6 V tolerant inputs/outputs
- CMOS low power consumption
- Direct interface with TTL levels (2.7 V to 3.6 V)
- Power-down mode
- Latch-up performance exceeds 250 mA
- Complies with JEDEC standards:
  - ◆ JESD8-7 (1.65 V to 1.95 V)
  - ◆ JESD8-5 (2.3 V to 2.7 V)
  - ◆ JESD8B/JESD36 (2.7 V to 3.6 V)
- ESD protection:
  - ◆ HBM JESD22-A114E exceeds 2000 V
  - ◆ MM JESD22-A115-A exceeds 200 V

## 3. Ordering information

Table 1. Ordering information

| Type number | Package           |          |  | Version  |
|-------------|-------------------|----------|--|----------|
|             | Temperature range | Name     | Description  |          |
| 74ALVC32D   | −40 °C to +85 °C  | SO14     | plastic small outline package; 14 leads;<br>body width 3.9 mm  | SOT108-1 |
| 74ALVC32PW  | −40 °C to +85 °C  | TSSOP14  | plastic thin shrink small outline package; 14 leads;<br>body width 4.4 mm  | SOT402-1 |
| 74ALVC32BQ  | −40 °C to +85 °C  | DHVQFN14 | plastic dual in-line compatible thermal enhanced very<br>thin quad flat package; no leads; 14 terminals;<br>body 2.5 × 3 × 0.85 mm | SOT762-1 |

## 4. Functional diagram




Fig 1. Logic symbol




Fig 2. IEC logic symbol




Fig 3. Logic diagram (one gate)

## 5. Pinning information

### 5.1 Pinning





Fig 4. Pin configuration SO14 and TSSOP14



- (1) This is not a supply pin. The substrate is attached to this pad using conductive die attach material. There is no electrical or mechanical requirement to solder this pad. However, if it is soldered, the solder land should remain floating or be connected to GND.

Fig 5. Pin configuration DHVQFN14

## 5.2 Pin description

Table 2. Pin description

| Symbol          | Pin          | Description    |
|-----------------|--------------|----------------|
| nA              | 1, 4, 9, 12  | data input     |
| nB              | 2, 5, 10, 13 | data input     |
| nY              | 3, 6, 8, 11  | data output    |
| V <sub>CC</sub> | 14           | supply voltage |
| GND             | 7            | ground (0 V)   |

## 6. Functional description

Table 3. Function table<sup>[1]</sup>

| Input nA | Input nB | Output nY |
|----------|----------|-----------|
| L        | L        | L         |
| L        | H        | H         |
| H        | L        | H         |
| H        | H        | H         |

- [1] H = HIGH voltage level  
L = LOW voltage level

## 7. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND (ground = 0 V).

| Symbol           | Parameter               | Conditions   | Min                                | Max                   | Unit |
|------------------|-------------------------|--|------------------------------------|-----------------------|------|
| V <sub>CC</sub>  | supply voltage          |  | -0.5                               | +4.6                  | V    |
| I <sub>IK</sub>  | input clamping current  | V <sub>I</sub> < 0 V                                     | -50                                | -                     | mA   |
| V <sub>I</sub>   | input voltage           |  | -0.5                               | +4.6                  | V    |
| I <sub>OK</sub>  | output clamping current | V <sub>O</sub> > V <sub>CC</sub> or V <sub>O</sub> < 0 V | -                                  | ±50                   | mA   |
| V <sub>O</sub>   | output voltage          | output HIGH or LOW state                                 | <sup>[1]</sup> <sup>[2]</sup> -0.5 | V <sub>CC</sub> + 0.5 | V    |
|                  |                         | output 3-state   | -0.5                               | +4.6                  | V    |
|                  |                         | power-down mode, V <sub>CC</sub> = 0 V                   | <sup>[2]</sup> -0.5                | +4.6                  | V    |
| I <sub>O</sub>   | output current          | V <sub>O</sub> = 0 V to V <sub>CC</sub>                  | -                                  | ±50                   | mA   |
| I <sub>CC</sub>  | supply current          |  | -                                  | 100                   | mA   |
| I <sub>GND</sub> | ground current          |  | -100                               | -                     | mA   |
| T <sub>stg</sub> | storage temperature     |  | -65                                | +150                  | °C   |
| P <sub>tot</sub> | total power dissipation | T <sub>amb</sub> = -40 °C to +85 °C                      | <sup>[3]</sup> -                   | 500                   | mW   |

- [1] The input and output voltage ratings may be exceeded if the input and output current ratings are observed.  
 [2] When V<sub>CC</sub> = 0 V (power-down mode), the output voltage can be 3.6 V in normal operation.  
 [3] For SO14 packages: above 70 °C derate linearly with 8 mW/K.  
 For TSSOP14 packages: above 60 °C derate linearly with 5.5 mW/K.  
 For DHVQFN14 packages: above 60 °C derate linearly with 4.5 mW/K.

## 8. Recommended operating conditions

**Table 5. Recommended operating conditions**

| Symbol              | Parameter                           | Conditions                      | Min  | Max      | Unit |
|---------------------|-------------------------------------|---------------------------------|------|----------|------|
| $V_{CC}$            | supply voltage                      |                                 | 1.65 | 3.6      | V    |
| $V_I$               | input voltage                       |                                 | 0    | 3.6      | V    |
| $V_O$               | output voltage                      | output HIGH or LOW state        | 0    | $V_{CC}$ | V    |
|                     |                                     | output 3-state                  | 0    | 3.6      | V    |
|                     |                                     | power-down mode; $V_{CC} = 0$ V | 0    | 3.6      | V    |
| $T_{amb}$           | ambient temperature                 | in free air                     | -40  | +85      | °C   |
| $\Delta t/\Delta V$ | input transition rise and fall rate | $V_{CC} = 1.65$ V to 2.7 V      | 0    | 20       | ns/V |
|                     |                                     | $V_{CC} = 2.7$ V to 3.6 V       | 0    | 10       | ns/V |

## 9. Static characteristics

**Table 6. Static characteristics**

At recommended operating conditions. Voltages are referenced to GND (ground = 0 V).

| Symbol    | Parameter                 | Conditions                                       | $T_{amb} = -40$ °C to +85 °C |                    |                      | Unit    |
|-----------|---------------------------|--|------------------------------|--------------------|----------------------|---------|
|           |                           |  | Min                          | Typ <sup>[1]</sup> | Max                  |         |
| $V_{IH}$  | HIGH-level input voltage  | $V_{CC} = 1.65$ V to 1.95 V                      | $0.65 \times V_{CC}$         | -                  | -                    | V       |
|           |                           | $V_{CC} = 2.3$ V to 2.7 V                        | 1.7                          | -                  | -                    | V       |
|           |                           | $V_{CC} = 2.7$ V to 3.6 V                        | 2.0                          | -                  | -                    | V       |
| $V_{IL}$  | LOW-level input voltage   | $V_{CC} = 1.65$ V to 1.95 V                      | -                            | -                  | $0.35 \times V_{CC}$ | V       |
|           |                           | $V_{CC} = 2.3$ V to 2.7 V                        | -                            | -                  | 0.7                  | V       |
|           |                           | $V_{CC} = 2.7$ V to 3.6 V                        | -                            | -                  | 0.8                  | V       |
| $V_{OH}$  | HIGH-level output voltage | $V_I = V_{IH}$ or $V_{IL}$                       |                              |                    |                      |         |
|           |                           | $I_O = -100$ $\mu$ A; $V_{CC} = 1.65$ V to 3.6 V | $V_{CC} - 0.2$               | -                  | -                    | V       |
|           |                           | $I_O = -6$ mA; $V_{CC} = 1.65$ V                 | 1.25                         | 1.51               | -                    | V       |
|           |                           | $I_O = -12$ mA; $V_{CC} = 2.3$ V                 | 1.8                          | 2.10               | -                    | V       |
|           |                           | $I_O = -18$ mA; $V_{CC} = 2.3$ V                 | 1.7                          | 2.01               | -                    | V       |
|           |                           | $I_O = -12$ mA; $V_{CC} = 2.7$ V                 | 2.2                          | 2.53               | -                    | V       |
|           |                           | $I_O = -18$ mA; $V_{CC} = 3.0$ V                 | 2.4                          | 2.76               | -                    | V       |
|           |                           | $I_O = -24$ mA; $V_{CC} = 3.0$ V                 | 2.2                          | 2.68               | -                    | V       |
| $V_{OL}$  | LOW-level output voltage  | $V_I = V_{IH}$ or $V_{IL}$                       |                              |                    |                      |         |
|           |                           | $I_O = 100$ $\mu$ A; $V_{CC} = 1.65$ V to 3.6 V  | -                            | -                  | 0.2                  | V       |
|           |                           | $I_O = 6$ mA; $V_{CC} = 1.65$ V                  | -                            | 0.11               | 0.3                  | V       |
|           |                           | $I_O = 12$ mA; $V_{CC} = 2.3$ V                  | -                            | 0.17               | 0.4                  | V       |
|           |                           | $I_O = 18$ mA; $V_{CC} = 2.3$ V                  | -                            | 0.25               | 0.6                  | V       |
|           |                           | $I_O = 12$ mA; $V_{CC} = 2.7$ V                  | -                            | 0.16               | 0.4                  | V       |
|           |                           | $I_O = 18$ mA; $V_{CC} = 3.0$ V                  | -                            | 0.23               | 0.4                  | V       |
|           |                           | $I_O = 24$ mA; $V_{CC} = 3.0$ V                  | -                            | 0.30               | 0.55                 | V       |
| $I_I$     | input leakage current     | $V_{CC} = 3.6$ V; $V_I = 3.6$ V or GND           | -                            | $\pm 0.1$          | $\pm 5$              | $\mu$ A |
| $I_{OFF}$ | power-off leakage current | $V_{CC} = 0$ V; $V_I$ or $V_O = 0$ V to 3.6 V    | -                            | $\pm 0.1$          | $\pm 10$             | $\mu$ A |

**Table 6. Static characteristics ...continued**

At recommended operating conditions. Voltages are referenced to GND (ground = 0 V).

| Symbol           | Parameter                 | Conditions   | T <sub>amb</sub> = -40 °C to +85 °C |                    |     | Unit |
|------------------|---------------------------|--|-------------------------------------|--------------------|-----|------|
|                  |                           |  | Min                                 | Typ <sup>[1]</sup> | Max |      |
| I <sub>CC</sub>  | supply current            | V <sub>CC</sub> = 3.6 V; V <sub>I</sub> = V <sub>CC</sub> or GND;<br>I <sub>O</sub> = 0 A                          | -                                   | 0.2                | 10  | μA   |
| ΔI <sub>CC</sub> | additional supply current | per input pin; V <sub>CC</sub> = 3.0 V to 3.6 V;<br>V <sub>I</sub> = V <sub>CC</sub> - 0.6 V; I <sub>O</sub> = 0 A | -                                   | 5                  | 750 | μA   |
| C <sub>I</sub>   | input capacitance         |  | -                                   | 3.5                | -   | pF   |

[1] All typical values are measured at V<sub>CC</sub> = 3.3 V (unless stated otherwise) and T<sub>amb</sub> = 25 °C.

## 10. Dynamic characteristics

**Table 7. Dynamic characteristics**Voltages are referenced to GND (ground = 0 V). For test circuit see [Figure 7](#).


| Symbol          | Parameter                        | Conditions   | T <sub>amb</sub> = -40 °C to +85 °C |                    |     | Unit |
|-----------------|----------------------------------|--|-------------------------------------|--------------------|-----|------|
|                 |                                  |  | Min                                 | Typ <sup>[1]</sup> | Max |      |
| t <sub>pd</sub> | propagation delay                | CP to Qn; see <a href="#">Figure 6</a> <sup>[2]</sup>                                      |                                     |                    |     |      |
|                 |                                  | V <sub>CC</sub> = 1.65 V to 1.95 V   | 1.0                                 | 2.8                | 4.7 | ns   |
|                 |                                  | V <sub>CC</sub> = 2.3 V to 2.7 V   | 1.0                                 | 2.0                | 3.1 | ns   |
|                 |                                  | V <sub>CC</sub> = 2.7 V  | 1.0                                 | 2.2                | 2.9 | ns   |
|                 |                                  | V <sub>CC</sub> = 3.0 V to 3.6 V   | 1.0                                 | 2.0                | 2.8 | ns   |
| C <sub>PD</sub> | power dissipation<br>capacitance | per gate; V <sub>I</sub> = GND to V <sub>CC</sub> ; V <sub>CC</sub> = 3.3 V <sup>[3]</sup> | -                                   | 25                 | -   | pF   |

[1] Typical values are measured at T<sub>amb</sub> = 25 °C[2] t<sub>pd</sub> is the same as t<sub>PHL</sub> and t<sub>PLH</sub>.[3] C<sub>PD</sub> is used to determine the dynamic power dissipation (P<sub>D</sub> in μW).P<sub>D</sub> = C<sub>PD</sub> × V<sub>CC</sub><sup>2</sup> × f<sub>i</sub> × N + Σ(C<sub>L</sub> × V<sub>CC</sub><sup>2</sup> × f<sub>o</sub>) where:f<sub>i</sub> = input frequency in MHz; f<sub>o</sub> = output frequency in MHzC<sub>L</sub> = output load capacitance in pFV<sub>CC</sub> = supply voltage in Volts

N = number of inputs switching

Σ(C<sub>L</sub> × V<sub>CC</sub><sup>2</sup> × f<sub>o</sub>) = sum of the outputs

## 11. Waveforms




Measurement points are given in [Table 8](#).

**Fig 6. Inputs nA, nB to output nY propagation delay times**

**Table 8. Measurement points**

| Supply voltage $V_{CC}$ | Input $V_I$ | $V_M$       |
|-------------------------|-------------|-------------|
| 1.65 V to 1.95 V        | $V_{CC}$    | $0.5V_{CC}$ |
| 2.3 V to 2.7 V          | $V_{CC}$    | $0.5V_{CC}$ |
| 2.7 V                   | 2.7 V       | 1.5 V       |
| 3.0 V to 3.6 V          | 2.7 V       | 1.5 V       |



Test data is given in [Table 9](#).

Definitions for test circuit:

$R_L$  = Load resistance.

$C_L$  = Load capacitance including jig and probe capacitance.

$R_T$  = Termination resistance should be equal to output impedance  $Z_o$  of the pulse generator.

$V_{EXT}$  = External voltage for measuring switching times.

**Fig 7. Test circuitry for measuring switching times**

**Table 9. Test data**

| Supply voltage $V_{CC}$ | Input    |               | Load  |              | $V_{EXT}$          |                    |                    |
|-------------------------|----------|---------------|-------|--------------|--------------------|--------------------|--------------------|
|                         | $V_I$    | $t_r, t_f$    | $C_L$ | $R_L$        | $t_{PLH}, t_{PHL}$ | $t_{PLZ}, t_{PZL}$ | $t_{PHZ}, t_{PZH}$ |
| 1.65 V to 1.95 V        | $V_{CC}$ | $\leq 2.0$ ns | 30 pF | 1 k $\Omega$ | open               | $2 \times V_{CC}$  | GND                |
| 2.3 V to 2.7 V          | $V_{CC}$ | $\leq 2.0$ ns | 30 pF | 500 $\Omega$ | open               | $2 \times V_{CC}$  | GND                |
| 2.7 V                   | 2.7 V    | $\leq 2.5$ ns | 50 pF | 500 $\Omega$ | open               | 6 V                | GND                |
| 3.0 V to 3.6 V          | 2.7 V    | $\leq 2.5$ ns | 50 pF | 500 $\Omega$ | open               | 6 V                | GND                |

## 12. Package outline

SO14: plastic small outline package; 14 leads; body width 3.9 mm

SOT108-1




Fig 8. Package outline SOT108-1 (SO14)



TSSOP14: plastic thin shrink small outline package; 14 leads; body width 4.4 mm

SOT402-1




Fig 9. Package outline SOT402-1 (TSSOP14)

DHVQFN14: plastic dual in-line compatible thermal enhanced very thin quad flat package; no leads; 14 terminals; body 2.5 x 3 x 0.85 mm

SOT762-1




Fig 10. Package outline SOT762-1 (DHVQFN14)

## 13. Abbreviations

Table 10. Abbreviations

| Acronym | Description                 |
|---------|-----------------------------|
| CDM     | Charged Device Model        |
| DUT     | Device Under Test           |
| ESD     | ElectroStatic Discharge     |
| HBM     | Human Body Model            |
| MM      | Machine Model               |
| TTL     | Transistor-Transistor Logic |

## 14. Revision history

Table 11. Revision history

| Document ID  | Release date | Data sheet status     | Change notice  | Supersedes   |
|--------------|--------------|-----------------------|--|--------------|
| 74ALVC32 v.3 | 20140120     | Product data sheet    | -  | 74ALVC32 v.2 |
|              |              |                       | <ul style="list-style-type: none"><li>The format of this data sheet has been redesigned to comply with the new identity guidelines of NXP Semiconductors.</li><li>Legal texts have been adapted to the new company name where appropriate.</li></ul> |              |
| 74ALVC32 v.2 | 20071210     | Product data sheet    | -  | 74ALVC32 v.1 |
| 74ALVC32 v.1 | 20021115     | Product specification | -  | -            |

## 15. Legal information

### 15.1 Data sheet status

| Document status <sup>[1][2]</sup> | Product status <sup>[3]</sup> | Definition  |
|-----------------------------------|-------------------------------|---|
| Objective [short] data sheet      | Development                   | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet    | Qualification                 | This document contains data from the preliminary specification.                       |
| Product [short] data sheet        | Production                    | This document contains the product specification.                                     |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nexperia.com>.

### 15.2 Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

**Product specification** — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

### 15.3 Disclaimers

**Limited warranty and liability** — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Nexperia takes no responsibility for the content in this document if provided by an information source outside of Nexperia.

In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Nexperia.

**Right to make changes** — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — Nexperia products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of a Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia and its suppliers accept no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Nexperia products, and Nexperia accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Nexperia product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Nexperia does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Nexperia products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Nexperia does not accept any liability in this respect.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

**Terms and conditions of commercial sale** — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nexperia.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

**Non-automotive qualified products** — Unless this data sheet expressly states that this specific Nexperia product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Nexperia accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without Nexperia's warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond

Nexperia's specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies Nexperia for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond Nexperia's standard warranty and Nexperia's product specifications.

**Translations** — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

## 15.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

## 16. Contact information

For more information, please visit: <http://www.nexperia.com>

For sales office addresses, please send an email to: [salesaddresses@nexperia.com](mailto:salesaddresses@nexperia.com)

## 17. Contents

---

|           |   |           |
|-----------|---|-----------|
| <b>1</b>  | <b>General description</b> .....              | <b>1</b>  |
| <b>2</b>  | <b>Features and benefits</b> .....            | <b>1</b>  |
| <b>3</b>  | <b>Ordering information</b> .....             | <b>1</b>  |
| <b>4</b>  | <b>Functional diagram</b> .....               | <b>2</b>  |
| <b>5</b>  | <b>Pinning information</b> .....              | <b>2</b>  |
| 5.1       | Pinning .....                                 | 2         |
| 5.2       | Pin description .....                         | 3         |
| <b>6</b>  | <b>Functional description</b> .....           | <b>3</b>  |
| <b>7</b>  | <b>Limiting values</b> .....                  | <b>3</b>  |
| <b>8</b>  | <b>Recommended operating conditions</b> ..... | <b>4</b>  |
| <b>9</b>  | <b>Static characteristics</b> .....           | <b>4</b>  |
| <b>10</b> | <b>Dynamic characteristics</b> .....          | <b>5</b>  |
| <b>11</b> | <b>Waveforms</b> .....                        | <b>6</b>  |
| <b>12</b> | <b>Package outline</b> .....                  | <b>8</b>  |
| <b>13</b> | <b>Abbreviations</b> .....                    | <b>11</b> |
| <b>14</b> | <b>Revision history</b> .....                 | <b>11</b> |
| <b>15</b> | <b>Legal information</b> .....                | <b>12</b> |
| 15.1      | Data sheet status .....                       | 12        |
| 15.2      | Definitions .....                             | 12        |
| 15.3      | Disclaimers .....                             | 12        |
| 15.4      | Trademarks .....                              | 13        |
| <b>16</b> | <b>Contact information</b> .....              | <b>13</b> |
| <b>17</b> | <b>Contents</b> .....                         | <b>14</b> |



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.