

## TC74VHC74F, TC74VHC74FN, TC74VHC74FT, TC74VHC74FK

### Dual D-Type Flip-Flop with Preset and Clear

The TC74VHC74 is an advanced high speed CMOS D-FLIP FLOP fabricated with silicon gate C<sup>2</sup>MOS technology.

It achieves the high speed operation similar to equivalent Bipolar Schottky TTL while maintaining the CMOS low power dissipation.

The signal level applied to the D INPUT is transferred to Q OUTPUT during the positive going transition of the CK pulse.

$\overline{\text{CLR}}$  and  $\overline{\text{PR}}$  are independent of the CK and are accomplished by setting the appropriate input low.


An input protection circuit ensures that 0 to 5.5 V can be applied to the input pins without regard to the supply voltage. This device can be used to interface 5 V to 3 V systems and two supply systems such as battery back up. This circuit prevents device destruction due to mismatched supply and input voltages.

### Features

- High speed:  $f_{\text{max}} = 170 \text{ MHz}$  (typ.) at  $V_{\text{CC}} = 5 \text{ V}$
- Low power dissipation:  $I_{\text{CC}} = 2 \mu\text{A}$  (max) at  $T_a = 25^\circ\text{C}$
- High noise immunity:  $V_{\text{NIH}} = V_{\text{NIL}} = 28\% V_{\text{CC}}$  (min)
- Power down protection is provided on all inputs.
- Balanced propagation delays:  $t_{\text{pLH}} \approx t_{\text{pHL}}$
- Wide operating voltage range:  $V_{\text{CC (opr)}} = 2 \text{ V}$  to  $5.5 \text{ V}$
- Pin and function compatible with 74ALS74


Note: The JEDEC SOP (FN) is not available in Japan.

TC74VHC74F




SOP14-P-300-1.27A

TC74VHC74FN




SOL14-P-150-1.27

TC74VHC74FT



TSSOP14-P-0044-0.65A

TC74VHC74FK




VSSOP14-P-0030-0.50


### Weight

|                      |                 |
|----------------------|-----------------|
| SOP14-P-300-1.27A    | : 0.18 g (typ.) |
| SOL14-P-150-1.27     | : 0.12 g (typ.) |
| TSSOP14-P-0044-0.65A | : 0.06 g (typ.) |
| VSSOP14-P-0030-0.50  | : 0.02 g (typ.) |

## Pin Assignment



## IEC Logic Symbol



## Truth Table

| Inputs |    |   |    | Outputs        |                 | Function  |
|--------|----|---|----|----------------|-----------------|-----------|
| CLR    | PR | D | CK | Q              | Q̄              |           |
| L      | H  | X | X  | L              | H               | Clear     |
| H      | L  | X | X  | H              | L               | Preset    |
| L      | L  | X | X  | H              | H               | —         |
| H      | H  | L | ↑  | L              | H               | —         |
| H      | H  | H | ↑  | H              | L               | —         |
| H      | H  | X | ↓  | Q <sub>n</sub> | Q̄ <sub>n</sub> | No Change |

X: Don't care

## Absolute Maximum Ratings (Note)

| Characteristics                    | Symbol           | Rating                        | Unit |
|------------------------------------|------------------|-------------------------------|------|
| Supply voltage range               | V <sub>CC</sub>  | -0.5 to 7.0                   | V    |
| DC input voltage                   | V <sub>IN</sub>  | -0.5 to 7.0                   | V    |
| DC output voltage                  | V <sub>OUT</sub> | -0.5 to V <sub>CC</sub> + 0.5 | V    |
| Input diode current                | I <sub>IK</sub>  | -20                           | mA   |
| Output diode current               | I <sub>OK</sub>  | ±20                           | mA   |
| DC output current                  | I <sub>OUT</sub> | ±25                           | mA   |
| DC V <sub>CC</sub> /ground current | I <sub>CC</sub>  | ±50                           | mA   |
| Power dissipation                  | P <sub>D</sub>   | 180                           | mW   |
| Storage temperature                | T <sub>stg</sub> | -65 to 150                    | °C   |

Note: Exceeding any of the absolute maximum ratings, even briefly, lead to deterioration in IC performance or even destruction.

Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings and the operating ranges.

Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook ("Handling Precautions"/"Derating Concept and Methods") and individual reliability data (i.e. reliability test report and estimated failure rate, etc).

## Operating Ranges (Note)

| Characteristics          | Symbol    | Rating                                                                    | Unit |
|--------------------------|-----------|---------------------------------------------------------------------------|------|
| Supply voltage           | $V_{CC}$  | 2.0 to 5.5                                                                | V    |
| Input voltage            | $V_{IN}$  | 0 to 5.5                                                                  | V    |
| Output voltage           | $V_{OUT}$ | 0 to $V_{CC}$                                                             | V    |
| Operating temperature    | $T_{opr}$ | -40 to 85                                                                 | °C   |
| Input rise and fall time | dt/dv     | 0 to 100 ( $V_{CC} = 3.3 \pm 0.3$ V)<br>0 to 20 ( $V_{CC} = 5 \pm 0.5$ V) | ns/V |

Note: The operating ranges must be maintained to ensure the normal operation of the device.  
Unused inputs must be tied to either  $V_{CC}$  or GND.

## Electrical Characteristics

### DC Characteristics

| Characteristics           | Symbol          | Test Condition                                       |                                                    | Ta = 25°C           |                               |        | Ta =<br>-40 to 85°C           |                               | Unit                          |     |
|---------------------------|-----------------|------------------------------------------------------|----------------------------------------------------|---------------------|-------------------------------|--------|-------------------------------|-------------------------------|-------------------------------|-----|
|                           |                 |                                                      |                                                    | V <sub>CC</sub> (V) | Min                           | Typ.   | Max                           | Min                           |                               | Max |
| High-level input voltage  | V <sub>IH</sub> | —                                                    |                                                    | 2.0<br>3.0 to 5.5   | 1.50<br>V <sub>CC</sub> × 0.7 | —<br>— | —<br>—                        | 1.50<br>V <sub>CC</sub> × 0.7 | —<br>—                        | V   |
| Low-level input voltage   | V <sub>IL</sub> | —                                                    |                                                    | 2.0<br>3.0 to 5.5   | —<br>—                        | —<br>— | 0.50<br>V <sub>CC</sub> × 0.3 | —<br>—                        | 0.50<br>V <sub>CC</sub> × 0.3 | V   |
| High-level output voltage | V <sub>OH</sub> | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub> | I <sub>OH</sub> = -50 μA                           | 2.0                 | 1.9                           | 2.0    | —                             | 1.9                           | —                             | V   |
|                           |                 |                                                      |                                                    | 3.0                 | 2.9                           | 3.0    | —                             | 2.9                           | —                             |     |
|                           |                 |                                                      | I <sub>OH</sub> = -4 mA<br>I <sub>OH</sub> = -8 mA | 4.5                 | 4.4                           | 4.5    | —                             | 4.4                           | —                             |     |
|                           |                 |                                                      |                                                    | 3.0<br>4.5          | 2.58<br>3.94                  | —<br>— | —<br>—                        | 2.48<br>3.80                  | —<br>—                        |     |
| Low-level output voltage  | V <sub>OL</sub> | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub> | I <sub>OL</sub> = 50 μA                            | 2.0                 | —                             | 0.0    | 0.1                           | —                             | 0.1                           | V   |
|                           |                 |                                                      |                                                    | 3.0                 | —                             | 0.0    | 0.1                           | —                             | 0.1                           |     |
|                           |                 |                                                      | I <sub>OL</sub> = 4 mA<br>I <sub>OL</sub> = 8 mA   | 4.5                 | —                             | 0.0    | 0.1                           | —                             | 0.1                           |     |
|                           |                 |                                                      |                                                    | 3.0<br>4.5          | —<br>—                        | —<br>— | 0.36<br>0.36                  | —<br>—                        | 0.44<br>0.44                  |     |
| Input leakage current     | I <sub>IN</sub> | V <sub>IN</sub> = 5.5 V or GND                       |                                                    | 0 to 5.5            | —                             | —      | ±0.1                          | —                             | ±1.0                          | μA  |
| Quiescent supply current  | I <sub>CC</sub> | V <sub>IN</sub> = V <sub>CC</sub> or GND             |                                                    | 5.5                 | —                             | —      | 2.0                           | —                             | 20.0                          | μA  |

## Timing Requirements (input: $t_r = t_f = 3 \text{ ns}$ )

| Characteristics                                                              | Symbol            | Test Condition | $V_{CC} \text{ (V)}$ | $T_a = 25^\circ\text{C}$<br>Limit | $T_a = -40 \text{ to } 85^\circ\text{C}$<br>Limit | Unit |
|------------------------------------------------------------------------------|-------------------|----------------|----------------------|-----------------------------------|---------------------------------------------------|------|
|                                                                              |                   |                |                      |                                   |                                                   |      |
| Minimum pulse width<br>(CK)                                                  | $t_w \text{ (L)}$ | —              | $3.3 \pm 0.3$        | 6.0                               | 7.0                                               | ns   |
|                                                                              | $t_w \text{ (H)}$ |                | $5.0 \pm 0.5$        | 5.0                               | 5.0                                               |      |
| Minimum pulse width<br>( $\overline{\text{CLR}}$ , $\overline{\text{PR}}$ )  | $t_w \text{ (L)}$ | —              | $3.3 \pm 0.3$        | 6.0                               | 7.0                                               | ns   |
|                                                                              |                   |                | $5.0 \pm 0.5$        | 5.0                               | 5.0                                               |      |
| Minimum set-up time                                                          | $t_s$             | —              | $3.3 \pm 0.3$        | 6.0                               | 7.0                                               | ns   |
|                                                                              |                   |                | $5.0 \pm 0.5$        | 5.0                               | 5.0                                               |      |
| Minimum hold time                                                            | $t_h$             | —              | $3.3 \pm 0.3$        | 0.5                               | 0.5                                               | ns   |
|                                                                              |                   |                | $5.0 \pm 0.5$        | 0.5                               | 0.5                                               |      |
| Minimum removal time<br>( $\overline{\text{CLR}}$ , $\overline{\text{PR}}$ ) | $t_{\text{rem}}$  | —              | $3.3 \pm 0.3$        | 5.0                               | 5.0                                               | ns   |
|                                                                              |                   |                | $5.0 \pm 0.5$        | 3.0                               | 3.0                                               |      |


## AC Characteristics (input: $t_r = t_f = 3 \text{ ns}$ )

| Characteristics                                                                                   | Symbol                               | Test Condition | $T_a = 25^\circ\text{C}$ |                    |     | $T_a = -40 \text{ to } 85^\circ\text{C}$ |      | Unit |
|---------------------------------------------------------------------------------------------------|--------------------------------------|----------------|--------------------------|--------------------|-----|------------------------------------------|------|------|
|                                                                                                   |                                      |                | $V_{CC} \text{ (V)}$     | $C_L \text{ (pF)}$ | Min | Typ.                                     | Max  |      |
| Propagation delay time<br>(CK-Q, $\overline{Q}$ )                                                 | $t_{\text{pLH}}$<br>$t_{\text{pHL}}$ | —              | $3.3 \pm 0.3$            | 15                 | —   | 6.7                                      | 11.9 | ns   |
|                                                                                                   |                                      |                |                          | 50                 | —   | 9.2                                      | 15.4 |      |
|                                                                                                   |                                      |                | $5.0 \pm 0.5$            | 15                 | —   | 4.6                                      | 7.3  |      |
|                                                                                                   |                                      |                |                          | 50                 | —   | 6.1                                      | 9.3  |      |
| Propagation delay time<br>( $\overline{\text{CLR}}$ , $\overline{\text{PR}}$ -Q, $\overline{Q}$ ) | $t_{\text{pLH}}$<br>$t_{\text{pHL}}$ | —              | $3.3 \pm 0.3$            | 15                 | —   | 7.6                                      | 12.3 | ns   |
|                                                                                                   |                                      |                |                          | 50                 | —   | 10.1                                     | 15.8 |      |
|                                                                                                   |                                      |                | $5.0 \pm 0.5$            | 15                 | —   | 4.8                                      | 7.7  |      |
|                                                                                                   |                                      |                |                          | 50                 | —   | 6.3                                      | 9.7  |      |
| Maximum clock frequency                                                                           | $f_{\text{max}}$                     | —              | $3.3 \pm 0.3$            | 15                 | 80  | 125                                      | —    | MHz  |
|                                                                                                   |                                      |                |                          | 50                 | 50  | 75                                       | —    |      |
|                                                                                                   |                                      |                | $5.0 \pm 0.5$            | 15                 | 130 | 170                                      | —    |      |
|                                                                                                   |                                      |                |                          | 50                 | 90  | 115                                      | —    |      |
| Input capacitance                                                                                 | $C_{\text{IN}}$                      | —              | —                        | —                  | —   | 4                                        | 10   | pF   |
| Power dissipation capacitance                                                                     | $C_{\text{PD}}$                      | (Note)         | —                        | —                  | —   | 25                                       | —    | pF   |

Note:  $C_{\text{PD}}$  is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load.

Average operating current can be obtained by the equation:




$$I_{\text{CC (opr)}} = C_{\text{PD}} \cdot V_{\text{CC}} \cdot f_{\text{IN}} + I_{\text{CC}}/2 \text{ (per F/F)}$$

**Input Equivalent Circuit**

## Package Dimensions

SOP14-P-300-1.27A

Unit: mm




Weight: 0.18 g (typ.)

## Package Dimensions (Note)

SOL14-P-150-1.27

Unit : mm




Note: This package is not available in Japan.

Weight: 0.12 g (typ.)

Package Dimensions

TSSOP14-P-0044-0.65A

Unit: mm




Weight: 0.06 g (typ.)

## Package Dimensions

VSSOP14-P-0030-0.50

Unit: mm



Weight: 0.02 g (typ.)

**RESTRICTIONS ON PRODUCT USE**

20070701-EN GENERAL

- The information contained herein is subject to change without notice.
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.  
In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc.
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The products described in this document shall not be used or embedded to any downstream products of which manufacture, use and/or sale are prohibited under any applicable laws and regulations.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patents or other rights of TOSHIBA or the third parties.
- Please contact your sales representative for product-by-product details in this document regarding RoHS compatibility. Please use these products in this document in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances. Toshiba assumes no liability for damage or losses occurring as a result of noncompliance with applicable laws and regulations.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.