

Surface mount type

SVPE Series

RoHS directive/Halogen-free compliant
 Super Low ESR (8mΩ~18mΩ)
 Large capacitance(1,200μF)



Specifications

| Items | Condition | Specifications | | | | |
|--|---|--|---|-----|----|----|
| | | 2.0 | 2.5 | 6.3 | 10 | 16 |
| Rated voltage (V) | — | 2.0 | 2.5 | 6.3 | 10 | 16 |
| Surge voltage (V) | Room temperature | 2.6 | 3.3 | 8.2 | 12 | 18 |
| Category temperature range(°C) | — | -55 to +105 | | | | |
| Capacitance tolerance (%) | 120Hz/20°C | M : ±20 | | | | |
| Dissipation Factor (DF) | 120Hz/20°C | Please see the attached characteristics list | | | | |
| Leakage current*1 | Rated voltage applied, after 2 minutes | Please see the attached characteristics list | | | | |
| Equivalent series resistance (ESR) | 100kHz/20°C | Please see the attached characteristics list | | | | |
| Characteristics of impedance ratio at high temp. and low temp. | Based the value at 100kHz, +20°C | -55°C | Z/Z _{20°C} | | | |
| | | +105°C | Z/Z _{20°C} | | | |
| Endurance | 105°C, 2,000h, Rated voltage applied | ΔC/C | Within ±20% of the initial value | | | |
| | | DF | Within 1.5 times of the initial limit | | | |
| | | ESR | Within 1.5 times of the initial limit | | | |
| | | LC | Within the initial limit | | | |
| | | LC | Within the initial limit | | | |
| Damp heat (Steady state) | 60°C, 90 to 95%RH, 1,000h, No-applied voltage | ΔC/C | Within ±20% of the initial value | | | |
| | | DF | Within 1.5 times of the initial limit | | | |
| | | ESR | Within 1.5 times of the initial limit | | | |
| | | LC | Within the initial limit (after voltage processing) | | | |
| Resistance to soldering heat*2 | VPS (230°C X 75s) | ΔC/C | Within ±10% of the initial value (±15% for 2.5V) | | | |
| | | DF | Within 1.3 times of the initial limit | | | |
| | | ESR | Within 1.3 times of the initial limit | | | |
| | | LC | Within the initial limit (after voltage processing) | | | |

*1 When measured values are questionable, measure after voltage processing mentioned below.

Voltage processing: Apply voltage for 120 minutes at 105°C.

*2 Please refer to page 25 for reflow soldering conditions.

Marking and dimensions

(unit : mm)

| Size code | φD ±0.5 | L ^{+0.1} _{-0.4} | W ±0.2 | H ±0.2 | C ±0.2 | R | P ±0.2 |
|-----------|---------|-----------------------------------|--------|--------|--------|---------|--------|
| B6 | 5.0 | 5.9 | 5.3 | 5.3 | 6.0 | 0.6~0.8 | 1.4 |
| C6 | 6.3 | 5.9 | 6.6 | 6.6 | 7.3 | 0.6~0.8 | 2.1 |
| C10 | 6.3 | 9.9 | 6.6 | 6.6 | 7.3 | 0.6~0.8 | 2.1 |
| F12 | 10.0 | 12.6 | 10.3 | 10.3 | 11.0 | 0.8~1.1 | 4.6 |

Size list

RV : Rated voltage

| μF | RV | 2.0 | 2.5 | 6.3 | 10 | 16 |
|------|-----|-----|-------|-------|----|-----|
| 150 | | | | B6 | | |
| 180 | | | | B6 | | C10 |
| 220 | | | | B6,C6 | C6 | |
| 270 | | | B6 | | | |
| 330 | | | B6 | | | |
| 390 | | | B6,C6 | | | |
| 470 | | | | | | F12 |
| 1200 | C10 | | | | | |

OS-CON Line-up

Guidelines and precautions

Series system diagram

Image of case size

Products list

Packing specifications (SMD type)

Packing specifications (Radial lead type)

Recommended soldering condition

Fundamental structure

Characteristics

Reliability

Selection guide

Technical data

Surface mount type

Radial lead type

Catalog Deletion and EOL series

POSCAP Line-up

Guidelines and precautions

Selection guide

Technical data

Surface mount type


Catalog Deletion and EOL models

SVPE series characteristics list

| Size code | Part number | Rated voltage (V) | Rated capacitance (μ F) | ESR($m\Omega$) (max) | | Rated ripple current 100kHz (mA _{rms}) at 105°C | DF (% max) | Leakage current (μ A) (max) After 2 minutes |
|-----------|--------------|-------------------|------------------------------|------------------------|---------------|---|------------|--|
| | | | | 100kHz/20°C | 300kHz/20°C※1 | | | |
| B6 | 6SVPE150M | 6.3 | 150 | 12 | 10 | 3520 | 12 | 500 |
| | 6SVPE180M | 6.3 | 180 | 15 | 13 | 3150 | 12 | 500 |
| | 6SVPE220MW | 6.3 | 220 | 15 | 13 | 3150 | 12 | 500 |
| | 2R5SVPE270M | 2.5 | 270 | 10 | 9 | 3860 | 12 | 500 |
| | 2R5SVPE330M | 2.5 | 330 | 15 | 13 | 3150 | 12 | 500 |
| | 2R5SVPE330MY | 2.5 | 330 | 10 | 9 | 3860 | 12 | 500 |
| | 2R5SVPE390MX | 2.5 | 390 | 10 | 9 | 3860 | 12 | 700 |
| C6 | 10SVPE220M | 10 | 220 | 20 | 18 | 2700 | 12 | 500 |
| | 6SVPE220M | 6.3 | 220 | 10 | 9 | 3900 | 12 | 500 |
| | 2R5SVPE390M | 2.5 | 390 | 10 | 9 | 3900 | 12 | 500 |
| C10 | 16SVPE180M | 16 | 180 | 11 | 10 | 4460 | 12 | 576 |
| | 2SVPE1200M | 2.0 | 1200 | 8 | 8 | 5230 | 12 | 500 |
| F12 | 16SVPE470M | 16 | 470 | 10 | 9 | 6100 | 12 | 1504 |

※1 The ESR value in 300kHz is a reference one.

Recommended land pattern dimension of PWB



| Size code | a | b | c |
|-----------|-----|------|-----|
| B6 | 1.4 | 7.4 | 1.6 |
| C6 | 2.1 | 9.1 | 1.6 |
| C10 | 2.1 | 9.1 | 1.6 |
| F12 | 4.3 | 13.1 | 1.9 |

(unit : mm)

Frequency coefficient for ripple current

| Frequency | 120Hz ≤ f < 1kHz | 1kHz ≤ f < 10kHz | 10kHz ≤ f < 100kHz | 100kHz ≤ f ≤ 500kHz |
|-------------|------------------|------------------|--------------------|---------------------|
| Coefficient | 0.05 | 0.3 | 0.7 | 1 |



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.