

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0428784218

Status:

Active

Description:

Modular Jack, Vertical, Low Profile, 4/2

Documents:

- 3D Model

Product Specification PS-42878 (PDF)
- Drawing (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA	LR19980
UL	E107635

General

Product Family	Modular Jacks/Plugs
Series	42878
Comments	Flush Mount Flangeless 2 PCB Thick
Component Type	PCB Jack
Magnetic	No
Performance Category	3
Power over Ethernet (PoE)	N/A
Product Name	N/A

Physical

Boot Color	N/A
Color - Resin	Black
Durability (mating cycles max)	500
Flammability	94V-0
Inverted / Top Latch	N/A
Lightpipes/LEDs	None
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	Polyester
Orientation	Vertical (Top Entry)
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness Recommended (in)	0.062 In
PCB Thickness Recommended (mm)	1.57 mm
Packaging Type	Tray
Pitch - Mating Interface (in)	0.040 In
Pitch - Mating Interface (mm)	1.02 mm
Pitch - Term. Interface (in)	0.050 In
Pitch - Term. Interface (mm)	1.27 mm
Plating min: Mating (µin)	50
Plating min: Mating (µm)	1.25
Plating min: Termination (µin)	100
Plating min: Termination (µm)	2.5
Ports	1
Positions / Loaded Contacts	4/4
Surface Mount Compatible (SMC)	No
Temperature Range - Operating	-40°C to +85°C
Termination Interface: Style	Through Hole
Waterproof / Dustproof	No
Wire/Cable Type	N/A

Electrical




image - Reference only

Series

EU RoHS

ELV and RoHS
Compliant
REACH SVHC
Not Reviewed
Halogen-Free
Status

China RoHS



Need more information on product
environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of
Compliance, [click here](#)

Please visit the [Contact Us](#) section for any
non-product compliance questions.

Search Parts in this Series
42878Series

Mates With
FCC 68 Plugs

Current - Maximum per Contact	1.5A
Shielded	No
Voltage - Maximum	150V AC (RMS)
Solder Process Data	
Duration at Max. Process Temperature (seconds)	5
Lead-free Process Capability	Wave Capable (TH only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	235

Material Info

Reference - Drawing Numbers

Packaging Specification	PK-42878-492
Product Specification	PS-42878
Sales Drawing	SDA-42878-****
Test Summary	TS-42878-001

This document was generated on 06/07/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

1b_frame_D_P_ME_T
Rev. E 2006/04/15

	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1																																																																																																																																																																																																																																																																																																																																																																																														
M	<table><tr><td rowspan="2">X*NOT TOOLED</td><td rowspan="2">ASSEMBLY NUMBER</td><td colspan="4">PART CHARACTERISTICS</td></tr><tr><td>EXTERNAL CONNECTOR SIZE</td><td>NUMBER OF POSITIONS</td><td>P. C. BOARD THICKNESS</td><td>MOUNTING EARS OPTION</td></tr><tr><td rowspan="6">L</td><td>42878-4216</td><td>4 POS. BODY</td><td>4</td><td>.062</td><td>YES</td></tr><tr><td>42878-4218</td><td>↑</td><td>4</td><td>.062</td><td>NO</td></tr><tr><td>42878-4264</td><td></td><td>4</td><td>.125</td><td>YES</td></tr><tr><td>42878-4266</td><td></td><td>4</td><td>.125</td><td>NO</td></tr><tr><td>42878-4360</td><td></td><td>2</td><td>.062</td><td>YES</td></tr><tr><td>42878-4362</td><td></td><td>2</td><td>.062</td><td>NO</td></tr><tr><td rowspan="6">K</td><td>42878-4408</td><td>↓</td><td>2</td><td>.125</td><td>YES</td></tr><tr><td>42878-4410</td><td>4 POS. BODY</td><td>2</td><td>.125</td><td>NO</td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">J</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">I</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">H</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">G</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">F</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">E</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">D</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">C</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">B</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">A</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr></table>																				X*NOT TOOLED	ASSEMBLY NUMBER	PART CHARACTERISTICS				EXTERNAL CONNECTOR SIZE	NUMBER OF POSITIONS	P. C. BOARD THICKNESS	MOUNTING EARS OPTION	L	42878-4216	4 POS. BODY	4	.062	YES	42878-4218	↑	4	.062	NO	42878-4264		4	.125	YES	42878-4266		4	.125	NO	42878-4360		2	.062	YES	42878-4362		2	.062	NO	K	42878-4408	↓	2	.125	YES	42878-4410	4 POS. BODY	2	.125	NO																					J																															I																															H																															G																															F																															E																															D																															C																															B																															A																														
X*NOT TOOLED	ASSEMBLY NUMBER	PART CHARACTERISTICS																																																																																																																																																																																																																																																																																																																																																																																																																
		EXTERNAL CONNECTOR SIZE	NUMBER OF POSITIONS	P. C. BOARD THICKNESS	MOUNTING EARS OPTION																																																																																																																																																																																																																																																																																																																																																																																																													
L	42878-4216	4 POS. BODY	4	.062	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4218	↑	4	.062	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4264		4	.125	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4266		4	.125	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4360		2	.062	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4362		2	.062	NO																																																																																																																																																																																																																																																																																																																																																																																																													
K	42878-4408	↓	2	.125	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4410	4 POS. BODY	2	.125	NO																																																																																																																																																																																																																																																																																																																																																																																																													
J																																																																																																																																																																																																																																																																																																																																																																																																																		
I																																																																																																																																																																																																																																																																																																																																																																																																																		
H																																																																																																																																																																																																																																																																																																																																																																																																																		
G																																																																																																																																																																																																																																																																																																																																																																																																																		
F																																																																																																																																																																																																																																																																																																																																																																																																																		
E																																																																																																																																																																																																																																																																																																																																																																																																																		
D																																																																																																																																																																																																																																																																																																																																																																																																																		
C																																																																																																																																																																																																																																																																																																																																																																																																																		
B																																																																																																																																																																																																																																																																																																																																																																																																																		
A																																																																																																																																																																																																																																																																																																																																																																																																																		
<table><tr><td rowspan="2">X*NOT TOOLED</td><td rowspan="2">ASSEMBLY ITEM NUMBER</td><td colspan="4">PART CHARACTERISTICS</td></tr><tr><td>EXTERNAL CONNECTOR SIZE</td><td>NUMBER OF POSITIONS</td><td>P. C. BOARD THICKNESS</td><td>MOUNTING EARS OPTION</td></tr><tr><td rowspan="12"></td><td>42878-6216</td><td>6 POS. BODY</td><td>6</td><td>.062</td><td>YES</td></tr><tr><td>42878-6218</td><td>↑</td><td>6</td><td>.062</td><td>NO</td></tr><tr><td>42878-6264</td><td></td><td>6</td><td>.125</td><td>YES</td></tr><tr><td>42878-6266</td><td></td><td>6</td><td>.125</td><td>NO</td></tr><tr><td>42878-6360</td><td></td><td>4</td><td>.062</td><td>YES</td></tr><tr><td>42878-6362</td><td></td><td>4</td><td>.062</td><td>NO</td></tr><tr><td>42878-6408</td><td></td><td>4</td><td>.125</td><td>YES</td></tr><tr><td>42878-6410</td><td></td><td>4</td><td>.125</td><td>NO</td></tr><tr><td>42878-6504</td><td></td><td>2</td><td>.062</td><td>YES</td></tr><tr><td>42878-6506</td><td></td><td>2</td><td>.062</td><td>NO</td></tr><tr><td>42878-6552</td><td>↓</td><td>2</td><td>.125</td><td>YES</td></tr><tr><td>42878-6554</td><td>6 POS. BODY</td><td>2</td><td>.125</td><td>NO</td></tr><tr><td rowspan="6"></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr></table>																				X*NOT TOOLED	ASSEMBLY ITEM NUMBER	PART CHARACTERISTICS				EXTERNAL CONNECTOR SIZE	NUMBER OF POSITIONS	P. C. BOARD THICKNESS	MOUNTING EARS OPTION		42878-6216	6 POS. BODY	6	.062	YES	42878-6218	↑	6	.062	NO	42878-6264		6	.125	YES	42878-6266		6	.125	NO	42878-6360		4	.062	YES	42878-6362		4	.062	NO	42878-6408		4	.125	YES	42878-6410		4	.125	NO	42878-6504		2	.062	YES	42878-6506		2	.062	NO	42878-6552	↓	2	.125	YES	42878-6554	6 POS. BODY	2	.125	NO																																																																																																																																																																																																																																																																																																																								
X*NOT TOOLED	ASSEMBLY ITEM NUMBER	PART CHARACTERISTICS																																																																																																																																																																																																																																																																																																																																																																																																																
		EXTERNAL CONNECTOR SIZE	NUMBER OF POSITIONS	P. C. BOARD THICKNESS	MOUNTING EARS OPTION																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6216	6 POS. BODY	6	.062	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6218	↑	6	.062	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6264		6	.125	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6266		6	.125	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6360		4	.062	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6362		4	.062	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6408		4	.125	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6410		4	.125	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6504		2	.062	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6506		2	.062	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6552	↓	2	.125	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6554	6 POS. BODY	2	.125	NO																																																																																																																																																																																																																																																																																																																																																																																																													
<table><tr><td colspan="5">CHARACTERISTICS LEGEND</td></tr><tr><td colspan="5">EXTERNAL CONNECTOR BODY DIMENSIONS: AVAILABLE IN 4, 6, AND 8 POSITION BODY</td></tr><tr><td colspan="5">NUMBER OF CONTACT POSITIONS: CONNECTOR SIZE 4 ACCOMMODATES 2, 4, OR 6 TERMINALS, CONNECTOR SIZE 6 ACCOMMODATES 2, 4, OR 6 TERMINALS, CONNECTOR SIZE 8 ACCOMMODATES 2, 4, 6, 8, OR 10 TERMINALS</td></tr><tr><td colspan="5">POLARIZATION OPTION: (AVAILABLE ON CONNECTOR SIZE 8 ONLY) "NO"= WITHOUT KEYING SLOT "YES"= WITH KEYING SLOT</td></tr><tr><td colspan="5">MOUNTING EARS OPTION: "YES"= PART WITH MOUNTING EARS "NO"= PART WITHOUT MOUNTING EARS</td></tr><tr><td colspan="5">(SEE SHEET 1 & 2 FOR PART DESCRIPTIONS AND DIMENSIONS)</td></tr></table>																				CHARACTERISTICS LEGEND					EXTERNAL CONNECTOR BODY DIMENSIONS: AVAILABLE IN 4, 6, AND 8 POSITION BODY					NUMBER OF CONTACT POSITIONS: CONNECTOR SIZE 4 ACCOMMODATES 2, 4, OR 6 TERMINALS, CONNECTOR SIZE 6 ACCOMMODATES 2, 4, OR 6 TERMINALS, CONNECTOR SIZE 8 ACCOMMODATES 2, 4, 6, 8, OR 10 TERMINALS					POLARIZATION OPTION: (AVAILABLE ON CONNECTOR SIZE 8 ONLY) "NO"= WITHOUT KEYING SLOT "YES"= WITH KEYING SLOT					MOUNTING EARS OPTION: "YES"= PART WITH MOUNTING EARS "NO"= PART WITHOUT MOUNTING EARS					(SEE SHEET 1 & 2 FOR PART DESCRIPTIONS AND DIMENSIONS)																																																																																																																																																																																																																																																																																																																																																																					
CHARACTERISTICS LEGEND																																																																																																																																																																																																																																																																																																																																																																																																																		
EXTERNAL CONNECTOR BODY DIMENSIONS: AVAILABLE IN 4, 6, AND 8 POSITION BODY																																																																																																																																																																																																																																																																																																																																																																																																																		
NUMBER OF CONTACT POSITIONS: CONNECTOR SIZE 4 ACCOMMODATES 2, 4, OR 6 TERMINALS, CONNECTOR SIZE 6 ACCOMMODATES 2, 4, OR 6 TERMINALS, CONNECTOR SIZE 8 ACCOMMODATES 2, 4, 6, 8, OR 10 TERMINALS																																																																																																																																																																																																																																																																																																																																																																																																																		
POLARIZATION OPTION: (AVAILABLE ON CONNECTOR SIZE 8 ONLY) "NO"= WITHOUT KEYING SLOT "YES"= WITH KEYING SLOT																																																																																																																																																																																																																																																																																																																																																																																																																		
MOUNTING EARS OPTION: "YES"= PART WITH MOUNTING EARS "NO"= PART WITHOUT MOUNTING EARS																																																																																																																																																																																																																																																																																																																																																																																																																		
(SEE SHEET 1 & 2 FOR PART DESCRIPTIONS AND DIMENSIONS)																																																																																																																																																																																																																																																																																																																																																																																																																		
<table><tr><td rowspan="2">SEE SHEET ONE</td><td rowspan="2">REV</td><td rowspan="2">DESCRIPTION</td><td rowspan="2">QUALITY SYMBOLS</td><td colspan="2">GENERAL TOLERANCES (UNLESS SPECIFIED)</td><td rowspan="2">SCALE ---</td><td rowspan="2">DESIGN UNITS INCH</td><td rowspan="2">THIRD ANGLE PROJECTION</td><td rowspan="2">REVISE ON CAD ONLY</td></tr><tr><td>mm</td><td>INCH</td></tr><tr><td rowspan="2">H</td><td rowspan="2"></td><td rowspan="2"></td><td rowspan="2">▽.0</td><td>4 PLACES ±</td><td>±</td><td rowspan="2">IN/MM</td><td rowspan="2">DRAWN BY DATE</td><td rowspan="2">TITLE</td><td rowspan="2"></td></tr><tr><td>3 PLACES ±</td><td>±</td></tr><tr><td rowspan="2"></td><td rowspan="2"></td><td rowspan="2"></td><td rowspan="2">▽.0</td><td>2 PLACES ±</td><td>±</td><td rowspan="2">BAP 1992/04/09</td><td rowspan="2">CHECKED BY DATE</td><td rowspan="2">MOLEX INCORPORATED</td><td rowspan="2">4 OF 5</td></tr><tr><td>1 PLACE ±</td><td>±</td></tr><tr><td colspan="4"></td><td colspan="2">ANGULAR ±1/2°</td><td colspan="2">BAP 1992/04/09</td><td colspan="2"></td></tr><tr><td colspan="4"></td><td colspan="2">DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS</td><td colspan="2">APPROVED BY DATE</td><td colspan="2"></td></tr><tr><td colspan="4"></td><td colspan="2"></td><td colspan="2">RAS 1992/04/09</td><td colspan="2"></td></tr><tr><td colspan="4"></td><td colspan="2"></td><td colspan="2">THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION</td><td colspan="2"></td></tr></table>																				SEE SHEET ONE	REV	DESCRIPTION	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		SCALE ---	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY	mm	INCH	H			▽.0	4 PLACES ±	±	IN/MM	DRAWN BY DATE	TITLE		3 PLACES ±	±				▽.0	2 PLACES ±	±	BAP 1992/04/09	CHECKED BY DATE	MOLEX INCORPORATED	4 OF 5	1 PLACE ±	±					ANGULAR ±1/2°		BAP 1992/04/09								DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		APPROVED BY DATE										RAS 1992/04/09										THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																																																																																																																																																																																																																																																																																																																						
SEE SHEET ONE	REV	DESCRIPTION	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		SCALE ---	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY																																																																																																																																																																																																																																																																																																																																																																																																									
				mm	INCH																																																																																																																																																																																																																																																																																																																																																																																																													
H			▽.0	4 PLACES ±	±	IN/MM	DRAWN BY DATE	TITLE																																																																																																																																																																																																																																																																																																																																																																																																										
				3 PLACES ±	±																																																																																																																																																																																																																																																																																																																																																																																																													
			▽.0	2 PLACES ±	±	BAP 1992/04/09	CHECKED BY DATE	MOLEX INCORPORATED	4 OF 5																																																																																																																																																																																																																																																																																																																																																																																																									
				1 PLACE ±	±																																																																																																																																																																																																																																																																																																																																																																																																													
				ANGULAR ±1/2°		BAP 1992/04/09																																																																																																																																																																																																																																																																																																																																																																																																												
				DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		APPROVED BY DATE																																																																																																																																																																																																																																																																																																																																																																																																												
						RAS 1992/04/09																																																																																																																																																																																																																																																																																																																																																																																																												
						THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																																																																																																																																																																																																																																																																																																																																																																																																												
to frame D.P.M.E.T Rev. C 2002/05/05		19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1																																																																																																																																																																																																																																																																																																																																																																																														



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.