THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- .
© COPYRIGHT 2011 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST
DW	—

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	B1	REVISED (ECR-12-007103), OBSOLETE 2-1734084-2	31JUL12	JC	WK







REAR VIEW



RECOMMENDED P.C.B. LAYOUT (THICKNESS=1.6mm)
(TOP VIEW) (TOLERANCE:±0.05mm)

NOTES:
1. MATERIAL:
   HOUSING: THERMOPLASTIC (SEE TABLE), WITH 30% GF, UL 94V-0, BLACK COLOR.
   CONTACT: PHOSPHOR BRONZE, (t=0.25mm).
   SHIELD: COLD ROLL STEEL, (t=0.35mm)
   GROUNDING STRIP: STAINLESS, (t=0.20 & 0.25mm)

2. FINISH :
   CONTACT: 0.762μm [30μ"] MIN. GOLD PLATING ON CONTACT AREA,
   3.81μm [150μ"] MIN. BRIGHT TIN PLATING ON SOLDERTAILS,
   1.27μm [50μ"] MIN. NICKEL UNDERPLATING OVERALL.
   SHIELD: 3.048μm [120μ"] MIN. NICKEL PLATED OVERALL.

△3 WAVE SOLDER CAPABLE TO 245°C PER TE SPEC109-201, CONDITION A.

△4 REFLOW SOLDER CAPABLE TO 260°C PER TE SPEC 109-201, CONDITION B.

OBSOLETE	△4 PA9T	W/	W/O	2-1734084-2
	△3 PBT	W/	W/O	2-1734084-1
	△4 PA9T	W/O	W/	1-1734084-2
	△3 PBT	W/O	W/	1-1734084-1
	△4 PA9T	W/O	W/O	0-1734084-2
OBSOLETE	△3 PBT	W/O	W/O	0-1734084-1
	HSG.MATERIAL	GROUND PANEL B	GROUND PANEL A	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	± -
1 PLC	± 0.35
2 PLC	± 0.25
3 PLC	± 0.15
4 PLC	± -
ANGLES	± 3°

MATERIAL: SEE NOTE

FINISH: SEE NOTE

DWN	O. HU 07JUL2005
CHK	S. JOU 07JUL2005
APVD	W.J. KE 07JUL2005
PRODUCT SPEC	108-57549
APPLICATION SPEC	—
WEIGHT	6.16 GRAMS

TE Connectivity

NAME: RCPT, STACKED, USB, R/A, A TYPE

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C-1734084	—

CUSTOMER DRAWING | SCALE — | SHEET 1 OF 2 | REV B1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION –,– .
© COPYRIGHT 2011 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST
DW	—

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
		SEE SHEET 1.			



NOTES:
1. MATERIAL:
   TRAY: PE.
   POLYLONE:POLYLONE
   SHIPPING CARTON: CORRUGATED FIBER.
2. DIMENSION :
   TRAY : L=307mm, W=235mm, H=24mm
   SHIPPING CARTON : L=325mm, W=256mm, H=285mm
   POLYLONE : L=305mm, W=236mm, H=11.5mm

7.30 Kg	6.16 Kg	100	10	1000
GROSS WEIGHT	NET WEIGHT	PCS/TRAY	TRAY /CARTON	QUANTITY

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± –
4 PLC ± –
ANGLES ± –

MATERIAL –
FINISH –

DWN –
CHK –
APVD –
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

TE Connectivity

NAME
RCPT, STACKED, USB, R/A, A TYPE

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C-1734084	—

CUSTOMER DRAWING | SCALE — | SHEET 2 OF 2 | REV B1

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.