Is Now Part of

ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at
www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild_questions@onsemi.com.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

FAIRCHILD SEMICONDUCTOR®

December 2010

NC7SV57 / NC7SV58
TinyLogic® ULP-A Universal Configurable Two-Input Logic Gates

Features

- 0.9V to 3.6V V_{CC} Supply Operation
- 3.6V Over-Voltage Tolerant I/Os at V_{CC} from 0.9V to 3.6V
- Extremely High Speed t_{PD}
  - 2.5ns: Typical for 2.7V to 3.6V V_{CC}
  - 3.1ns: Typical for 2.3V to 2.7V V_{CC}
  - 4.0ns: Typical for 1.65V to 1.95V V_{CC}
  - 6.0ns: Typical for 1.4V to 1.6V V_{CC}
  - 8.0ns: Typical for 1.1V to 1.3V V_{CC}
  - 23.0ns: Typical for 0.9V V_{CC}
- Power-Off High-Impedance Inputs and Outputs
- High Static Drive (I_{OH}/I_{OL})
  - ±24mA at 3.00V V_{CC}
  - ±18mA at 2.30V V_{CC}
  - ±6mA at 1.65V V_{CC}
  - ±4mA at 1.4V V_{CC}
  - ±2mA at 1.1V V_{CC}
  - ±0.1mA at 0.9V V_{CC}
- Proprietary Quiet Series™ Noise/EMI Reduction
- Ultra-Small MicroPak™ Package
- Ultra-Low Dynamic Power

Description

The NC7SV57 and NC7SV58 are universal configurable two-input logic gates from Fairchild's Ultra-Low Power (ULP-A) series of TinyLogic®. ULP-A is ideal for applications that require extreme high-speed, high drive, and low power. This product is designed for a wide low-voltage operating range (0.9V to 3.6V V_{CC}) and applications that require more drive and speed than the TinyLogic® ULP series, but still offer best-in-class, low-power operation.

Each device is capable of being configured for 1 of 5 unique two-input logic functions. Any possible two-input combinatorial logic function can be implemented, as shown in the *Function Selection Table*. Device functionality is selected by how the device is wired at the board level. *Figures 1 through 10* illustrate how to connect the NC7SV57 and NC7SV58, respectively, for the desired logic function. All inputs have been implemented with hysteresis.

The NC7SV57 and NC7SV58 are uniquely designed for optimized power and speed and are fabricated with an advanced CMOS technology to achieve high-speed operation while maintaining low CMOS power dissipation.

Ordering Information

Part Number	Top Mark	Package	Packing Method
NC7SV57P6X	V57	6-Lead SC70, EIAJ SC-88a, 1.25mm Wide	3000 Units on Tape & Reel
NC7SV57L6X	H3	6-Lead Micropak™, 1.0mm Wide	5000 Units on Tape & Reel
NC7SV57FHX	H3	6-Lead, MicroPak2™, 1x1mm Body, .35mm Pitch	
NC7SV58P6X	V58	6-Lead SC70, EIAJ SC-88a, 1.25mm Wide	3000 Units on Tape & Reel
NC7SV58L6X	H4	6-Lead Micropak™, 1.0mm Wide	5000 Units on Tape & Reel
NC7SV58FHX	H4	6-Lead, MicroPak2™, 1x1mm Body, .35mm Pitch	

© 2002 Fairchild Semiconductor Corporation

Battery Life



Figure 1. Battery Life vs. V_{CC} Supply Voltage

Notes:

1. TinyLogic® ULP and ULP-A with up to 50% less power consumption can extend your battery life significantly.
   Battery Life = $(V_{battery} \bullet I_{battery} \bullet .9)/(P_{device})/24hrs/day$
   where $P_{device} = (I_{CC} \bullet V_{CC}) + (C_{PD} + C_L) \bullet V_{CC}^2 \bullet f$.
2. Assumes ideal 3.6V Lithium Ion battery with current rating of 900mAH and derated 90% and device frequency at 10MHz, with C_L = 15pF load.

Pin Configurations



Figure 2. SC70 (Top View)



Figure 3. MicroPak™ (Top Through View)



Figure 4. Pin 1 Orientation

Notes:
3. AAA represents product code top mark (*see Ordering Information*).
4. Orientation of top mark determines pin one location.
5. Reading the top mark left to right, pin one is the lower left pin.

Pin Definitions

Pin # SC70	Pin # MicroPak™	Name	Description
1	1	I_1	Data Input
2	2	GND	Ground
3	3	I_0	Data Input
4	4	Y	Output
5	5	V_{CC}	Supply Voltage
6	6	I_2	Data Input

© 2002 Fairchild Semiconductor Corporation

Function Table

Inputs			NC7SV57	NC7SV58
I_2	I_1	I_0	$Y = \overline{(I_0)} \bullet \overline{(I_2)} + (I_1) \bullet (I_2)$	$Y = (I_0) \bullet \overline{(I_2)} + \overline{(I_1)} \bullet (I_2)$
L	L	L	H	L
L	L	H	L	H
L	H	L	H	L
L	H	H	L	H
H	L	L	L	H
H	L	H	L	H
H	H	L	H	L
H	H	H	H	L

H = HIGH Logic Level
L = LOW Logic Level

Function Selection Table

2-Input Logic Function	Device Selection	Connection Configuration
2-Input AND	NC7SV57	Figure 5
2-Input AND with Inverted Input	NC7SV58	Figure 11, Figure 12
2-Input AND with Both Inputs Inverted	NC7SV57	Figure 8
2-Input NAND	NC7SV58	Figure 10
2-Input NAND with Inverted Input	NC7SV57	Figure 6, Figure 7
2-Input NAND with Both Inputs Inverted	NC7SV58	Figure 13
2-Input OR	NC7SV58	Figure 13
2-Input OR with Inverted Input	NC7SV57	Figure 6, Figure 7
2-Input OR with Both Inputs Inverted	NC7SV58	Figure 10
2-Input NOR	NC7SV57	Figure 8
2-Input NOR with Inverted Input	NC7SV58	Figure 10, Figure 11
2-Input NOR with Both Inputs Inverted	NC7SV57	Figure 5
2-Input XOR	NC7SV58	Figure 14
2-Input XNOR	NC7SV57	Figure 9

© 2002 Fairchild Semiconductor Corporation

NC7SV57 Logic Configurations

Figure 5 through Figure 9 show the logical functions that can be implemented using the NC7SV57. The diagrams show the DeMorgan's equivalent logic duals for a given two-input function. The logical implementation is next to the board-level physical implementation of how the pins of the function should be connected.



Figure 5. 2-Input AND Gate



Figure 6. 2-Input NAND Gate with Inverted A Input



Figure 7. 2-Input NAND with Inverted B Input



Figure 8. 2-Input NOR Gate



Figure 9. 2-Input XNOR Gate

© 2002 Fairchild Semiconductor Corporation

NC7SV58 Logic Configurations

Figure 10 through Figure 14 show the logical functions that can be implemented using the NC7SV58. The diagrams show the DeMorgan's equivalent logic duals for a given two-input function. The logical implementation is next to the board-level physical implementation of how the pins of the function should be connected.



Figure 10. 2-Input NAND Gate



Figure 11. 2-Input AND Gate with Inverted A Input



Figure 12. 2-Input AND with Inverted B Input



Figure 13. 2-Input OR Gate



Figure 14. 2-Input XOR Gate

Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Symbol	Parameter		Min.	Max.	Unit
V_{CC}	Supply Voltage		-0.5	4.6	V
V_{IN}	DC Input Voltage		-0.5	4.6	V
V_{OUT}	DC Output Voltage	HIGH or LOW State[6]	-0.5	V_{CC} + 0.5	V
		V_{CC}=0V	-0.5	4.6	
I_{IK}	DC Input Diode Current	V_{IN} < 0V		±50	mA
I_{OK}	DC Output Diode Current	V_{OUT} < 0V		-50	mA
		V_{OUT} > V_{CC}		+50	
I_{OH} / I_{OL}	DC Output Source / Sink Current			±50	mA
I_{CC} or I_{GND}	DC V_{CC} or Ground Current per Supply Pin			±50	mA
T_{STG}	Storage Temperature Range		-65	+150	°C
P_D	Power Dissipation at +85°C	MicroPak™-6		130	mW
		SC70-6		150	
		MicroPak2™-6		120	
ESD	Human Body Model, JEDEC:JESD22-A114			4000	V
	Charged Device Model, JEDEC:JESD22-C101			2000	

Note:
6. IO absolute maximum rating must be observed.

Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to Absolute Maximum Ratings.

Symbol	Parameter	Conditions	Min.	Max.	Unit
V_{CC}	Supply Voltage Operating		0.9	3.6	V
V_{IN}	Input Voltage		0	3.6	V
V_{OUT}	Output Voltage	V_{CC}=0V	0	3.6	V
		HIGH or LOW State	0	V_{CC}	
I_{OH}/I_{OL}	Output Current	V_{CC}=3.0V to 3.6V		±24.0	mA
		V_{CC}=2.3V to 2.7V		±18.0	
		V_{CC}=1.65V to 1.95V		±6.0	
		V_{CC}=1.4V to 1.6V		±4.0	
		V_{CC}=1.1V to 1.3V		±2.0	
		V_{CC}=0.9V		±0.1	µA
T_A	Operating Temperature, Free Air		-40	+85	°C
$\Delta t/\Delta V$	Minimum Input Edge Rate	V_{IN}=0.8V to 2.0, V_{CC}=3.0V		10	ns/V
θ_{JA}	Thermal Resistance	SC70-6		425	°C/W
		MicroPak™-6		500	
		MicroPak2™-6		560	

Note:
7. Unused inputs must be held HIGH or LOW. They may not float.

© 2002 Fairchild Semiconductor Corporation

DC Electrical Characteristics

Symbol	Parameter	V_{CC}	Conditions	T_A=25°C		T_A=-40 to 85°C		Units
				Min.	Max.	Min.	Max.	
V_P	Positive Threshold Voltage	0.90		0.30	0.70	0.30	0.70	V
		1.10		0.40	1.00	0.40	1.00	
		1.40		0.50	1.40	0.50	1.40	
		1.65		0.70	1.50	0.70	1.50	
		2.30		1.00	1.80	1.00	1.80	
		2.70		1.30	2.20	1.30	2.20	
V_N	Negative Threshold Voltage	0.90		0.10	0.60	0.10	0.60	V
		1.10		0.15	0.70	0.15	0.70	
		1.40		0.20	0.80	0.20	0.80	
		1.65		0.25	0.90	0.25	0.90	
		2.30		0.40	1.15	0.40	1.15	
		2.70		0.60	1.50	0.60	1.50	
V_H	Hysteresis Voltage	0.90		0.07	0.50	0.07	0.50	V
		1.10		0.08	0.60	0.08	0.60	
		1.40		0.10	0.80	0.10	0.80	
		1.65		0.15	1.00	0.15	1.00	
		2.30		0.25	1.10	0.25	1.10	
		2.70		0.40	1.20	0.40	1.20	
V_{OH}	HIGH Level Output Voltage	0.90	I_{OH}=-100µA	V_{CC}-0.1		V_{CC}-0.1		V
		1.10 ≤ V_{CC} ≤ 1.30		V_{CC}-0.1		V_{CC}-0.1		
		1.40 ≤ V_{CC} ≤ 1.60		V_{CC}-0.2		V_{CC}-0.2		
		1.65 ≤ V_{CC} ≤ 1.95		V_{CC}-0.2		V_{CC}-0.2		
		2.30 ≤ V_{CC} ≤ 2.70		V_{CC}-0.2		V_{CC}-0.2		
		2.70 ≤ V_{CC} ≤ 3.60		V_{CC}-0.2		V_{CC}-0.2		
		1.10 ≤ V_{CC} ≤ 1.30	I_{OH}=-2mA	.75 x V_{CC}		.75 x V_{CC}		
		1.40 ≤ V_{CC} ≤ 1.60	I_{OH}=-4mA	.75 x V_{CC}		.75 x V_{CC}		
		1.65 ≤ V_{CC} ≤ 1.95	I_{OH}=-6mA	1.25		1.25		
		2.30 ≤ V_{CC} ≤ 2.70		2.0		2.0		
		2.30 ≤ V_{CC} ≤ 2.70	I_{OH}=-12mA	1.8		1.8		
		2.70 ≤ V_{CC} ≤ 3.60		2.2		2.2		
		2.30 ≤ V_{CC} ≤ 2.70	I_{OH}=-18mA	1.7		1.7		
		2.70 ≤ V_{CC} ≤ 3.60		2.4		2.4		
		2.70 ≤ V_{CC} ≤ 3.60	I_{OH}=-24mA	2.2		2.2		

Continued on following page….

© 2002 Fairchild Semiconductor Corporation

DC Electrical Characteristics (Continued)

Symbol	Parameter	V_{CC}	Conditions	T_A=25°C		T_A=-40 to 85°C		Units
				Min.	Max.	Min.	Max.	
V_{OL}	LOW Level Output Voltage	0.90	I_{OL}=100µA		0.1		0.1	V
		$1.10 \le V_{CC} \le 1.30$			0.1		0.1	
		$1.40 \le V_{CC} \le 1.60$			0.2		0.2	
		$1.65 \le V_{CC} \le 1.95$			0.2		0.2	
		$2.30 \le V_{CC} \le 2.70$			0.2		0.2	
		$2.70 \le V_{CC} \le 3.60$			0.2		0.2	
		$1.10 \le V_{CC} \le 1.30$	I_{OL}=2mA		.25 x V_{CC}		.25 x V_{CC}	
		$1.40 \le V_{CC} \le 1.60$	I_{OL}=4mA		.25 x V_{CC}		.25 x V_{CC}	
		$1.65 \le V_{CC} \le 1.95$	I_{OL}=6mA		0.3		0.3	
		$2.30 \le V_{CC} \le 2.70$	I_{OL}=12mA		0.4		0.4	
		$2.70 \le V_{CC} \le 3.60$			0.4		0.4	
		$2.30 \le V_{CC} \le 2.70$	I_{OL}=18mA		0.6		0.6	
		$2.70 \le V_{CC} \le 3.60$			0.4		0.4	
		$2.70 \le V_{CC} \le 3.60$	I_{OL}=24mA		0.55		0.55	
I_{IN}	Input Leakage Current	0.90 to 3.60	$0 \le V_{IN} \le 3.6V$		±0.1		±0.5	µA
I_{OFF}	Power Off Leakage Current	0	$0 \le (V_{IN,} V_O) \le 3.60$		0.5		0.5	µA
I_{CC}	Quiescent Supply Current	0.90 to 3.60	$V_{IN}=V_{CC}$ or GND		0.9		0.9	µA
			$V_{CC} \le V_{IN} \le 3.6V$				±0.9	

AC Electrical Characteristics

Symbol	Parameter	V_{CC}	Conditions	T_A=25°C			T_A=-40 to 85°C		Units	Figure
				Min.	Typ.	Min.	Typ.	Min.		
t_{PHL}, t_{PLH}	Propagation Delay	0.90	C_L=15pF, R_L=1MΩ		15.0				ns	Figure 15 Figure 16
		$1.10 \le V_{CC} \le 1.30$	C_L=15pF, R_L=2KΩ	4.0	8.0	16.5	3.3	31.0		
		$1.40 \le V_{CC} \le 1.60$		2.0	6.0	10.0	2.0	12.0		
		$1.65 \le V_{CC} \le 1.95$	C_L=30pF, R_L=500Ω	2.0	4.0	9.1	1.9	10.0		
		$2.30 \le V_{CC} \le 2.70$		1.5	3.1	6.2	1.4	6.7		
		$2.70 \le V_{CC} \le 3.60$		1.2	2.5	5.4	1.2	6.1		
C_{IN}	Input Capacitance	0			8				pF	
C_{OUT}	Output Capacitance	0			12				pF	
C_{PD}	Power Dissipation Capacitance	0.90 to 3.60	V_I=0V or V_{CC}, f=10MHz		10				pF	

© 2002 Fairchild Semiconductor Corporation

AC Loadings and Waveforms



Figure 15. AC Test Circuit



Figure 16. AC Waveforms

Symbol	V_{CC}					
	3.3V ± 0.3V	**2.5V ± 0.2V**	**1.8V ± 0.15V**	**1.5V ± 0.10V**	**1.2V ± 0.10V**	**0.9V**
V_{mi}	1.5V	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$
V_{mo}	1.5V	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$

Physical Dimensions



Figure 17. 6-Lead, SC70, EIAJ SC-88a, 1.25mm Wide

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:
http://www.fairchildsemi.com/packaging/.

Tape and Reel Specifications

Please visit Fairchild Semiconductor's online packaging area for the most recent tape and reel specifications:
http://www.fairchildsemi.com/products/analog/pdf/sc70-6_tr.pdf

Package Designator	Tape Section	Cavity Number	Cavity Status	Cover Type Status
P6X	Leader (Start End)	125 (Typical)	Empty	Sealed
	Carrier	3000	Filled	Sealed
	Trailer (Hub End)	75 (Typical)	Empty	Sealed

© 2002 Fairchild Semiconductor Corporation

Physical Dimensions



Notes:

1. CONFORMS TO JEDEC STANDARD M0-252 VARIATION UAAD
2. DIMENSIONS ARE IN MILLIMETERS
3. DRAWING CONFORMS TO ASME Y14.5M-1994
4. FILENAME AND REVISION: MAC06AREV4
5. PIN ONE IDENTIFIER IS 2X LENGTH OF ANY OTHER LINE IN THE MARK CODE LAYOUT.

Figure 18. 6-Lead, MicroPak™, 1.0mm Wide

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:
http://www.fairchildsemi.com/packaging/.

Tape and Reel Specifications

Please visit Fairchild Semiconductor's online packaging area for the most recent tape and reel specifications:
http://www.fairchildsemi.com/products/logic/pdf/micropak_tr.pdf.

Package Designator	Tape Section	Cavity Number	Cavity Status	Cover Type Status
L6X	Leader (Start End)	125 (Typical)	Empty	Sealed
	Carrier	5000	Filled	Sealed
	Trailer (Hub End)	75 (Typical)	Empty	Sealed

© 2002 Fairchild Semiconductor Corporation

Physical Dimensions



NOTES:

A. COMPLIES TO JEDEC MO-252 STANDARD
B. DIMENSIONS ARE IN MILLIMETERS.
C. DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 1994
D. LANDPATTERN RECOMMENDATION IS BASED ON FSC DESIGN.
E. DRAWING FILENAME AND REVISION: MGF06AREV3

Figure 19. 6-Lead, MicroPak2, 1x1mm Body, .35mm Pitch

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:
http://www.fairchildsemi.com/packaging/.

Tape and Reel Specifications

Please visit Fairchild Semiconductor's online packaging area for the most recent tape and reel specifications:
http://www.fairchildsemi.com/packaging/MicroPAK2_6L_tr.pdf

.

Package Designator	Tape Section	Cavity Number	Cavity Status	Cover Type Status
FHX	Leader (Start End)	125 (Typical)	Empty	Sealed
	Carrier	5000	Filled	Sealed
	Trailer (Hub End)	75 (Typical)	Empty	Sealed

© 2002 Fairchild Semiconductor Corporation

FAIRCHILD SEMICONDUCTOR®

TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

AccuPower™
Auto-SPM™
Build it Now™
CorePLUS™
CorePOWER™
CROSSVOLT™
CTL™
Current Transfer Logic™
DEUXPEED®
Dual Cool™
EcoSPARK®
EfficientMax™
ESBC™
F®
Fairchild®
Fairchild Semiconductor®
FACT Quiet Series™
FACT®
FAST®
FastvCore™
FETBench™
FlashWriter®*
FPS™
F-PFS™
FRFET®
Global Power Resource℠
Green FPS™
Green FPS™ e-Series™
Gmax™
GTO™
IntelliMAX™
ISOPLANAR™
MegaBuck™
MICROCOUPLER™
MicroFET™
MicroPak™
MicroPak2™
MillerDrive™
MotionMax™
Motion-SPM™
OptoHiT™
OPTOLOGIC®
OPTOPLANAR®
PDP SPM™
Power-SPM™
PowerTrench®
PowerXS™
Programmable Active Droop™
QFET®
QS™
Quiet Series™
RapidConfigure™
™
Saving our world, 1mW/W/kW at a time™
SignalWise™
SmartMax™
SMART START™
SPM®
STEALTH™
SuperFET®
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SupreMOS®
SyncFET™
Sync-Lock™
SYSTEM GENERAL®*
The Power Franchise®
The Right Technology for Your Success™
the power franchise
TinyBoost™
TinyBuck™
TinyCalc™
TinyLogic®
TINYOPTO™
TinyPower™
TinyPWM™
TinyWire™
TriFault Detect™
TRUECURRENT™*
μSerDes™
SerDes
UHC®
Ultra FRFET™
UniFET™
VCX™
VisualMax™
XS™

* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.

Rev. I51

© 2002 Fairchild Semiconductor Corporation

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ON Semiconductor:

NC7SV57P6X NC7SV57L6X NC7SV57FHX

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.