


- [RoHs Compliant Containing No Lead and Bromide](#) ②
- Integrated Monolithic Schottky Diode
- Low Profile (<0.7 mm)
- [Dual Sided Cooling Compatible](#) ①
- Low Package Inductance
- Optimized for High Frequency Switching
- Ideal for CPU Core DC-DC Converters
- Optimized for Sync. FET socket of Sync. Buck Converter
- Low Conduction and Switching Losses
- [Compatible with existing Surface Mount Techniques](#) ①
- 100% R_g tested
- Footprint compatible to DirectFET

HEXFET® Power MOSFET plus Schottky Diode ②

Typical values (unless otherwise specified)

V _{DSS}	V _{GS}	R _{DS(on)}	R _{DS(on)}
25V min	±16V max	0.9mΩ @ 10V	1.4mΩ @ 4.5V
Q _{g tot}	Q _{gd}	Q _{gs2}	Q _{rr}
31nC	10nC	3.0nC	58nC



[Applicable DirectFET™ Outline and Substrate Outline \(see p.7,8 for details\)](#) ①

SQ	SX	ST		MQ	MX	MT	MP		

Description

The IRF6894MPbF combines the latest HEXFET® Power MOSFET Silicon technology with the advanced DirectFET™ packaging to achieve the lowest on-state resistance in a package that has the footprint of a SO-8 and only 0.7 mm profile. The DirectFET™ package is compatible with existing layout geometries used in power applications, PCB assembly equipment and vapor phase, infra-red or convection soldering techniques. Application note [AN-1035](#) is followed regarding the manufacturing methods and processes. The DirectFET™ package allows dual sided cooling to maximize thermal transfer in power systems, improving previous best thermal resistance by 80%.

The IRF6894MPbF balances industry leading on-state resistance while minimizing gate charge along with low gate resistance to reduce both conduction and switching losses. This part contains an integrated Schottky diode to reduce the Q_{rr} of the body drain diode further reducing the losses in a Synchronous Buck circuit. The reduced losses make this product ideal for high frequency/high efficiency DC-DC converters that power high current loads such as the latest generation of microprocessors. The IRF6894MPbF has been optimized for parameters that are critical in synchronous buck converter's Sync FET sockets.

Base part number	Package Type	Standard Pack		Orderable Part Number
		Form	Quantity	
IRF6894MTRPbF	DirectFET® Medium Can	Tape and Reel	4800	IRF6894MTRPbF

Absolute Maximum Ratings

	Parameter	Max.	Units
V _{DS}	Drain-to-Source Voltage	25	V
V _{GS}	Gate-to-Source Voltage	±16	
I _D @ T _A = 25°C	Continuous Drain Current, V _{GS} @ 10V (Silicon Limited)④	37	
I _D @ T _A = 70°C	Continuous Drain Current, V _{GS} @ 10V (Silicon Limited)④	29	
I _D @ T _C = 25°C	Continuous Drain Current, V _{GS} @ 10V (Silicon Limited)③	163	A
I _{DM}	Pulsed Drain Current⑤	296	
E _{AS}	Single Pulse Avalanche Energy ⑥	540	mJ
I _{AR}	Avalanche Current ⑥	30	A





Fig 1. Typical On-Resistance vs. Gate Voltage

Notes

- ① Click on this section to link to the appropriate technical paper.
② Click on this section to link to the DirectFET™ Website.
③ Surface mounted on 1 in. square Cu board, steady state.

Fig 2. Typical Total Gate Charge vs. Gate-to-Source Voltage

- ④ TC measured with thermocouple mounted to top (Drain) of part.
⑤ Repetitive rating; pulse width limited by max. junction temperature.
⑥ Starting T_J = 25°C, L = 1.2mH, R_G = 50Ω, I_{AS} = 30A.

Static @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions	
BV_{DSS}	Drain-to-Source Breakdown Voltage	25	—	—	V	$\text{V}_{\text{GS}} = 0\text{V}, \text{I}_D = 1.0\text{mA}$	
$\Delta \text{BV}_{\text{DSS}}/\Delta T_J$	Breakdown Voltage Temp. Coefficient	—	0.02	—	$\text{V}/^\circ\text{C}$	$\text{I}_D = 10\text{mA} (25^\circ\text{C}-125^\circ\text{C})$	
$R_{\text{DS(on)}}$	Static Drain-to-Source On-Resistance	—	0.9	1.3	$\text{m}\Omega$	$\text{V}_{\text{GS}} = 10\text{V}, \text{I}_D = 37\text{A} \textcircled{7}$	
		—	1.4	1.8		$\text{V}_{\text{GS}} = 4.5\text{V}, \text{I}_D = 30\text{A} \textcircled{7}$	
$\text{V}_{\text{GS(th)}}$	Gate Threshold Voltage	1.1	1.6	2.1	V	$\text{V}_{\text{DS}} = \text{V}_{\text{GS}}, \text{I}_D = 100\mu\text{A}$	
$\Delta \text{V}_{\text{GS(th)}}/\Delta T_J$	Gate Threshold Voltage Temp. Coefficient	—	-3.8	—	$\text{mV}/^\circ\text{C}$	$\text{V}_{\text{DS}} = \text{V}_{\text{GS}}, \text{I}_D = 10\text{mA}$	
I_{DSS}	Drain-to-Source Leakage Current	—	—	500	μA	$\text{V}_{\text{DS}} = 20\text{ V}, \text{V}_{\text{GS}} = 0\text{V}$	
I_{GSS}	Gate-to-Source Forward Leakage	—	—	100	nA	$\text{V}_{\text{GS}} = 16\text{V}$	
	Gate-to-Source Reverse Leakage	—	—	-100		$\text{V}_{\text{GS}} = -16\text{V}$	
gfs	Forward Transconductance	193	—	—	S	$\text{V}_{\text{DS}} = 13\text{V}, \text{I}_D = 30\text{A}$	
Q_g	Total Gate Charge	—	31	47	nC	$\text{V}_{\text{DS}} = 13\text{V}$ $\text{V}_{\text{GS}} = 4.5\text{V}$ $\text{I}_D = 30\text{A}$ See Fig 15	
Q_{gs1}	Pre- V_{th} Gate-to-Source Charge	—	8.1	—			
Q_{gs2}	Post- V_{th} Gate-to-Source Charge	—	3.0	—			
Q_{gd}	Gate-to-Drain Charge	—	10	—			
Q_{godr}	Gate Charge Overdrive	—	10	—			
Q_{sw}	Switch Charge ($\text{Q}_{\text{gs2}} + \text{Q}_{\text{gd}}$)	—	13	—	nC	$\text{V}_{\text{DS}} = 16\text{V}, \text{V}_{\text{GS}} = 0\text{V}$	
Q_{oss}	Output Charge	—	33	—			
R_G	Gate Resistance	—	0.2	—	Ω	$\text{V}_{\text{DD}} = 13\text{V}, \text{V}_{\text{GS}} = 4.5\text{V} \textcircled{7}$ $\text{I}_D = 30\text{A}$ $\text{R}_G = 1.8\Omega$ See Fig 17	
$t_{\text{d(on)}}$	Turn-On Delay Time	—	17	—	ns		
t_r	Rise Time	—	47	—			
$t_{\text{d(off)}}$	Turn-Off Delay Time	—	23	—			
t_f	Fall Time	—	13	—			
C_{iss}	Input Capacitance	—	4232	—	pF	$\text{V}_{\text{GS}} = 0\text{V}$ $\text{V}_{\text{DS}} = 13\text{V}$ $f = 1.0\text{MHz}$	
C_{oss}	Output Capacitance	—	1260	—			
C_{rss}	Reverse Transfer Capacitance	—	255	—			

Diode Characteristics

	Parameter	Min.	Typ.	Max.	Units	Conditions
I_s	Continuous Source Current (Body Diode)	—	—	37	A	MOSFET symbol showing the integral reverse p-n junction diode.
	Pulsed Source Current (Body Diode) $\textcircled{5}$	—	—	296		
V_{SD}	Diode Forward Voltage	—	—	0.75	V	$T_J = 25^\circ\text{C}, I_s = 30\text{A}, \text{V}_{\text{GS}} = 0\text{V} \textcircled{7}$
t_{rr}	Reverse Recovery Time	—	28	42	ns	$T_J = 25^\circ\text{C}, I_F = 30\text{A}$
Q_{rr}	Reverse Recovery Charge	—	58	87	nC	$dI/dt = 320\text{A}/\mu\text{s} \textcircled{7}$


Notes:


- $\textcircled{5}$ Repetitive rating; pulse width limited by max. junction temperature.
 $\textcircled{7}$ Pulse width $\leq 400\mu\text{s}$; duty cycle $\leq 2\%$.

Absolute Maximum Ratings

Symbol	Parameter	Max.	Units
P _D @ T _A = 25°C	Power Dissipation ③④	2.8	W
P _D @ T _A = 70°C	Power Dissipation ③④	1.8	
P _D @ T _C = 25°C	Power Dissipation ④	54	
T _P	Peak Soldering Temperature	270	°C
T _J T _{STG}	Operating Junction and Storage Temperature Range	-40 to + 150	


Thermal Resistance

Symbol	Parameter	Typ.	Max.	Units
R _{θJA}	Junction-to-Ambient ③	—	45	°C/W
R _{θJA}	Junction-to-Ambient ⑧	12.5	—	
R _{θJA}	Junction-to-Ambient ⑨	20	—	
R _{θJC}	Junction-to-Can ④⑩	—	2.3	
R _{θJA-PCB}	Junction-to-PCB Mounted	1.0	—	
	Linear Derating Factor ③	0.022	W/°C	



Fig 3. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient^③
Notes:

- ③ Surface mounted on 1 in. square Cu board, steady state.
④ T_C measured with thermocouple in contact with top (Drain) of part.


- ⑧ Used double sided cooling, mounting pad with large heatsink.
⑨ Mounted on minimum footprint full size board with metalized back and with small clip heatsink.
⑩ R_θ is measured at T_J of approximately 90°C.









③ Surface mounted on 1 in. square Cu board (still air).



⑨ Mounted to a PCB with small clip heatsink (still air)



⑩ Mounted on minimum footprint full size board with metalized back and with small clip heatsink (still air)

**Fig 4.** Typical Output Characteristics**Fig 5.** Typical Output Characteristics**Fig 6.** Typical Transfer Characteristics**Fig 7.** Normalized On-Resistance vs. Temperature**Fig 8.** Typical Capacitance vs. Drain-to-Source Voltage**Fig 9.** Typical On-Resistance vs. Drain Current and Gate Voltage




Fig 10. Typical Source-Drain Diode Forward Voltage




Fig 11. Maximum Safe Operating Area




Fig 12. Maximum Drain Current vs. Case Temperature




Fig 13. Typical Threshold Voltage vs. Junction Temperature




Fig 14. Maximum Avalanche Energy vs. Drain Current




Fig 15a. Gate Charge Test Circuit




Fig 15b. Gate Charge Waveform




Fig 16a. Unclamped Inductive Test Circuit




Fig 16b. Unclamped Inductive Waveforms




Fig 17a. Switching Time Test Circuit




Fig 17b. Switching Time Waveforms





Fig 18. Diode Reverse Recovery Test Circuit for HEXFET® Power MOSFETs

DirectFET™ Board Footprint, MX Outline (Medium Size Can, X-Designation).



Please see DirectFET™ application note [AN-1035](#) for all details regarding the assembly of DirectFET™. This includes all recommendations for stencil and substrate designs.




Note: For the most current drawing please refer to website at <http://www.irf.com/package/>

**DirectFET™ Outline Dimension, MX Outline
(Medium Size Can, X-Designation).**

Please see DirectFET™ application note [AN-1035](#) for all details regarding the assembly of DirectFET™. This includes all recommendations for stencil and substrate designs.



**DirectFET™ Part Marking**

Note: For the most current drawing please refer to website at <http://www.irf.com/package/>

DirectFET™ Tape & Reel Dimension (Showing component orientation).


NOTE: Controlling dimensions in mm
Std reel quantity is 4800 parts. (ordered as IRF6894MTRPBF). For 1000 parts on 7" reel, order IRF6894MTR1PBF

REEL DIMENSIONS								
CODE	STANDARD OPTION (QTY 4800)				TR1 OPTION (QTY 1000)			
	METRIC	IMPERIAL	METRIC	IMPERIAL	METRIC	IMPERIAL	METRIC	IMPERIAL
A	330.0	N.C.	12.992	N.C.	177.77	N.C.	6.9	N.C.
B	20.2	N.C.	0.795	N.C.	19.06	N.C.	0.75	N.C.
C	12.8	13.2	0.504	0.520	13.5	12.8	0.53	0.50
D	1.5	N.C.	0.059	N.C.	1.5	N.C.	0.059	N.C.
E	100.0	N.C.	3.937	N.C.	58.72	N.C.	2.31	N.C.
F	N.C.	18.4	N.C.	0.724	N.C.	13.50	N.C.	0.53
G	12.4	14.4	0.488	0.567	11.9	12.01	0.47	N.C.
H	11.9	15.4	0.469	0.606	11.9	12.01	0.47	N.C.

LOADED TAPE FEED DIRECTION


NOTE: CONTROLLING DIMENSIONS IN MM

CODE	METRIC		IMPERIAL	
	MIN	MAX	MIN	MAX
A	7.90	8.10	0.311	0.319
B	3.90	4.10	0.154	0.161
C	11.90	12.30	0.469	0.484
D	5.45	5.55	0.215	0.219
E	5.10	5.30	0.201	0.209
F	6.50	6.70	0.256	0.264
G	1.50	N.C.	0.059	N.C.
H	1.50	1.60	0.059	0.063

Note: For the most current drawing please refer to website at <http://www.irf.com/package/>

Qualification Information

Qualification Level	Industrial [†]	
Moisture Sensitivity Level	DirectFET™ Medium Can	MSL1 (per JEDEC J-STD-020D [†])
RoHS Compliant	Yes	

[†] Applicable version of JEDEC standard at the time of product release.

Revision History

Date	Comment
10/13/2016	<ul style="list-style-type: none">• Changed datasheet with "Infineon" logo –all pages.• Changed Rth from "60°C/W" to "45°C/W" –page 3• Changed ID @ TA 25C/70C from "32A/25A" to "37A/29A" –page 1 & 2.• Changed Fig.1 to Fig.15 –page 1 to 9.• Added disclaimer on last page.

Published by

Infineon Technologies AG
81726 München, Germany

© Infineon Technologies AG 2015
All Rights Reserved.

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie"). With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies office (www.infineon.com).

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помошь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помошь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.