



For more Information  
please call

1-800-Belden1



## General Description:

PTZ (CCTV+Control+Power) Cable, Plenum-CMP, 1-RG59 20 AWG solid bare copper with foam PFA, 95% bare copper braid, 1-18 AWG stranded bare copper pair with FEP insulation and Beldfoil® shield, 2-18 AWG stranded bare copper conductors with Flamarrest® insulation, Siamese with Flamarrest® jacket

## Coax

### Physical Characteristics

#### Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	20	Solid	BC - Bare Copper	0.813

#### Insulation

Insulation Material:

Insulation Material	Dia. (mm)
FPFA - Foam Perfluoroalkoxy	3.378

#### Outer Shield

Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	BC - Bare Copper	95.000

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (mm)
4.902

#### Overall Cabling

Overall Cabling Color Code Chart:

Number	Color
Video	Black

## Applicable Specifications and Agency Compliance

### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMP

CEC/C(UL) Specification: CMP

EU CE Mark: Yes

RG Type: 59/U

### Flame Test

UL Flame Test: NFPA 262

### Suitability

Suitability - Indoor: Yes

## Electrical Characteristics

Nom. Characteristic Impedance:

Impedance (Ohm)
75

Nom. Inductance:

Inductance (µH/m)
0.318

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
52.824

Nominal Velocity of Propagation:

**VP (%)**  
84.000

**Nominal Delay:**

**Delay (ns/m)**  
3.970

**Nom. Conductor DC Resistance:**

**DCR @ 20°C (Ohm/km)**  
32.810

**Nominal Outer Shield DC Resistance:**

**DCR @ 20°C (Ohm/km)**  
8.203

**Nom. Attenuation:**

Freq. (MHz)	Attenuation (dB/100m)
1.000	0.951
5.000	2.297
10.000	3.609
50.000	5.906
100.000	8.859
200.000	12.796
400.000	19.358
700.000	27.889
900.000	32.810
1000.000	35.107

**Max. Operating Voltage - UL:** 300 V RMS

## Twisted Pair

### Physical Characteristics

#### Conductor

**AWG:**

# Pairs	AWG	Stranding	Conductor Material	Dia. (mm)
1	18	19x30	BC - Bare Copper	1.118

#### Insulation

**Insulation Material:**

Insulation Material	Dia. (mm)
FEP - Fluorinated Ethylene Propylene	1.499

#### Inner Jacket

**Inner Jacket Color Code Chart:**

Number	Color
1	Blue and White/Blue

#### Outer Shield

**Outer Shield Material:**

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000

**Outer Shield Drain Wire AWG:**

AWG	Stranding	Drain Wire Conductor Material
20	19x32	TC - Tinned Copper

#### Outer Jacket

**Outer Jacket Material:**

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

**Outer Jacket Diameter:**

**Nom. Dia. (mm)**  
3.810

**Outer Jacket Color Code Chart:**

Number	Color
1	Blue

### Applicable Specifications and Agency Compliance

#### Applicable Standards & Environmental Programs

**NEC/(UL) Specification:** CMP

**CEC/C(UL) Specification:** CMP

#### Flame Test

**UL Flame Test:** NFPA 262

### Suitability

Suitability - Indoor: Yes

### Electrical Characteristics

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)

318.257

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)

167.331

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

18.046

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

23.951

Max. Operating Voltage - Other:

Voltage

300 V RMS

Max. Recommended Current:

Current

5.2 Amps per conductor @ 25°C

### Multi Conductor

#### Physical Characteristics

##### Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (mm)
2	18	7x26	BC - Bare Copper	1.194

##### Insulation

Insulation Material:

Insulation Trade Name Insulation Material

Flamarrest® LS PVC - Low Smoke Polyvinyl Chloride

Insulation Color Code Chart:

Number Color

1	Red
2	Black

##### Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name Outer Jacket Material

Flamarrest® LS PVC - Low Smoke Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (mm)

4.013

Outer Jacket Color Code Chart:

Number Color

1	White
---	-------

### Electrical Characteristics

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m)

98.430

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

21.327

Max. Operating Voltage - Other:

Voltage

300 V RMS

Max. Recommended Current:

Current

5 Amps per conductor @ 25°C

## 602PTZ Composite - For PTZ Cameras: CCTV + Control + Power

### Physical Characteristics (Overall)

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
Unjacketed

#### Overall Cable

Overall Nominal Diameter: 9.220 mm

### Mechanical Characteristics (Overall)

Operating Temperature Range: -10°C To +75°C

Separation Temperature Range: 0°C To +75°C

Bulk Cable Weight: 98.221 Kg/Km

Max. Recommended Pulling Tension: 720.608 N

Min. Bend Radius/Minor Axis: 91.440 mm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

#### Applicable Patents:

Country
www.belden.com/p

#### Plenum/Non-Plenum

Plenum (Y/N): Yes

Plenum Number: 502PTZ

### Notes (Overall)

**Notes:** RG59 CCTV + 1 STP 18 AWG Control Grade + 2C 18 AWG CMP. Individually jacketed and color coded components, cabled around and each fused to a central binding spline. Cold environment installation: When installing cables that have been stored at ambient temperatures of 32 degrees Fahrenheit (0 degrees Centigrade) or lower, Belden recommends conditioning of the cable for 12 hours at room temperature prior to individual cable leg separation.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
602PTZ 0001000	1,000 FT	70.000 LB	NONE	C	RG59 +2C18 FS +2C18 CMP BPEEL
602PTZ 000500	500 FT	36.000 LB	NONE	C	RG59 +2C18 FS +2C18 CMP BPEEL

#### Notes:

C = CRATE REEL PUT-UP.

Revision Number: 0 Revision Date: 02-28-2014

© 2016 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.