

# Serial Input 16-Bit 4 mA–20 mA, 0 mA–20 mA DAC

# AD420

### FEATURES

4 mA-20 mA, 0 mA-20 mA or 0 mA-24 mA current output 16-bit resolution and monotonicity ±0.012% max integral nonlinearity ±0.05% max offset (trimmable) ±0.15% max total output error (trimmable) Flexible serial digital interface (3.3 MBPS) On-Chip loop fault detection On-chip 5 V reference (25 ppm/°C max) Asynchronous CLEAR function Maximum power supply range of 32 V Output loop compliance of 0 V to V<sub>cc</sub> - 2.75 V 24-Lead SOIC and PDIP packages

### **GENERAL DESCRIPTION**

The AD420 is a complete digital to current loop output converter, designed to meet the needs of the industrial control market. It provides a high precision, fully integrated, low cost single-chip solution for generating current loop signals in a compact 24-lead SOIC or PDIP package.

The output current range can be programmed to 4 mA to 20 mA, 0 mA to 20 mA or to an overrange function of 0 mA to 24 mA. The AD420 can alternatively provide a voltage output from a separate pin that can be configured to provide 0 V to 5 V, 0 V to 10 V,  $\pm$ 5 V, or  $\pm$ 10 V with the addition of a single external buffer amplifier.

The 3.3 M Baud serial input logic design minimizes the cost of galvanic isolation and allows for simple connection to commonly used microprocessors. It can be used in 3-wire or asynchronous mode and a serial-out pin is provided to allow daisy chaining of multiple DACs on the current loop side of the isolation barrier.

The AD420 uses sigma-delta  $(\Sigma - \Delta)$  DAC technology to achieve 16-bit monotonicity at very low cost. Full-scale settling to 0.1% occurs within 3 ms. The only external components that are required (in addition to normal transient protection circuitry) are two low cost capacitors which are used in the DAC output filter.

If the AD420 is used at extreme temperatures and supply voltages, an external output transistor can be used to minimize power dissipation on the chip via the BOOST pin. The FAULT DETECT pin signals when an open circuit occurs in the loop. The on-chip voltage reference can be used to supply a precision +5 V to external components in addition to the AD420 or, if the

#### Rev. H

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

#### FUNCTIONAL BLOCK DIAGRAM



user desires temperature stability exceeding 25 ppm/°C, an external precision reference such as the AD586 can be used as the reference. The AD420 is available in a 24-lead SOIC and PDIP over the industrial temperature range of  $-40^{\circ}$ C to  $+85^{\circ}$ C.

### **PRODUCT HIGHLIGHTS**

- 1. The AD420 is a single chip solution for generating 4 mA to 20 mA or 0 mA to 20 mA signals at the controller end of the current loop.
- 2. The AD420 is specified with a power supply range from 12 V to 32 V. Output loop compliance is 0 V to  $V_{CC}$  2.75 V.
- 3. The flexible serial input can be used in 3-wire mode with SPI<sup>®</sup> or MICROWIRE<sup>®</sup> microcontrollers, or in asynchronous mode, which minimizes the number of control signals required.
- 4. The serial data out pin can be used to daisy chain any number of AD420s together in 3-wire mode.
- 5. At power-up, the AD420 initializes its output to the low end of the selected range.
- 6. The AD420 has an asynchronous CLEAR pin, which sends the output to the low end of the selected range (0 mA, 4 mA, or 0 V).
- 7. The AD420 BOOST pin accommodates an external transistor to off-load power dissipation from the chip.
- 8. The offset of  $\pm 0.05\%$  and total output error of  $\pm 0.15\%$  can be trimmed if desired, using two external potentiometers.

 One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.

 Tel: 781.329.4700
 www.analog.com

 Fax: 781.461.3113
 ©1999-2011 Analog Devices, Inc. All rights reserved.

# TABLE OF CONTENTS

Features 1
Functional Block Diagram 1
General Description 1
Product Highlights 1
Revision History 2
Specifications
Absolute Maximum Ratings 5
ESD Caution 5
Pin Configuration and Function Descriptions
Timing Requirements
Three-Wire Interface7
Three-Wire Interface Fast Edges on Digital Input7
Asynchronous Interface7
Terminology
Theory of Operation9
Applications Information10
Current Output10

## **REVISION HISTORY**

#### 1/11-Rev. G to Rev. H

Changes to Figure 13 Changes to Ordering Guide	
11/09—Rev. F to Rev. G	
Updated Format	Universal
Changes to Table 2	5
Updated Outline Dimensions	
Changes to Ordering Guide	15

9/99—Rev. E to Rev. F

Driving Inductive Loads	
Voltage-Mode Output	
Optional Span and Zero Trim	
Three-Wire Interface	11
Using Multiple DACS with Fault Detect	11
Asynchronous Interface Using Optocouplers	11
Microprocessor Interface	
AD420-To-MC68HC11 (SPI Bus) Interface	
AD420 to Microwire Interface	
External Boost Function	
AD420 Protection	14
Transient Voltage Protection	14
Board Layout And Grounding	14
Power Supplies and Decoupling	14
Outline Dimensions	15
Ordering Guide	15

# **SPECIFICATIONS**

 $T_{\rm A}=T_{\rm MIN}-T_{\rm MAX}\text{, }V_{\rm CC}$  = +24 V, unless otherwise noted.

### Table 1.

	AD420-32 Version				
Parameter	Min	Тур	Max	Units	Comments
RESOLUTION	16			Bits	
IOUT CHARACTERISTICS					$R_L = 500 \Omega$
Operating Current Ranges	4		20	mA	
	0		20	mA	
	0		24	mA	
Current Loop Voltage Compliance	0		$V_{CC} - 2.75 V$	V	
Settling Time (to 0.1% of FS) <sup>1</sup>		2.5	3	ms	
Output Impedance (Current Mode)		25		MΩ	
Accuracy <sup>2</sup>					
Monotonicity	16			Bits	
Integral Nonlinearity		±0.002	±0.012	%	
Offset (0 mA or 4 mA) ( $T_A = +25^{\circ}C$ )			±0.05	%	
Offset Drift		20	50	ppm/° C	
Total Output Error (20 mA or 24 mA) ( $T_A = +25^{\circ}C$ )			±0.15	%	
Total Output Error Drift		20	50	ppm/° C	
PSRR <sup>3</sup>		5	10	μA/V	
Vout CHARACTERISTICS					
FS Output Voltage Range (Pin 17)	0		5	V	
VOLTAGE REFERENCE					
REF OUT					
Output Voltage ( $T_A = +25^{\circ}$ C)	4.995	5.0	5.005	V	
Drift			±25	ppm/° C	
Externally Available Current		5		mA	
Short Circuit Current		7		mA	
REF IN					
Resistance		30		kΩ	
Vii					
Output Voltage		4.5		V	
Externally Available Current		5		mA	
Short Circuit Current		20		mA	
DIGITAL INPUTS					
$V_{\rm H}$ (Logic 1)	24			V	
$V_{\parallel}$ (Logic 0)			0.8	v	
$I_{\rm H} (V_{\rm N} = 5.0  {\rm V})$			+10	uА	
$\lim_{N \to \infty} (V_{N} = 0 V)$			+10	μA	
Data Input Rate (3-Wire Mode)	No Minimum		33	MBPS	
Data Input Rate (Asynchronous Mode)	No Minimum		150	kBPS	
Vou (10 kO Pull-Un Besistor to Vu)	36	45		V	
$V_{ol}$ (10 kO Pull-Un Besistor to $V_{u}$ )	5.0	0.2	0.4	v	
$V_{\text{ol}} = 25 \text{ mA}$		0.6	5.1	v	
		0.0		ľ	
$V_{out}(l_{out}0.8 \text{ mA})$	36	43		v	
$V_{or} (I_{or} = 1.6 \text{ mA})$	5.0	 0 3	04	v	
		0.5	0.7	l V	1

	AD420-32 Version				
Parameter	Min	Тур	Max	Units	Comments
POWER SUPPLY					
Operating Range Vcc	12		32	V	
Quiescent Current		4.2	5.5	mA	
Quiescent Current (External VLL)		3		mA	
TEMPERATURE RANGE					
Specified Performance	-40		+85	°C	

<sup>1</sup> External capacitor selection must be as described in Figure 6.
 <sup>2</sup> Total Output Error includes Offset and Gain Error. Total Output Error and Offset Error are with respect to the Full-Scale Output and are measured with an ideal +5 V reference. If the internal reference is used, the reference errors must be added to the Offset and Total Output Errors.
 <sup>3</sup> PSRR is measured by varying V<sub>cc</sub> from 12 V to its maximum 32 V.

# **ABSOLUTE MAXIMUM RATINGS**

#### Table 2.

Parameter	Rating
V <sub>cc</sub> to GND	32 V
lout to GND	Vcc
Digital Inputs to GND	–0.5 V to +7 V
Digital Output to GND	$-0.5$ V to V $_{\text{LL}}$ + 0.3 V
$V_{LL}$ and REF OUT: Outputs Safe for	
Indefinite Short to Ground	
Storage Temperature	–65°C to +150°C
Lead Temperature (Soldering, 10 sec)	+300°C
Lead Temperature, Soldering Reflow	+260°C
Thermal Impedance:	
SOIC (R) Package	$\theta_{JA} = 75^{\circ}C/W$
PDIP (N) Package	$\theta_{JA} = 50^{\circ}C/W$

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Table 3.	Truth Table		
Inputs			
CLEAR	Range Select 2	Range Select 1	Operation
0	Х	Х	Normal operation
1	х	Х	Output at bottom of
			span
Х	0	0	0 V–5 V range
Х	0	1	4 mA–20 mA range
Х	1	0	0 mA–20 mA range
Х	1	1	0 mA–24 mA range

### **ESD CAUTION**



**ESD** (electrostatic discharge) sensitive device. Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

# **PIN CONFIGURATION AND FUNCTION DESCRIPTIONS**



#### Table 4. Pin Function Descriptions

Pin No.	Mnemonic	Function
1, 12, 13, 24	NC	No Connection. No internal connections inside device.
2	VLL	Auxiliary buffered +4.5 V digital logic voltage. This pin is the internal supply voltage for the digital circuitry and can be used as a termination for pull-up resistors. An external +5 V power supply can be connected to V <sub>LL</sub> . It will override this buffered voltage, thus reducing the internal power dissipation. The V <sub>LL</sub> pin should be decoupled to GND with a 0.1 $\mu$ F capacitor. See the Power Supplies and Decoupling section.
3	FAULT DETECT	FAULT DETECT, connected to a pull-up resistor, is asserted low when the output current does not match the DAC's programmed value, for example, in case the current loop is broken.
4	RANGE SELECT 2	Selects the converter's output operating range. One output voltage range and three
5	RANGE SELECT 1	output current ranges are available.
6	CLEAR	Valid V <sup>⊪</sup> unconditionally forces the output to go to the minimum of its programmed range. After CLEAR is removed the DAC output will remain at this value. The data in the input register is unaffected.
7	LATCH	In the 3-wire interface mode a rising edge parallel loads the serial input register data into the DAC. To use the asynchronous mode connect LATCH through a current limiting resistor to $V_{CC}$ .
8	CLOCK	Data Clock Input. The clock period is equal to the input data bit rate in the 3-wire interface mode and is 16 times the bit rate in asynchronous mode.
9	DATA IN	Serial Data Input.
10	DATA OUT	Serial Data Output. In the 3-wire interface mode, this output can be used for daisy-chaining multiple AD420s. In the asynchronous mode a positive pulse will indicate a framing error after the stop-bit is received.
11	GND	Ground (Common).
14	REF OUT	+5 V Reference Output.
15	REF IN	Reference Input.
16	OFFSET TRIM	Offset Adjust.
17	Vout	Voltage Output.
18	lout	Current Output.
19	BOOST	Connect to an external transistor to reduce the power dissipated in the AD420 output transistor, if desired.
20	CAP 1	These pins are used for internal filtering. Connect capacitors between each of these
21	CAP 2	pins and V <sub>cc</sub> . Refer to the description of current output operation.
22	NC	No Connection. Do not connect anything to this pin.
23	V <sub>cc</sub>	Power Supply Input. The $V_{CC}$ pin should always be decoupled to GND with a 0.1 $\mu F$ capacitor. See the Power Supplies and Decoupling section.

# TIMING REQUIREMENTS



Figure 3. Timing Diagram for 3-Wire Interface

#### Table 5. Timing Specification for 3-Wire Interface

Parameter	Label	Limit	Units
Data Clock Period	tск	300	ns min
Data Clock Low Time	t <sub>CL</sub>	80	ns min
Data Clock High Time	t <sub>сн</sub>	80	ns min
Data Stable Width	t <sub>DW</sub>	125	ns min
Data Setup Time	t <sub>DS</sub>	40	ns min
Data Hold Time	t <sub>DH</sub>	5	ns min
Latch Delay Time	t <sub>LD</sub>	80	ns min
Latch Low Time	tLL	80	ns min
Latch High Time	t <sub>LH</sub>	80	ns min
Serial Output Delay Time	t <sub>sD</sub>	225	ns max
Clear Pulse Width	t <sub>clr</sub>	50	ns min

# THREE-WIRE INTERFACE FAST EDGES ON DIGITAL INPUT

With a fast rising edge (<10 ns) on one of the serial inputs (CLOCK, DATA IN, LATCH) while another input is logic high, the part may be triggered into a test mode and the contents of the data register may become corrupted, which may result in the output being loaded with an incorrect value. If fast edges are expected on the digital input lines, it is recommended that the latch line remain at Logic 0 during serial loading of the DAC. Similarly, the clock line should remain low during updates of the DAC via the latch pin. Alternatively, the addition of small value capacitors on the digital lines will slow down the edge.



T 11 C	<b>m</b> •••	· · · · ·	c .	1	T / C
l able 6.	Iming	Specifications	for As	ynchronous	Interface

Parameter	Label	Limit	Units
Asynchronous Clock Period	t <sub>ACK</sub>	400	ns min
Asynchronous Clock Low Time	t <sub>ACL</sub>	50	ns min
Asynchronous Clock High Time	<b>t</b> ACH	150	ns min
Data Stable Width (Critical Clock Edge)	tadw	300	ns min
Data Setup Time (Critical Clock Edge)	t <sub>ADS</sub>	60	ns min
Data Hold Time (Critical Clock Edge)	<b>t</b> <sub>ADH</sub>	20	ns min
Clear Pulse Width	$t_{CLR}$	50	ns min

### ASYNCHRONOUS INTERFACE

Note that in the timing diagram for asynchronous mode operation each data word is framed by a START (0) bit and a STOP (1) bit. The data timing is with respect to the rising edge of the CLOCK at the center of each bit cell. Bit cells are 16 clocks long, and the first cell (the START bit) begins at the first clock following the leading (falling) edge of the START bit. Thus, the MSB (D15) is sampled 24 clock cycles after the beginning of the START bit, D14 is sampled at clock number 40, and so on. During any dead time before writing the next word the DATA IN pin must remain at Logic 1.

The DAC output updates when the STOP bit is received. In the case of a framing error (the STOP bit sampled as a 0) the AD420 will output a pulse at the DATA OUT pin one clock period wide during the clock period subsequent to sampling the STOP bit. The DAC output will not update if a framing error is detected.

# TERMINOLOGY

#### Resolution

For 16-bit resolution, 1 LSB = 0.0015% of the FSR. In the 4 mA-20 mA range 1 LSB = 244 nA.

#### **Integral Nonlinearity**

Analog Devices defines integral nonlinearity as the maximum deviation of the actual, adjusted DAC output from the ideal analog output (a straight line drawn from 0 to FS - 1 LSB) for any bit combination. This is also referred to as relative accuracy.

#### **Differential Nonlinearity**

Differential nonlinearity is the measure of the change in the analog output, normalized to full scale, associated with an LSB change in the digital input code. Monotonic behavior requires that the differential linearity error be greater than -1 LSB over the temperature range of interest.

#### Monotonicity

A DAC is monotonic if the output either increases or remains constant for increasing digital inputs with the result that the output will always be a single-valued function of the input.

#### Gain Error

Gain error is a measure of the output error between an ideal DAC and the actual device output with all 1s loaded after offset error has been adjusted out.

#### Offset Error

Offset error is the deviation of the output current from its ideal value expressed as a percentage of the fullscale output with all 0s loaded in the DAC.

### Drift

Drift is the change in a parameter (such as gain and offset) over a specified temperature range. The drift temperature coefficient, specified in ppm/°C, is calculated by measuring the parameter at  $T_{MIN}$ , 25°C, and  $T_{MAX}$  and dividing the change in the parameter by the corresponding temperature change.

#### **Current Loop Voltage Compliance**

The voltage compliance is the maximum voltage at the  $I_{\rm OUT}\,pin$  for which the output current will be equal to the programmed value.

# **THEORY OF OPERATION**

The AD420 uses a sigma-delta  $(\Sigma - \Delta)$  architecture to carry out the digital-to-analog conversion. This architecture is particularly well suited for the relatively low bandwidth requirements of the industrial control environment because of its inherent monotonicity at high resolution.

In the AD420 a second order modulator is used to keep complexity and die size to a minimum. The single bit stream from the modulator controls a switched current source that is then filtered by two, continuous time resistor-capacitor sections. The capacitors are the only external components that have to be added for standard current-out operation. The filtered current is amplified and mirrored to the supply rail so that the application simply sees a 4 mA-20 mA, 0 mA-20 mA, or 0 mA-24 mA current source output with respect to ground. The AD420 is manufactured on a BiCMOS process that is well suited to implementing low voltage digital logic with high performance and high voltage analog circuitry.

The AD420 can also provide a voltage output instead of a current loop output if desired. The addition of a single external amplifier allows the user to obtain 0 V–5 V, 0 V–10 V,  $\pm$ 5 V, or  $\pm$ 10 V.

The AD420 has a loop fault detection circuit that warns if the voltage at  $I_{OUT}$  attempts to rise above the compliance range, due to an open-loop circuit or insufficient power supply voltage. The FAULT DETECT is an active low open drain signal so that one can connect several AD420s together to one pull-up resistor for global error detection. The pull-up resistor can be tied to the  $V_{LL}$  pin, or an external +5 V logic supply.

The I<sub>OUT</sub> current is controlled by a PMOS transistor and an internal amplifier as shown in the functional block diagram. The internal circuitry that develops the fault output avoids using a comparator with window limits since this would require an actual output error before the FAULT DETECT output becomes active. Instead, the signal is generated when the internal amplifier in the output stage of the AD420 has less than

approximately one volt remaining of drive capability (when the gate of the output PMOS transistor nearly reaches ground). Thus the FAULT DETECT output activates slightly before the compliance limit is reached. Since the comparison is made within the feedback loop of the output amplifier, the output accuracy is maintained by its open-loop gain, and no output error occurs before the fault detect output becomes active.

The 3-wire digital interface, comprising DATA IN, CLOCK, and LATCH, interfaces to all commonly used serial microprocessors without the addition of any external glue logic. Data is loaded into an input register under control of CLOCK and is loaded to the DAC when LATCH is strobed. If a user wants to minimize the number of galvanic isolators in an intrinsically safe application, the AD420 can be configured to run in asynchronous mode. This mode is selected by connecting the LATCH pin to  $V_{CC}$  through a current limiting resistor. The data must then be combined with a start and stop bit to frame the information and trigger the internal LATCH signal.



Figure 5. Functional Block Diagram

## APPLICATIONS INFORMATION CURRENT OUTPUT

The AD420 can provide 4 mA–20 mA, 0 mA–20 mA, or 0 mA–24 mA output without any active external components. Filter capacitors C1 and C2 can be any type of low cost ceramic capacitors. To meet the specified full-scale settling time of 3 ms, low dielectric absorption capacitors (NPO) are required. Suitable values are C1 = 0.01  $\mu$ F and C2 = 0.01  $\mu$ F.



#### Figure 6. Standard Configuration

### **DRIVING INDUCTIVE LOADS**

When driving inductive or poorly defined loads , connect a 0.01  $\mu$ F capacitor between I<sub>OUT</sub> (Pin 18) and GND (Pin 11). This ensures stability of the AD420 with loads beyond 50 mH. There is no maximum capacitance limit. The capacitive component of the load may cause slower settling, though this may be masked by the settling time of the AD420. A programmed change in the current may cause a back EMF voltage on the output that may exceed the compliance of the AD420. To prevent this voltage from exceeding the supply rails connect protective diodes between I<sub>OUT</sub> and each of V<sub>CC</sub> and GND.

## **VOLTAGE-MODE OUTPUT**

Since the AD420 is a single supply device, it is necessary to add an external buffer amplifier to the  $V_{OUT}$  pin to obtain a selection of bipolar output voltage ranges as shown in Figure 7.



Table 7. Buffer	Amplifier	Configuration
-----------------	-----------	---------------

R1	R2	R3	Vout
Open	Open	0	0 V – 5 V
Open	R	R	
R	Open	R	±5 V
R	2R	2R	±10 V

Suitable  $R = 5 k\Omega$ .

### **OPTIONAL SPAN AND ZERO TRIM**

For users who would like lower than the specified values of offset and gain error, Figure 8 shows a simple way to trim these parameters. Care should be taken to select low drift resistors because they affect the temperature drift performance of the DAC.

The adjustment algorithm is iterative. The procedure for trimming the AD420 in the 4 mA–20 mA mode can be accomplished as follows:

- 1. Offset adjust. Load all zeros. Adjust RZERO for 4.00000 mA of output current.
- Gain adjust. Load all ones. Adjust RSPAN for 19.99976 mA (FS – 1 LSB) of output current.

Return to Step I and iterate until convergence is obtained.



Figure 8. Offset and Gain Adjust

Variation of RZERO between REF OUT (5 V) and GND leads to an offset adjust range from -1.5 mA to 6 mA, (1.5 mA/V centered at 1 V).

The 5 k $\Omega$  RSPAN2 resistor is connected in parallel with the internal 40 W sense resistor, which leads to a gain increase of +0.8%.

As RSPAN is changed to 500  $\Omega$ , the voltage on REF IN is attenuated by the combination of RSPAN and the 30 k $\Omega$  REF IN input resistance. When added together with RSPAN2 this results in an adjustment range of -0.8% to +0.8%.

### THREE-WIRE INTERFACE

Figure 9 shows the AD420 connected in the 3-wire interface mode. The AD420 data input block contains a serial input shift register and a parallel latch. The contents of the shift register are controlled by the DATA IN signal and the rising edges of the CLOCK. Upon request of the LATCH pin the DAC and internal latch are updated from the shift register parallel outputs. The CLOCK should remain inactive while the DAC is updated. Refer to the timing requirements for 3-wire interface.



Figure 9. Three-Wire Interface Using Multiple DACs with Joint Fault Detect

## USING MULTIPLE DACS WITH FAULT DETECT

The 3-wire interface mode can utilize the serial DATA OUT for easy interface to multiple DACs. To program the two AD420s in Figure 9, 32 data bits are required. The first 16 bits are clocked into the input shift register of DAC1. The next 16 bits transmitted pass the first 16 bits from the DATA OUT pin of DAC1 to the input register of DAC2. The input shift registers of the two DACs operate as a single 32-bit shift register, with the leading 16 bits representing information for DAC2 and the trailing 16 bits serving for DAC1. Each DAC is then updated upon request of the LATCH pin. The daisy-chain can be extended to as many DACs as required.

### ASYNCHRONOUS INTERFACE USING OPTOCOUPLERS

The AD420 connected in asynchronous interface mode with optocouplers is shown in Figure 10. Asynchronous operation minimizes the number of control signals required for isolation of the digital system from the control loop. The resistor connected between the LATCH pin and  $V_{CC}$  is required to activate this mode. For operation with  $V_{CC}$  below 18 V use a 50 k $\Omega$  pull-up resistor; from 18 V to 32 V, use 100 k $\Omega$ .

Asynchronous mode requires that the clock run at 16 times the data bit rate, therefore, to operate at the maximum input data rate of 150 kBPS, an input clock of 2.4 MHz is required. The actual data rate achieved may be limited by the type of optocouplers chosen. The number of control signals can be further reduced by creating the appropriate clock signal on the current loop side of the isolation barrier. If optocouplers with relatively slow rise and fall times are used, Schmitt triggers may be required on the digital inputs to prevent erroneous data being presented to the DAC.



Figure 10. Asynchronous Interface Using Optocouplers

# MICROPROCESSOR INTERFACE AD420-TO-MC68HC11 (SPI BUS) INTERFACE

The AD420 interface to the Motorola serial peripheral interface (SPI) is shown in Figure 11. The MOSI, SCK, and  $\overline{SS}$  pins of the HC11 are respectively connected to the DATA IN, CLOCK, and LATCH pins of the AD420. The majority of the interfacing issues are done in the software initialization. A typical routine, such as the one shown below, begins by initializing the state of the various SPI data and control registers.

INIT	LDAA	#\$2F	; <del>SS</del> = 1;  SCK = 0; MOSI = 1	
	STAA	PORTD	;SEND TO SPI OUTPUTS	
	LDAA	#\$38	; <del>ss</del> , sck, mosi = Outputs	
	STAA	DDRD	;SEND DATA DIRECTION INFO	
	LDAA	#\$50	;DABL INTRPTS, SPI IS MASTER & ON	
	STAA	SPCR	;CPOL = 0, CPHA = 0, 1MHZ BAUDRATE	
NEXTPT	LDAA	MSBY	;LOAD ACCUM W/UPPER 8 BITS	
	BSR	SENDAT	;JUMP TO DAC OUTPUT ROUTINE	
	JMP	NEXTPT	;INFINITE LOOP	
SENDAT	LDY	#\$1000	; POINT AT ON-CHIP REGISTERS	
	BCLR	\$08,Y,\$20	; DRIVE $\overline{SS}$ (LATCH) LOW	
	STAA	SPDR	;SEND MS-BYTE TO SPI DATA REG	
WAIT1	LDAA	SPSR	;CHECK STATUS OF SPIE	
	BPL	WAIT1	;POLL FOR END OF X- MISSION	
	LDAA	LSBY	;GET LOW 8 BITS FROM MEMORY	
	STAA	SPDR	;SEND LS-BYTE TO SPI DATA REG	
WAIT2	LDAA	SPSR	;CHECK STATUS OF SPIE	
	BPL	WAIT2;	;POLL FOR END OF X- MISSION	
	BSET	\$08,Y,\$20	;DRIVE SS HIGH TO LATCH DATA	
	RTS			

The SPI data port is configured to process data in 8-bit bytes. The most significant data byte (MSBY) is retrieved from memory and processed by the SENDAT routine. The  $\overline{SS}$  pin is driven low by indexing into the PORTD data register and clear Bit 5. The MSBY is then sent to the SPI data register where it is automatically transferred to the AD420 internal shift resister. The HC11 generates the requisite eight clock pulses with data valid on the rising edges. After the MSBY is transmitted, the least significant byte (LSBY) is loaded from memory and transmitted in a similar fashion. To complete the transfer, the LATCH pin is driven high when loading the complete 16-bit word into the AD420.



**AD420 TO MICROWIRE INTERFACE** 

The flexible serial interface of the AD420 is also compatible with the National Semiconductor MICROWIRE interface. The MICROWIRE interface is used in microcontrollers such as the COP400 and COP800 series of processors. A generic interface to use the MICROWIRE interface is shown in Figure 12. The G1, SK, and SO pins of the MICROWIRE interface are respectively connected to the LATCH, CLOCK, and DATA IN pins of the AD420.



### **EXTERNAL BOOST FUNCTION**

The external boost transistor reduces the power dissipated in the AD420 by reducing the current flowing in the on-chip output transistor (dividing it by the current gain of the external circuit). A discrete NPN transistor with a breakdown voltage,  $BV_{CEO}$ , greater than 32 V can be used as shown in Figure 13.



Figure 13. External Boost Configuration

The external boost capability has been developed for those users who may wish to use the AD420, in the SOIC package, at the extremes of the supply voltage, load current, and temperature range. The PDIP package (because of its lower thermal resistance) will operate safely over the entire specified voltage, temperature, and load current ranges without the boost transistor. The plot in Figure 14 shows the safe operating region for both package types. The boost transistor can also be used to reduce the amount of temperature induced drift in the part. This will minimize the temperature induced drift of the on-chip voltage reference, which improves drift and linearity.



# AD420 PROTECTION TRANSIENT VOLTAGE PROTECTION

The AD420 contains ESD protection diodes, which prevent damage from normal handling. The industrial control environment can, however, subject I/O circuits to much higher transients. To protect the AD420 from excessively high voltage transients, such as those specified in IEC 801, external power diodes and a surge current limiting resistor may be required, as shown in Figure 15. The constraint on the resistor is that during normal operation the output voltage level at I<sub>OUT</sub> must remain within its voltage compliance limit

 $(I_{OUT} \times (Rp + R_{LOAD}) \le V_{CC} - 2.75 V)$ 

and the two protection diodes and resistor must have appropriate power ratings.



Figure 15. Output Transient Voltage Protection

### **BOARD LAYOUT AND GROUNDING**

The AD420 ground pin, designated GND, is the high quality ground reference point for the device. Any external loads on the REF OUT and  $V_{OUT}$  pins of the AD420 should be returned to this reference point. Analog and digital ground currents should not share a common path. Each signal should have an appropriate analog or digital signal return routed close to it. Using this approach, signal loops enclose a small area, minimizing the inductive coupling of noise. Wide PC tracks, large gauge wire, and ground planes are highly recommended to provide low impedance signal paths.

### POWER SUPPLIES AND DECOUPLING

The AD420 supply pins,  $V_{CC}$  (Pin 23) and  $V_{LL}$  (Pin 2), should be decoupled to GND with 0.1  $\mu$ F capacitors to eliminate high frequency noise that may otherwise get coupled into the analog system. High frequency ceramic capacitors are recommended. The decoupling capacitors should be located in close proximity to the pins and the ground line to have maximum effect. Further reductions in noise, and improvements in performance, may be achieved by using a larger value capacitor on the  $V_{LL}$  pin.



Figure 17. 24-Lead Standard Small Outline [SOIC\_W] Wide Body (RW-24) Dimensions shown in millimeters and (inches)

#### **ORDERING GUIDE**

Model <sup>1</sup>	Temperature Range	Max Operating Voltage	Package Description	Package Option
AD420AN-32	–40°C to +85° C	32 V	24-Lead PDIP	N-24-1
AD420ANZ-32	–40°C to +85° C	32 V	24-Lead PDIP	N-24-1
AD420AR-32	–40°C to +85° C	32 V	24-Lead SOIC_W	RW-24
AD420AR-32-REEL	–40°C to +85° C	32 V	24-Lead SOIC_W	RW-24
AD420ARZ-32	–40°C to +85° C	32 V	24-Lead SOIC_W	RW-24
AD420ARZ-32-REEL	–40°C to +85° C	32 V	24-Lead SOIC_W	RW-24

<sup>1</sup> Z = RoHS Compliant Part.

# NOTES



www.analog.com

Rev. H | Page 16 of 16



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный) **Факс:** 8 (812) 320-02-42 **Электронная почта:** <u>org@eplast1.ru</u> **Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.