PLL102-05

Low Skew Output Buffer


FEATURES

- Frequency range 25 ~ 60MHz.
- Internal phase locked loop will allow spread spectrum modulation on reference clock to pass to the outputs (up to 100kHz SST modulation).
- Zero input - output delay.
- Less than 700 ps device - device skew.
- Less than 250 ps skew between outputs.
- Less than 150 ps cycle - cycle jitter.
- Output Enable function tri-state outputs.
- 3.3V operation.
- Available in 8-Pin 150mil SOIC.

DESCRIPTION

The PLL102-05 is a high performance, low skew, low jitter zero delay buffer designed to distribute high speed clocks and is available in 8-pin SOIC package. It has four outputs that are synchronized with the input. The synchronization is established via CLKOUT feed back to the input of the PLL. Since the skew between the input and output is less than ±350 ps, the device acts as a zero delay buffer.


PIN CONFIGURATION



Remark

If REF clock is stopped for more than 10us after it has already been provided to the chip, and after power-up, the output clocks will disappear. In that instance, a full power-up reset is required in order to reactivate the output clocks.

BLOCK DIAGRAM



PIN DESCRIPTIONS

Name	Number	Type	Description
REF[1]	1	I	Input reference frequency. Spread spectrum modulation on this signal will be passed to the output (up to 100kHz SST modulation).
CLK2[2]	2	O	Buffered clock output.
CLK1[2]	3	O	Buffered clock output.
GND	4	P	Ground.
CLK3[2]	5	O	Buffered clock output.
VDD	6	P	3.3V Power Supply.
CLK4[2]	7	O	Buffered clock output.
CLKOUT[2]	8	O	Buffered clock output. Internal feed back on this pin.

Notes: 1: Weak pull-down. 2: Weak pull-down on all outputs.

ELECTRICAL SPECIFICATIONS

1. Absolute Maximum Ratings

PARAMETERS	SYMBOL	MIN.	MAX.	UNITS
Supply Voltage	V_{DD}		4.6	V
Input Voltage, dc	V_I	-0.5	V_{DD}+0.5	V
Output Voltage, dc	V_O	-0.5	V_{DD}+0.5	V
Storage Temperature	T_S	-65	150	°C
Ambient Operating Temperature*	T_A	-40	85	°C
Junction Temperature	T_J		125	°C
Lead Temperature (soldering, 10s)			260	°C
ESD Protection, Human Body Model			2	kV

Exposure of the device under conditions beyond the limits specified by Maximum Ratings for extended periods may cause permanent damage to the device and affect product reliability. These conditions represent a stress rating only, and functional operations of the device at these or any other conditions above the operational limits noted in this specification is not implied.

* **Note**: Operating Temperature is guaranteed by design for all parts (COMMERCIAL and INDUSTRIAL), but tested for COMMERCIAL grade only.

2. Electrical Characteristics


PARAMETERS	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Supply Voltage	V_{DD}		2.97		3.63	V
Input Low Voltage	V_{IL}				0.8	V
Input High Voltage	V_{IH}		2.0			V
Input Low Current	I_{IL}	V_{IN} = 0V		19	50.0	µA
Input High Current	I_{IH}	V_{IN} = V_{DD}		0.10	100.0	µA
Output Low Voltage	V_{OL}	I_{OL} = 50mA		0.25	0.4	V
Output High Voltage	V_{OH}	I_{OH} = 50mA	2.4	2.9		V
Power Down Supply Current	I_{DD}	REF = 0MHz		0.3	50.0	µA
Supply Current	I_{DD}	Unloaded outputs at 133MHz, SEL inputs at V_{DD} or GND		35	45	mA

3. Switching Characteristics


PARAMETERS	SYMBOL	DESCRIPTION	MIN.	TYP.	MAX.	UNITS
Output Frequency	t1		25		60	MHz
Duty Cycle (t2 ÷ t1)	Dt1	Measured at 1.4V, C_L=30pF, F_{out} = 60MHz	40.0	50.0	60.0	%
Duty Cycle (t2 ÷ t1)	Dt2	Measured at 1.4V	45.0	50.0	55.0	%
Rise Time	T_r	Measured between 0.8V and 2.0V, C_L=30pF		1.2	1.5	ns
Fall Time	T_f	Measured between 2.0V and 0.8V, C_L=30pF		1.2	1.5	ns
Output to Output Skew	T_{skew}	All outputs equally loaded, C_L=20pF			250	ps
Delay, REF Rising Edge to CLKOUT Rising Edge	T_{delay}	Measured at 1.4V		0	±350	ps
Device to Device Skew	$T_{dsk-dsk}$	Measured at V_{DD}/2 on the CLKOUT pins of devices		0	700	ps
Cycle to Cycle Jitter	$T_{cyc-cyc}$	Loaded outputs			150	ps
PLL Lock Time	T_{lock}	Stable power supply, valid clock presented on REF pin			1.0	ms
Jitter; Absolute Jitter	T_{jabs}	At 10,000 cycles, C_L=30pF		70	100	ps
Jitter; 1-sima	T_{j1-s}	At 10,000 cycles, C_L=30pF		10	20	ps

SWITCHING WAVEFORMS

Duty Cycle Timing




Output - Output Skew




SWITCHING WAVE FORMS


All Outputs Rise/Fall Time



Input to Output Propagation Delay



Device to Device Skew




Output-Output Skew

The skew between CLKOUT and the CLK(1-4) outputs is not dynamically adjusted by the PLL. Since CLKOUT is one of the inputs to the PLL, zero phase difference is maintained from REF to CLKOUT. If all outputs are equally loaded, zero phase difference will maintained from REF to all outputs.


If applications requiring zero output-output skew, all the outputs must equally loaded.

If the CLK(1-4) outputs are less loaded than CLKOUT, CLK(1-4) outputs will lead it; if the CLK(0-4) is more loaded than CLKOUT, CLK(1-4) will lag the CLKOUT.


Since the CLKOUT and the CLK(1-4) outputs are identical, they all start at the same time, but difference loads cause them to have different rise times and different times crossing the measurement thresholds.



REF input and all outputs loaded equally



REF input and CLK(1-4) outputs loaded equally, with CLK(1-4) less loaded than CLKOUT.




REF input and CLK(1-4) outputs loaded equally, with CLK(1-4) more loaded than CLKOUT.

PACKAGE INFORMATION

8 PIN Narrow SOIC (mm)

	SOIC	
Symbol	Min.	Max.
A	1.55	1.73
A1	0.15	0.18
B	0.35	0.49
C	0.19	0.25
D	4.80	4.98
E	3.81	3.99
H	5.84	6.20
L	0.41	0.89
e	1.27 BSC	



ORDERING INFORMATION

For part ordering, please contact our Sales Department:
47745 Fremont Blvd., Fremont, CA 94538, USA
Tel: (510) 492-0990 Fax: (510) 492-0991

PART NUMBER

The order number for this device is a combination of the following:
Device number, Package type and Operating temperature range

PLL102-05 X X X X

PART NUMBER

NONE= TUBE
R=TAPE AND REEL

NONE=NORMAL PACKAGE
L=GREEN PACKAGE

PACKAGE TYPE
S=SOIC

TEMPERATURE
C=COMMERCIAL,
I=INDUSTRIAL

Part / Order Number	Marking	Package Option	Temperature
PLL102-05SC-R	P102-05SC	SOIC - Tape and Reel	0 to +70° C
PLL102-05SC	P102-05SC	SOIC – Tube	0 to +70° C
PLL102-05SCL-R	P102-05SCL	SOIC - Tape and Reel	0 to +70° C
PLL102-05SCL	P102-05SCL	SOIC – Tube	0 to +70° C

PhaseLink Corporation, reserves the right to make changes in its products or specifications, or both at any time without notice. The information furnished by Phaselink is believed to be accurate and reliable. However, PhaseLink makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of whatever nature resulting from the use of, or reliance upon this product.

LIFE SUPPORT POLICY: PhaseLink's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President of PhaseLink Corporation.


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.