
HIGH-STABILITY HIGH-FREQUENCY OSCILLATOR

HG-1000/2000 series

- Cylindrical AT crystal unit built-in, thus assuring high reliability.
- Excellent shock resistance and heat resistance.
- Low current consumption.




Specifications (characteristics)

Item		Symbol	HG-1012JA	HG-2012JA	Remarks
			Specifications		
Output frequency range		f_0	1.5000 MHz to 28.63636 MHz		V_{DD} =4.75V to 5.25V
Power source voltage	Max. supply voltage	V_{DD}-GND	-0.5V to +7.0V		
	Operating voltage	V_{DD}	5.0V ±0.25V		
Temperature range	Storage temperature	T_{STG}	-55˚C to +125˚C		
	Operable temperature	T_{OPR}	-40˚C to + 85˚C		
Soldering condition		T_{SOL}	Under 260˚C within 10 sec. x 2 times		
Frequency stability		$\Delta f/f_0$	AV: ±20ppm, BV: ±25ppm	SV: ±15ppm, AV: ±20ppm	Ta= -20˚C to +70˚C
			BX: ±25ppm, CX: ±30ppm	BX: ±25ppm	Ta= -40˚C to +85˚C
Current consumption		Iop	10mA max.		No load condition
Duty		tw/t	40% to 60%		1/2 V_{DD} level
High output voltage		V_{OH}	V_{DD} -0.4V min.		I_{OH}= -0.8mA
Low output voltage		V_{OL}	0.4V max.		I_{OL}=3.2mA
Output load condition		C_L	15pF max.		
Output rise time		t_{TLH}	8ns max.		20%→80% V_{DD} level
Output fall time		t_{THL}			80%→20% V_{DD} level
Oscillation start up time		t_{OSC}	4ms max.		Time at 4.75V to be 0 sec.
Aging		fa	±5ppm/year max.	±2ppm/year max.	Ta=25˚C
Shock resistance		S.R.	±10ppm max.	±2ppm max.	Three drops on a hard wooden board from 75 cm or excitation test with 3000G x 0.3ms x 1/2sine wave in 3 directions

External dimensions

(Unit: mm)




NO.	Pin terminal
1	Ts
2	GND
3	OUT
4	V_{DD}

Do not connect Ts-pin external device.

Recommended soldering pattern

(Unit: mm)



THE CRYSTALMASTER


ENERGY SAVING EPSON

EPSON offers effective savings to its customers through a wide range of electronic devices, such as semiconductors, liquid crystal display (LCD) modules, and crystal devices. These savings are achieved through a sophisticated melding of three different efficiency technologies.

Power saving technology provides low power consumption at low voltages.

Space saving technology provides further reductions in product size and weight through super-precise processing and high-density assembly technology.

Time saving technology shortens the time required for design and development on the customer side and shortens delivery times.



Our concept of Energy Saving technology conserves resources by blending the essence of these three efficiency technologies. The essence of these technologies is represented in each of the products that we provide to our customers.

In the industrial sector, leading priorities include measures to counter the greenhouse effect by reducing CO2, measures to preserve the global environment, and the development of energy-efficient products. Environmental problems are of global concern, and although the contribution of energy-saving technology developed by EPSON may appear insignificant, we seek to contribute to the development of energy-saving products by our customers through the utilization of our electronic devices. EPSON is committed to the conservation of energy, both for the sake of people and of the planet on which we live.

SEIKO EPSON CORP. QUARTZ DEVICE DIVISION acquired ISO9001 and ISO14001 certification by B.V.Q.I. (Bureau Veritas Quality International) .

ISO9001 in October, 1992.

ISO14001 in November,1997.

NOTICE

No part of this material may be reproduced or duplicated in any form or by any means without the written permission of Seiko Epson. Seiko Epson reserves the right to make changes to this material without notice. Seiko Epson does not assume any liability of any kind arising out of any inaccuracies contained in this material or due to its application or use in any product or circuit and, further, there is no representation that this material is applicable to products requiring high level reliability, such as, medical products. Moreover, no license to any intellectual property rights is granted by implication or otherwise, and there is no representation or warranty that anything made in accordance with this material will be free from any patent or copyright infringement of a third party. This material of portions there may contain technology or the subject relating to strategic products under the control of the Foreign Exchange and Foreign Trade Control Law of Japan and may require an export license from the Ministry of International Trade and Industry or other approval from another government agency.


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.