



STTH20002TV


TURBO 2 ULTRAFAST HIGH VOLTAGE RECTIFIER

MAIN PRODUCT CHARACTERISTICS

$I_{F(AV)}$	Up to 2 x 120 A
V_{RRM}	200 V
T_j	150°C
V_F (typ)	0.75 V
t_{rr} (typ)	41 ns

FEATURES AND BENEFITS

- Suited for SMPS
- Very Low Forward Losses
- Low recovery time
- High surge current capability
- Insulated:
Insulating voltage=2500V_{RMS}
Capacitance = 55pF



DESCRIPTION

Dual rectifier suited for welding equipment, high power industrial application.
Packaged in Isotop, this device is intended for use in the secondary rectification of the applications.

ABSOLUTE RATINGS (limiting values, per diode)

Symbol	Parameter	Value	Unit	
V_{RRM}	Repetitive peak reverse voltage	200	V	
$I_{F(RMS)}$	RMS forward voltage	170	A	
$I_{F(AV)}$	Average forward current $\delta = 0.5$	$T_c = 95^\circ\text{C}$ Per diode	100	A
		$T_c = 80^\circ\text{C}$ Per diode	120	
I_{FSM}	Surge non repetitive forward current	$t_p = 10\text{ms}$ sinusoidal	1000	A
T_{stg}	Storage temperature range	-55 to + 150	°C	
T_j	Maximum operating junction temperature	150	°C	

Order Codes

Part Number	Marking
STTH20002TV1	STTH20002TV1

THERMAL RESISTANCE

Symbol	Parameter	Maximum	Unit
$R_{th(j-c)}$	Junction to case	Per diode	0.52
		Total	0.31
$R_{th(c)}$	Coupling	0.1	$^{\circ}\text{C}/\text{W}$

When the diodes 1 and 2 are used simultaneously:

$$\Delta T_j(\text{diode } 1) = P(\text{diode } 1) \times R_{th(j-c)}(\text{Per diode}) + P(\text{diode } 2) \times R_{th(c)}$$

STATIC ELECTRICAL CHARACTERISTICS (per diode)

Symbol	Parameter	Test conditions	Min.	Typ	Max.	Unit
I_R^*	Reverse leakage current	$T_j = 25^{\circ}\text{C}$	$V_R = V_{RRM}$		100	μA
		$T_j = 125^{\circ}\text{C}$		80	800	
V_F^{**}	Forward voltage drop	$T_j = 25^{\circ}\text{C}$	$I_F = 100\text{A}$		1.05	V
			$I_F = 200\text{A}$		1.20	
		$T_j = 150^{\circ}\text{C}$	$I_F = 100\text{A}$	0.75	0.85	
			$I_F = 200\text{A}$		1.05	

Pulse test: * $t_p = 5 \text{ ms}$, $\delta < 2\%$

** $t_p = 380 \mu\text{s}$, $\delta < 2\%$

To evaluate the conduction losses use the following equation: $P = 0.65 \times I_{F(AV)} + 0.002 I_F^2(\text{RMS})$

DYNAMIC CHARACTERISTICS (per diode)

Symbol	Parameter	Test conditions	Min.	Typ	Max.	Unit
t_{rr}	Reverse recovery time	$T_j = 25^{\circ}\text{C}$ $I_F = 1\text{A}$ $di_F/dt = 200 \text{ A}/\mu\text{s}$ $V_R = 30\text{V}$		41	50	ns
I_{RM}	Reverse recovery current	$T_j = 125^{\circ}\text{C}$ $I_F = 100\text{A}$ $V_R = 160\text{V}$ $di_F/dt = 200 \text{ A}/\mu\text{s}$		11.5	15	A
t_{fr}	Forward recovery time	$T_j = 25^{\circ}\text{C}$ $I_F = 100\text{A}$ $di_F/dt = 200 \text{ A}/\mu\text{s}$ $V_{FR} = 1.1 \times V_{Fmax}$			800	ns
V_{FP}	Forward recovery voltage	$T_j = 25^{\circ}\text{C}$ $I_F = 100\text{A}$ $di_F/dt = 200 \text{ A}/\mu\text{s}$		2.5		V

Fig. 1: Peak current versus duty cycle (per diode).




Fig. 2-2: Forward voltage drop versus forward current (maximum values, per diode).




Fig. 4: Junction capacitance versus reverse voltage applied (typical values, per diode).




Fig. 2-1: Forward voltage drop versus forward current (typical values, per diode).




Fig. 3: Relative variation of thermal impedance junction to case versus pulse duration.




Fig. 5: Reverse recovery charges versus di/dt (typical values, per diode).




Fig. 6: Reverse recovery time versus di_F/dt (typical values, per diode).




Fig. 7: Peak reverse recovery current versus di_F/dt (typical values, per diode).





Fig. 8: Dynamic parameters versus junction temperature.



STTH20002TV

PACKAGE MECHANICAL DATA ISOTOP

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	11.80	12.20	0.465	0.480
A1	8.90	9.10	0.350	0.358
B	7.8	8.20	0.307	0.323
C	0.75	0.85	0.030	0.033
C2	1.95	2.05	0.077	0.081
D	37.80	38.20	1.488	1.504
D1	31.50	31.70	1.240	1.248
E	25.15	25.50	0.990	1.004
E1	23.85	24.15	0.939	0.951
E2	24.80 typ.		0.976 typ.	
G	14.90	15.10	0.587	0.594
G1	12.60	12.80	0.496	0.504
G2	3.50	4.30	0.138	0.169
F	4.10	4.30	0.161	0.169
F1	4.60	5.00	0.181	0.197
P	4.00	4.30	0.157	0.69
P1	4.00	4.40	0.157	0.173
S	30.10	30.30	1.185	1.193

ORDERING INFORMATION

Ordering type	Marking	Package	Weight	Base qty	Delivery mode
STTH20002TV1	STTH20002TV1	ISOTOP	27 g (without screws)	10 (with screws)	Tube

- Epoxy meets UL94, V0
- Cooling method: by conduction (C)

REVISION HISTORY

Table 1: Revision history

Date	Revision	Description of Changes
26-May-2004	1	First issue
13-Jul-2004	2	Figure 6 legend corrected: "Forward" changed to "Reverse"

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics.
All other names are the property of their respective owners

© 2004 STMicroelectronics - All rights reserved

STMicroelectronics GROUP OF COMPANIES

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States

www.st.com



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.