

40 Series

Ohmicone® Silicone-Ceramic Conformal Axial Terminal Wirewound 1% and 5% Tolerance Standard



Ohmite 40 Series resistors are the most economical conformal silicone-ceramic coated resistors offered. These all-welded units are characterized by their low temperature coefficients and resistance to thermal shock, making them ideal for a wide range of electrical and electronic applications.

Units with 1% and 5% tolerances are identical in construction and electrical specifications. Durable but economical 40 Series resistors exceed industry requirements for quality.

FEATURES

- Economical
- Applications include commercial, industrial and communications equipment
- Stability under high temperature conditions
- All-welded construction
- RoHS compliant; add "E" suffix to part number to specify.

SERIES SPECIFICATIONS

| Series | Wattage | Ohms | Voltage |
|--------|---------|-----------|---------|
| 41 | 1.0 | 0.10-6K | 150 |
| 42 | 2.0 | 0.10-8K | 100 |
| 43 | 3.0 | 0.10-20K | 200 |
| 45 | 5.0 | 0.10-70K | 460 |
| 47 | 7.0 | 0.10-80K | 670 |
| 40 | 10.0 | 0.10-150K | 1000 |

Non-Inductive versions available. Insert "N" before tolerance code.
Example: 42NJ27R

CHARACTERISTICS

| | |
|--------------------------------|---|
| Coating | Conformal silicone-ceramic. |
| Core | Ceramic. |
| Terminals | Solder-coated copper clad axial. RoHS solder composition is 96% Sn, 3.5% Ag, 0.5% Cu |
| Derating | Linearly from 100% @ +25°C to 0% @ +275°C. |
| Tolerance | ±5% (J type), ±1% (F type) (other tolerances available). |
| Power rating | Based on 25°C free air rating |
| Overload | Under 5 watts: 5 times rated wattage for 5 seconds. 5 watts and over: 10 times rated wattage for 5 seconds. |
| Temperature coefficient | Under 1Ω: ±90 ppm/°C; 1Ω to 9.99Ω: ±50 ppm/°C; 10Ω and over: ±20 ppm/°C |
| Operating temp. range | -55°C to 275°C |

DIMENSIONS

(in./mm max.)



| Series | Wattage | Length | Diam. | Lead ga. |
|--------|---------|--------------|--------------|----------|
| 41 | 1.0 | 0.437 / 11.1 | 0.125 / 3.2 | 24 |
| 42 | 2.0 | 0.406 / 10.3 | 0.219 / 5.6 | 20 |
| 43 | 3.0 | 0.593 / 15.1 | 0.219 / 5.6 | 20 |
| 45 | 5.0 | 0.937 / 23.8 | 0.343 / 8.7 | 18 |
| 47 | 7.0 | 1.280 / 32.5 | 0.343 / 8.7 | 18 |
| 40 | 10.0 | 1.900 / 48.3 | 0.406 / 10.3 | 18 |

(continued)

40 Series

Ohmicone® Silicone-Ceramic Conformal Axial Terminal Wirewound 1% and 5% Tolerance Standard

ORDERING INFORMATION

Standard part numbers

| Ohmic value | Wattage and Tolerance | | | | | | | | | | Ohmic value | Wattage and Tolerance | | | | | | | | | | Ohmic value | Wattage and Tolerance | | | | | | | | | | | |
|-------------|----------------------------------|---|---|---|----|--------------|---|---|---|----|-------------|-----------------------|---|---|---|----|--------------|---|---|---|----|-------------|-----------------------|---|---|---|----|--------------|-------------|---|---|----|---|---|
| | 1% Tolerance | | | | | 5% Tolerance | | | | | | 1% Tolerance | | | | | 5% Tolerance | | | | | | 1% Tolerance | | | | | 5% Tolerance | | | | | | |
| | Part No. Prefix ▶ Suffix ▼ | 1 | 3 | 5 | 10 | 1 | 2 | 3 | 5 | 10 | | 1 | 2 | 3 | 5 | 10 | 1 | 2 | 3 | 5 | 10 | | 1 | 2 | 3 | 5 | 10 | 1 | 2 | 3 | 5 | 10 | | |
| 0.1 —R10 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 68 —68R | ✓ | ✓ | ✓ | ✓ | ✓ | 2,200 —2K2 | ✓ | ✓ | ✓ | ✓ | ✓ | 2,500 —2K5 | ✓ | ✓ | ✓ | ✓ | ✓ | 2,700 —2K7 | ✓ | ✓ | ✓ | ✓ | ✓ |
| 0.15 —R15 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 75 —75R | ✓ | ✓ | ✓ | ✓ | ✓ | 3,000 —3K0 | ✓ | ✓ | ✓ | ✓ | ✓ | 3,300 —3K3 | ✓ | ✓ | ✓ | ✓ | ✓ | 3,500 —3K5 | ✓ | ✓ | ✓ | ✓ | ✓ |
| 0.2 —R20 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 82 —82R | ✓ | ✓ | ✓ | ✓ | ✓ | 3,900 —3K9 | ✓ | ✓ | ✓ | ✓ | ✓ | 4,000 —4K0 | ✓ | ✓ | ✓ | ✓ | ✓ | 4,500 —4K5 | ✓ | ✓ | ✓ | ✓ | ✓ |
| 0.25 —R25 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 100 —100 | ✓ | ✓ | ✓ | ✓ | ✓ | 4,700 —4K7 | ✓ | ✓ | ✓ | ✓ | ✓ | 5,000 —5K0 | ✓ | ✓ | ✓ | ✓ | ✓ | 6,000 —6K0 | ✓ | ✓ | ✓ | ✓ | ✓ |
| 0.3 —R30 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 120 —120 | ✓ | ✓ | ✓ | ✓ | ✓ | 6,800 —6K8 | ✓ | ✓ | ✓ | ✓ | ✓ | 7,000 —7K0 | ✓ | ✓ | ✓ | ✓ | ✓ | 7,500 —7K5 | ✓ | ✓ | ✓ | ✓ | ✓ |
| 0.33 —R33 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 125 —125 | ✓ | ✓ | ✓ | ✓ | ✓ | 8,000 —8K0 | ✓ | ✓ | ✓ | ✓ | ✓ | 9,000 —9K0 | ✓ | ✓ | ✓ | ✓ | ✓ | 10,000 —10K | ✓ | ✓ | ✓ | ✓ | ✓ |
| 0.4 —R40 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 150 —150 | ✓ | ✓ | ✓ | ✓ | ✓ | 10,000 —10K | ✓ | ✓ | ✓ | ✓ | ✓ | 12,000 —12K | ✓ | ✓ | ✓ | ✓ | ✓ | 13,000 —13K | ✓ | ✓ | ✓ | ✓ | ✓ |
| 0.5 —R50 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 180 —180 | ✓ | ✓ | ✓ | ✓ | ✓ | 15,000 —15K | ✓ | ✓ | ✓ | ✓ | ✓ | 17,000 —17K | ✓ | ✓ | ✓ | ✓ | ✓ | 20,000 —20K | ✓ | ✓ | ✓ | ✓ | ✓ |
| 0.75 —R75 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 200 —200 | ✓ | ✓ | ✓ | ✓ | ✓ | 20,000 —20K | ✓ | ✓ | ✓ | ✓ | ✓ | 22,000 —22K | ✓ | ✓ | ✓ | ✓ | ✓ | 25,000 —25K | ✓ | ✓ | ✓ | ✓ | ✓ |
| 1 —R100 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 220 —220 | ✓ | ✓ | ✓ | ✓ | ✓ | 30,000 —30K | ✓ | ✓ | ✓ | ✓ | ✓ | 33,000 —33K | ✓ | ✓ | ✓ | ✓ | ✓ | 35,000 —35K | ✓ | ✓ | ✓ | ✓ | ✓ |
| 1.5 —R150 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 225 —225 | ✓ | ✓ | ✓ | ✓ | ✓ | 40,000 —40K | ✓ | ✓ | ✓ | ✓ | ✓ | 50,000 —50K | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | |
| 2 —R200 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 250 —250 | ✓ | ✓ | ✓ | ✓ | ✓ | 450 —450 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | |
| 2.2 —R220 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 270 —270 | ✓ | ✓ | ✓ | ✓ | ✓ | 470 —470 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | |
| 3 —R300 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 300 —300 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 4 —R400 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 330 —330 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 5 —R500 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 350 —350 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 7.5 —R750 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 390 —390 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 10 —R1000 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 400 —400 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 12 —R1200 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 450 —450 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 15 —R1500 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 470 —470 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 18 —R1800 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 500 —500 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 20 —R2000 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 560 —560 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 22 —R2200 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 600 —600 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 25 —R2500 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 680 —680 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 27 —R2700 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 750 —750 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 30 —R3000 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 800 —800 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 33 —R3300 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 820 —820 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 35 —R3500 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 900 —900 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 39 —R3900 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 1,000 —1K0 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 40 —R4000 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 1,100 —1K1 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 47 —R4700 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 1,200 —1K2 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 50 —R5000 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 1,500 —1K5 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 56 —R5600 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 1,800 —1K8 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |
| 62 —R6200 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 2,000 —2K0 | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | | | | | | | | | | | | |

Shaded values involve very fine resistance wire and should not be used in critical applications without burn-in and/or thermal cycling.

✓ = Standard values
 ✦ = Non-standard values subject to minimum handling charge per item





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.