


## Glass Passivated Single-Phase Bridge Rectifier



Case Type GBL

### FEATURES

- UL recognition file number E54214
- Ideal for printed circuit boards
- High surge current capability
- Typical  $I_R$  less than 0.1  $\mu\text{A}$
- High case dielectric strength
- Solder dip 260 °C, 40 s
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC


**RoHS**  
COMPLIANT

### TYPICAL APPLICATIONS

General purpose use in ac-to-dc bridge full wave rectification for monitor, TV, printer, SMPS, adapter, audio equipment, and home appliances application.

### MECHANICAL DATA

**Case:** GBL

Epoxy meets UL 94V-0 flammability rating

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD22-B102

E3 suffix for consumer grade, meets JESD 201 class 1A whisker test

**Polarity:** As marked on body

| PRIMARY CHARACTERISTICS |                 |
|-------------------------|-----------------|
| $I_{F(AV)}$             | 4 A             |
| $V_{RRM}$               | 50 V to 1000 V  |
| $I_{FSM}$               | 150 A           |
| $I_R$                   | 5 $\mu\text{A}$ |
| $V_F$                   | 1.0 V           |
| $T_J \text{ max.}$      | 150 °C          |

| MAXIMUM RATINGS ( $T_A = 25$ °C unless otherwise noted)                            |                |  |       |       |       |       |       |                  |      |
|--|----------------|--|-------|-------|-------|-------|-------|------------------|------|
| PARAMETER  | SYMBOL         | GBL005                                   | GBL01 | GBL02 | GBL04 | GBL06 | GBL08 | GBL10            | UNIT |
| Maximum repetitive peak reverse voltage  | $V_{RRM}$      | 50                                       | 100   | 200   | 400   | 600   | 800   | 1000             | V    |
| Maximum RMS voltage  | $V_{RMS}$      | 35                                       | 70    | 140   | 280   | 420   | 560   | 700              | V    |
| Maximum DC blocking voltage  | $V_{DC}$       | 50                                       | 100   | 200   | 400   | 600   | 800   | 1000             | V    |
| Maximum average forward rectified output current at $T_C = 50$ °C<br>$T_A = 40$ °C | $I_{F(AV)}$    | 4.0 <sup>(1)</sup><br>3.0 <sup>(2)</sup> |       |       |       |       |       | A                |      |
| Peak forward surge current single sine-wave superimposed on rated load             | $I_{FSM}$      | 150                                      |       |       |       |       |       | A                |      |
| Rating for fusing ( $t < 8.3$ ms)  | $I^2t$         | 93                                       |       |       |       |       |       | A <sup>2</sup> s |      |
| Operating junction and storage temperature range                                   | $T_J, T_{STG}$ | - 55 to + 150                            |       |       |       |       |       | °C               |      |

#### Notes:

(1) Unit mounted on 3.0 x 3.0 x 0.11" thick (7.5 x 7.5 x 0.3 cm) aluminum plate

(2) Unit mounted on P.C.B. at 0.375" (9.5 mm) lead length and 0.5 x 0.5" (12 x 12 mm) copper pads

| ELECTRICAL CHARACTERISTICS ( $T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted) |   |        |        |       |       |       |       |       |       |               |
|---|---|--------|--------|-------|-------|-------|-------|-------|-------|---------------|
| PARAMETER   | TEST CONDITIONS   | SYMBOL | GBL005 | GBL01 | GBL02 | GBL04 | GBL06 | GBL08 | GBL10 | UNIT          |
| Maximum instantaneous forward voltage drop per diode                                  | 4.0 A   | $V_F$  |        |       |       | 1.00  |       |       |       | V             |
| Maximum DC reverse current at rated DC blocking voltage per diode                     | $T_A = 25\text{ }^\circ\text{C}$<br>$T_A = 125\text{ }^\circ\text{C}$ | $I_R$  |        |       |       | 5.0   |       |       |       | $\mu\text{A}$ |
| Typical junction capacitance per diode  | 4.0 V, 1 MHz  | $C_J$  |        | 95    |       |       |       | 40    |       | pF            |

| THERMAL CHARACTERISTICS ( $T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted) |                                    |        |       |       |   |       |       |       |                    |  |
|--|------------------------------------|--------|-------|-------|---|-------|-------|-------|--------------------|--|
| PARAMETER  | SYMBOL                             | GBL005 | GBL01 | GBL02 | GBL04                                   | GBL06 | GBL08 | GBL10 | UNIT               |  |
| Typical thermal resistance   | $R_{\theta JA}$<br>$R_{\theta JC}$ |        |       |       | 22 <sup>(2)</sup><br>3.5 <sup>(1)</sup> |       |       |       | $^\circ\text{C/W}$ |  |

**Notes:**

- (1) Unit mounted on 3.0 x 3.0 x 0.11" thick (7.5 x 7.5 x 0.3 cm) aluminum plate
- (2) Unit mounted on P.C.B. at 0.375" (9.5 mm) lead length and 0.5 x 0.5" (12 x 12 mm) copper pads

| ORDERING INFORMATION (Example) |                 |                        |               |                      |
|--------------------------------|-----------------|------------------------|---------------|----------------------|
| PREFERRED P/N                  | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE        |
| GBL06-E3/45                    | 2.18            | 45                     | 20            | Tube                 |
| GBL06-E3/51                    | 2.18            | 51                     | 400           | Anti-static PVC tray |

## RATINGS AND CHARACTERISTICS CURVES

( $T_A = 25\text{ }^\circ\text{C}$  unless otherwise noted)




Figure 1. Derating Curves Output Rectified Current




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current Per Diode




Figure 3. Typical Forward Voltage Characteristics Per Diode




Figure 5. Typical Junction Capacitance Per Diode




Figure 4. Typical Reverse Characteristics Per Diode





Figure 6. Typical Transient Thermal Impedance Per Diode

**PACKAGE OUTLINE DIMENSIONS** in inches (millimeters)

**Case Type GBL**



Polarity shown on front side of case, positive lead beveled corner



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.