

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0760105005

Status:

Active

Overview:

iPass™ Connector System

Description:

0.80mm Pitch iPass™ I/O Connector Shell, Vertical, Retention Fit, 26 Circuits, Left Key

Documents:

Drawing (PDF)


RoHS Certificate of Compliance (PDF)

|                |                         |
|----------------|-------------------------|
| General        |                         |
| Product Family | I/O Connectors          |
| Series         | 76010                   |
| Application    | Wire-to-Board           |
| Component Type | Shell Body              |
| Overview       | iPass™ Connector System |
| Product Name   | iPass™                  |
| Type           | N/A                     |
| UPC            | 822350748346            |

|                                |                    |
|--------------------------------|--------------------|
| Physical                       |                    |
| Boot Color                     | N/A                |
| Circuits (Loaded)              | N/A                |
| Circuits (maximum)             | 26                 |
| Circuits Detail                | 26                 |
| Durability (mating cycles max) | 25                 |
| Gender                         | N/A                |
| Keying to Mating Part          | Yes                |
| Lock to Mating Part            | None               |
| Material - Metal               | Copper-Nickel-Zinc |
| Material - Plating Mating      | N/A                |
| Net Weight                     | 1.728/g            |
| Number of Rows                 | 0                  |
| Orientation                    | Vertical           |
| PCB Locator                    | No                 |
| PCB Retention                  | Yes                |
| Packaging Type                 | Tray               |
| Panel Mount                    | N/A                |
| Pitch - Mating Interface       | N/A                |
| Polarized to Mating Part       | N/A                |
| Polarized to PCB               | Yes                |
| Surface Mount Compatible (SMC) | N/A                |
| Temperature Range - Operating  | -40°C to +80°C     |
| Termination Interface: Style   | Through Hole       |
| Waterproof / Dustproof         | No                 |
| Wire Size AWG                  | N/A                |

|                               |             |
|-------------------------------|-------------|
| Electrical                    |             |
| Current - Maximum per Contact | N/A         |
| Grounding to Panel            | None        |
| Shield Type                   | Full Shield |
| Shielded                      | Yes         |
| Voltage - Maximum             | N/A         |

|                                                |        |
|------------------------------------------------|--------|
| Solder Process Data                            |        |
| Duration at Max. Process Temperature (seconds) | 020    |
| Lead-freeProcess Capability                    | REFLOW |
| Max. Cycles at Max. Process Temperature        | 001    |
| Process Temperature max. C                     | 260    |



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

China RoHS

Compliant

REACH SVHC

Contains SVHC(2014

December 17): No

Halogen-Free

Status

Low-Halogen

Need more information on product

environmental compliance?

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
Please visit the [Contact Us](#) section for any  
non-product compliance questions.

China ROHS

Green Image

ELV

Not Relevant

Search Parts in this Series

76010 Series

Mates With

79575 iPass™ Internal Cable, 74563

iPass™ Mini-SAS Internal Cable, 79576

iPass™ 36 Circuit-SATA Fanout Cable,

74573 iPass™ 36 Circuit RA-SATA Cable,

79536 iPass™ 36 Circuit SATA Cable,

74562 iPass™ 36 Circuit Right Angle

Use With

75577 0.80mm Pitch iPass™ I/O Connector

**Material Info**

**Reference - Drawing Numbers**

Sales Drawing

SD-76010-002

This document was generated on 06/26/2015

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.