

TRM Professional Multianode

Tantalum Ultra Low ESR Capacitor



FEATURES

- Improved reliability – 0.5%/1khrs (twice better than standard)
- DCL reduced by 25% to 0.0075 CV
- Robust against higher thermo-mechanical stresses during assembly process
- Multi-anode construction
- Super low ESR
- CV range 4.7-1500µF / 2.5-50V
- “Mirror” construction used with D case capacitors reduces ESL to half
- Automotive, industrial and other higher end applications



SnPb termination option is not
RoHS compliant.

APPLICATIONS

- Automotive, Avionics and Industrial high power DC/DC converters



MULTIANODE CONSTRUCTION



MULTIANODE TPM D, Y LOW SELF INDUCTANCE CONSTRUCTION “MIRROR” DESIGN



MARKING

D, E, U CASE



CASE DIMENSIONS: millimeters (inches)

| Code | EIA Code | EIA Metric | L±0.20 (0.008) | W+0.20 (0.008) -0.10 (0.004) | H+0.20 (0.008) -0.10 (0.004) | W ₁ ±0.20 (0.008) | A+0.30 (0.012) -0.20 (0.008) | S Min. |
|------|----------|------------|----------------|------------------------------|------------------------------|------------------------------|------------------------------|--------------|
| D | 2917 | 7343-31 | 7.30 (0.287) | 4.30 (0.169) | 2.90 (0.114) | 2.40 (0.094) | 1.30 (0.051) | 4.40 (0.173) |
| E | 2917 | 7343-43 | 7.30 (0.287) | 4.30 (0.169) | 4.10 (0.162) | 2.40 (0.094) | 1.30 (0.051) | 4.40 (0.173) |
| U | 2924 | 7361-43 | 7.30 (0.287) | 6.10 (0.240) | 4.10 (0.162) | 3.10 (0.122) | 1.30 (0.051) | 4.40 (0.173) |

W1 dimension applies to the termination width for A dimensional area only.

HOW TO ORDER

| TRM | E | 108 | * | 004 | R | 0023 |
|------|------------------------------|--|-----------------------------------|---|--|-----------|
| Type | Case Size See table above | Capacitance Code pF code: 1st two digits represent significant figures, 3rd digit represents multiplier (number of zeros to follow) | Tolerance K = ±10% M = ±20% | Rated DC Voltage 002 = 2.5Vdc 004 = 4Vdc 006 = 6.3Vdc 010 = 10Vdc 012 = 12Vdc 016 = 16Vdc 020 = 20Vdc 025 = 25Vdc 035 = 35Vdc 050 = 50Vdc | Packaging R = Pure Tin 7" Reel S = Pure Tin 13" Reel H = Tin Lead 7" Reel (Contact Manufacturer) K = Tin Lead 13" Reel (Contact Manufacturer) H, K = Non RoHS | ESR in mΩ |

TECHNICAL SPECIFICATIONS

| | | | | | | | | | | | |
|------------------------------------|--|-----|-----|-----|----|----|----|----|----|----|----|
| Technical Data: | All technical data relate to an ambient temperature of +25°C | | | | | | | | | | |
| Capacitance Range: | 4.7 µF to 1500 µF | | | | | | | | | | |
| Capacitance Tolerance: | ±10%; ±20% | | | | | | | | | | |
| Rated Voltage (V _R) | ≤ +85°C: | 2.5 | 4 | 6.3 | 10 | 12 | 16 | 20 | 25 | 35 | 50 |
| Category Voltage (V _C) | ≤ +125°C: | 1.7 | 2.7 | 4 | 7 | 8 | 10 | 13 | 17 | 23 | 33 |
| Surge Voltage (V _S) | ≤ +85°C: | 3.3 | 5.2 | 8 | 13 | 16 | 20 | 26 | 32 | 46 | 65 |
| Surge Voltage (V _S) | ≤ +125°C: | 2.2 | 3.4 | 5 | 8 | 10 | 13 | 16 | 20 | 28 | 40 |
| Temperature Range: | -55°C to +125°C | | | | | | | | | | |
| Reliability: | 0.5% per 1000 hours at 85°C, V _R with 0.1Ω/V series impedance, 60% confidence level | | | | | | | | | | |
| | Meets requirements of AEC-Q200 | | | | | | | | | | |



The Important Information/Disclaimer is incorporated in these specifications by reference and should be reviewed in full before placing any order.

TRM Professional Multianode

Tantalum Ultra Low ESR Capacitor



CAPACITANCE AND RATED VOLTAGE RANGE (LETTER DENOTES CASE SIZE)

| Capacitance | | Rated Voltage DC (V _R) to 85°C | | | | | | | | | |
|-------------|------|--|-------------------|----------|----------|---------|----------|----------|---------|--------------------|---------|
| µF | Code | 2.5V (e) | 4V (G) | 6.3V (J) | 10V (A) | 12V (B) | 16V (C) | 20V (D) | 25V (E) | 35V (V) | 50V (T) |
| 4.7 | 475 | | | | | | | | | | D(200) |
| 6.8 | 685 | | | | | | | | | | |
| 10 | 106 | | | | | | | | | D(120) | |
| 15 | 156 | | | | | | | | | | |
| 22 | 226 | | | | | | | | | D(70) E(60,100) | |
| 33 | 336 | | | | | | | | D(65) | E(50,65) | |
| 47 | 476 | | | | | | D(100) | D(55) | E(65) | | |
| 68 | 686 | | | | | | | | | | |
| 100 | 107 | | | | | | | E(35,45) | | | |
| 150 | 157 | | | | D(45) | | E(30,40) | | | | |
| 220 | 227 | | | | D(35) | E(35) | U(30,40) | | | | |
| 330 | 337 | | D(35) | D(35) | E(35) | | | | | | |
| 470 | 477 | | D(35) | E(30) | U(23,30) | | | | | | |
| 680 | 687 | | E(23) | U(18,23) | | | | | | | |
| 1000 | 108 | D(25) | E(23) U(18,23) | | | | | | | | |
| 1500 | 158 | E(18) U(18,23) | | | | | | | | | |

Released ratings, (ESR ratings in mOhms in parentheses)

Note: Voltage ratings are minimum values. AVX reserves the right to supply higher voltage ratings in the same case size, to the same reliability standards.

TRM Professional Multianode

Tantalum Ultra Low ESR Capacitor



RATINGS & PART NUMBER REFERENCE

| AVX Part No. | Case Size | Capacitance (µF) | Rated Voltage (V) | Rated Temperature (°C) | Category Voltage (V) | Category Temperature (°C) | DCL Max. (µA) | DF Max. (%) | ESR Max. @ 100kHz (mΩ) | 100kHz RMS Current (A) | | | MSL |
|------------------------|-----------|------------------|-------------------|------------------------|----------------------|---------------------------|---------------|-------------|------------------------|------------------------|-------|-------|-----|
| | | | | | | | | | | 25°C | 85°C | 125°C | |
| 2.5 Volt @ 85°C | | | | | | | | | | | | | |
| TRMD108*002#0025 | D | 1000 | 2.5 | 85 | 1.7 | 125 | 18.8 | 8 | 25 | 3.194 | 2.874 | 1.277 | 3 |
| TRME158*002#0018 | E | 1500 | 2.5 | 85 | 1.7 | 125 | 28.1 | 6 | 18 | 3.873 | 3.486 | 1.549 | 3 |
| TRMU158*002R0018 | U | 1500 | 2.5 | 85 | 1.7 | 125 | 22.5 | 6 | 18 | 4.048 | 3.643 | 1.619 | 3 |
| TRMU158*002R0023 | U | 1500 | 2.5 | 85 | 1.7 | 125 | 22.5 | 6 | 23 | 3.581 | 3.223 | 1.433 | 3 |
| 4 Volt @ 85°C | | | | | | | | | | | | | |
| TRMD337*004#0035 | D | 330 | 4 | 85 | 2.7 | 125 | 9.9 | 8 | 35 | 2.699 | 2.429 | 1.080 | 3 |
| TRMD477*004#0035 | D | 470 | 4 | 85 | 2.7 | 125 | 14.1 | 8 | 35 | 2.699 | 2.429 | 1.080 | 3 |
| TRME687*004#0023 | E | 680 | 4 | 85 | 2.7 | 125 | 20.4 | 6 | 23 | 3.426 | 3.084 | 1.370 | 3 |
| TRME108*004#0023 | E | 1000 | 4 | 85 | 2.7 | 125 | 30 | 6 | 23 | 3.426 | 3.084 | 1.370 | 3 |
| TRMU108*004R0018 | U | 1000 | 4 | 85 | 2.7 | 125 | 30 | 6 | 18 | 4.048 | 3.643 | 1.619 | 3 |
| TRMU108*004R0023 | U | 1000 | 4 | 85 | 2.7 | 125 | 30 | 6 | 23 | 3.581 | 3.223 | 1.433 | 3 |
| 6.3 Volt @ 85°C | | | | | | | | | | | | | |
| TRMD337*006#0035 | D | 330 | 6.3 | 85 | 4 | 125 | 14.9 | 8 | 35 | 2.699 | 2.429 | 1.080 | 3 |
| TRME477*006#0030 | E | 470 | 6.3 | 85 | 4 | 125 | 21.2 | 6 | 30 | 3.000 | 2.700 | 1.200 | 3 |
| TRMU687*006R0018 | U | 680 | 6.3 | 85 | 4 | 125 | 30.6 | 6 | 18 | 4.048 | 3.643 | 1.619 | 3 |
| TRMU687*006R0023 | U | 680 | 6.3 | 85 | 4 | 125 | 30.6 | 6 | 23 | 3.581 | 3.223 | 1.433 | 3 |
| 10 Volt @ 85°C | | | | | | | | | | | | | |
| TRMD157*010#0045 | D | 150 | 10 | 85 | 7 | 125 | 11.3 | 8 | 45 | 2.380 | 2.142 | 0.952 | 3 |
| TRMD227*010#0035 | D | 220 | 10 | 85 | 7 | 125 | 16.5 | 8 | 35 | 2.699 | 2.429 | 1.080 | 3 |
| TRME337*010#0035 | E | 330 | 10 | 85 | 7 | 125 | 24.8 | 6 | 35 | 2.777 | 2.500 | 1.111 | 3 |
| TRMU477*010R0023 | U | 470 | 10 | 85 | 7 | 125 | 35.3 | 8 | 23 | 3.581 | 3.223 | 1.433 | 3 |
| TRMU477*010R0030 | U | 470 | 10 | 85 | 7 | 125 | 35.3 | 8 | 30 | 3.136 | 2.822 | 1.254 | 3 |
| 12 Volt @ 85°C | | | | | | | | | | | | | |
| TRME227*012#0035 | E | 220 | 12 | 85 | 8.4 | 125 | 19.8 | 6 | 35 | 2.777 | 2.500 | 1.111 | 3 |
| 16 Volt @ 85°C | | | | | | | | | | | | | |
| TRMD476*016#0100 | D | 47 | 16 | 85 | 10 | 125 | 5.6 | 8 | 100 | 1.597 | 1.437 | 0.639 | 3 |
| TRME157*016#0030 | E | 150 | 16 | 85 | 10 | 125 | 18 | 6 | 30 | 3.000 | 2.700 | 1.200 | 3 |
| TRME157*016#0040 | E | 150 | 16 | 85 | 10 | 125 | 18 | 6 | 40 | 2.598 | 2.338 | 1.039 | 3 |
| TRMU227*016R0030 | U | 220 | 16 | 85 | 10 | 125 | 26.4 | 8 | 30 | 3.136 | 2.822 | 1.254 | 3 |
| TRMU227*016R0040 | U | 220 | 16 | 85 | 10 | 125 | 26.4 | 8 | 40 | 2.716 | 2.444 | 1.086 | 3 |
| 20 Volt @ 85°C | | | | | | | | | | | | | |
| TRMD476*020#0055 | D | 47 | 20 | 85 | 13 | 125 | 7.1 | 8 | 55 | 2.153 | 1.938 | 0.861 | 3 |
| TRME107*020#0035 | E | 100 | 20 | 85 | 13 | 125 | 15 | 6 | 35 | 2.777 | 2.500 | 1.111 | 3 |
| TRME107*020#0045 | E | 100 | 20 | 85 | 13 | 125 | 15 | 6 | 45 | 2.449 | 2.205 | 0.980 | 3 |
| 25 Volt @ 85°C | | | | | | | | | | | | | |
| TRMD336*025#0065 | D | 33 | 25 | 85 | 17 | 125 | 6.2 | 8 | 65 | 1.981 | 1.783 | 0.792 | 3 |
| TRME476*025#0065 | E | 47 | 25 | 85 | 17 | 125 | 8.8 | 6 | 65 | 2.038 | 1.834 | 0.815 | 3 |
| 35 Volt @ 85°C | | | | | | | | | | | | | |
| TRMD106*035#0120 | D | 10 | 35 | 85 | 23 | 125 | 2.6 | 8 | 120 | 1.458 | 1.312 | 0.583 | 3 |
| TRMD226*035#0070 | D | 22 | 35 | 85 | 23 | 125 | 5.8 | 8 | 70 | 1.909 | 1.718 | 0.763 | 3 |
| TRME226*035#0060 | E | 22 | 35 | 85 | 23 | 125 | 5.8 | 6 | 60 | 2.121 | 1.909 | 0.849 | 3 |
| TRME226*035#0100 | E | 22 | 35 | 85 | 23 | 125 | 5.8 | 6 | 100 | 1.643 | 1.479 | 0.657 | 3 |
| TRME336*035#0050 | E | 33 | 35 | 85 | 23 | 125 | 8.7 | 6 | 50 | 2.324 | 2.091 | 0.930 | 3 |
| TRME336*035#0065 | E | 33 | 35 | 85 | 23 | 125 | 8.7 | 6 | 65 | 2.038 | 1.834 | 0.815 | 3 |
| 50 Volt @ 85°C | | | | | | | | | | | | | |
| TRMD475*050#0200 | D | 4.7 | 50 | 85 | 33 | 125 | 1.8 | 8 | 200 | 1.129 | 1.016 | 0.452 | 3 |

Moisture Sensitivity Level (MSL) is defined according to J-STD-020.

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5V RMS with a maximum DC bias of 2.2 volts.

DCL is measured at rated voltage after 5 minutes.

The EIA & CECC standards for low ESR Solid Tantalum Capacitors allow an ESR movement to 1.25 times catalogue limit post mounting.

For typical weight and composition see page 274.

NOTE: AVX reserves the right to supply higher voltage ratings or tighter tolerance part in the same case size, to the same reliability standards.



The Important Information/Disclaimer is incorporated in these specifications by reference and should be reviewed in full before placing any order.

TRM Professional Multianode

Tantalum Ultra Low ESR Capacitor



QUALIFICATION TABLE

| TEST | TRM professional multianode series (Temperature range -55°C to +125°C) | | | | | | | | | | |
|------------------------------|---|---------------|---------------|--------------------|------------------------------------|-----------|------------|------------|------------|------------|--|
| | Condition | | | Characteristics | | | | | | | |
| Endurance | Apply rated voltage (Ur) at 85°C and / or category voltage (Uc) at 125°C for 2000 hours through a circuit impedance of $\leq 0.1\Omega/V$. Stabilize at room temperature for 1-2 hours before measuring. | | | Visual examination | no visible damage | | | | | | |
| | | | | DCL | initial limit | | | | | | |
| | | | | $\Delta C/C$ | within $\pm 10\%$ of initial value | | | | | | |
| | | | | DF | initial limit | | | | | | |
| | | | | ESR | 1.25 x initial limit | | | | | | |
| Storage Life | Store at 125°C, no voltage applied, for 2000 hours. Stabilize at room temperature for 1-2 hours before measuring. | | | Visual examination | no visible damage | | | | | | |
| | | | | DCL | 1.25 x initial limit | | | | | | |
| | | | | $\Delta C/C$ | within $\pm 10\%$ of initial value | | | | | | |
| | | | | DF | initial limit | | | | | | |
| | | | | ESR | 1.25 x initial limit | | | | | | |
| Humidity | Store at 65°C and 95% relative humidity for 500 hours, with no applied voltage. Stabilize at room temperature and humidity for 1-2 hours before measuring. | | | Visual examination | no visible damage | | | | | | |
| | | | | DCL | 1.5 x initial limit | | | | | | |
| | | | | $\Delta C/C$ | within $\pm 10\%$ of initial value | | | | | | |
| | | | | DF | 1.2 x initial limit | | | | | | |
| | | | | ESR | 1.25 x initial limit | | | | | | |
| Biased Humidity | Apply rated voltage (Ur) at 85°C, 85% relative humidity for 1000 hours. Stabilize at room temperature and humidity for 1-2 hours before measuring. | | | Visual examination | no visible damage | | | | | | |
| | | | | DCL | 2 x initial limit | | | | | | |
| | | | | $\Delta C/C$ | within $\pm 10\%$ of initial value | | | | | | |
| | | | | DF | 1.2 x initial limit | | | | | | |
| | | | | ESR | 1.25 x initial limit | | | | | | |
| Temperature Stability | Step | Temperature°C | Duration(min) | | +20°C | -55°C | +20°C | +85°C | +125°C | +20°C | |
| | 1 | +20 | 15 | DCL | IL* | n/a | IL* | 10 x IL* | 12.5 x IL* | IL* | |
| | 2 | -55 | 15 | $\Delta C/C$ | n/a | +0/-10% | $\pm 5\%$ | +10/-0% | +12/-0% | $\pm 5\%$ | |
| | 3 | +20 | 15 | DF | IL* | 1.5 x IL* | IL* | 1.5 x IL* | 2 x IL* | IL* | |
| | 4 | +85 | 15 | ESR | 1.25 x IL* | 2.5 x IL* | 1.25 x IL* | 1.25 x IL* | 1.25 x IL* | 1.25 x IL* | |
| | 5 | +125 | 15 | | | | | | | | |
| | 6 | +20 | 15 | | | | | | | | |
| Surge Voltage | Apply 1.3x category voltage (Uc) at 125°C for 1000 cycles of duration 6 min (30 sec charge, 5 min 30 sec discharge) through a charge / discharge resistance of 1000 Ω | | | Visual examination | no visible damage | | | | | | |
| | | | | DCL | initial limit | | | | | | |
| | | | | $\Delta C/C$ | within $\pm 5\%$ of initial value | | | | | | |
| | | | | DF | initial limit | | | | | | |
| | | | | ESR | 1.25 x initial limit | | | | | | |
| Mechanical Shock | MIL-STD-202, Method 213, Condition F | | | Visual examination | no visible damage | | | | | | |
| | | | | DCL | initial limit | | | | | | |
| | | | | $\Delta C/C$ | within $\pm 5\%$ of initial value | | | | | | |
| | | | | DF | initial limit | | | | | | |
| | | | | ESR | 1.25 x initial limit | | | | | | |
| Vibration | MIL-STD-202, Method 204, Condition D | | | Visual examination | no visible damage | | | | | | |
| | | | | DCL | initial limit | | | | | | |
| | | | | $\Delta C/C$ | within $\pm 5\%$ of initial value | | | | | | |
| | | | | DF | initial limit | | | | | | |
| | | | | ESR | 1.25 x initial limit | | | | | | |

*Initial Limit

TRM Professional Multianode

Tantalum Ultra Low ESR Capacitor



AVX SOLID ELECTROLYTIC CAPACITOR ROADMAP



FIVE CAPACITOR CONSTRUCTION STYLES



SERIES LINE UP: CONVENTIONAL SMD MnO₂



The Important Information/Disclaimer is incorporated in these specifications by reference and should be reviewed in full before placing any order.

IMPORTANT INFORMATION/DISCLAIMER

All product specifications, statements, information and data (collectively, the “Information”) in this datasheet or made available on the website are subject to change. The customer is responsible for checking and verifying the extent to which the Information contained in this publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Statements of suitability for certain applications are based on AVX’s knowledge of typical operating conditions for such applications, but are not intended to constitute and AVX specifically disclaims any warranty concerning suitability for a specific customer application or use.

ANY USE OF PRODUCT OUTSIDE OF SPECIFICATIONS OR ANY STORAGE OR INSTALLATION INCONSISTENT WITH PRODUCT GUIDANCE VOIDS ANY WARRANTY.

The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by AVX with reference to the use of AVX’s products is given without regard, and AVX assumes no obligation or liability for the advice given or results obtained.

Although AVX designs and manufactures its products to the most stringent quality and safety standards, given the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage.

Unless specifically agreed to in writing, AVX has not tested or certified its products, services or deliverables for use in high risk applications including medical life support, medical device, direct physical patient contact, water treatment, nuclear facilities, weapon systems, mass and air transportation control, flammable environments, or any other potentially life critical uses. Customer understands and agrees that AVX makes no assurances that the products, services or deliverables are suitable for any high-risk uses. Under no circumstances does AVX warrant or guarantee suitability for any customer design or manufacturing process.

Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated or that other measures may not be required.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.