


Ultra High Precision Z Foil Through-Hole Resistor
with TCR of ± 0.2 ppm/ $^{\circ}\text{C}$, Tolerance of $\pm 0.005\%$ (50 ppm),
Load Life Stability of $\pm 0.005\%$

FEATURES

- **Temperature coefficient of resistance (TCR):**
 ± 0.2 ppm/ $^{\circ}\text{C}$ typical (-55°C to $+125^{\circ}\text{C}$, $+25^{\circ}\text{C}$ ref.)
(see table 1)
- Rated power: to 1 W at $+125^{\circ}\text{C}$ (see table 2)
- Resistance tolerance: to $\pm 0.005\%$ (50 ppm)
- Load life stability: $\pm 0.005\%$ at 70°C , 2000 h or $\pm 0.015\%$ at 70°C , 10000 h (see table 4)
- Resistance range: 5 Ω to 600 k Ω
- Bulk Metal[®] Foil resistors are not restricted to standard values; specific “as required” values can be supplied at no extra cost or delivery (e.g. 1K2345 vs. 1K)
- Total accumulated change in resistance value over life or Total Error Budget $< 0.1\%$ (or tighter with PMO)**
- Electrostatic Discharge (ESD): at least to 25 kV
- Non-inductive, non-capacitive design
- Rise time: 1 ns effectively no ringing
- Current noise: ≤ 0.010 $\mu\text{V}_{\text{RMS}}/\text{V}$ of applied voltage (< -40 dB)
- Thermal EMF: 0.05 $\mu\text{V}/^{\circ}\text{C}$ typical
- Voltage coefficient: < 3 ppm/V
- Low inductance: < 0.08 μH typical
- Thermal stabilization time < 1 s (to reach within 10 ppm of steady state value)
- Pattern design minimizing hot spots
- Terminal finish: lead (Pb)-free or tin/lead alloy
- Matched sets are available per request (TCR tracking: to 0.5 ppm/ $^{\circ}\text{C}$)
- Military established reliability “R” level resistor available (see resistor model RNC90Z)
- Screen/test flow as modified from S-311-P813 proposed by NASA available (see datasheet for resistor model 303143)
- Prototype quantities available please contact foil@vpgsensors.com

INTRODUCTION

The Bulk Metal[®] Foil resistor is based on a special thermo-metallic stress concept wherein a proprietary bulk metal cold rolled foil is cemented to a ceramic substrate. It is then photoetched into a resistive pattern. Then it is laser adjusted to any desired value and tolerance. Because the metals used are not drawn, wound or mistreated in any way during manufacturing process, the Bulk Metal Foil resistor maintains all its design, physical and electrical characteristics while winding of wire or sputtering does not. Z Foil resistors achieve maximum stability and near-zero TCR. These performance characteristics are built-in for every unit, and do not rely on screening or other artificial means for uniform performance.



RoHS*
COMPLIANT

The stability of a resistor depends primarily on its history of exposures to temperature. Stability is affected by:

1. Reversible changes in the ambient temperature and heat from adjacent components (defined by the Temperature Coefficient of Resistance, or TCR)
2. Short-term steady-state self-heating (defined by Power TCR or PCR)
3. Irreversible destabilizing shock of suddenly-applied power
4. Long-term exposure to applied power (load-life stability)

In very high-precision resistors, these effects must be taken into account to achieve high stability with changes in load (Joule Effect) and ambient temperature.

Vishay Foil Resistors' Z Foil technology provides an order of magnitude reduction in the Bulk Metal Foil element's sensitivity to temperature changes – both external and internal. This technology provides TCR of ± 0.2 ppm/ $^{\circ}\text{C}$ typical (military range: -55°C to $+125^{\circ}\text{C}$, $+25^{\circ}\text{C}$ ref), and a PCR of 5 ppm at rated power.

In order to take full advantage of this TCR improvement, it is necessary to take into account the differences in the resistor's response to each of the above-mentioned effects. The Z series has been developed to successfully deal with these factors.

* This datasheet provides information about parts that are RoHS-compliant and/or parts that are non-RoHS-compliant. For example, parts with lead (Pb) terminations are not RoHS compliant. Please see the information/tables in this datasheet for details.
** See PMO page 5

TABLE 1 – TYPICAL TCR AND MAX. SPREAD
(-55°C to $+125^{\circ}\text{C}$, $+25^{\circ}\text{C}$ ref.)

| VALUE | STANDARD TOLERANCE | TYPICAL TCR AND MAX. SPREAD (ppm/ $^{\circ}\text{C}$) |
|--------------------------------|--------------------|--|
| 100 Ω to 600 k Ω | $\pm 0.005\%$ | $\pm 0.2 \pm 0.6$ |
| 80 Ω to $< 100 \Omega$ | $\pm 0.005\%$ | $\pm 0.2 \pm 0.8$ |
| 50 Ω to $< 80 \Omega$ | $\pm 0.01\%$ | $\pm 0.2 \pm 1.0$ |
| 25 Ω to $< 50 \Omega$ | $\pm 0.01\%$ | $\pm 0.2 \pm 1.3$ |
| 10 Ω to $< 25 \Omega$ | $\pm 0.02\%$ | $\pm 0.2 \pm 1.6$ |
| 5 Ω to $< 10 \Omega$ | $\pm 0.05\%$ | $\pm 0.2 \pm 2.3$ |

FIGURE 1 – TYPICAL RESISTANCE/TEMPERATURE CURVE

(for more details, see table 1)



Note

The TCR values for <math><100 \Omega</math> are influenced by the termination composition and result in deviation from this curve

FIGURE 2 – POWER DERATING CURVE





FIGURE 3 – TRIMMING TO VALUES (conceptual illustration)



Note

To acquire a precision resistance value, the Bulk Metal® Foil chip is trimmed by selectively removing built-in "shorting bars." To increase the resistance in known increments, marked areas are cut, producing progressively smaller increases in resistance. This method reduces the effect of "hot spots" and improves the long-term stability of Bulk Metal Foil resistors.

FIGURE 4 - THROUGH-HOLE STYLE (29 YEARS)



TABLE 2 – MODEL SELECTION

| MODEL NUMBER | RESISTANCE RANGE ⁽²⁾ | MAXIMUM WORKING VOLTAGE | AMBIENT POWER RATING | | AVERAGE WEIGHT | DIMENSIONS | |
|--------------------------------|---------------------------------|-------------------------|----------------------|-----------|----------------|--|---|
| | | | at +70°C | at +125°C | | INCHES | mm |
| Z201 (Z201L) ⁽¹⁾ | 5 Ω to 100 kΩ | 300 V | 0.6 W | 0.3 W | 0.5 g | W: 0.105 ±0.010 L: 0.300 ±0.010 H: 0.326 ±0.010 ST: 0.010 min. SW: 0.040 ±0.005 LL: 1.000 ±0.125 LS: 0.150 ±0.005 ⁽¹⁾ | 2.67 ±0.25 7.62 ±0.25 8.28 ±0.25 0.254 min. 1.02 ±0.13 25.4 ±3.18 3.81 ±0.13 |
| Z204 | 5 Ω to 200 kΩ | 350 V | 1.0 W | 0.5 W | 1.25 g | W: 0.160 max. L: 0.575 max. H: 0.413 max. ST: 0.035 ±0.005 SW: 0.050 ±0.005 LL: 1.000 ±0.125 LS: 0.400 ±0.020 | 4.06 max. 14.61 max. 10.49 max. 0.889 ±0.13 1.27 ±0.13 25.4 ±3.18 10.16 ±0.51 |
| Z205 | 5 Ω to 300 kΩ | 350 V | 1.5 W | 0.75 W | 1.75 g | W: 0.160 max. L: 0.820 max. H: 0.413 max. ST: 0.035 ±0.005 SW: 0.050 ±0.005 LL: 1.000 ±0.125 LS: 0.650 ±0.020 | 4.06 max. 20.83 max. 10.49 max. 0.889 ±0.13 1.27 ±0.13 25.4 ±3.18 16.51 ±0.51 |
| Z206 | 5 Ω to 600 kΩ | 500 V | 2.0 W | 1.0 W | 3.7 g | W: 0.260 max. L: 1.200 max. H: 0.413 max. ST: 0.035 ±0.005 SW: 0.050 ±0.005 LL: 1.000 ±0.125 LS: 0.900 ±0.020 | 6.60 max. 30.48 max. 10.49 max. 0.889 ±0.13 1.27 ±0.13 25.4 ±3.18 22.86 ±0.51 |
| | | | up to 400K | | | | |
| | | | 1.0 W | 0.5 W | | | |
| | | | over 400K | | | | |

Note

⁽¹⁾ 0.200 in (5.08 mm) lead spacing available – specify Z201L instead of Z201.

⁽²⁾ For non standard values please contact Application Engineering at foil@vpgsensors.com

FIGURE 5 – STANDARD IMPRINTING AND DIMENSIONS



Note

1. The standoffs shall be so located as to give a lead clearance of 0.010 in minimum between the resistor body and the printed circuit board when the standoffs are seated on the printed circuit board. This is to allow for proper cleaning of flux and other contaminants from the unit after all soldering processes.

TABLE 3 – ENVIRONMENTAL PERFORMANCE COMPARISON

| | MIL-PRF-55182 CHAR J | Z SERIES TYPICAL ΔR | Z SERIES MAXIMUM ΔR ⁽¹⁾ |
|--|---|---|---|
| Test Group I Thermal shock, 5 × (–65°C to +150°C) Short time overload, 6.25 × rated power | ±0.2% ±0.2% | ±0.002% (20 ppm) ±0.003% (30 ppm) | ±0.01% (100 ppm) ±0.01% (100 ppm) |
| Test Group II Resistance temperature characteristics Low temperature storage (24 h at –65°C) Low temperature operation (45 min, rated power at –65°C) Terminal strength | ±25 ppm/°C ±0.15% ±0.15% ±0.20% | ±0.2 ppm/°C ±0.002% (20 ppm) ±0.002% (20 ppm) ±0.002% (20 ppm) | see table 1 ±0.01% (100 ppm) ±0.01% (100 ppm) ±0.01% (100 ppm) |
| Test Group III DWV Insulation resistance Resistance to solder heat Moisture resistance | ±0.15% ≥10 ⁴ MΩ ±0.10% ±0.40% | ±0.002% (20 ppm) ±0.005% (50 ppm) ±0.010% (100 ppm) | ±0.01% (100 ppm) ≥10 ⁴ MΩ ±0.01% (100 ppm) ±0.02% (200 ppm) |
| Test Group IV Shock Vibration | ±0.2% ±0.2% | ±0.002% (20 ppm) ±0.002% (20 ppm) | ±0.01% (100 ppm) ±0.01% (100 ppm) |
| Test Group V Life test at rated power / +125°C 2 000 h 10 000 h | ±0.5% ±2.0% | ±0.005% (50 ppm) ±0.015% (150 ppm) | ±0.015% (150 ppm) ±0.050% (500 ppm) |
| Test Group Va Life test at 2 × rated power / +70°C, 2 000 h | ±0.5% | ±0.005% (50 ppm) | ±0.015% (150 ppm) |
| Test Group VI High temperature exposure (2 000 h at +175°C) | ±2.0% | ±0.02% (200 ppm) | ±0.05% (500 ppm) |
| Test Group VII Voltage coefficient | 5 ppm/V | | 3 ppm/V |

⁽¹⁾ Measurement error allowed for ΔR limits: 0.01 Ω

STANDARD OPERATIONS AND TEST CONDITIONS

A. Standard Test Operations

By 100% Inspection:

- TCR
- Short-time overload (6.25 × rated power for 5 s)
- Resistance – tolerance check
- Visual and mechanical

By Sample Inspection:

- Environmental tests per table 3 on a quarterly basis to establish performance by similarity

B. Test Conditions

- Lead test point: 0.5 in (12.7 mm) from resistor body
- Temperature: +23°C ±2°C
- Relative humidity: per MIL-STD-202

LONG-TERM STABILITY

Some process controls are not very critical but many, many are – particularly when a process is operating near a tipping point where it could get out of control quickly if not well monitored.

In process control applications, entire production batches have been lost or suffered reduced reliability when critical parameters were not kept within narrow limits. One thing that can cause this to happen is changes in the precision resistor over time. Reference points in the control process thus become less and less reliable. Repeatability of the process from batch to batch begins to drift. The process is changing while the monitors appear to be holding it within specified limits because the sense resistor is producing a different output voltage than it was in previous runs for the same sensor output. So the process appears to be under control when, in reality, it is experiencing an undetected drift.

Long-term stability is thus one of the considerations that drive the selection of which resistor technology to use in the application.

But the typical permanent resistance drift of a Bulk Metal Foil resistor is less than 60 ppm (0.006%) after 10 years running at 0.1 W at 70°C.

**FIGURE 6 – LOAD LIFE TEST FOR
10 000 HRS @ 0.3 W +125°C; Z201, N=24**



**FIGURE 7 – IMPROVED STABILITY
WITH THROUGH-HOLE**

Through-hole achieve better stability because they are not subjected to thermo-mechanical stresses from the PCB



THERMAL EMF

In a resistor, the resistance is composed of a resistance element of one material and two terminations of a different material. When the junction of the element and the termination is heated in a closed circuit, there is a DC voltage generated in the circuit (see Seebeck and Peltier Effects). Hence, if both termination junctions of the resistor are at exactly the same temperature across terminations there is no net thermal EMF voltage generated in the circuit due to thermal EMF error voltages in the resistor.

In fact, however, the terminals are very seldom at the same temperature because their temperatures are influenced by uneven power dissipation within the resistor, differential heating from other components on the board, and heat conducted along the board itself. Obviously, in a sense resistor that's supposed to accurately convert a current to a voltage, the presence of an extraneous thermal EMF voltage could constitute a significant error source in the system. That is why it's important that Bulk Metal Foil resistors have a thermal EMF voltage of less than 0.1 mV/°C difference across the element to termination junction.

POST MANUFACTURING OPERATIONS (PMO)

Many analog applications can include requirements for performance under conditions of stress beyond the normal and over extended periods of time. This calls for more than just selecting a standard device and applying it to a circuit. The standard device may turn out to be all that is needed but an analysis of the projected service conditions should be made and it may well dictate a routine of stabilization known as post manufacturing operations or PMO. The PMO operations that will be discussed are only applicable to Bulk Metal® Foil resistors. They stabilize Bulk Metal Foil resistors while they are harmful to other types. Short time overload, accelerated load life, and temperature cycling are the three PMO exercises that do the most to reduce drifts down the road. VFR Bulk Metal Foil resistors are inherently stable as manufactured. These PMO exercises are only of value on Bulk Metal Foil resistors and they improve the performance by small but significant amounts. Users are encouraged to contact Vishay Foil Resistors' applications engineering for assistance in choosing the PMO operations that are right for their application.

TABLE 4 – “Z” SERIES SPECIFICATIONS

| | | |
|--|---|--|
| Stability (1) Load life at 2 000 h Load life at 10 000 h | ±0.015% (150 ppm) ±0.005% (50 ppm) ±0.050% (500 ppm) ±0.015% (100 ppm) | Maximum ΔR at 0.3 W/+125°C Maximum ΔR at 0.1 W/+70°C Maximum ΔR at 0.3 W/+125°C Maximum ΔR at 0.1 W/+70°C |
| Current Noise | 0.010 μV _{RMS} /V of applied voltage (<-40 dB) | |
| High Frequency Operation Rise time Inductance (L) ⁽²⁾ Capacitance (C) | 1.0 ns at 1 kΩ 0.1 μH maximum; 0.08 μH typical 1.0 pF maximum; 0.5 pF typical | |
| Voltage Coefficient | <3 ppm/V ⁽³⁾ | |
| Thermal EMF⁽⁴⁾ | 0.05 μV/°C typical 1 μV/W (Model Z201) | |

Notes

- (1) Load life ΔR maximum can be reduced by 80%, please contact applications engineering.
 (2) Inductance (L) due mainly to the leads.
 (3) The resolution limit of existing test equipment (within the measurement capability of the equipment.)
 (4) μV/°C relates to EMF due to lead temperature difference and μV/watt due to power applied to the resistor.

TABLE 5 – GLOBAL PART NUMBER INFORMATION⁽¹⁾

NEW GLOBAL PART NUMBER: Y145380K5000V9L (preferred part number format)



FOR EXAMPLE: ABOVE GLOBAL ORDER Y1453 80K5000 V 9 L:

TYPE: Z201


VALUE: 80.5 $k\Omega$

ABSOLUTE TOLERANCE: $\pm 0.005\%$

TERMINATION: lead (Pb)-free

PACKAGING: bulk pack

HISTORICAL PART NUMBER: Z201 T 80K500 V B (will continue to be used)



Note

⁽¹⁾ For non-standard requests, please contact application engineering.



Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.