



For more Information  
please call

1-800-Belden1



## General Description:

SFP+ Passive Cable Assembly, SFP+ / SFP+, 10G, 30 AWG , Black 02 ft

## Usage (Overall)

Suitable Applications: 10Gbps Ethernet, SFP+ Direct Attach

## Multi Conductor

### Physical Characteristics

#### Conductor

AWG:

# Conductors	# Pairs	AWG	Stranding	Conductor Material	Cable Type
4	2	30	Solid	Silver Plated Copper	Twinax

## Cable Characteristics (Connectivity)

### Outer Shield

Outer Shield Material:

Layer #	Coverage (%)	Description
1	100.000	Al - Mylar
2	85.000	Braid

### Outer Jacket

Outer Jacket Color Code Chart:

Number	Color
00	Black

### Overall Diameter

Overall Nominal Diameter: 0.177 in.

## Physical Characteristics (Connectivity)

### Materials

Materials:

Description	Material
Contacts	Gold plated pads (30 u inch min.)
Back Shell	Nickel plated zinc alloy diecast

### Weight

Weight: 0.286 lbs.

### Packaging

Packaging: Individually packaged in an antistatic clear plastic bag.

## Mechanical Characteristics (Connectivity)

Footprint/Type: SFP+ to SFP+

Termination Interface:

Connection	Durabilities
Mated Connection	200 Cycles

Cable/Connector Retention: 20.200 lbs.

Storage Temperature Range: -20°C To +80°C

Operating Temperature Range: 0°C To +75°C

Max. Recommended Pull Tension: 2.800 lbs.

Min. Bend Radius (Overall Cable): 1 in.

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

CEC/C(UL) Specification: CL2

IEEE Specification: IEEE 802.3ae 10 Gigabit Ethernet Standard

## SSFP-P0002F Cable Assemblies - SFP+ Passive

EU Directive 2002/95/EC (RoHS):	Yes
Safety Listing:	Bi-national Standard Listed
Other Specification:	SFF-8431, SFF-8432, SFF-8472

### Flame Test

UL Flame Test:	UL1685 Vertical Tray Flame Test
CSA Flame Test:	FT4

### Transmission Characteristics (Connectivity)

Dielectric Strength:	300 V DC
Current Rating:	0.500 A
Insulation Resistance:	1000 M-Ohm Minimum
Max. Contact Resistance:	20 m-Ohm

### Electrical Characteristics (Overall)

Differential Impedance @ 1 MHz:	100 ± 5 Ohms
---------------------------------	--------------

### Labeling

Labeling:	Manufacturer name, Part Number, Serial Number, Length and Date Code
-----------	---

### Notes (Overall)

#### Product Family

##### Product List:

Belden P/N	Description
SSFP-P0002F	ASM CBL, SFP+ 10Gb/s Passive 30 AWG PVC Black 2FT
SSFP-P0003F	ASM CBL, SFP+ 10Gb/s Passive 30 AWG PVC Black 3FT
SSFP-P0004F	ASM CBL, SFP+ 10Gb/s Passive 30 AWG PVC Black 4FT
SSFP-P0005F	ASM CBL, SFP+ 10Gb/s Passive 30 AWG PVC Black 5FT
SSFP-P0006F	ASM CBL, SFP+ 10Gb/s Passive 30 AWG PVC Black 6FT
SSFP-P0007F	ASM CBL, SFP+ 10Gb/s Passive 30 AWG PVC Black 7FT
SSFP-P0008F	ASM CBL, SFP+ 10Gb/s Passive 30 AWG PVC Black 8FT
SSFP-P0009F	ASM CBL, SFP+ 10Gb/s Passive 30 AWG PVC Black 9FT
SSFP-P0010F	ASM CBL, SFP+ 10Gb/s Passive 30 AWG PVC Black 10FT
SSFP-P0011F	ASM CBL, SFP+ 10Gb/s Passive 24 AWG PVC Black 11FT
SSFP-P0012F	ASM CBL, SFP+ 10Gb/s Passive 24 AWG PVC Black 12FT
SSFP-P0013F	ASM CBL, SFP+ 10Gb/s Passive 24 AWG PVC Black 13FT
SSFP-P0014F	ASM CBL, SFP+ 10Gb/s Passive 24 AWG PVC Black 14FT
SSFP-P0015F	ASM CBL, SFP+ 10Gb/s Passive 24 AWG PVC Black 15FT
SSFP-P0016F	ASM CBL, SFP+ 10Gb/s Passive 24 AWG PVC Black 16FT
SSFP-P0017F	ASM CBL, SFP+ 10Gb/s Passive 24 AWG PVC Black 17FT
SSFP-P0018F	ASM CBL, SFP+ 10Gb/s Passive 24 AWG PVC Black 18FT
SSFP-P0019F	ASM CBL, SFP+ 10Gb/s Passive 24 AWG PVC Black 19FT
SSFP-P0020F	ASM CBL, SFP+ 10Gb/s Passive 24 AWG PVC Black 20FT
SSFP-P0021F	ASM CBL, SFP+ 10Gb/s Passive 24 AWG PVC Black 21FT
SSFP-P0022F	ASM CBL, SFP+ 10Gb/s Passive 24 AWG PVC Black 22FT
SSFP-P0023F	ASM CBL, SFP+ 10Gb/s Passive 24 AWG PVC Black 23FT

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0    Revision Date: 11-30-2011

© 2016 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.