


OPTION "B"

[illegible]

1. APPLICABLE TERMINAL PART NUMBERS (SOLD SEPARATELY):
FOR TIN APPLICATIONS: 1393367 AND 1393366.
FOR GOLD APPLICATIONS: 1393365 AND 1393364.
FOR TERMINATION AND REELING OPTIONS
SEE DRAWINGS 1393367, 1393366, 1393365, AND 1393364.
2. COMPATIBLE WIRE SIZES FOR MAT SEAL DESIGN I.19 TO 2.06 O.D.
(22-18 AWG, 0.35-0.75 mm2)
3. TPA IS SHIPPED IN IT'S PRE-LOADED POSITION. ALL ASSEMBLIES ARE TO
BE TRAY PACKAGED.
4. CUSTOMER PART NUMBER AND TRACEABILITY CODE (YY = TWO DIGIT YEAR,
JJJ = JULIAN DAY, HH = TWO DIGIT MILITARY HOUR, A = ASSEMBLY
PROCESS USED) ARE PRINTED IN THIS LOCATION.
5. PART ASSEMBLY WEIGHT WITHOUT TERMINALS AND WITH STANDARD PIN-OUT
CONFIGURATION IS 14.39 GRAMS.
6. OPTIONAL WIRESHIELD P/N 7-1419157-8 (SOLD SEPARATELY). PLEASE CONTACT
YOUR TYCO ELECTRONICS SALES REPRESENTATIVE FOR AVAILABILITY AND PRICING.

KEYING OPTION "A" SHOWN

[illegible]

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN R. VESTAL 24JUL2007 CHK W. WELLINSKY 24JUL2007 APP'D W. WELLINSKY 24JUL2007		 TE Connectivity	
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±. 1 PLC ±0.3 2 PLC ±0.10 3 PLC ±. 4 PLC ±. ANGLES ±°		NAME 24 WAY ARM PLUG ASSEMBLY WITH SELECT LOAD SHORTING BARS CUSTOMER SPEC.	
		PRODUCT SPEC APPLICATION SPEC		SIZE CAGE CODE DRAWING NO A1 00779 C-1924674	
MATERIAL SEE CHART ABOVE		FINISH -		WEIGHT SEE-NOTE 5 CUSTOMER DRAWING	
				SCALE 3:1 SHEET 1 OF 5 REV S	

LOC	DIST	REVISIONS					
FX	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-		SEE SHEET 1	-	-	-

ASSEMBLY PART NUMBERS																																			
2098376-1																											1924686-1	1924685-1	1924684-1	1924683-1	1924682-1				
I																											I	I	I	I	I	7	CPA	PBT-GF15	RED
I																											I	I	I	I	I	6	SHORTING BAR	S.S.	SEE COMPONENT DRAWING
I																											I	I	I	I	I	5	PERIMETER SEAL	SILICONE	
I																											I	I	I	I	I	4	GROMMET	SILICONE	BROWN
I																											I	I	I	I	I	3	COVER	PA66 35% GF	BLACK
I																											I	I	I	I	I	2	TPA WITH 3 SHORTING BAR POSITIONS CONFIGURATION	sPS 30% GF	NATURAL
I																															I	3 SHORTING BAR POSITIONS CONFIGURATION	PA66 30% GF	BLACK	
																											I				I	3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK	
																													I		I	3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK	
																														I	I	3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK	
																												I			I	3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK	
																												I			I	3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	NATURAL	
																													I		I	3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK	
																														I	I	3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	GRAY	
QUANTITY																												ITEM	DESCRIPTION	MATERIAL	FINISH/COLOR				

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

9 PLC ±.3
1 PLC ±0.3
2 PLC ±0.10
3 PLC ±.
4 PLC ±.
ANGLES ±°
FINISH -

MATERIAL

SEE CHART ABOVE

DWN
R. VESTAL 24JUL2007

CHK
W. WELLINSKY 24JUL2007

APVD
W. WELLINSKY 24JUL2007

PRODUCT SPEC
-

APPLICATION SPEC
-

WEIGHT
-

CUSTOMER DRAWING

NAME
24 WAY ARM PLUG ASSEMBLY
WITH SELECT LOAD SHORTING BARS
CUSTOMER SPEC.

SIZE
A1

CAGE CODE
00779

DRAWING NO
1924674

RESTRICTED TO
-

SCALE
3:1

SHEET
2

OF
5

REV
S

TE Connectivity

[illegible]

PIN-OUT CHART

[illegible]

LOC	DIST	REVISIONS					
FX	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-		SEE SHEET 1	-	-	-

PIN-OUT CHART																																
		1 / 2																								N	2098376-1	KEY "F"				
		1 / 2																								N	1924686-1	KEY "E"				
		1 / 2																								N	1924685-1	KEY "D"				
		1 / 2																								N	1924684-1	KEY "C"				
		1 / 2																								N	1924683-1	KEY "B"				
		1 / 2																								N	1924682-1	KEY "A"				
5 / 6	3 / 4	1 / 2	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	CPA	ASSEMBLY PART NUMBER	PLUG KEYING OPTION			
SHORTING BAR POSITION			TERMINAL HOLE POSITION																													
CAVITIES W/ A NUMERIC SYMBOL INDICATE SHORTING BAR LOADED			CAVITIES WITH A NUMERIC SYMBOL INDICATE CLOSED TERMINAL HOLE POSITIONS																													
BLANK CAVITIES INDICATE NO SHORTING BAR LOADED			BLANK CAVITIES INDICATE OPEN TERMINAL HOLE POSITIONS																													

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

MATERIAL

SEE CHART ABOVE

TOLERANCES UNLESS OTHERWISE SPECIFIED:

9 PLC ±.3

1 PLC ±0.10

2 PLC ±.10

3 PLC ±.

4 PLC ±.

ANGLES ±°

FINISH -

DWN R. VESTAL 24JUL2007

CHK W. WELLINSKY 24JUL2007

APVD W. WELLINSKY 24JUL2007

PRODUCT SPEC -

APPLICATION SPEC -

WEIGHT -

CUSTOMER DRAWING

NAME 24 WAY ARM PLUG ASSEMBLY WITH SELECT LOAD SHORTING BARS CUSTOMER SPEC.

SIZE A1 CAGE CODE 00779 DRAWING NO C=1924674

RESTRICTED TO -

SCALE 3:1 SHEET 5 OF 5 REV S

TE Connectivity



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.