




## Metallized Polyester Film Capacitors MKT Radial Potted Types



### FEATURES

- Material categorization:  
for definitions of compliance please see  
[www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**  
**GREEN**  
(5-2008)

### APPLICATIONS


Blocking, bypassing, filtering and timing, high frequency coupling and decoupling for fast digital and analog ICs, interference suppression in low voltage applications.

| QUICK REFERENCE DATA                            |                                                                                                          |
|-------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| Capacitance range                               | 1 nF to 1.0 $\mu$ F (E12 series)                                                                         |
| Capacitance tolerance                           | $\pm 20\%$ (M), $\pm 10\%$ (K), $\pm 5\%$ (J)                                                            |
| Climatic testing class according to IEC 60068-1 | 55/100/56 for rated voltage 63 V<br>55/105/56 for rated voltage > 63 V                                   |
| Reference specifications                        | IEC 60384-2                                                                                              |
| Dielectric                                      | Polyester film                                                                                           |
| Electrodes                                      | Metallized                                                                                               |
| Construction                                    | Mono construction<br> |
| Encapsulation                                   | Flame retardant plastic case and epoxy resin sealed (UL-class 94 V-0)                                    |
| Leads                                           | Tinned wire                                                                                              |
| Marking                                         | Manufacturer's logo/type/C-value/rated voltage/tolerance/date of manufacture                             |
| Rated DC voltage                                | 63 V <sub>DC</sub> , 100 V <sub>DC</sub> , 250 V <sub>DC</sub> , 400 V <sub>DC</sub>                     |
| Rated AC voltage                                | 40 V <sub>AC</sub> , 63 V <sub>AC</sub> , 160 V <sub>AC</sub> , 200 V <sub>AC</sub>                      |
| Rated temperature                               | 85 °C                                                                                                    |
| Maximum application temperature                 | 100 °C for rated voltage 63 V<br>105 °C for rated voltage > 63 V                                         |
| Performance grade                               | 1 (long life)                                                                                            |

#### Note


- For more detailed data and test requirements, contact [dc-film@vishay.com](mailto:dc-film@vishay.com)

### DIMENSIONS in millimeters





# COMPOSITION OF CATALOG NUMBER



| SPECIFIC REFERENCE DATA                                                                              |                                                   |                                                                    |                           |                           |
|------------------------------------------------------------------------------------------------------|---------------------------------------------------|--------------------------------------------------------------------|---------------------------|---------------------------|
| DESCRIPTION                                                                                          |                                                   | VALUE                                                              |                           |                           |
| Tangent of loss angle:                                                                               |                                                   | at 1 kHz                                                           | at 10 kHz                 | at 100 kHz                |
| $C \leq 0.1 \mu\text{F}$                                                                             |                                                   | $\leq 80 \times 10^{-4}$                                           | $\leq 150 \times 10^{-4}$ | $\leq 250 \times 10^{-4}$ |
| $0.1 \mu\text{F} < C \leq 1.0 \mu\text{F}$                                                           |                                                   | $\leq 80 \times 10^{-4}$                                           | $\leq 150 \times 10^{-4}$ | -                         |
| PITCH<br>(mm)                                                                                        | RATED VOLTAGE PULSE SLOPE (dU/dt) <sub>R</sub> AT |                                                                    |                           |                           |
|                                                                                                      | 63 V <sub>DC</sub>                                | 100 V <sub>DC</sub>                                                | 250 V <sub>DC</sub>       | 400 V <sub>DC</sub>       |
| 5                                                                                                    | 60                                                | 110                                                                | 330                       | 630                       |
| If the maximum pulse voltage is less than the rated voltage higher dV/dt values can be permitted.    |                                                   |                                                                    |                           |                           |
| R between leads, for $C \leq 0.33 \mu\text{F}$ and $U_R \leq 100 \text{ V}$                          |                                                   | > 15 000 MΩ                                                        |                           |                           |
| R between leads, for $C \leq 0.33 \mu\text{F}$ and $U_R > 100 \text{ V}$                             |                                                   | > 30 000 MΩ                                                        |                           |                           |
| RC between leads, for $C > 0.33 \mu\text{F}$ and $U_R \leq 100 \text{ V}$                            |                                                   | > 5000 s                                                           |                           |                           |
| RC between leads, for $C > 0.33 \mu\text{F}$ and $U_R > 100 \text{ V}$                               |                                                   | > 10 000 s                                                         |                           |                           |
| R between interconnecting leads and casing 100 V (foil method)                                       |                                                   | > 30 000 MΩ                                                        |                           |                           |
| Withstanding (DC) voltage (cut off current 10 mA) <sup>(1)</sup> ; rise time $\leq 1000 \text{ V/s}$ |                                                   | $1.6 \times U_{RDC}$ , 1 min                                       |                           |                           |
| Withstanding (DC) voltage between leads and case                                                     |                                                   | $2.0 \times U_{RDC}$ , with minimum of 200 V <sub>DC</sub> ; 1 min |                           |                           |
| Maximum application temperature                                                                      |                                                   | 100 °C for rated voltage 63 V<br>105 °C for rated voltage > 63 V   |                           |                           |

## Note

<sup>(1)</sup> See "Voltage Proof Test for Metalized Film Capacitors": [www.vishay.com/doc?28169](http://www.vishay.com/doc?28169)



| <b>ELECTRICAL DATA</b> |                    |                     |              |          |                                 |
|------------------------|--------------------|---------------------|--------------|----------|---------------------------------|
| $U_{RDC}$<br>(V)       | CAP.<br>( $\mu$ F) | CAPACITANCE<br>CODE | VOLTAGE CODE | $V_{AC}$ | DIMENSIONS<br>w x h x l<br>(mm) |
| 63                     | 0.10               | -410                | 06           | 40       | 2.5 x 6.5 x 7.2                 |
|                        | 0.15               | -415                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.22               | -422                |              |          | 3.5 x 8.0 x 7.2                 |
|                        | 0.33               | -433                |              |          | 3.5 x 8.0 x 7.2                 |
|                        | 0.47               | -447                |              |          | 3.5 x 8.0 x 7.2                 |
|                        | 0.68               | -468                |              |          | 4.5 x 9.0 x 7.2                 |
|                        | 1.0                | -510                |              |          | 6.0 x 11.0 x 7.2                |
| 100                    | 0.022              | -322                | 01           | 63       | 2.5 x 6.5 x 7.2                 |
|                        | 0.033              | -333                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.047              | -347                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.068              | -368                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.10               | -410                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.15               | -415                |              |          | 3.5 x 8.0 x 7.2                 |
|                        | 0.22               | -422                |              |          | 4.5 x 9.0 x 7.2                 |
| 250                    | 0.33               | -433                | 25           | 160      | 4.5 x 9.0 x 7.2                 |
|                        | 0.0033             | -233                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.0047             | -247                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.0068             | -268                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.010              | -310                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.015              | -315                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.022              | -322                |              |          | 3.5 x 8.0 x 7.2                 |
| 250                    | 0.033              | -333                | 25           | 160      | 3.5 x 8.0 x 7.2                 |
|                        | 0.047              | -347                |              |          | 4.5 x 9.0 x 7.2                 |
|                        | 0.068              | -368                |              |          | 6.0 x 11.0 x 7.2                |
|                        | 0.10               | -410                |              |          | 6.0 x 11.0 x 7.2                |
|                        | 0.0033             | -233                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.0047             | -247                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.0068             | -268                |              |          | 2.5 x 6.5 x 7.2                 |
| 250                    | 0.010              | -310                | 25           | 160      | 2.5 x 6.5 x 7.2                 |
|                        | 0.015              | -315                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.022              | -322                |              |          | 3.5 x 8.0 x 7.2                 |
|                        | 0.033              | -333                |              |          | 3.5 x 8.0 x 7.2                 |
|                        | 0.047              | -347                |              |          | 4.5 x 9.0 x 7.2                 |
|                        | 0.068              | -368                |              |          | 6.0 x 11.0 x 7.2                |
|                        | 0.10               | -410                |              |          | 6.0 x 11.0 x 7.2                |
| 400                    | 0.0010             | -210                | 40           | 200      | 2.5 x 6.5 x 7.2                 |
|                        | 0.0015             | -215                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.0022             | -222                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.0033             | -233                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.0047             | -247                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.0068             | -268                |              |          | 2.5 x 6.5 x 7.2                 |
|                        | 0.010              | -310                |              |          | 3.5 x 8.0 x 7.2                 |
|                        | 0.015              | -315                |              |          | 3.5 x 8.0 x 7.2                 |
|                        | 0.022              | -322                |              |          | 4.5 x 9.0 x 7.2                 |

| <b>RECOMMENDED PACKAGING</b> |                      |                    |                       |                           |            |
|------------------------------|----------------------|--------------------|-----------------------|---------------------------|------------|
| PACKAGING<br>CODE            | TYPE OF<br>PACKAGING | HEIGHT (H)<br>(mm) | REEL DIAMETER<br>(mm) | ORDERING CODE<br>EXAMPLES | PITCH<br>5 |
| D                            | Ammo                 | 16.5               | S <sup>(1)</sup>      | MKT1817233255D            | x          |
| G                            | Ammo                 | 18.5               | S <sup>(1)</sup>      | MKT1817233255G            | x          |
| F                            | Reel                 | 16.5               | 350                   | MKT1817233255F            | x          |
| W                            | Reel                 | 18.5               | 350                   | MKT1817233255W            | x          |
| -                            | Bulk                 | -                  | -                     | MKT1817233255             | x          |

**Note**<sup>(1)</sup> S = box size 55 mm x 210 mm x 340 mm (w x h x l)



## MOUNTING

### Normal Use

The capacitors are designed for mounting on printed-circuit boards. The capacitors packed in bandoliers are designed for mounting in printed-circuit boards by means of automatic insertion machines.

For detailed tape specifications refer to packaging information [www.vishay.com/docs?28139](http://www.vishay.com/docs?28139)

### Specific Method of Mounting to Withstand Vibration and Shock

In order to withstand vibration and shock tests, it must be ensured that the stand-off pips are in good contact with the printed-circuit board.


- For pitches  $\leq 15$  mm the capacitors shall be mechanically fixed by the leads
- For larger pitches the capacitors shall be mounted in the same way and the body clamped

### Space Requirements on Printed-Circuit Board

The maximum space for length ( $l_{\max.}$ ), width ( $w_{\max.}$ ) and height ( $h_{\max.}$ ) of film capacitors to take in account on the printed-circuit board is shown in the drawings.

- For products with pitch  $\leq 15$  mm,  $\Delta w = \Delta l = 0.3$  mm;  $\Delta h = 0.1$  mm

Eccentricity defined as in drawing. The maximum eccentricity is smaller than or equal to the lead diameter of the product concerned.



## SOLDERING CONDITIONS

For general soldering conditions and wave soldering profile, we refer to the document “Characteristics and Definitions Used for Film Capacitors”: [www.vishay.com/doc?28147](http://www.vishay.com/doc?28147)

### Storage Temperature

$T_{\text{stg}} = -25$  °C to  $+35$  °C with RH maximum 75 % without condensation


### Ratings and Characteristics Reference Conditions

Unless otherwise specified, all electrical values apply to an ambient free air temperature of  $23$  °C  $\pm 1$  °C, an atmospheric pressure of 86 kPa to 106 kPa and a relative humidity of  $50$  %  $\pm 2$  %.


For reference testing, a conditioning period shall be applied over  $96$  h  $\pm 4$  h by heating the products in a circulating air oven at the rated temperature and a relative humidity not exceeding 20 %.




## CHARACTERISTICS




Capacitance as a function of ambient temperature (typical) for voltage 63 V




Capacitance as a function of ambient temperature (typical) for voltages > 63 V




Capacitance as a function of frequency (typical curve)




Impedance as a function of frequency




Max. AC voltage as a function of frequency




Max. AC voltage as a function of frequency




Max. AC voltage as a function of frequency




Max. AC voltage as a function of frequency




Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency



Max. AC voltage as a function of frequency









Max. AC voltage as a function of frequency



### Maximum RMS Current (Sinewave) as a Function of Frequency

The maximum RMS current is defined by  $I_{ac} = \omega \times C \times U_{ac}$ .

$U_{ac}$  is the maximum AC voltage depending on the ambient temperature in the curves "Max. RMS voltage and AC current as a function of frequency".





**HEAT CONDUCTIVITY (G) AS A FUNCTION OF (ORIGINAL) PITCH AND CAPACITOR BODY THICKNESS IN mW/°C**

| $W_{\max.}$<br>(mm) | HEAT CONDUCTIVITY (mW/°C) |
|---------------------|---------------------------|
|                     | PITCH 5 mm                |
| 2.5                 | 2.5                       |
| 3.0                 | 3.0                       |
| 4.5                 | 4.0                       |
| 6.0                 | 5.5                       |

**POWER DISSIPATION AND MAXIMUM COMPONENT TEMPERATURE RISE**

The power dissipation must be limited in order not to exceed the maximum allowed component temperature rise as a function of the free ambient temperature.


The power dissipation can be calculated according type detail specification “HQN-384-01/101: Technical Information Film Capacitors”.

The component temperature rise ( $\Delta T$ ) can be measured (see section “Measuring the Component Temperature” for more details) or calculated by  $\Delta T = P/G$ :

- $\Delta T$  = component temperature rise (°C)
- $P$  = power dissipation of the component (mW)
- $G$  = heat conductivity of the component (mW/°C)

**MEASURING THE COMPONENT TEMPERATURE**

A thermocouple must be attached to the capacitor body as in:



The temperature is measured in unloaded ( $T_{\text{amb}}$ ) and maximum loaded condition ( $T_C$ ).

The temperature rise is given by  $\Delta T = T_C - T_{\text{amb}}$ .

To avoid radiation or convection, the capacitor should be tested in a wind-free box.

**APPLICATION NOTE AND LIMITING CONDITIONS**

These capacitors are not suitable for mains applications as across-the-line capacitors without additional protection, as described hereunder. These mains applications are strictly regulated in safety standards and therefore electromagnetic interference suppression capacitors conforming the standards must be used.

For capacitors connected in parallel, normally the proof voltage and possibly the rated voltage must be reduced. For information depending of the capacitance value and the number of parallel connections contact: [dc-film@vishay.com](mailto:dc-film@vishay.com)

To select the capacitor for a certain application, the following conditions must be checked:

1. The peak voltage ( $U_P$ ) shall not be greater than the rated DC voltage ( $U_{RDC}$ )
2. The peak-to-peak voltage ( $U_{P-P}$ ) shall not be greater than  $2\sqrt{2} \times U_{RAC}$  to avoid the ionization inception level
3. The voltage peak slope ( $dU/dt$ ) shall not exceed the rated voltage pulse slope in an RC-circuit at rated voltage and without ringing. If the pulse voltage is lower than the rated DC voltage, the rated voltage pulse slope may be multiplied by  $U_{RDC}$  and divided by the applied voltage.

For all other pulses following equation must be fulfilled:

$$2 \times \int_0^T \left( \frac{dU}{dt} \right)^2 \times dt < U_{RDC} \times \left( \frac{dU}{dt} \right)_{\text{rated}}$$

T is the pulse duration.

4. The maximum component surface temperature rise must be lower than the limits (see graph "Max. allowed component temperature rise").
5. Since in circuits used at voltages over 280 V peak-to-peak the risk for an intrinsically active flammability after a capacitor breakdown (short circuit) increases, it is recommended that the power to the component is limited to 100 times the values mentioned in the table: "Heat Conductivity"
6. When using these capacitors as across-the-line capacitor in the input filter for mains applications or as series connected with an impedance to the mains the applicant must guarantee that the following conditions are fulfilled in any case (spikes and surge voltages from the mains included).

**VOLTAGE CONDITIONS FOR 6 ABOVE**

| ALLOWED VOLTAGES                             | $T_{\text{amb}} \leq 85^\circ\text{C}$ | $85^\circ\text{C} < T_{\text{amb}} \leq 100^\circ\text{C}$ FOR 63 V   |
|----------------------------------------------|----------------------------------------|-----------------------------------------------------------------------|
|                                              |                                        | $85^\circ\text{C} < T_{\text{amb}} \leq 100^\circ\text{C}$ FOR > 63 V |
| Maximum continuous RMS voltage               | $U_{RAC}$                              | See "Max. AC voltage as function of temperature" per characteristics  |
| Maximum temperature RMS-overvoltage (< 24 h) | $1.25 \times U_{RAC}$                  | $U_{RAC}$                                                             |
| Maximum peak voltage ( $U_{O-P}$ ) (< 2 s)   | $1.6 \times U_{RDC}$                   | $1.3 \times U_{RDC}$                                                  |

**Example**


C = 330 nF - 63 V used for the voltage signal shown in next drawing.

$U_{P-P} = 40$  V;  $U_P = 35$  V;  $T_1 = 100$   $\mu$ s;  $T_2 = 200$   $\mu$ s

The ambient temperature is  $35^\circ\text{C}$

Checking conditions:

1. The peak voltage  $U_P = 35$  V is lower than 63 V<sub>DC</sub>
2. The peak-to-peak voltage 40 V is lower than  $2\sqrt{2} \times 40$  V<sub>AC</sub> = 113  $U_{P-P}$
3. The voltage pulse slope ( $dU/dt$ ) =  $40$  V/ $100$   $\mu$ s =  $0.4$  V/ $\mu$ s  
This is lower than 60 V/ $\mu$ s (see specific reference data for each version)
4. The dissipated power is 16.2 mW as calculated with fourier terms  
The temperature rise for  $w_{\text{max.}} = 3.5$  mm and pitch = 5 mm will be  $16.2$  mW/ $3.0$  mW/ $^\circ\text{C}$  =  $5.4^\circ\text{C}$   
This is lower than  $15^\circ\text{C}$  temperature rise at  $35^\circ\text{C}$ , according figure "Max. allowed component temperature rise"
5. Not applicable
6. Not applicable

**Voltage Signal**



## INSPECTION REQUIREMENTS

### General Notes

Sub-clause numbers of tests and performance requirements refer to the “Sectional Specification, Publication IEC 60384-2 and Specific Reference Data”.

| GROUP C INSPECTION REQUIREMENTS                           |                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                          |
|-----------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SUB-CLAUSE NUMBER AND TEST                                | CONDITIONS                                                                                                                                                                                                                                        | PERFORMANCE REQUIREMENTS                                                                                                                                                                                                                                                                                                                                                 |
| <b>SUB-GROUP C1A PART OF SAMPLE OF SUB-GROUP C1</b>       |                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                          |
| 4.1 Dimensions (detail)                                   |                                                                                                                                                                                                                                                   | As specified in chapters “MKT370 General Data” of this specification                                                                                                                                                                                                                                                                                                     |
| 4.3.1 Initial measurements                                | Capacitance<br>Tangent of loss angle:<br>for $C \leq 470$ nF at 100 kHz<br>for $C > 470$ nF at 10 kHz                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                          |
| 4.3 Robustness of terminations                            | Tensile and bending                                                                                                                                                                                                                               | No visible damage                                                                                                                                                                                                                                                                                                                                                        |
| 4.4 Resistance to soldering heat                          | Method: 1A<br>Solder bath: $280\text{ °C} \pm 5\text{ °C}$<br>Duration: 10 s                                                                                                                                                                      |                                                                                                                                                                                                                                                                                                                                                                          |
| 4.14 Component solvent resistance                         | Isopropylalcohol at room temperature<br>Method: 2<br>Immersion time: 5 min $\pm$ 0.5 min<br>Recovery time: min. 1 h, max. 2 h                                                                                                                     |                                                                                                                                                                                                                                                                                                                                                                          |
| 4.4.2 Final measurements                                  | Visual examination<br><br>Capacitance<br><br>Tangent of loss angle                                                                                                                                                                                | No visible damage<br>Legible marking<br><br>$ \Delta C/C  \leq 2\%$ of the value measured initially<br><br>Increase of $\tan \delta$ :<br>$\leq 0.005$ for: $C \leq 100$ nF or<br>$\leq 0.010$ for: $100\text{ nF} < C \leq 220$ nF or<br>$\leq 0.015$ for: $220\text{ nF} < C \leq 470$ nF or<br>$\leq 0.003$ for: $C > 470$ nF<br>Compared to values measured in 4.3.1 |
| <b>SUB-GROUP C1B OTHER PART OF SAMPLE OF SUB-GROUP C1</b> |                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                          |
| 4.6.1 Initial measurements                                | Capacitance<br>Tangent of loss angle:<br>for $C \leq 470$ nF at 100 kHz<br>for $C > 470$ nF at 10 kHz                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                          |
| 4.6 Rapid change of temperature                           | $\theta A = -55\text{ °C}$<br>$\theta B = +100\text{ °C}$<br>5 cycles<br>Duration $t = 30$ min                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                          |
| 4.7 Vibration                                             | Visual examination<br>Mounting:<br>see section “Mounting” of this specification<br>Procedure B4<br>Frequency range: 10 Hz to 55 Hz<br>Amplitude: 0.75 mm or<br>Acceleration $98\text{ m/s}^2$<br>(whichever is less severe)<br>Total duration 6 h | No visible damage                                                                                                                                                                                                                                                                                                                                                        |



| <b>GROUP C INSPECTION REQUIREMENTS</b>                                     |                                                                                                                                                       |                                                                                                                                                                                                           |
|----------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>SUB-CLAUSE NUMBER AND TEST</b>                                          | <b>CONDITIONS</b>                                                                                                                                     | <b>PERFORMANCE REQUIREMENTS</b>                                                                                                                                                                           |
| <b>SUB-GROUP C1B OTHER PART OF SAMPLE OF SUB-GROUP C1</b>                  |                                                                                                                                                       |                                                                                                                                                                                                           |
| 4.7.2 Final inspection                                                     | Visual examination                                                                                                                                    | No visible damage                                                                                                                                                                                         |
| 4.9 Shock                                                                  | Mounting:<br>see section "Mounting" of this specification<br>Pulse shape: half sine<br>Acceleration: 490 m/s <sup>2</sup><br>Duration of pulse: 11 ms |                                                                                                                                                                                                           |
| 4.9.3 Final measurements                                                   | Visual examination                                                                                                                                    | No visible damage                                                                                                                                                                                         |
|                                                                            | Capacitance                                                                                                                                           | $ \Delta C/C  \leq 3\%$ of the value measured in 4.6.1                                                                                                                                                    |
|                                                                            | Tangent of loss angle                                                                                                                                 | Increase of $\tan \delta$ :<br>$\leq 0.010$ for: $C \leq 220$ nF or<br>$\leq 0.015$ for: $220$ nF $< C \leq 470$ nF or<br>$\leq 0.003$ for: $C > 470$ nF<br>Compared to values measured in 4.6.1          |
|                                                                            | Insulation resistance                                                                                                                                 | As specified in section "Specific Reference Data 370" of this specification                                                                                                                               |
| <b>SUB-GROUP C1 COMBINED SAMPLE OF SPECIMENS OF SUB-GROUPS C1A AND C1B</b> |                                                                                                                                                       |                                                                                                                                                                                                           |
| 4.10 Climatic sequence                                                     |                                                                                                                                                       |                                                                                                                                                                                                           |
| 4.10.2 Dry heat                                                            | Temperature:<br>+100 °C for rated voltage 63 V<br>+105 °C for rated voltage > 63 V<br>Duration: 16 h                                                  |                                                                                                                                                                                                           |
| 4.10.3 Damp heat cyclic<br>Test Db, first cycle                            |                                                                                                                                                       |                                                                                                                                                                                                           |
| 4.10.4 Cold                                                                | Temperature: -55 °C<br>Duration: 2 h                                                                                                                  |                                                                                                                                                                                                           |
| 4.10.6 Damp heat cyclic<br>Test Db, remaining cycles                       | Voltage proof = $U_{RDC}$ for 1 min within 15 min<br>after removal from testchamber                                                                   | No breakdown or flash-over                                                                                                                                                                                |
| 4.10.6.2 Final measurements                                                | Visual examination                                                                                                                                    | No visible damage<br>Legible marking                                                                                                                                                                      |
|                                                                            | Capacitance                                                                                                                                           | $ \Delta C/C  \leq 3\%$ of the value measured in 4.4.2 or 4.9.3                                                                                                                                           |
|                                                                            | Tangent of loss angle                                                                                                                                 | Increase of $\tan \delta$ :<br>$\leq 0.010$ for: $C \leq 220$ nF or<br>$\leq 0.015$ for: $220$ nF $< C \leq 470$ nF or<br>$\leq 0.005$ for: $C > 470$ nF<br>Compared to values measured in 4.3.1 or 4.6.1 |
|                                                                            | Insulation resistance                                                                                                                                 | $\geq 50\%$ of values specified in section "Specific Reference Data 370" of this specification                                                                                                            |



| GROUP C INSPECTION REQUIREMENTS |                                                                                                                                                                                  |                                                                                                                                                                                                                                      |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SUB-CLAUSE NUMBER AND TEST      | CONDITIONS                                                                                                                                                                       | PERFORMANCE REQUIREMENTS                                                                                                                                                                                                             |
| <b>SUB-GROUP C2</b>             |                                                                                                                                                                                  |                                                                                                                                                                                                                                      |
| 4.11 Damp heat steady state     | 56 days, 40 °C, 90 % to 95 % RH                                                                                                                                                  |                                                                                                                                                                                                                                      |
| 4.11.1 Initial measurements     | Capacitance<br>Tangent of loss angle at 1 kHz                                                                                                                                    |                                                                                                                                                                                                                                      |
| 4.11.3 Final measurements       | Voltage proof = $U_{RDC}$ for 1 min within 15 min after removal from testchamber                                                                                                 | No breakdown or flash-over                                                                                                                                                                                                           |
|                                 | Visual examination                                                                                                                                                               | No visible damage<br>Legible marking                                                                                                                                                                                                 |
|                                 | Capacitance                                                                                                                                                                      | $ \Delta C/C  \leq 5\%$ of the value measured in 4.11.1.                                                                                                                                                                             |
|                                 | Tangent of loss angle                                                                                                                                                            | Increase of $\tan \delta$ : $\leq 0.005$<br>Compared to values measured in 4.11.1                                                                                                                                                    |
|                                 | Insulation resistance                                                                                                                                                            | $\geq 50\%$ of values specified in section "Specific Reference Data 370" of this specification                                                                                                                                       |
| <b>SUB GROUP C3</b>             |                                                                                                                                                                                  |                                                                                                                                                                                                                                      |
| 4.12 Endurance                  | Duration: 2000 h<br>$1.25 \times U_{RDC}$ at 85 °C<br>$0.8 \times 1.25 U_{RDC}$ at 100 °C for rated voltage 63 V<br>$0.8 \times 1.25 U_{RDC}$ at 105 °C for rated voltage > 63 V |                                                                                                                                                                                                                                      |
| 4.12.1 Initial measurements     | Capacitance<br>Tangent of loss angle:<br>for $C \leq 470$ nF at 100 kHz<br>for $C > 470$ nF at 10 kHz                                                                            |                                                                                                                                                                                                                                      |
| 4.12.5 Final measurements       | Visual examination                                                                                                                                                               | No visible damage<br>Legible marking                                                                                                                                                                                                 |
|                                 | Capacitance                                                                                                                                                                      | $ \Delta C/C  \leq 5\%$ compared to values measured in 4.12.1                                                                                                                                                                        |
|                                 | Tangent of loss angle                                                                                                                                                            | Increase of $\tan \delta$ :<br>$\leq 0.005$ at 85 °C<br>$\leq 0.010$ at 100 °C for: $C \leq 220$ nF or<br>$\leq 0.015$ for: $220$ nF < $C \leq 470$ nF or<br>$\leq 0.003$ for: $C > 470$ nF<br>Compared to values measured in 4.12.1 |
|                                 | Insulation resistance                                                                                                                                                            | $\geq 50\%$ of values specified in section "Specific Reference Data 370" of this specification                                                                                                                                       |



| GROUP C INSPECTION REQUIREMENTS |                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SUB-CLAUSE NUMBER AND TEST      | CONDITIONS                                                                                                            | PERFORMANCE REQUIREMENTS                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>SUB-GROUP C4</b>             |                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| 4.13 Charge and discharge       | 10 000 cycles<br>Charged to $U_{RDC}$<br><br>Discharge resistance:<br>$R = \frac{U_R}{C \times 2.5 \times (dU/dt)_R}$ |                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| 4.13.1 Initial measurements     | Capacitance<br>Tangent of loss angle:<br>for $C \leq 470 \text{ nF}$ at 100 kHz<br>for $C > 470 \text{ nF}$ at 10 kHz |                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| 4.13.3 Final measurements       | Capacitance<br><br>Tangent of loss angle<br><br>Insulation resistance                                                 | $ \Delta C/C  \leq 3 \%$ compared to values measured in 4.13.1<br><br>Increase of $\tan \delta$ :<br>$\leq 0.005$ for: $C \leq 100 \text{ nF}$ or<br>$\leq 0.010$ for: $100 \text{ nF} < C \leq 220 \text{ nF}$ or<br>$\leq 0.015$ for: $220 \text{ nF} < C \leq 470 \text{ nF}$ or<br>$\leq 0.003$ for: $C > 470 \text{ nF}$<br>Compared to values measured in 4.13.1<br><br>$\geq 50 \%$ of values specified in section "Specific Reference Data 370" of this specification |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.