


Attenuators


SMA Miniature Type

DC - 4.0 GHz		238 Series	Model Numbers
Male/Female	Female/Female		Male/Male
ATT-0238-XX-SMA-02	ATT-238F-XX-SMA-02		ATT-238M-XX-SMA-02
XX = Attenuation Value: Select 01-30dB in 1dB increments (.5 dB increments available)			
<i>HIGH PERFORMANCE</i>			



Attenuation Value	Length A
1-20 dB	1.20
21-60 dB	1.49


DC - 2.0 GHz		208 Series	Model Numbers
Male/Female	Female/Female		Male/Male
ATT-0208-XX-SMA-02	ATT-208F-XX-SMA-02		ATT-208M-XX-SMA-02
XX = Attenuation Value: Select 01-60dB in 1dB increments (.5 dB increments available)			
<i>HIGH PERFORMANCE</i>			



Attenuation Value	Length A
1-20 dB	1.07
21-60 dB	1.36

Low Cost - Inexpensive Types

DC - 18.0 GHz		333 Series	Model Numbers
Male/Female	Female/Female		Male/Male
ATT-0333-XX-SMA-02	ATT-333F-XX-SMA-02		ATT-333M-XX-SMA-02
XX = Attenuation Value: Select 01-60dB in 1dB increments			
<i>LOW COST</i>			



Attenuation Value	Length A
1-20 dB	1.33
21-60 dB	1.62

DC - 8.0 GHz		334 Series	Model Numbers
Male/Female	Female/Female		Male/Male
ATT-0334-XX-SMA-02	ATT-334F-XX-SMA-02		ATT-334M-XX-SMA-02
XX = Attenuation Value: Select 01-60dB in 1dB increments			
<i>LOW COST</i>			

SPECIFICATIONS - LOW COST

Attenuation Accuracy:

	DC - 12.4 GHz	12.4 - 18 GHz
1-4 dB	± 0.75 dB	± 0.75 dB
5-8 dB	± 0.75 dB	± 1.00 dB
9-12 dB	± 1.00 dB	± 1.25 dB
13-20 dB	± 1.50 dB	± 1.50 dB
21-40 dB	± 2.00 dB	± 2.00 dB
41-60 dB	± 2.50 dB	± 2.50 dB

VSWR:

VSWR:	Frequency (GHz)
1.25 max	DC - 4.0
1.45 max	4.0 - 12.4
1.65 max	12.4 - 18.0

Power: 2 Watts Average @ 25C derated linearly to .5 watts @ 125C

Peak Power: 200 Watts

Operating Temperature Range: -65 to +125C

Finish: Passivated Stainless Steel

Dimensions: Same as 263 Series

DC - 2.0 GHz		335 Series	Model Numbers
Male/Female	Female/Female		Male/Male
ATT-0335-XX-SMA-02	ATT-335F-XX-SMA-02		ATT-335M-XX-SMA-02
XX = Attenuation Value: Select 01-60dB in 1dB increments			
<i>LOW COST</i>			



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.