



# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable

**MAX4265-MAX4270**

## General Description

The MAX4265–MAX4270 ultra-low distortion, voltage-feedback op amps are capable of driving a 100Ω load while maintaining ultra-low distortion over a wide bandwidth. They offer superior spurious-free dynamic range (SFDR) performance: -90dBc at 5MHz and -59dBc at 100MHz (MAX4269). Additionally, input voltage noise density is 8nV/√Hz while operating from a single +4.5V to +8.0V supply or from dual ±2.25V to ±4.0V supplies. These features make the MAX4265–MAX4270 ideal for use in high-performance communications and signal-processing applications that require low distortion and wide bandwidth.

The MAX4265 single and MAX4268 dual amplifiers are unity-gain stable. The MAX4266 single and MAX4269 dual amplifiers are compensated for a minimum stable gain of +2V/V, while the MAX4267 single and MAX4270 dual amplifiers are compensated for a minimum stable gain of +5V/V.

For additional power savings, these amplifiers feature a low-power disable mode that reduces supply current and places the outputs in a high-impedance state. The MAX4265/MAX4266/MAX4267 are available in a space-saving 8-pin μMAX® package, and the MAX4268/MAX4269/MAX4270 are available in a 16-pin QSOP package.

## Applications

Base-Station Amplifiers  
 IF Amplifiers  
 High-Frequency ADC Drivers  
 High-Speed DAC Buffers  
 RF Telecom Applications  
 High-Frequency Signal Processing

## Features

- ◆ Operates from +4.5V to +8.0V
- ◆ Superior SFDR with 100Ω Load
  - 90dBc (f<sub>c</sub> = 5MHz)
  - 59dBc (f<sub>c</sub> = 100MHz)
- ◆ 35dBm IP3 (f<sub>c</sub> = 20MHz)
- ◆ 8nV/√Hz Voltage Noise Density
- ◆ 100MHz 0.1dB Gain Flatness (MAX4268)
- ◆ 900V/μs Slew Rate
- ◆ ±45mA Output Driving Capability
- ◆ Disable Mode Places Outputs in High-Impedance State

## Ordering Information

| PART               | TEMP. RANGE    | PIN-PACKAGE |
|--------------------|----------------|-------------|
| <b>MAX4265</b> EUA | -40°C to +85°C | 8 μMAX      |
| MAX4265ESA         | -40°C to +85°C | 8 SO        |
| <b>MAX4266</b> EUA | -40°C to +85°C | 8 μMAX      |
| MAX4266ESA         | -40°C to +85°C | 8 SO        |
| <b>MAX4267</b> EUA | -40°C to +85°C | 8 μMAX      |
| MAX4267ESA         | -40°C to +85°C | 8 SO        |
| <b>MAX4268</b> EEE | -40°C to +85°C | 16 QSOP     |
| MAX4268ESD         | -40°C to +85°C | 14 SO       |
| <b>MAX4269</b> EEE | -40°C to +85°C | 16 QSOP     |
| MAX4269ESD         | -40°C to +85°C | 14 SO       |
| <b>MAX4270</b> EEE | -40°C to +85°C | 16 QSOP     |
| MAX4270ESD         | -40°C to +85°C | 14 SO       |

μMAX is a registered trademark of Maxim Integrated Products, Inc.

Pin Configurations appear at end of data sheet.

## Selector Guide

| PART    | NO. OF OP AMPS | MIN GAIN (V/V) | -3dB BANDWIDTH (MHz) | GBP (MHz) | FULL-POWER BANDWIDTH (MHz) |
|---------|----------------|----------------|----------------------|-----------|----------------------------|
| MAX4265 | 1              | 1              | 400                  | 400       | 270                        |
| MAX4266 | 1              | 2              | 350                  | 700       | 350                        |
| MAX4267 | 1              | 5              | 300                  | 1500      | 300                        |
| MAX4268 | 2              | 1              | 300                  | 300       | 175                        |
| MAX4269 | 2              | 2              | 350                  | 700       | 200                        |
| MAX4270 | 2              | 5              | 200                  | 1000      | 200                        |



# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable

## ABSOLUTE MAXIMUM RATINGS

Supply Voltage ( $V_{CC}$  to  $V_{EE}$ ).....+8.5V  
 Voltage on Any Other Pin.....( $V_{EE} - 0.3V$ ) to ( $V_{CC} + 0.3V$ )  
 Short-Circuit Duration ( $V_{OUT}$  to  $V_{CC}$  or  $V_{EE}$ ).....Continuous  
 Continuous Power Dissipation ( $T_A = +70^\circ\text{C}$ )  
   8-Pin  $\mu\text{MAX}$  (derate 4.10mW/ $^\circ\text{C}$  above  $+70^\circ\text{C}$ ).....330mW  
   16-Pin QSOP (derate 8.33mW/ $^\circ\text{C}$  above  $+70^\circ\text{C}$ ).....667mW  
   8-Pin SO (derate 5.9mW/ $^\circ\text{C}$  above  $+70^\circ\text{C}$ ).....471mW  
   14-Pin SO (derate 8.33mW/ $^\circ\text{C}$  above  $+70^\circ\text{C}$ ).....667mW

Operating Temperature Range .....-40 $^\circ\text{C}$  to +85 $^\circ\text{C}$   
 Storage Temperature Range .....-65 $^\circ\text{C}$  to +150 $^\circ\text{C}$   
 Junction Temperature .....+150 $^\circ\text{C}$   
 Lead Temperature (soldering, 10s) .....+300 $^\circ\text{C}$

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

## DC ELECTRICAL CHARACTERISTICS

( $V_{CC} = +5V$ ,  $V_{EE} = 0$ ,  $R_L = 100\Omega$  to  $V_{CC}/2$ ,  $V_{CM} = V_{CC}/2$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^\circ\text{C}$ .)

| PARAMETER  | SYMBOL       | CONDITIONS   | MIN            | TYP      | MAX            | UNITS                        |
|--|--------------|--|----------------|----------|----------------|------------------------------|
| Operating Supply Voltage Range                       | $V_{CC}$     | Inferred from PSRR test  | 4.5            |          | 8.0            | V                            |
| Common-Mode Input Voltage                            | $V_{CM}$     | Inferred from CMRR test  | $V_{EE} + 1.6$ |          | $V_{CC} - 1.6$ | V                            |
| Input Offset Voltage                                 | $V_{OS}$     |  |                | 1        | 9              | mV                           |
| Input Offset Voltage Drift                           | $TCV_{OS}$   |  |                | 1.5      |                | $\mu\text{V}/^\circ\text{C}$ |
| Input Offset Voltage Channel Matching                |              | MAX4268/MAX4269/MAX4270  |                | 1        |                | mV                           |
| Input Bias Current                                   | $I_B$        |  |                | 3.5      | 40             | $\mu\text{A}$                |
| Input Offset Current                                 | $I_{OS}$     |  |                | 0.1      | 6              | $\mu\text{A}$                |
| Common-Mode Input Resistance                         | $R_{INCM}$   | Either input ( $V_{EE} + 1.6V$ ) $\leq V_{CM} \leq (V_{CC} - 1.6V)$      |                | 1        |                | $M\Omega$                    |
| Differential Input Resistance                        | $R_{INDIFF}$ | $-10mV \leq V_{IN} \leq 10mV$  |                | 40       |                | $k\Omega$                    |
| Common-Mode Rejection Ratio                          | CMRR         | ( $V_{EE} + 1.6V$ ) $\leq V_{CM} \leq (V_{CC} - 1.6V)$ , no load         | 60             | 85       |                | dB                           |
| Power-Supply Rejection Ratio                         | PSRR         | $V_{CC} = 4.5V$ to $8.0V$  | 60             | 85       |                | dB                           |
| Open-Loop Voltage Gain                               | $A_{OL}$     | $1.75V \leq V_{OUT} \leq 3.25V$  | 60             | 95       |                | dB                           |
| Output Voltage Swing                                 | $V_{OUT}$    | $V_{CC} - V_{OH}$ , $V_{OL} - V_{EE}$                                    |                | 1.1      | 1.5            | V                            |
| Output Current Drive                                 | $I_{OUT}$    | $R_L = 20\Omega$   | $\pm 30$       | $\pm 45$ |                | mA                           |
| Output Short-Circuit Current                         | $I_{SC}$     | Sinking or sourcing to $V_{CC}$ or $V_{EE}$                              |                | 100      |                | mA                           |
| Closed-Loop Output Resistance                        | $R_{OUT}$    |  |                | 0.035    |                | $\Omega$                     |
| Power-Up Time  | $t_{PWRUP}$  | $V_{OUT} = 1V$ step, 0.1% settling time                                  |                | 10       |                | $\mu\text{s}$                |
| Quiescent Supply Current (per amplifier)             | $I_S$        | Normal mode, $\overline{\text{DISABLE}} = V_{CC}$ or floating            |                | 28       | 32             | mA                           |
|  |              | Disable mode, $\overline{\text{DISABLE}} = V_{EE}$                       |                | 1.6      | 5              |                              |
| Disable Output Leakage Current                       |              | $\overline{\text{DISABLE}} = V_{EE}$ , $V_{EE} \leq V_{OUT} \leq V_{CC}$ |                | 0.2      | 2.5            | $\mu\text{A}$                |
| $\overline{\text{DISABLE}}$ Logic Low                |              |  |                |          | $V_{CC} - 3.5$ | V                            |
| $\overline{\text{DISABLE}}$ Logic High               |              |  | $V_{CC} - 1.5$ |          |                | V                            |
| $\overline{\text{DISABLE}}$ Logic Input Low Current  |              | $\overline{\text{DISABLE}} = V_{EE}$                                     |                | 5        | 100            | $\mu\text{A}$                |
| $\overline{\text{DISABLE}}$ Logic Input High Current |              | $\overline{\text{DISABLE}} = V_{CC}$                                     |                | 1        | 30             | $\mu\text{A}$                |

# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable

**MAX4265-MAX4270**

## AC ELECTRICAL CHARACTERISTICS

( $V_{CC} = +5V$ ,  $V_{EE} = 0$ ,  $R_L = 100\Omega$  to  $V_{CC}/2$ ,  $V_{CM} = V_{CC}/2$ , MAX4265/MAX4268  $A_V = +1V/V$ , MAX4266/MAX4269  $A_V = +2V/V$ , MAX4267/MAX4270  $A_V = +5V/V$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^\circ C$ .)

| PARAMETER                   | SYMBOL      | CONDITIONS   | MIN            | TYP | MAX | UNITS      |
|-----------------------------|-------------|--|----------------|-----|-----|------------|
| Small-Signal -3dB Bandwidth | BW-3dB      | $V_{OUT} = 100mVp-p$                                   | MAX4265        | 400 |     | MHz        |
|                             |             |  | MAX4266        | 350 |     |            |
|                             |             |  | MAX4267        | 300 |     |            |
|                             |             |  | MAX4268        | 300 |     |            |
|                             |             |  | MAX4269        | 350 |     |            |
|                             |             |  | MAX4270        | 200 |     |            |
| Full-Power Bandwidth        | FPBW        | $V_{OUT} = 1Vp-p$                                      | MAX4265        | 270 |     | MHz        |
|                             |             |  | MAX4266        | 350 |     |            |
|                             |             |  | MAX4267        | 300 |     |            |
|                             |             |  | MAX4268        | 175 |     |            |
|                             |             |  | MAX4269        | 200 |     |            |
|                             |             |  | MAX4270        | 200 |     |            |
| 0.1dB Gain Flatness         | BW0.1dB     | $V_{OUT} = 100mVp-p$                                   | MAX4265        | 80  |     | MHz        |
|                             |             |  | MAX4266        | 30  |     |            |
|                             |             |  | MAX4267        | 55  |     |            |
|                             |             |  | MAX4268        | 100 |     |            |
|                             |             |  | MAX4269        | 35  |     |            |
|                             |             |  | MAX4270        | 35  |     |            |
| All-Hostile Crosstalk       |             | $f = 10MHz$  |                | 85  |     | dB         |
| Slew Rate                   | SR          | $V_{OUT} = +1V$ step                                   |                | 900 |     | V/ $\mu s$ |
| Rise/Fall Times             | $t_R, t_F$  | $V_{OUT} = +1V$ step                                   |                | 1   |     | ns         |
| Settling Time (0.1%)        | $t_{S,0.1}$ | $V_{OUT} = +1V$ step                                   |                | 15  |     | ns         |
| Spurious-Free Dynamic Range | SFDR        | $V_{OUT} = 1Vp-p$<br>(MAX4265/<br>MAX4266/<br>MAX4267) | $f_C = 1MHz$   | 83  |     | dBc        |
|                             |             |  | $f_C = 5MHz$   | 85  |     |            |
|                             |             |  | $f_C = 10MHz$  | 87  |     |            |
|                             |             |  | $f_C = 20MHz$  | 81  |     |            |
|                             |             |  | $f_C = 60MHz$  | 50  |     |            |
|                             |             |  | $f_C = 100MHz$ | 47  |     |            |
|                             |             | $V_{OUT} = 1Vp-p$<br>(MAX4268)                         | $f_C = 1MHz$   | 85  |     |            |
|                             |             |  | $f_C = 5MHz$   | 85  |     |            |
|                             |             |  | $f_C = 10MHz$  | 84  |     |            |
|                             |             |  | $f_C = 20MHz$  | 79  |     |            |
|                             |             |  | $f_C = 60MHz$  | 68  |     |            |
|                             |             |  | $f_C = 100MHz$ | 60  |     |            |

# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable

## AC ELECTRICAL CHARACTERISTICS (continued)

( $V_{CC} = +5V$ ,  $V_{EE} = 0$ ,  $R_L = 100\Omega$  to  $V_{CC}/2$ ,  $V_{CM} = V_{CC}/2$ , MAX4265/MAX4268  $A_V = +1V/V$ , MAX4266/MAX4269  $A_V = +2V/V$ , MAX4267/MAX4270  $A_V = +5V/V$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^\circ C$ .)

| PARAMETER                         | SYMBOL         | CONDITIONS                        | MIN            | TYP   | MAX          | UNITS |  |    |     |
|-----------------------------------|----------------|-----------------------------------|----------------|---|--------------|-------|--|----|-----|
| Spurious-Free Dynamic Range       | SFDR           | $V_{OUT} = 1V_{p-p}$<br>(MAX4269) | $f_C = 1MHz$   |   | 88           | dBc   |  |    |     |
|                                   |                |                                   | $f_C = 5MHz$   |   | 90           |       |  |    |     |
|                                   |                |                                   | $f_C = 10MHz$  |   | 88           |       |  |    |     |
|                                   |                |                                   | $f_C = 20MHz$  |   | 79           |       |  |    |     |
|                                   |                |                                   | $f_C = 60MHz$  |   | 68           |       |  |    |     |
|                                   |                |                                   | $f_C = 100MHz$ |   | 59           |       |  |    |     |
|                                   |                | $V_{OUT} = 1V_{p-p}$<br>(MAX4270) | $f_C = 1MHz$   |   | 86           |       |  |    |     |
|                                   |                |                                   | $f_C = 5MHz$   |   | 81           |       |  |    |     |
|                                   |                |                                   | $f_C = 10MHz$  |   | 75           |       |  |    |     |
|                                   |                |                                   | $f_C = 20MHz$  |   | 68           |       |  |    |     |
|                                   |                |                                   | $f_C = 60MHz$  |   | 60           |       |  |    |     |
|                                   |                |                                   | $f_C = 100MHz$ |   | 56           |       |  |    |     |
|                                   |                | Second Harmonic Distortion        |                | $V_{OUT} = 1V_{p-p}$<br>(MAX4265/<br>MAX4266/<br>MAX4267) | $f_C = 1MHz$ |       |  | 83 | dBc |
|                                   |                |                                   |                |   | $f_C = 5MHz$ |       |  | 85 |     |
| $f_C = 10MHz$                     |                |                                   |                |   | 87           |       |  |    |     |
| $f_C = 20MHz$                     |                |                                   |                |   | 81           |       |  |    |     |
| $f_C = 60MHz$                     |                |                                   |                |   | 50           |       |  |    |     |
| $f_C = 100MHz$                    |                |                                   |                |   | 47           |       |  |    |     |
| $V_{OUT} = 1V_{p-p}$<br>(MAX4268) | $f_C = 1MHz$   |                                   |                |   | 85           |       |  |    |     |
|                                   | $f_C = 5MHz$   |                                   |                |   | 85           |       |  |    |     |
|                                   | $f_C = 10MHz$  |                                   |                |   | 84           |       |  |    |     |
|                                   | $f_C = 20MHz$  |                                   |                |   | 79           |       |  |    |     |
|                                   | $f_C = 60MHz$  |                                   |                |   | 68           |       |  |    |     |
|                                   | $f_C = 100MHz$ |                                   |                |   | 60           |       |  |    |     |
| $V_{OUT} = 1V_{p-p}$<br>(MAX4269) | $f_C = 1MHz$   |                                   |                |   | 88           |       |  |    |     |
|                                   | $f_C = 5MHz$   |                                   |                |   | 90           |       |  |    |     |
|                                   | $f_C = 10MHz$  |                                   |                |   | 88           |       |  |    |     |
|                                   | $f_C = 20MHz$  |                                   |                |   | 79           |       |  |    |     |
|                                   | $f_C = 60MHz$  |                                   |                |   | 68           |       |  |    |     |
|                                   | $f_C = 100MHz$ |                                   |                |   | 59           |       |  |    |     |
| $V_{OUT} = 1V_{p-p}$<br>(MAX4270) | $f_C = 1MHz$   |                                   |                |   | 86           |       |  |    |     |
|                                   | $f_C = 5MHz$   |                                   |                |   | 81           |       |  |    |     |
|                                   | $f_C = 10MHz$  |                                   |                |   | 75           |       |  |    |     |
|                                   | $f_C = 20MHz$  |                                   |                |   | 68           |       |  |    |     |
|                                   | $f_C = 60MHz$  |                                   |                |   | 60           |       |  |    |     |
|                                   | $f_C = 100MHz$ |                                   |                |   | 56           |       |  |    |     |

# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable

**MAX4265-MAX4270**

## AC ELECTRICAL CHARACTERISTICS (continued)

( $V_{CC} = +5V$ ,  $V_{EE} = 0$ ,  $R_L = 100\Omega$  to  $V_{CC}/2$ ,  $V_{CM} = V_{CC}/2$ , MAX4265/MAX4268  $A_V = +1V/V$ , MAX4266/MAX4269  $A_V = +2V/V$ , MAX4267/MAX4270  $A_V = +5V/V$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^\circ C$ .)

| PARAMETER                                  | SYMBOL | CONDITIONS  | MIN             | TYP | MAX | UNITS |
|--|--------|---|-----------------|-----|-----|-------|
| Third Harmonic Distortion                  |        | $V_{OUT} = 1V_{p-p}$<br>(MAX4265/<br>MAX4266/<br>MAX4267)           | $f_C = 1MHz$    |     | 98  | dBc   |
|  |        |   | $f_C = 5MHz$    |     | 96  |       |
|  |        |   | $f_C = 10MHz$   |     | 91  |       |
|  |        |   | $f_C = 20MHz$   |     | 85  |       |
|  |        |   | $f_C = 60MHz$   |     | 75  |       |
|  |        |   | $f_C = 100MHz$  |     | 61  |       |
|  |        | $V_{OUT} = 1V_{p-p}$<br>(MAX4268)                                   | $f_C = 1MHz$    |     | 95  |       |
|  |        |   | $f_C = 5MHz$    |     | 95  |       |
|  |        |   | $f_C = 10MHz$   |     | 93  |       |
|  |        |   | $f_C = 20MHz$   |     | 86  |       |
|  |        |   | $f_C = 60MHz$   |     | 72  |       |
|  |        |   | $f_C = 100MHz$  |     | 64  |       |
|  |        | $V_{OUT} = 1V_{p-p}$<br>(MAX4269)                                   | $f_C = 1MHz$    |     | 88  |       |
|  |        |   | $f_C = 5MHz$    |     | 90  |       |
|  |        |   | $f_C = 10MHz$   |     | 88  |       |
|  |        |   | $f_C = 20MHz$   |     | 79  |       |
|  |        |   | $f_C = 60MHz$   |     | 68  |       |
|  |        |   | $f_C = 100MHz$  |     | 59  |       |
|  |        | $V_{OUT} = 1V_{p-p}$<br>(MAX4270)                                   | $f_C = 1MHz$    |     | 96  |       |
|  |        |   | $f_C = 5MHz$    |     | 97  |       |
|  |        |   | $f_C = 10MHz$   |     | 91  |       |
|  |        |   | $f_C = 20MHz$   |     | 84  |       |
|  |        |   | $f_C = 60MHz$   |     | 74  |       |
|  |        |   | $f_C = 100MHz$  |     | 69  |       |
| Two-Tone, Third-Order Intercept Distortion | IP3    | $V_{OUT} = 1V_{p-p}$ ,<br>$f_{CA} = 20MHz$ ,<br>$f_{CB} = 21.25MHz$ | MAX4265/MAX4268 |     | 32  | dBm   |
|  |        |   | MAX4266/MAX4269 |     | 35  |       |
|  |        |   | MAX4267/MAX4270 |     | 35  |       |

# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable


## AC ELECTRICAL CHARACTERISTICS (continued)

( $V_{CC} = +5V$ ,  $V_{EE} = 0$ ,  $R_L = 100\Omega$  to  $V_{CC}/2$ ,  $V_{CM} = V_{CC}/2$ , MAX4265/MAX4268  $A_V = +1V/V$ , MAX4266/MAX4269  $A_V = +2V/V$ , MAX4267/MAX4270  $A_V = +5V/V$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^\circ C$ .)

| PARAMETER                    | SYMBOL    | CONDITIONS  | MIN             | TYP   | MAX | UNITS          |
|------------------------------|-----------|---|-----------------|-------|-----|----------------|
| Input -1dB Compression Point |           | $f_C = 20MHz$   |                 | 12    |     | dBm            |
| Differential Gain            | $D_G$     | NTSC, $f = 3.58MHz$ , $R_L = 150\Omega$ to $V_{CC}/2$ |                 | 0.015 |     | %              |
| Differential Phase           | $D_P$     | NTSC, $f = 3.58MHz$ , $R_L = 150\Omega$ to $V_{CC}/2$ |                 | 0.03  |     | degrees        |
| Input Capacitance            | $C_{IN}$  |   |                 | 2     |     | pF             |
| Output Impedance             | $R_{OUT}$ | $f = 10MHz$   |                 | 1     |     | $\Omega$       |
| Disabled Output Capacitance  |           | $\overline{DISABLE}_- = V_{EE}$                       |                 | 5     |     | pF             |
| Enable Time                  | $t_{EN}$  | $V_{IN} = +1V$  |                 | 100   |     | ns             |
| Disable Time                 | $t_{DIS}$ | $V_{IN} = +1V$  |                 | 750   |     | $\mu s$        |
| Capacitive Load Stability    |           | No sustained oscillation                              | MAX4265/MAX4268 | 15    |     | pF             |
|                              |           |   | MAX4266/MAX4269 | 15    |     |                |
|                              |           |   | MAX4267/MAX4270 | 22    |     |                |
| Input Voltage Noise Density  | $e_n$     | $f = 1kHz$  |                 | 8     |     | $nV/\sqrt{Hz}$ |
| Input Current Noise Density  | $i_n$     | $f = 1kHz$  |                 | 1     |     | $pA/\sqrt{Hz}$ |

## Typical Operating Characteristics

( $V_{CC} = +5V$ ,  $V_{EE} = 0$ ,  $\overline{DISABLE}_- = +5V$ ,  $R_L = 100\Omega$  to  $V_{CC}/2$ , MAX4265/MAX4268  $A_V = +1V/V$ , MAX4266/MAX4269  $A_V = +2V/V$ , MAX4267/MAX4270  $A_V = +5V/V$ ,  $T_A = +25^\circ C$ , unless otherwise noted.)












# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable

MAX4265-MAX4270

## Typical Operating Characteristics (continued)






( $V_{CC} = +5V$ ,  $V_{EE} = 0$ ,  $\overline{DISABLE} = +5V$ ,  $R_L = 100\Omega$  to  $V_{CC}/2$ , MAX4265/MAX4268  $A_V = +1V/V$ , MAX4266/MAX4269  $A_V = +2V/V$ , MAX4267/MAX4270  $A_V = +5V/V$ ,  $T_A = +25^\circ C$ , unless otherwise noted.)



# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable

## Typical Operating Characteristics (continued)

( $V_{CC} = +5V$ ,  $V_{EE} = 0$ ,  $\overline{DISABLE}_- = +5V$ ,  $R_L = 100\Omega$  to  $V_{CC}/2$ , MAX4265/MAX4268  $A_V = +1V/V$ , MAX4266/MAX4269  $A_V = +2V/V$ , MAX4267/MAX4270  $A_V = +5V/V$ ,  $T_A = +25^\circ C$ , unless otherwise noted.)











# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable

**MAX4265-MAX4270**

## Typical Operating Characteristics (continued)

( $V_{CC} = +5V$ ,  $V_{EE} = 0$ ,  $\overline{DISABLE} = +5V$ ,  $R_L = 100\Omega$  to  $V_{CC}/2$ , MAX4265/MAX4268  $A_V = +1V/V$ , MAX4266/MAX4269  $A_V = +2V/V$ , MAX4267/MAX4270  $A_V = +5V/V$ ,  $T_A = +25^\circ C$ , unless otherwise noted.)



# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable


## Typical Operating Characteristics (continued)

( $V_{CC} = +5V$ ,  $V_{EE} = 0$ ,  $\overline{DISABLE} = +5V$ ,  $R_L = 100\Omega$  to  $V_{CC}/2$ , MAX4265/MAX4268  $A_V = +1V/V$ , MAX4266/MAX4269  $A_V = +2V/V$ , MAX4267/MAX4270  $A_V = +5V/V$ ,  $T_A = +25^\circ C$ , unless otherwise noted.)


**POWER-UP/POWER-DOWN RESPONSE**




**DISABLE/ENABLE RESPONSE**




**INPUT OFFSET VOLTAGE vs. SUPPLY VOLTAGE**




**INPUT BIAS CURRENT vs. SUPPLY VOLTAGE**




**SUPPLY CURRENT (PER AMPLIFIER) vs. SUPPLY VOLTAGE**




**INPUT OFFSET VOLTAGE vs. TEMPERATURE**




**INPUT BIAS CURRENT vs. TEMPERATURE**



**INPUT OFFSET CURRENT vs. TEMPERATURE**



**SUPPLY CURRENT (PER AMPLIFIER) vs. TEMPERATURE**



# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable

**MAX4265-MAX4270**

## Typical Operating Characteristics (continued)

( $V_{CC} = +5V$ ,  $V_{EE} = 0$ ,  $\overline{DISABLE}_- = +5V$ ,  $R_L = 100\Omega$  to  $V_{CC}/2$ , MAX4265/MAX4268  $A_V = +1V/V$ , MAX4266/MAX4269  $A_V = +2V/V$ , MAX4267/MAX4270  $A_V = +5V/V$ ,  $T_A = +25^\circ C$ , unless otherwise noted.)



# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable

## Pin Description

| PIN                           |                               |              | NAME   | FUNCTION   |
|-------------------------------|-------------------------------|--------------|--|--|
| MAX4265<br>MAX4266<br>MAX4267 | MAX4268<br>MAX4269<br>MAX4270 |              |  |  |
| 8 $\mu$ MAX/SO                | 14 SO                         | 16 QSOP      |  |  |
| 1                             | —                             | —            | $\overline{\text{DISABLE}}$                              | Disable Input. Active low.                                 |
| —                             | 4, 5                          | 4, 5         | $\overline{\text{DISABLEA}}, \overline{\text{DISABLEB}}$ | Disable Input. Active low.                                 |
| 2                             | —                             | —            | IN-  | Inverting Input  |
| —                             | 2, 9                          | 2, 11        | INA-, INB-   | Inverting Input  |
| 3                             | —                             | —            | IN+  | Noninverting Input   |
| —                             | 3, 10                         | 3, 12        | INA+, INB+   | Noninverting Input   |
| 4, 5                          | 6, 7                          | 6, 7         | V <sub>EE</sub>  | Negative Power Supply                                      |
| 6                             | —                             | —            | OUT  | Amplifier Output   |
| —                             | 1, 8                          | 1, 10        | OUTA, OUTB   | Amplifier Output   |
| 7, 8                          | 13, 14                        | 15, 16       | V <sub>CC</sub>  | Positive Power Supply. Connect to a +4.5V to +8.0V supply. |
| —                             | 11, 12                        | 8, 9, 13, 14 | N.C.   | No Connection. Not internally connected.                   |

### Detailed Description

The MAX4265–MAX4270 family of operational amplifiers features ultra-low distortion and wide bandwidth. Their low distortion and low noise make them ideal for driving high-speed ADCs up to 16 bits in telecommunication applications and high-performance signal processing.

These devices can drive a 100 $\Omega$  load and deliver 45mA while maintaining DC accuracy and AC performance. The input common-mode voltage ranges from (V<sub>EE</sub> + 1.6V) to (V<sub>CC</sub> - 1.6V), while the output typically swings to within 1.1V of the rails.

### Low Distortion

The MAX4265–MAX4270 use proprietary bipolar technology to achieve minimum distortion in low-voltage systems. This feature is typically available only in dual-supply op amps.

Several factors can affect the noise and distortion that a device contributes to the input signal. The following guidelines explain how various design choices impact the total harmonic distortion (THD):

- Choose the proper feedback-resistor and gain-resistor values for the application. In general, the smaller the closed-loop gain, the smaller the THD generated, especially when driving heavy resistive loads. Large-value feedback resistors can significantly improve distortion. The MAX4265–MAX4270's THD normally increases at approximately 20dB per decade at frequencies above 1MHz; this is a lower rate than that of comparable dual-supply op amps.
- Operating the device near or above the full-power bandwidth significantly degrades distortion (see the Total Harmonic Distortion vs. Frequency graph in the *Typical Operating Characteristics*).
- The decompensated devices (MAX4266/MAX4267/MAX4269/MAX4270) deliver the best distortion performance since they have a slightly higher slew rate and provide a higher amount of loop gain for a given closed-loop gain setting.

# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable

MAX4265-MAX4270

## Choosing Resistor Values

### Unity-Gain Configurations

The MAX4265 and MAX4268 are internally compensated for unity gain. When configured for unity gain, they require a small resistor ( $R_F$ ) in series with the feedback path (Figure 1). This resistor improves AC response by reducing the Q of the tank circuit, which is formed by parasitic feedback inductance and capacitance.

### Inverting and Noninverting Configurations

The values of the gain-setting feedback and input resistors are important design considerations. Large resistor values will increase voltage noise and interact with the amplifier's input and PC board capacitance to generate undesirable poles and zeros, which can decrease bandwidth or cause oscillations. For example, a noninverting gain of +2V/V (Figure 1) using  $R_F = R_G = 1k\Omega$  combined with 2pF of input capacitance and 0.5pF of board capacitance will cause a feedback pole at 128MHz. If this pole is within the anticipated amplifier bandwidth, it will jeopardize stability. Reducing the 1k $\Omega$  resistors to 100 $\Omega$  extends the pole frequency to 1.28GHz, but could limit output swing by adding 200 $\Omega$  in parallel with the amplifier's load. Clearly, the selection of resistor values must be tailored to the specific application.

### Distortion Considerations

The MAX4265-MAX4270 are ultra-low-distortion, high-bandwidth op amps. Output distortion will degrade as the total load resistance seen by the amplifier decreases. To minimize distortion, keep the input and gain-setting resistor values relatively large. A 500 $\Omega$  feedback resistor combined with an appropriate input resistor to set the gain will provide excellent AC performance without significantly increasing distortion.

### Noise Considerations

The amplifier's input-referred noise-voltage density is dominated by flicker noise at lower frequencies and by thermal noise at higher frequencies. Because the thermal noise contribution is affected by the parallel combination of the feedback resistive network, those resistor values should be reduced in cases where the system bandwidth is large and thermal noise is dominant. This noise-contribution factor decreases, however, with increasing gain settings. For example, the input noise voltage density at the op amp input with a gain of +10V/V using  $R_F = 100k\Omega$  and  $R_G = 11k\Omega$  is  $e_n = 18nV/\sqrt{Hz}$ . The input noise can be reduced to 8nV/ $\sqrt{Hz}$  by choosing  $R_F = 1k\Omega$ ,  $R_G = 110\Omega$ .

## Driving Capacitive Loads

The MAX4265-MAX4270 are not designed to drive highly reactive loads. Stability is maintained with loads up to 15pF with less than 2dB peaking in the frequency response. To drive higher capacitive loads, place a small isolation resistor in series between the amplifier's output and the capacitive load (Figure 1). This resistor improves the amplifier's phase margin by isolating the capacitor from the op amp's output.

To ensure a load capacitance that limits peaking to less than 2dB, select a resistance value from Figure 2. For example, if the capacitive load is 100pF, the corresponding isolation resistor is 6 $\Omega$  (MAX4266/MAX4269). Figures 3 and 4 show the peaking that occurs in the frequency response with and without an isolation resistor.

Coaxial cable and other transmission lines are easily driven when terminated at both ends with their characteristic impedance. When driving back-terminated transmission lines, the capacitive load of the transmission line is essentially eliminated.

## ADC Input Buffer

Input buffer amplifiers can be a source of significant errors in high-speed ADC applications. The input buffer is usually required to rapidly charge and discharge the ADC's input, which is often capacitive (see *Driving Capacitive Loads*). In addition, since a high-speed ADC's input impedance often changes very rapidly during the conversion cycle, measurement accuracy must



Figure 1. Noninverting Configuration

# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable

be maintained using an amplifier with very low output impedance at high frequencies. The combination of high speed, fast slew rate, low noise, and a low and stable distortion overload makes the MAX4265-MAX4270 ideally suited for use as buffer amplifiers in high-speed ADC applications.

### Low-Power Disable Mode

The MAX4265-MAX4270 feature an active-low disable mode that can be used to save power and place the outputs in a high-impedance state. Drive DISABLE\_ with logic levels, or connect DISABLE\_ to VCC for normal operation. In the dual versions (MAX4268/ MAX4269/ MAX4270), each individual op amp is disabled separately, allowing the devices to be used in a multiplex configuration. The supply current in low-power mode is reduced to 1.6mA per amplifier. Enable time is typically 100ns, and disable time is typically 750μs.




Figure 2. MAX4265-MAX4270 Isolation Resistance vs. Capacitive Load




Figure 3a. MAX4268 Small-Signal Gain vs. Frequency Without Isolation Resistor




Figure 3b. MAX4269 Small-Signal Gain vs. Frequency Without Isolation Resistor




Figure 3c. MAX4270 Small-Signal Gain vs. Frequency Without Isolation Resistor




Figure 4a. MAX4268 Small-Signal Gain vs. Frequency With Isolation Resistor

# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable

MAX4265-MAX4270




Figure 4b. MAX4269 Small-Signal Gain vs. Frequency With Isolation Resistor




Figure 4c. MAX4270 Small-Signal Gain vs. Frequency With Isolation Resistor

## Power Supplies, Bypassing, and Layout

The MAX4265–MAX4270 operate from a single +4.5V to +8.0V supply or in a dual-supply configuration.

When operating with a single supply, connect the VEE pins directly to the ground plane. Bypass VCC to ground with ceramic chip capacitors. Due to the MAX4265–MAX4270s' wide bandwidth, use a 1nF capacitor in parallel with a 0.1μF to 1μF capacitor. If the device is located more than 10cm from the power supply, adding a larger bulk capacitor will improve performance.

When operating with dual supplies, ensure that the total voltage across the device (VCC to VEE) does not exceed +8V. Therefore, supplies of ±2.5V, ±3.3V, and asymmetrical supplies are possible. For example, operation with VCC = +5V and VEE = -3V provides sufficient voltage swing for the negative pulses found in video signals. When operating with dual supplies, the VCC pins and the VEE pins should be bypassed using the same guidelines stated in the paragraph above.

Because the MAX4265–MAX4270 have high bandwidth, circuit layout becomes critical. A solid ground plane provides a low-inductance path for high-speed transient currents. Use multiple vias to the ground plane for each bypass capacitor. If VEE is connected to ground, use multiple vias here, too. Avoid sharing ground vias with other signals to reduce crosstalk between circuit sections.

Avoid stray capacitance at the op amp's inverting inputs. Stray capacitance, in conjunction with the feedback resistance, forms an additional pole in the circuit's transfer function, with its associate phase shift. Minimizing the trace lengths connected to the inverting input helps minimize stray capacitance.

## Chip Information


MAX4265/66/67 TRANSISTOR COUNT: 132

MAX4268/69/70 TRANSISTOR COUNT: 285

PROCESS: Bipolar

# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable

## Pin Configurations





# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable

## Package Information

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to [www.maxim-ic.com/packages](http://www.maxim-ic.com/packages).)

MAX4265-MAX4270



8L uMAX/uSOP

**DALLAS SEMICONDUCTOR** **MAXIM**

PROPRIETARY INFORMATION

TITLE:  
PACKAGE OUTLINE, 8L uMAX/uSOP


|          |                                 |        |     |
|----------|---------------------------------|--------|-----|
| APPROVAL | DOCUMENT CONTROL NO.<br>21-0036 | REV. J | 1/1 |
|----------|---------------------------------|--------|-----|

# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable


## Package Information (continued)

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to [www.maxim-ic.com/packages](http://www.maxim-ic.com/packages).)


SOICN, EPS



TOP VIEW



FRONT VIEW



SIDE VIEW

| DIM | INCHES    |       | MILLIMETERS |      |
|-----|-----------|-------|-------------|------|
|     | MIN       | MAX   | MIN         | MAX  |
| A   | 0.053     | 0.069 | 1.35        | 1.75 |
| A1  | 0.004     | 0.010 | 0.10        | 0.25 |
| B   | 0.014     | 0.019 | 0.35        | 0.49 |
| C   | 0.007     | 0.010 | 0.19        | 0.25 |
| e   | 0.050 BSC |       | 1.27 BSC    |      |
| E   | 0.150     | 0.157 | 3.80        | 4.00 |
| H   | 0.228     | 0.244 | 5.80        | 6.20 |
| L   | 0.016     | 0.050 | 0.40        | 1.27 |

VARIATIONS:

| DIM | INCHES |       | MILLIMETERS |       | N  | MS012 |
|-----|--------|-------|-------------|-------|----|-------|
|     | MIN    | MAX   | MIN         | MAX   |    |       |
| D   | 0.189  | 0.197 | 4.80        | 5.00  | 8  | AA    |
| D   | 0.337  | 0.344 | 8.55        | 8.75  | 14 | AB    |
| D   | 0.386  | 0.394 | 9.80        | 10.00 | 16 | AC    |

**NOTES:**

1. D&E DO NOT INCLUDE MOLD FLASH.
2. MOLD FLASH OR PROTRUSIONS NOT TO EXCEED 0.15mm (.006").
3. LEADS TO BE COPLANAR WITHIN 0.10mm (.004").
4. CONTROLLING DIMENSION: MILLIMETERS.
5. MEETS JEDEC MS012.
6. N = NUMBER OF PINS.

|  |                                     |                     |                    |
|--|-------------------------------------|---------------------|--------------------|
| <b>DALLAS SEMICONDUCTOR</b>            |                                     | <b>MAXIM</b>        |                    |
| <small>PROPRIETARY INFORMATION</small> |                                     |                     |                    |
| <small>TITLE:</small>                  |                                     |                     |                    |
| <b>PACKAGE OUTLINE, .150" SOIC</b>     |                                     |                     |                    |
| <small>APPROVAL</small>                | <small>DOCUMENT CONTROL NO.</small> | <small>REV.</small> | <small>1/1</small> |
|  | 21-0041                             | B                   |                    |


# Ultra-Low-Distortion, +5V, 400MHz Op Amps with Disable

## Package Information (continued)

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to [www.maxim-ic.com/packages](http://www.maxim-ic.com/packages).)

MAX4265-MAX4270

QSOPEPS



| DIM | INCHES         |       | MILLIMETERS |       |
|-----|----------------|-------|-------------|-------|
|     | MIN            | MAX   | MIN         | MAX   |
| A   | .061           | .068  | 1.55        | 1.73  |
| A1  | .004           | .0098 | 0.102       | 0.249 |
| A2  | .055           | .061  | 1.40        | 1.55  |
| B   | .008           | .012  | 0.20        | 0.31  |
| C   | .0075          | .0098 | 0.191       | 0.249 |
| D   | SEE VARIATIONS |       |             |       |
| E   | .150           | .157  | 3.81        | 3.99  |
| e   | .025 BSC       |       | 0.635 BSC   |       |
| H   | .230           | .244  | 5.84        | 6.20  |
| h   | .010           | .016  | 0.25        | 0.41  |
| L   | .016           | .035  | 0.41        | 0.89  |
| N   | SEE VARIATIONS |       |             |       |
| X   | SEE VARIATIONS |       |             |       |
| Y   | .071           | .087  | 1.803       | 2.209 |
| α   | 0°             | 8°    | 0°          | 8°    |

### VARIATIONS:

| DIM | INCHES |       | MILLIMETERS |       | N     |
|-----|--------|-------|-------------|-------|-------|
|     | MIN.   | MAX.  | MIN.        | MAX.  |       |
| D   | .189   | .196  | 4.80        | 4.98  | 16 AA |
| S   | .0020  | .0070 | 0.05        | 0.18  |       |
| X   | .107   | .123  | 2.72        | 3.12  |       |
| D   | .337   | .344  | 8.56        | 8.74  | 20 AB |
| S   | .0500  | .0550 | 1.270       | 1.397 |       |
| D   | .337   | .344  | 8.56        | 8.74  | 24 AC |
| S   | .0250  | .0300 | 0.635       | 0.762 |       |
| D   | .386   | .393  | 9.80        | 9.98  | 28 AD |
| S   | .0250  | .0300 | 0.635       | 0.762 |       |
| X   | .271   | .287  | 6.88        | 7.29  |       |

### NOTES:

1. D & E DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS.
2. MOLD FLASH OR PROTRUSIONS NOT TO EXCEED .006" PER SIDE.
3. HEAT SLUG DIMENSIONS X AND Y APPLY ONLY TO 16 AND 28 LEAD POWER-QSOP PACKAGES.
4. CONTROLLING DIMENSIONS: INCHES.
5. MEETS JEDEC MO137.

**MAXIM**

PROPRIETARY INFORMATION

TITLE:  
PACKAGE OUTLINE, QSOP, .150", .025" LEAD PITCH

|          |                      |       |
|----------|----------------------|-------|
| APPROVAL | DOCUMENT CONTROL NO. | REV   |
|          | 21-0055              | C 1/1 |

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600 \_\_\_\_\_ 19



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.