

Component Housings

Weidmuller DK 4 and DKT 4 modular terminals are suitable for the installation of electronic components with a maximum diameter or width of 4.5 mm. Four independent clamping yoke screw connections are available for this purpose. A snap-on contour frame expands the installation space in the DK 4 by 6 mm. Depending on type, these modular terminals are suitable for mounting on TS 32, TS 35 x 7.5 or TS 35 x 15 mounting rails according to European Standards EN 50035 and EN 50022.

Weidmuller WDK 2.5 modular terminals are suitable for the installation of electronic components with a maximum width of 4 mm. Up to four independent clamping yoke screw connections or four 6.3 x 0.8 tab connections are available for this purpose. These modular terminals are suitable for mounting on TS 35 x 7.5 or TS 35 x 15 mounting rails.

Weidmuller EG 1 housings have four screw connections and, as accessories, up to four 0.8 x 2.8 or 0.8 x 4.8 mm solder/tab connections on a width of 18 mm. The screw clamp busbar ends with a solder ring inside the housing. Two end plates seal the module. Depending on type, the modules are mounted on TS 32, TS 35 x 7.5 or TS 35 x 15 mounting rails.

Weidmuller EG 2 housings — The external shape of these housings corresponds to Type EG 1. Four screw connections or up to eight 0.8 x 6.3 mm / 0.8 x 2.8 mm tab connectors are connected with a printed circuit board in the housing. They can be mounted on TS 32, TS 35 x 7.5 or TS 35 x 15 mounting rails.

Weidmuller EG 3 housings provide six screw connections or twelve 0.8 x 6.3 mm / 0.8 x 2.8 mm tab connections on a width of 22.5 mm. As an accessory, Weidmuller offers a speed printed circuit board with a 2.54 mm hole pitch or fully copper-coated. The engageable combination foot allows the terminals to be mounted on TS 32, TS 35 x 7.5 or TS 35 x 15 mounting rails. The MPL mounting plate is used to mount the housing directly (without mounting rail). Due to the sliding foot construction, the EG 3 can be turned through 180° in all types of assembly (e.g. exchanging input and output).

Weidmuller EG 4 housing, like Type EG 3, offers a width of 22.5 mm. However, the greater installation depth (75 mm) and height (109 mm) allow the installation of more complex circuit configurations. The installed circuit can be connected via six screw connections.

The engageable combination foot allows the terminals to be mounted on TS 32, TS 35 x 7.5 or TS 35 x 15 mounting rails. Due to the sliding foot construction, the EG 4 can be slid 6 mm forwards or backwards on the engaging foot and can be turned through 180° (e.g. exchanging input and output).

Weidmuller EG 5 housings — The external dimensions of these housings correspond to Type EG 4. The EG 5 has twelve screw connections which can be wired with solder lugs inside the housing. The engageable combination foot allows the terminals to be mounted on TS 32, TS 35 x 7.5 or TS 35 x 15 mounting rails. Due to the sliding foot construction, the EG 4 can be slid 6 mm forwards or backwards on the engaging foot and can be turned through 180° (e.g. exchanging input and output).

Weidmuller RS 70 individual parts for rail mounting — The end sections can be engaged to form units up to 20 mm wide. Any desired intermediate spacers or feet can be connected between two side pieces (fixing feet) at intervals of 5 mm. In this way, a carrier module is constructed for a printed circuit board on which various components can be soldered. The module snaps onto TS 32, TS 35 x 7.5 or TS 35 x 15 mounting rails.

Weidmuller rail-mounted profiles — The RS 45, RS 80 and RS 100 profiles are available as 2 m long strips. The extruded profiles can be easily cut to any length with a saw. In this way, a carrier module is constructed for a printed circuit board on which various components can be soldered. The fixing feet can be slid into these profiles for mounting on TS 32, TS 35 x 7.5 or TS 35 x 15 mounting rails. The sliding foot construction of the RS 80 also allows the fixing foot to be turned through 180°.


The Wavebox is characterized by:

- Optimal width for any application (12.5 mm, 17.5 mm, 22.5 mm, 45 mm)
- Large component assembly
- UL94 Flammability class V2
- No tools required for assembly
- Plug-in printed circuit board
- Plug-in cross-connection via ZQV 2.5 N
- Hinged, transparent cover
- BLZ 5.08 screw/plug and socket connector
- BLZF 5.08 optional tension clamp/plug and socket connector
- Marking option with WS tags
- Suitable for snap-fitting on TS 35

Modular Terminals

Dimensions			
Terminal width (+ 0.2 assembly tolerance)			
Insulation stripping length			
Connection Data			
Screw connection, solid strand			
Screw connection, flexible strand			
Conductor cross-section			
VDE rated Data			
Rated wire size			
Rated voltage			
Rated current			
Power loss			
Connection diagram			
Ordering Data			
Modular terminal used to widen component area	For TS 32		Type
			Part No.
	For TS 35		Type
			Part No.
Contour frame used to widen component area (6 mm width)	For TS 32		Type
			Part No.
	For TS 35		Type
			Part No.
Accessories			
Mounting rail (2 m long)			
End bracket (thickness mm)	For TS 32 For TS 35		
End plate (thickness mm)			
Small partition			
Socket for test plug			
Test plug (pin diameter)			
Jumpers (preassembled)	2-pole 3-pole 4-pole 10-pole		
Switchable jumper bracket			
Connection sleeve			
Screw			
Cover plate (4 terminals)			
Screw (plastic)			
Jumper bridge			

DK 4



DKT 4



WDK 2.5



WDK 2.5 F



WDK 2.5 FF



DK 4		DKT 4		WDK 2.5		WDK 2.5 F		WDK 2.5 FF	
6 mm		6 mm		5 mm	5 mm	5 mm		5 mm	
9 mm		9 mm		10 mm	10 mm	10 mm		–	
0.5...4 mm²		0.5...4 mm²		0.5...4 mm²	0.5...4 mm²	0.5...4 mm²			
0.5...4 mm²		0.5...4 mm²		0.5...2.5 mm²	0.5...2.5 mm²	0.5...2.5 mm²			
AWG #22...12		AWG #22...17		AWG #26...4	AWG #26...4	AWG #26...4			
4 mm²		4 mm²		2.5 mm²		2.5 mm²		1 mm²	
380 VAC		380 VAC		380 VAC		380 VAC		380 VAC	
10 A		10 A		26 A		12 A (2 x 6A)		12 A (2 x 6 A)	
0.5 W		0.5 W		0.5 W		0.5 W		0.5 W	
DK 4 PA 204988	DK 4 PA 111546	DKT 4 PA 68736	DKT 4 PA 111566						
DK 4/35 PA 202684	DK 4/35 PA 111556	DKT 4 /35 PA 68746	DKT 4/35 PA 111576	WDK 2.5 102320	WDK 2.5 102310	WDK 2.5 F 102160	WDK 2.5 FF 102170		
DK 4 RA 69096	DK 4 RA 69096								
DK 4 RA/35 69106	DK 4 RA/35 69106								
Type	Part No.	Type	Part No.	Type	Part No.	Type	Part No.	Type	Part No.
TS 32	12280	TS 32	12280	TS 35 x 7.5	38340	TS 35 x 7.5	38340	TS 35 x 7.5	38340
TS 35 x 7.5	38340	TS 35 x 7.5	38340	Slotted	51450	Slotted	51450	Slotted	51450
TS 35 x 15	49800	TS 35 x 15	49800	TS 35 x 15	49800	TS 35 x 15	49800	TS 35 x 15	49800
EWK 1 (8.5)	20616	EWK 1 (8.5)	20616						
EW 35 (8.5)	38356	EW 35 (8.5)	38356	EW 35 (8.5)	38356	EW 35 (8.5)	38356	EW 35 (8.5)	38356
AP PA (1.5)	35926	AP PA (1.5)	68756	WAP	105910	WAP	105910	WAP	105910
TSch 4	36336	TSch 4	36336						
StB 8.5	21570								
PS (ø 2.3)	18040								
Q 2	33640			WQV 2.5	105366	WQV 2.5	105366	WQV 2.5	105366
Q 3	33650			WQV 2.5	105376	WQV 2.5	105376	WQV 2.5	105376
Q 4	33660			WQV 2.5	105386	WQV 2.5	105386	WQV 2.5	105386
Q 10	36860			WQV 2.5	105446	WQV 2.5	105446	WQV 2.5	105446
VL 2	44670								
VH 10	44660								
BS M 2.5 x 14	26680								
AD 4	30340								
BSK M 2.5 x 18	30330								
QB 2*	48270	QB 2*	48270						
QB 3*	48280	QB 3*	48280						
QB 4*	48290	QB 4*	48290						
QB 75 bare*	52640	QB 75 blank*	52640						
Insulation prof.	52670	Insulation prof.	52670						

*When using QB: conductor connection = max. 2.5 mm²

PART NUMBER SELECTION TABLES

Weidmüller

WDK...N
for electronic components

390



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.