

Document Title**4Mx16 bit Page Mode Uni-Transistor Random Access Memory****Revision History**

<u>Revision No.</u>	<u>History</u>	<u>Draft Date</u>	<u>Remark</u>
0.0	Initial Draft - Design Target	November 3, 2004	Preliminary
1.0	Finalize	April 06, 2005	Final

The attached datasheets are provided by SAMSUNG Electronics. SAMSUNG Electronics CO., LTD. reserve the right to change the specifications and products. SAMSUNG Electronics will answer to your questions about device. If you have any questions, please contact the SAMSUNG branch offices.

4M x 16 bit Page Mode Uni-Transistor CMOS RAM**FEATURES**



- Process Technology: CMOS
- Organization: 4M x16 bit
- Power Supply Voltage: 1.7~2.0V
- Three State Outputs
- Compatible with Low Power SRAM
- Support 4 page read mode
- Package Type: TBD

GENERAL DESCRIPTION

The K1S6416BCC is fabricated by SAMSUNG's advanced CMOS technology using one transistor memory cell. The device supports 4 page read operation and Industrial temperature range. The device supports dual chip selection for user interface. The device also supports internal Temperature Compensated Self Refresh mode for the standby power saving at room temperature range.

PRODUCT FAMILY

Product Family	Operating Temp.	Vcc Range	Speed (trc)	Power Dissipation		PKG Type
				Standby (Isb1, Max.)	Operating (Icc2, Max.)	
K1S6416BCC-I	Industrial(-40~85°C)	1.7~2.0V	70ns	120μA(< 40°C)	40mA	TBD
				180μA(< 85°C)		

PIN DESCRIPTION**FUNCTIONAL BLOCK DIAGRAM**

Name	Function	Name	Function
$\overline{CS1}, CS2$	Chip Select Inputs	Vcc/VccQ ²⁾	Power Supply(core / I/O)
$\overline{OE}$	Output Enable Input	Vss	Ground
$\overline{WE}$	Write Enable Input	$\overline{UB}$	Upper Byte(I/O9~16)
A0~A21	Address Inputs	$\overline{LB}$	Lower Byte(I/O1~8)
I/O1~I/O16	Data Inputs/Outputs	NC	No Connection ¹⁾


1) Reserved for future use

2) Vcc and VccQ should be the same level


SAMSUNG ELECTRONICS CO., LTD. reserves the right to change products and specifications without notice.

POWER UP SEQUENCE

1. Apply power.
2. Maintain stable power (V_{CC} min. and V_{CCQ} min.=1.7V) for a minimum 200 μ s with $\overline{CS1}$ =high.or $CS2$ =low.

TIMING WAVEFORM OF POWER UP(1) ($\overline{CS1}$ controlled)**POWER UP(1)**

1. After V_{CC} reaches $V_{CC}(\text{Min.})$ and $V_{CCQ}(\text{Min.})$, wait 200 μ s with $\overline{CS1}$ high. Then the device gets into the normal operation.

TIMING WAVEFORM OF POWER UP(2) ($CS2$ controlled)**POWER UP(2)**

1. After V_{CC} reaches $V_{CC}(\text{Min.})$ and $V_{CCQ}(\text{Min.})$, wait 200 μ s with $CS2$ low. Then the device gets into the normal operation.

FUNCTIONAL DESCRIPTION

$\overline{\text{CS1}}$	CS2	$\overline{\text{OE}}$	$\overline{\text{WE}}$	$\overline{\text{LB}}$	$\overline{\text{UB}}$	I/O1~8	I/O9~16	Mode	Power
H	X ¹⁾	X ¹⁾	X ¹⁾	X ¹⁾	X ¹⁾	High-Z	High-Z	Deselected	Standby
X ¹⁾	L	X ¹⁾	X ¹⁾	X ¹⁾	X ¹⁾	High-Z	High-Z	Deselected	Standby
X ¹⁾	X ¹⁾	X ¹⁾	X ¹⁾	H	H	High-Z	High-Z	Deselected	Standby
L	H	H	H	L	X ¹⁾	High-Z	High-Z	Output Disabled	Active
L	H	H	H	X ¹⁾	L	High-Z	High-Z	Output Disabled	Active
L	H	L	H	L	H	Dout	High-Z	Lower Byte Read	Active
L	H	L	H	H	L	High-Z	Dout	Upper Byte Read	Active
L	H	L	H	L	L	Dout	Dout	Word Read	Active
L	H	X ¹⁾	L	L	H	Din	High-Z	Lower Byte Write	Active
L	H	X ¹⁾	L	H	L	High-Z	Din	Upper Byte Write	Active
L	H	X ¹⁾	L	L	L	Din	Din	Word Write	Active

1. X means don't care.(Must be low or high state)

ABSOLUTE MAXIMUM RATINGS¹⁾

Item	Symbol	Ratings	Unit
Voltage on any pin relative to Vss	V _{IN} , V _{OUT}	-0.2 to V _{CCQ} +0.3V	V
Voltage on Vcc supply relative to Vss	V _{CC}	-0.2 to 2.5V	V
Power Dissipation	P _D	1.0	W
Storage temperature	T _{STG}	-65 to 150	°C
Operating Temperature	T _A	-40 to 85	°C

1. Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. Functional operation should be restricted to be used under recommended operating condition. Exposure to absolute maximum rating conditions longer than 1 second may affect reliability.

PRODUCT LIST

Industrial Temperature Product(-40~85°C)	
Part Name	Function
K1S6416BCC	70ns, 1.85V

RECOMMENDED DC OPERATING CONDITIONS¹⁾

Item	Symbol	Min	Typ	Max	Unit
Supply voltage	V _{CC}	1.7	1.85	2.0	V
Ground	V _{SS}	0	0	0	V
Input high voltage	V _{IH}	0.8 x V _{CCQ}	-	V _{CCQ} +0.2 ²⁾	V
Input low voltage	V _{IL}	-0.2 ³⁾	-	0.4	V

1. T_A=-40 to 85°C, otherwise specified.

2. Overshoot: V_{CCQ}+1.0V in case of pulse width ≤20ns.

3. Undershoot: -1.0V in case of pulse width ≤20ns.

4. Overshoot and undershoot are sampled, not 100% tested.

CAPACITANCE¹⁾(f=1MHz, T_A=25°C)

Item	Symbol	Test Condition	Min	Max	Unit
Input capacitance	C _{IN}	V _{IN} =0V	-	8	pF
Input/Output capacitance	C _{IO}	V _{IO} =0V	-	10	pF

1. Capacitance is sampled, not 100% tested.

DC AND OPERATING CHARACTERISTICS


Item	Symbol	Test Conditions		Min	Typ	Max	Unit
Input leakage current	I _{LI}	V _{IN} =V _{SS} to V _{CCQ}		-1	-	1	μA
Output leakage current	I _{LO}	$\overline{CS1}=V_{IH}$ or $CS2=V_{IL}$ or $\overline{OE}=V_{IH}$ or $\overline{WE}=V_{IL}$ or $\overline{LB}=\overline{UB}=V_{IH}$, V _{IO} =V _{SS} to V _{CCQ}		-1	-	1	μA
Average operating current	I _{CC2}	Cycle time=t _{RC} +3t _{PC} , I _{IO} =0mA, 100% duty, $\overline{CS1}=V_{IL}$, $CS2=V_{IH}$, $\overline{LB}=V_{IL}$ or/and $\overline{UB}=V_{IL}$, V _{IN} =V _{IH} or V _{IL}		-	-	40	mA
Output low voltage	V _{OL}	I _{OL} =0.1mA		-	-	0.2	V
Output high voltage	V _{OH}	I _{OH} =-0.1mA		1.4	-	-	V
Standby Current(CMOS)	I _{SB1} ¹⁾	Other inputs=0-V _{CCQ} 1) $\overline{CS1} \geq V_{CCQ}-0.2V$, $CS2 \geq V_{CCQ}-0.2V$ ($\overline{CS1}$ controlled) or 2) $0V \leq CS2 \leq 0.2V$ ($CS2$ controlled)	< 40°C	-	-	120	μA
			< 85°C	-	-	180	μA

1. Standby mode is supposed to be set up after at least one active operation.after power up.

I_{SB1} is measured after 60ms from the time when standby mode is set up.

AC OPERATING CONDITIONS**TEST CONDITIONS**(Test Load and Test Input/Output Reference)Input pulse level: 0.2 to V_{CCQ} -0.2V

Input rising and falling time: 3ns

Input and output reference voltage: 0.5 x V_{CCQ} Output load (See right): $C_L=30pF$ **AC Output Load Circuit****AC CHARACTERISTICS** ($V_{CC}=V_{CCQ}=1.7\sim 2.0V$, $T_A=-40$ to $85^{\circ}C$)



Parameter List		Symbol	Speed Bins		Units
			70ns		
			Min	Max	
Common	$\overline{CS}$ High Pulse Width	tCSHP	10	-	ns
Read	Address Access Time	tAA	-	70	ns
	Chip Select to Output	tCO	-	70	ns
	Output Enable to Valid Output	tOE	-	35	ns
	$\overline{UB}$, $\overline{LB}$ Access Time	tBA	-	70	ns
	Chip Select to Low-Z Output	tLZ	10	-	ns
	$\overline{UB}$, $\overline{LB}$ Enable to Low-Z Output	tBLZ	10	-	ns
	Output Enable to Low-Z Output	tOLZ	5	-	ns
	Chip Disable to High-Z Output	tHZ	0	25	ns
	$\overline{UB}$, $\overline{LB}$ Disable to High-Z Output	tBHZ	0	25	ns
	Output Disable to High-Z Output	tOHZ	0	25	ns
	Output Hold from Address Change	tOH	3	-	ns
	Page Cycle	tPC	25	-	ns
	Page Access Time	tPA	-	20	ns
	Write	Write Cycle Time	tWC	70	-
Chip Select to End of Write		tCW	60	-	ns
Address Set-up Time		tAS	0	-	ns
Address Valid to End of Write		tAW	60	-	ns
$\overline{UB}$, $\overline{LB}$ Valid to End of Write		tBW	60	-	ns
Write Pulse Width		tWP	55 ¹⁾	-	ns
$\overline{WE}$ High Pulse Width		tWHP	5	-	ns
Write Recovery Time		tWR	0	-	ns
Write to Output High-Z		tWHZ	0	25	ns
Data to Write Time Overlap		tdW	30	-	ns
Data Hold from Write Time		tdH	0	-	ns
End Write to Output Low-Z		tOW	5	-	ns



1. tWP(min)=70ns for continuous write operation over 50 times.

TIMING WAVEFORM OF READ CYCLE(1)(Address Controlled, $\overline{CS1}=\overline{OE}=V_{IL}$, $CS2=\overline{WE}=V_{IH}$, $\overline{UB}$ or/and $\overline{LB}=V_{IL}$)



1. tHZ and tOHZ are defined as the time at which the outputs achieve the open circuit conditions and are not referenced to output voltage levels.
2. At any given temperature and voltage condition, tHZ(Max.) is less than tLZ(Min.) both for a given device and from device to device interconnection.
3. tOE(max) is met only when $\overline{\text{OE}}$ becomes enabled after tAA(max).
4. If invalid address signals shorter than min. tRC are continuously repeated for over 4 μ s, the device needs a normal read timing(tRC) or needs to sustain standby state for min. tRC at least once in every 4 μ s.

TIMING WAVEFORM OF WRITE CYCLE(1) ($\overline{WE}$ Controlled)TIMING WAVEFORM OF WRITE CYCLE(2) ($\overline{CS1}$ Controlled)

TIMING WAVEFORM OF WRITE CYCLE(3) (CS₂ Controlled)TIMING WAVEFORM OF WRITE CYCLE(4) ($\overline{UB}$, $\overline{LB}$ Controlled)

NOTES (WRITE CYCLE)

1. A write occurs during the overlap(t_{WP}) of low $\overline{CS1}$ and low $\overline{WE}$. A write begins when $\overline{CS1}$ goes low and $\overline{WE}$ goes low with asserting $\overline{UB}$ or $\overline{LB}$ for single byte operation or simultaneously asserting $\overline{UB}$ and $\overline{LB}$ for double byte operation. A write ends at the earliest transition when $\overline{CS1}$ goes high and $\overline{WE}$ goes high. The t_{WP} is measured from the beginning of write to the end of write.
2. t_{CW} is measured from the $\overline{CS1}$ going low to the end of write.
3. t_{AS} is measured from the address valid to the beginning of write.
4. t_{WR} is measured from the end of write to the address change. t_{WR} is applied in case a write ends with $\overline{CS1}$ or $\overline{WE}$ going high.

PACKAGE DIMENSION

TBD



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.