

3M

Specialty Bagged Terminals

Effective and reliable for use in the assembly and maintenance of electrical systems in various market applications



3M has been a leading supplier of terminals for more than 30 years. Our satisfied customers know our products for


- Effective and reliable performance, being UL Listed and CSA Certified, where appropriate;
- A wide variety of types, sizes and materials meeting a broad application range, as well as the demands of temperature and weather.

- Design features that assure the easy installation of 3M products—positive and easy wire insertion, elimination of strand hang-ups and wire twisting, and easy insulation entry.

These are just a few of the characteristics that make the installer's job easier!


Nylon Insulated Closed End Connectors (SF) (UL)

| UPC/Product # (054007) | Description | Wire Range (AWG) | Qty/Bag |
|---------------------------|-------------|---------------------|---------|
| 94813 | 722N | 22-14 | 50 |
| 94796 | 718N | 18-10 | 50 |




Heat Shrink Seamless Butt Connectors (SF) (UL)

| UPC/Product # (054007) | Description | Wire Range (AWG) | Qty/Bag |
|---------------------------|-------------|------------------|---------|
| 94861 | MH18BCX | 22-18 | 25 |
| 94857 | MH14BCX | 16-14 | 25 |
| 94850 | MH10BCX | 12-10 | 25 |




Nylon Insulated Seamless Butt Connectors (SF) (UL)

| UPC/Product # (054007) | Description | Wire Range (AWG) | Qty/Bag |
|---------------------------|-------------|------------------|---------|
| 94786 | 61-SN | 22-18 | 100 |
| 94789 | 62-SN | 16-14 | 100 |
| 94792 | 63-SN | 12-10 | 50 |




Nylon Insulated with Insulation Grip Butt Connectors (SF) (UL)

| UPC/Product # (054007) | Description | Wire Range (AWG) | Qty/Bag |
|---------------------------|-------------|------------------|---------|
| 94784 | 61-NB | 22-18 | 100 |
| 94787 | 62-NB | 16-14 | 100 |
| 94790 | 63-NB | 12-10 | 50 |




Vinyl Insulated Brazed Seam Butt Connectors (SF) (UL)

| UPC/Product # (054007) | Description | Wire Range (AWG) | Qty/Bag |
|---------------------------|-------------|------------------|---------|
| 94793 | 64-WP | 8 | 25 |
| 94794 | 65-WP | 6 | 25 |
| 94795 | 66-WP | 4 | 15 |




Vinyl Insulated Butted Seam Butt Connectors (SF) (UL)

| UPC/Product # (054007) | Description | Wire Range (AWG) | Qty/Bag |
|---------------------------|-------------|------------------|---------|
| 94785 | 61-P | 22-18 | 100 |
| 94788 | 62-P | 16-14 | 100 |
| 94791 | 63-P | 12-10 | 50 |




Vinyl Insulated Butted Seam Female Disconnects (SF) (UL)

| UPC/Product # (054007) | Description | Wire Range (AWG) | Male Tab Width (W) x Thickness | Qty/Bag |
|---------------------------|--------------|---------------------|-----------------------------------|---------|
| 94800 | 71F-187-20-P | 22-18 | 0.187 x 0.020 | 100 |
| 94804 | 71F-250-32-P | 22-18 | 0.250 x 0.032 | 100 |
| 94817 | 72F-187-20-P | 16-14 | 0.187 x 0.020 | 100 |
| 94821 | 72F-250-32-P | 16-14 | 0.250 x 0.032 | 100 |
| 94833 | 73F-250-32-P | 12-10 | 0.250 x 0.032 | 50 |




Nylon Insulated with Insulation Grip Female Disconnects 

| UPC/Product # (054007) | Description | Wire Range (AWG) | Male Tab Width (W) x Thickness | Qty/Bag |
|------------------------|---------------|------------------|--------------------------------|---------|
| 94797 | 71F-187-20-NB | 22-18 | 0.187 x 0.020 | 100 |
| 94801 | 71F-250-32-NB | 22-18 | 0.250 x 0.032 | 100 |
| 94814 | 72F-187-20-NB | 16-14 | 0.187 x 0.020 | 100 |
| 94818 | 72F-250-32-NB | 16-14 | 0.250 x 0.032 | 100 |
| 94830 | 73F-250-32-NB | 12-10 | 0.187 x 0.020 | 50 |




Fully Nylon Insulated Butted Seam Female Disconnects 

| UPC/Product # (054007) | Description | Wire Range (AWG) | Male Tab Width (W) x Thickness | Qty/Bag |
|------------------------|---------------|------------------|--------------------------------|---------|
| 94799 | 71F-187-20-NL | 22-18 | 0.187 x 0.020 | 100 |
| 94803 | 71F-250-32-NL | 22-18 | 0.250 x 0.032 | 100 |
| 94816 | 72F-187-20-NL | 16-14 | 0.187 x 0.020 | 100 |
| 94820 | 72F-250-32-NL | 16-14 | 0.250 x 0.032 | 100 |
| 94832 | 73F-250-32-NL | 12-10 | 0.250 x 0.032 | 50 |




Fully Nylon Insulated with Insulation Grip Female Disconnects 

| UPC/Product # (054007) | Description | Wire Range (AWG) | Male Tab Width (W) x Thickness | Qty/Bag |
|------------------------|----------------|------------------|--------------------------------|---------|
| 94798 | 71F-187-20-NBL | 22-18 | 0.187 x 0.020 | 100 |
| 94802 | 71F-250-32-NBL | 22-18 | 0.250 x 0.032 | 100 |
| 94815 | 72F-187-20-NBL | 16-14 | 0.187 x 0.020 | 100 |
| 94819 | 72F-250-32-NBL | 16-14 | 0.250 x 0.032 | 100 |
| 94831 | 73F-250-32-NBL | 12-10 | 0.250 x 0.032 | 50 |




Nylon Insulated Butted Seam Bullet Style Female Disconnects 

| UPC/Product # (054007) | Description | Wire Range (AWG) | Male Tab Width (W) | Qty/Bag |
|------------------------|-------------|------------------|--------------------|---------|
| 94842 | 82F-156-NL | 16-14 | 0.156 | 100 |
| 94843 | 82F-180-NL | 16-14 | 0.180 | 100 |




Nylon Insulated with Insulation Grip Bullet Style Female Disconnects 

| UPC/Product # (054007) | Description | Wire Range (AWG) | Qty/Bag |
|------------------------|-------------|------------------|---------|
| 94838 | 81F-156-NBL | 22-18 | 100 |
| 94839 | 81F-180-NBL | 22-18 | 100 |



Vinyl Insulated Butted Seam Male Disconnects 


| UPC/Product # (054007) | Description | Wire Range (AWG) | Male Tab Width (W) x Thickness | Qty/Bag |
|------------------------|--------------|------------------|--------------------------------|---------|
| 94808 | 71M-187-20-P | 22-18 | 0.187 x 0.020 | 100 |
| 94812 | 71M-250-32-P | 22-18 | 0.250 x 0.032 | 100 |
| 94825 | 72M-187-20-P | 16-14 | 0.187 x 0.020 | 100 |
| 94829 | 72M-250-32-P | 16-14 | 0.250 x 0.032 | 100 |
| 94837 | 73M-250-32-P | 12-10 | 0.250 x 0.032 | 50 |



Nylon Insulated with Insulation Grip Male Disconnects




| UPC/Product # (054007) | Description | Wire Range (AWG) | Male Tab Width (W') x Thickness | Qty/Bag |
|---------------------------|---------------|---------------------|------------------------------------|---------|
| 94805 | 71M-187-20-NB | 22-18 | 0.187 x 0.020 | 100 |
| 94809 | 71M-250-32-NB | 22-18 | 0.250 x 0.032 | 100 |
| 94822 | 72M-187-20-NB | 16-14 | 0.187 x 0.020 | 100 |
| 94826 | 72M-250-32-NB | 16-14 | 0.250 x 0.032 | 100 |
| 94834 | 73M-250-32-NB | 12-10 | 0.250 x 0.032 | 50 |



Fully Nylon Insulated Butted Seam Male Disconnects




| UPC/Product # (054007) | Description | Wire Range (AWG) | Male Tab Width (W') x Thickness | Qty/Bag |
|---------------------------|---------------|---------------------|------------------------------------|---------|
| 94807 | 71M-187-20-NL | 22-18 | 0.187 x 0.020 | 100 |
| 94811 | 71M-250-32-NL | 22-18 | 0.250 x 0.032 | 100 |
| 94824 | 72M-187-20-NL | 16-14 | 0.187 x 0.020 | 100 |
| 94828 | 72M-250-32-NL | 16-14 | 0.250 x 0.032 | 100 |
| 94836 | 73M-250-32-NL | 12-10 | 0.250 x 0.032 | 50 |



Fully Nylon Insulated with Insulation Grip Male Disconnects




| UPC/Product # (054007) | Description | Wire Range (AWG) | Male Tab Width (W') x Thickness | Qty/Bag |
|---------------------------|----------------|---------------------|------------------------------------|---------|
| 94806 | 71M-187-20-NBL | 22-18 | 0.187 x 0.020 | 100 |
| 94810 | 71M-250-32-NBL | 22-18 | 0.250 x 0.032 | 100 |
| 94823 | 72M-187-20-NBL | 16-14 | 0.187 x 0.020 | 100 |
| 94827 | 72M-250-32-NBL | 16-14 | 0.250 x 0.032 | 100 |
| 94835 | 73M-250-32-NBL | 12-10 | 0.250 x 0.032 | 50 |



Nylon Insulated with Insulation Grip Bullet Style Male Disconnects




| UPC/Product # (054007) | Description | Wire Range (AWG) | Mating Snap Diameter | Qty/Bag |
|---------------------------|-------------|---------------------|-------------------------|---------|
| 94840 | 81M-156-NB | 22-18 | 0.156 | 100 |
| 94841 | 81M-180-NB | 22-18 | 0.180 | 100 |
| 94844 | 82M-156-NB | 16-14 | 0.156 | 100 |
| 94845 | 82M-180-NB | 16-14 | 0.180 | 100 |



Heat Shrink Brazed Seam Ring Tongue Terminals 22-18 AWG




| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94859 | MH18-6R/L | 22-18 | 6 | 25 |
| 94860 | MH18-8R/L | 22-18 | 8 | 25 |
| 94858 | MH18-10R/L | 22-18 | 10 | 25 |



Heat Shrink Brazed Seam Ring Tongue Terminals 16-14 AWG




| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94855 | MH14-6R/L | 16-14 | 6 | 25 |
| 94856 | MH14-8R/L | 16-14 | 8 | 25 |
| 94851 | MH14-10R/L | 16-14 | 10 | 25 |
| 94852 | MH14-14R/S | 16-14 | 1/4 | 25 |
| 94853 | MH14-38R/S | 16-14 | 3/8 | 25 |




Heat Shrink Brazed Seam Ring Tongue Terminals 12-10 

| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94849 | MH10-8R | 12-10 | 8 | 25 |
| 94846 | MH10-10R | 12-10 | 10 | 25 |
| 94847 | MH10-14R | 12-10 | 1/4 | 25 |
| 94848 | MH10-38R | 12-10 | 3/8 | 25 |




Nylon Insulated Brazed Seam Ring Tongue Terminals 8 AWG 

| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94754 | 14-14S-WN | 8 | 1/4 | 25 |
| 94757 | 14-56-WN | 8 | 5/16 | 25 |
| 94755 | 14-38-WN | 8 | 3/8 | 25 |
| 94756 | 14-500S-WN | 8 | 1/2 | 25 |




Nylon Insulated Brazed Seam Ring Tongue Terminals 6 AWG 

| UPC/Product # (053007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94758 | 15-14S-WN | 6 | 1/4 | 25 |
| 94761 | 15-56-WN | 6 | 5/16 | 25 |
| 94759 | 15-38-WN | 6 | 3/8 | 25 |
| 94760 | 15-500S-WN | 6 | 1/2 | 25 |




Nylon Insulated Brazed Seam Ring Tongue Terminals 4 AWG 


| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94762 | 16-14-WN | 4 | 1/4 | 10 |
| 94765 | 16-56-WN | 4 | 5/16 | 10 |
| 94763 | 16-38-WN | 4 | 3/8 | 10 |
| 94764 | 16-500S-WN | 4 | 1/2 | 10 |




Nylon Insulated with Insulation Grip Ring Tongue Terminals 22-18 AWG 

| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94724 | 11-6S-NB | 22-18 | 6 | 100 |
| 94726 | 11-8-NB | 22-18 | 8 | 100 |
| 94716 | 11-10-NB | 22-18 | 10 | 100 |
| 94718 | 11-14S-NB | 22-18 | 1/4 | 100 |
| 94722 | 11-56S-NB | 22-18 | 5/16 | 100 |
| 94720 | 11-38-NB | 22-18 | 3/8 | 100 |




Nylon Insulated with Insulation Grip Ring Tongue Terminals 16-14 AWG 

| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94737 | 12-8S-NB | 16-14 | 6 | 100 |
| 94738 | 12-8-NB | 16-14 | 8 | 100 |
| 94728 | 12-10-NB | 16-14 | 10 | 100 |
| 94730 | 12-14S-NB | 16-14 | 1/4 | 100 |
| 94734 | 12-56S-NB | 16-14 | 5/16 | 100 |
| 94732 | 12-38-NB | 16-14 | 3/8 | 100 |




Nylon Insulated with Insulation Grip Ring Tongue Terminals 12-10 AWG 

| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94750 | 13-6S-NB | 12-10 | 6 | 50 |
| 94752 | 13-8-NB | 12-10 | 8 | 50 |
| 94740 | 13-10-NB | 12-10 | 10 | 50 |
| 94742 | 13-14S-NB | 12-10 | 1/4 | 50 |
| 94748 | 13-56S-NB | 12-10 | 5/16 | 50 |
| 94744 | 13-38-NB | 12-10 | 3/8 | 50 |
| 94746 | 13-500-NB | 12-10 | 1/2 | 50 |




Vinyl Insulated Butted Seam Ring Tongue Terminals 22-18 AWG 

| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94725 | 11-6S-P | 22-18 | 6 | 100 |
| 94727 | 11-8-P | 22-18 | 8 | 100 |
| 94717 | 11-10-P | 22-18 | 10 | 100 |
| 94719 | 11-14S-P | 22-18 | 1/4 | 100 |
| 94723 | 11-56S-P | 22-18 | 5/16 | 100 |
| 94721 | 11-38-P | 22-18 | 3/8 | 100 |




Vinyl Insulated Butted Seam Ring Tongue Terminals 16-14 AWG 



| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94736 | 12-6-P | 16-14 | 6 | 100 |
| 94739 | 12-8-P | 16-14 | 8 | 100 |
| 94729 | 12-10-P | 16-14 | 10 | 100 |
| 94731 | 12-14S-P | 16-14 | 1/4 | 100 |
| 94735 | 12-56S-P | 16-14 | 5/16 | 100 |
| 94733 | 12-38-P | 16-14 | 3/8 | 100 |




Vinyl Insulated Butted Seam Ring Tongue Terminals 12-10 AWG 

| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94751 | 13-6S-P | 12-10 | 6 | 50 |
| 94753 | 13-8-P | 12-10 | 8 | 50 |
| 94741 | 13-10-P | 12-10 | 10 | 50 |
| 94743 | 13-14S-P | 12-10 | 1/4 | 50 |
| 94749 | 13-56S-P | 12-10 | 5/16 | 50 |
| 94745 | 13-38-P | 12-10 | 3/8 | 50 |
| 94747 | 13-500-P | 12-10 | 1/2 | 50 |




Nylon Insulated with Insulation Grip Locking Fork Terminals 22-18 AWG  

| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94864 | SS-31-6-NB | 22-18 | 6 | 100 |
| 94866 | SS-31-8-NB | 22-18 | 8 | 100 |
| 94862 | SS-31-10-NB | 22-18 | 10 | 100 |




Nylon Insulated with Insulation Grip Locking Fork Terminals 16-14 AWG  

| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94872 | SS-32-6-NB | 16-14 | 6 | 100 |
| 94874 | SS-32-8-NB | 16-14 | 8 | 100 |
| 94868 | SS-32-10-NB | 16-14 | 10 | 100 |
| 94870 | SS-32-14-NB | 16-14 | 1/4 | 100 |




Nylon Insulated with Insulation Grip Locking Fork Terminals 12-10 AWG  

| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94880 | SS-33-6-NB | 12-10 | 6 | 50 |
| 94882 | SS-33-8-NB | 12-10 | 8 | 50 |
| 94876 | SS-33-10-NB | 12-10 | 10 | 100 |
| 94878 | SS-33-14-NB | 12-10 | 1/4 | 50 |




Vinyl Insulated Butted Seam Locking Fork Terminals 22-18 AWG  

| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94865 | SS-31-6-P | 22-18 | 6 | 100 |
| 94867 | SS-31-8-P | 22-18 | 8 | 100 |
| 94863 | SS-31-10-P | 22-18 | 10 | 100 |




Vinyl Insulated Butted Seam Locking Fork Terminals 16-14 AWG  

| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94873 | SS-32-6-P | 16-14 | 6 | 100 |
| 94875 | SS-32-8-P | 16-14 | 8 | 100 |
| 94869 | SS-32-10-P | 16-14 | 10 | 50 |
| 94871 | SS-32-14-P | 16-14 | 1/4 | 100 |




Vinyl Insulated Butted Seam Locking Fork Terminals 12-10 AWG  

| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94881 | SS-33-6-P | 12-10 | 6 | 50 |
| 94883 | SS-33-8-P | 12-10 | 8 | 50 |
| 94877 | SS-33-10-P | 12-10 | 10 | 50 |
| 94879 | SS-33-14-P | 12-10 | 1/4 | 50 |




Nylon Insulated with Insulation Grip Standard Fork Terminals



| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94768 | 31-6-NB | 22-18 | 6 | 100 |
| 94770 | 31-8-NB | 22-18 | 8 | 100 |
| 94766 | 31-10-NB | 22-18 | 10 | 100 |
| 94774 | 32-6-NB | 16-14 | 6 | 100 |
| 94776 | 32-8-NB | 16-14 | 8 | 100 |
| 94772 | 32-10-NB | 16-14 | 10 | 100 |
| 94780 | 33-6-NB | 12-10 | 6 | 50 |
| 94782 | 33-8-NB | 12-10 | 8 | 50 |
| 94778 | 33-10-NB | 12-10 | 10 | 50 |

Vinyl Insulated Butted Seam Standard Fork Terminals



| UPC/Product # (054007) | Description | Wire Range (AWG) | Stud Size | Qty/Bag |
|---------------------------|-------------|---------------------|-----------|---------|
| 94769 | 31-6-P | 22-18 | 6 | 100 |
| 94771 | 31-8-P | 22-18 | 8 | 100 |
| 94767 | 31-10-P | 22-18 | 10 | 100 |
| 94775 | 32-6-P | 16-14 | 6 | 100 |
| 94777 | 32-8-P | 16-14 | 8 | 100 |
| 94773 | 32-10-P | 16-14 | 10 | 100 |
| 94781 | 33-6-P | 12-10 | 6 | 100 |
| 94783 | 33-8-P | 12-10 | 8 | 100 |
| 94779 | 33-10-P | 12-10 | 10 | 100 |

For more UL information, call 1-800-245-3573.

Important Notice

Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture as of the date of purchase. 3M MAKES NO OTHER WARRANTIES

INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.**



Electrical Products Division

6801 River Place Blvd.
Austin, TX 78726-9000
800 245 3573
Fax 800 245 0329
<http://www.3M.com/electrical/OEM>

Recycled paper
40% pre-consumer
10% post-consumer

Litho in USA.

© 3M IPC 2002 80-6016-0024-2



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.