

Features

- High resistance to heat and humidity
- Resistance to mechanical shock and pressure
- Accurate dimensions for automatic surface mounting
- Wide impedance range
- RoHS compliant*

Applications

- Power supply lines
- IC power lines
- Signal lines

MH Series High Current Chip Ferrite Beads

Electrical Specifications

Model Number	Impedance (Ω) at 100 MHz	RDC (mΩ) Max.	IDC (A) Max.
MH4532-700Y	70 ±25 %	30	6.0
MH4532-800Y	80 ±25 %	10	6.0
MH4532-121Y	120 ±25 %	50	3.0
MH4532-131Y	130 ±25 %	40	3.0
MH4532-151Y	150 ±25 %	20	5.0
MH4532-681Y	680 ±25 %	30	4.0
MH4532-132Y	1300 ±25 %	60	3.0
MH4516-600Y	60 ±25 %	10	6.0
MH4516-750Y	75 ±25 %	25	3.0
MH4516-800Y	80 ±25 %	50	3.0
MH4516-102Y	1000 ±25 %	150	1.5
MH3261-190Y	19 ±25 %	40	3.0
MH3261-260Y	26 ±25 %	40	3.0
MH3261-310Y	31 ±25 %	40	3.0
MH3261-500Y	50 ±25 %	25	3.0
MH3261-700Y	70 ±25 %	30	4.0
MH3261-800Y	80 ±25 %	30	4.0
MH3261-900Y	90 ±25 %	40	3.0
MH3261-101Y	100 ±25 %	30	4.0
MH3261-121Y	120 ±25 %	100	2.0
MH3261-151Y	150 ±25 %	100	2.0
MH3261-301Y	300 ±25 %	200	1.0
MH3261-471Y	470 ±25 %	200	1.0
MH3261-501Y	500 ±25 %	40	3.0
MH3261-601Y	600 ±25 %	100	2.0
MH2029-070Y	7 ±25 %	30	3.0
MH2029-100Y	10 ±25 %	10	6.0
MH2029-300Y	30 ±25 %	25	3.0
MH2029-400Y	40 ±25 %	20	5.0
MH2029-600Y	60 ±25 %	20	5.0
MH2029-800Y	80 ±25 %	40	3.0
MH2029-101Y	100 ±25 %	100	2.0
MH2029-121Y	120 ±25 %	100	2.0
MH2029-151Y	150 ±25 %	100	2.0
MH2029-221Y	220 ±25 %	100	2.0
MH2029-301Y	300 ±25 %	200	1.0
MH2029-401Y	400 ±25 %	100	2.0
MH2029-471Y	470 ±25 %	200	1.0
MH2029-601Y	600 ±25 %	200	1.0
MH1608-100Y	10 ±25 %	100	6.0
MH1608-300Y	30 ±25 %	60	3.0
MH1608-600Y	60 ±25 %	40	3.0
MH1608-800Y	80 ±25 %	40	3.0
MH1608-101Y	100 ±25 %	40	3.0
MH1608-121Y	120 ±25 %	100	2.0
MH1608-151Y	150 ±25 %	100	2.0
MH1608-221Y	220 ±25 %	100	2.0
MH1608-301Y	300 ±25 %	200	1.0
MH1608-471Y	470 ±25 %	200	1.0
MH1608-601Y	600 ±25 %	200	1.0

General Specifications

Operating Temperature
.....-55 °C to +125 °C
Storage Temperature
.....-55 °C to +125 °C
Storage Condition
.....+40 °C max. at 70 % RH
Reflow Soldering .. 230 °C, 50 sec. max.
Resistance to Soldering Heat
..... +260 °C, 5 seconds
Rated Current.....Based on max
.....temperature rise of +40 °C
Terminal Strength
(Force "F" applied for 30 seconds)
4532 Series.....1.5 F (Kg)
4516 Series.....1.0 F (Kg)
3261 Series.....1.0 F (Kg)
2029 Series.....0.6 F (Kg)
1608 Series.....0.5 F (Kg)

Materials

Core Material.....Ferrite
Internal Conductor.....Ag or Ag/Pd
Terminal.....Ag/Ni/Sn

*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

Electrical Specifications (continued)

MH 4532- 700Y



MH 4532- 800Y



MH 4532- 121Y



MH 4532- 131Y



MH 4532- 151Y



MH 4532- 681Y



MH 4532- 132Y



MH 4516- 600Y



MH 4516- 750Y



REV. 02/13

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

Electrical Specifications (continued)

MH 4516- 800Y



MH 4516- 101Y



MH 4516- 102Y



MH 3261- 190Y



MH 3261- 260Y



MH 3261- 310Y



MH 3261- 500Y



MH 3261- 700Y



MH 3261- 800Y



Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

Electrical Specifications (continued)

MH 3261- 900Y



MH 3261- 101Y



MH 3261- 121Y



MH 3261- 151Y



MH 3261- 301Y



MH 3261- 471Y



MH 3261- 501Y



MH 3261- 601Y



MH 2029- 070Y



REV. 02/13

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

Electrical Specifications (continued)

MH 2029- 100Y



MH 2029- 300Y



MH 2029 -400Y



MH 2029 -600Y



MH 2029- 800Y



MH 2029- 101Y



MH 2029- 121Y



MH 2029- 151Y



MH 2029- 221Y



Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

Electrical Specifications (continued)

MH 2029- 301Y



MH 2029 -401Y



MH 2029- 471Y



MH 2029- 601Y



MH 1608 -100Y



MH 1608- 300Y



MH 1608 -600Y



MH 1608- 800Y



MH 1608- 101Y



Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

Electrical Specifications (continued)

MH 1608- 121Y



MH 1608- 151Y



MH 1608- 221Y



MH 1608- 301Y



MH 1608- 471Y



MH 1608- 601Y



Equivalent Circuit



Recommended Soldering



Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

MH Series High Current Chip Ferrite Beads

BOURNS®

Product Dimensions



Recommended Land Pattern



Series	A	B	C	D	G	H	I
4532	4.5 ± 0.2 (.177 ± .008)	3.2 ± 0.2 (.126 ± .008)	1.5 ± 0.2 (.059 ± .008)	0.5 ± 0.2 (.020 ± .008)	3.0 (.118)	3.0 (.118)	1.5 (.059)
4516	4.5 ± 0.2 (.177 ± .008)	1.6 ± 0.2 (.063 ± .008)	1.6 ± 0.2 (.063 ± .008)	0.5 ± 0.2 (.020 ± .008)	3.0 (.118)	1.4 (.055)	1.5 (.059)
3261	3.2 ± 0.2 (.126 ± .008)	1.6 ± 0.2 (.063 ± .008)	1.1 ± 0.2 (.043 ± .008)	0.5 ± 0.2 (.020 ± .008)	2.0 (.079)	1.4 (.053)	1.1 (.043)
2029	2.0 ± 0.2 (.079 ± .008)	1.2 ± 0.2 (.047 ± .008)	0.9 ± 0.2 (.035 ± .008)	0.5 ± 0.2 (.020 ± .008)	1.0 (.040)	1.0 (.040)	1.0 (.040)
1608	1.6 ± 0.2 (.063 ± .008)	0.8 ± 0.2 (.031 ± .008)	0.8 ± 0.2 (.031 ± .008)	0.5 ± 0.2 (.020 ± .008)	0.7 (.028)	0.7 (.028)	0.7 (.028)

Reel Dimensions





Series	Pcs. per Reel	Gross Weight (g)	D	E	G	T
4532	1,000	170	12.0 (.472)	8.0 (.315)	14.0 + 0 (.551 + 0)	16.5 (.650)
4516	2,000	180	12.0 (.472)	8.0 (.315)	14.0 + 0 (.551 + 0)	16.5 (.650)
3261	3,000	150	8.0 (.315)	4.0 (.157)	10.0 + 0 (.394 + 0)	12.5 (.492)
2029	4,000	120	8.0 (.315)	4.0 (.157)	10.0 + 0 (.394 + 0)	12.5 (.492)
1608	4,000	90	8.0 (.315)	4.0 (.157)	10.0 + 0 (.394 + 0)	12.5 (.492)

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.