

AX200091 Cable Assemblies - FiberExpress Duplex Patch Cord



For more Information
please call

1-800-Belden1



General Description:

FiberExpress Duplex Patch Cord, ST-ST, SPC-Polish, 3m (9ft 10in), Singlemode, OS2, SM

Usage (Overall)

| | |
|-------------------------------|--|
| Suitable Applications: | Data Centers, Main Equipment Rooms, Telecommunications Rooms and Work Area |
| Related Parts: | FiberExpress Adapter Strips, FiberExpress Manager Modules and FiberExpress Ultra Frames and Cassettes. Workstation Outlets |

Multi Conductor

Physical Characteristics

Overall Cabling

| | |
|---------------------------------|---|
| Overall Cabling Fillers: | Refer to cable Technical Specifications |
|---------------------------------|---|

Overall Diameter

| | |
|----------------------------------|-------------------|
| Overall Nominal Diameter: | 0.118 x 0.236 in. |
|----------------------------------|-------------------|

Physical Characteristics (Connectivity)

Fiber Type

| | |
|--------------------|-----------|
| Fiber Type: | SM, (OS2) |
|--------------------|-----------|

Materials

Materials:

| Description | Type | Material | Color |
|-----------------|------------|------------------|--------|
| Connector end 1 | ST | Metal | |
| Boot end 1 | | Rubber | White |
| Ferrule end 1 | 2.5mm | Zirconia-Ceramic | White |
| Connector end 2 | ST | Metal | |
| Boot end 2 | | Rubber | White |
| Ferrule end 2 | 2.5mm | Zirconia-Ceramic | White |
| Jacket | 3.0 mm Zip | OFNR | Yellow |

Wiring Scheme

| | |
|-----------------------|-----------------|
| Wiring Scheme: | TIA/EIA 568-C.3 |
|-----------------------|-----------------|

Weight

| | |
|----------------|------------|
| Weight: | 0.238 lbs. |
|----------------|------------|

Packaging

| | |
|-------------------|---|
| Packaging: | Individually packaged in a clear plastic bag. |
|-------------------|---|

Mechanical Characteristics (Connectivity)

| | |
|-------------------------------------|----------------|
| Storage Temperature Range: | -40°C To +75°C |
| Operating Temperature Range: | -40°C To +75°C |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|--|----------------------------------|
| UL Rating: | Riser |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2006 |
| MIL Order #39 (China RoHS): | EUP 50 |
| Telecommunications Standards: | TIA 568.C.3 |
| Safety Listing: | ACA, Bi-national Standard Listed |

Suitability

| | |
|------------------------------|-----|
| Suitability - Indoor: | Yes |
|------------------------------|-----|

AX200091 Cable Assemblies - FiberExpress Duplex Patch Cord

Transmission Characteristics (Connectivity)

Notes (Overall)

Product Family

Product List:

| Description | Belden Part Number Multimode - OM1 - 62.5 µm | Belden Part Number Multimode - OM2 - 50 µm | Belden Part Number Multimode - OM3 - 50 µm | Single-mode - OS2 |
|------------------------------------|--|--|--|-------------------|
| Duplex Patch Cord | | | | |
| ST-ST - 2 m (6 ft.) | 70102419 | AX200341 | AX200799 | AX200090 |
| ST-ST - 3 m (10 ft.) | 70102420 | AX200459 | AX200795 | AX200091 |
| ST-ST - 5 m (16 ft.) | 70102447 | AX200413 | AX200800 | AX200092 |
| 568SC-568SC - 2 m (6 ft.) | AX200056 | AX200084 | AX200603 | AX200094 |
| 568SC-568SC - 3 m (10 ft.) | AX200057 | AX200082 | AX200589 | AX200095 |
| 568SC-568SC - 5 m (16 ft.) | AX200058 | AX200280 | AX200624 | AX200096 |
| LC duplex-LC duplex - 2 m (6 ft.) | AX200517 | AX200527 | AX200664 | AX200507 |
| LC duplex-LC duplex - 3 m (10 ft.) | AX200518 | AX200528 | AX200665 | AX200508 |
| LC duplex-LC duplex - 5 m (16 ft.) | AX200519 | AX200529 | AX200666 | AX200509 |
| MTRJ-MTRJ - 2 m (6 ft.) | AX101122 | AX101139 | AX200801 | AX101157 |
| MTRJ-MTRJ - 3 m (10 ft.) | AX101123 | AX101138 | AX200802 | AX101156 |
| MTRJ-MTRJ - 5 m (16 ft.) | AX101125 | AX101137 | AX200803 | AX101155 |
| Hybrid Patch Cord | | | | |
| 568SC-ST - 3 m (10 ft.) | AX200060 | AX200196 | AX200900 | AX200421 |
| LC duplex-ST - 3 m (10 ft.) | AX200699 | AX200695 | AX200809 | AX200698 |
| LC duplex-568SC - 3 m (10 ft.) | AX200580 | AX200581 | AX200668 | AX200667 |
| MTRJ-ST - 3 m (10 ft.) | AX101133 | AX101151 | AX200810 | AX101166 |
| MTRJ-568SC - 3 m (10 ft.) | AX101128 | AX101143 | AX200797 | AX101161 |
| Single-ended (pigtailed) | | | | |
| ST-open - 2 m (6 ft.) | 70100390 | AX200458 | AX200811 | AX200097 |
| SC-open - 2 m (6 ft.) | 70101714 | AX200192 | AX200653 | AX200098 |
| LC-open - 2 m (6 ft.) | AX200657 | AX200658 | AX200660 | AX200659 |
| MTRJ(m)-open - 3 m (10 ft.) | AX101366 | AX101367 | AX200812 | AX101368 |

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|--------|-------|-------------|-------|-------|-----------|
|--------|-------|-------------|-------|-------|-----------|

Revision Number: 0 Revision Date: 05-13-2009

© 2014 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.