




# ADLINK Mini-ITX Boards Infotainment Applications




**ADLINK**  
TECHNOLOGY INC.

[www.adlinktech.com](http://www.adlinktech.com)

## ADLINK Mini-ITX Boards: Smaller form factor for today's compact systems

Industry trends indicate that users require a smaller and lower cost solution for their system requirements. Mini-ITX has a smaller board size and lower keep-out zones to enable a reduced chassis size for systems placed on the user's desk, mounted on a display, or installed in space-restrictive environments.



In addition to deployment in smaller chassis designed around the Mini-ITX form factor, these boards are compatible with ATX and microATX chassis without the need to retool the I/O shield. Mini-ITX boards are ideal for applications in industrial automation, self-service kiosks, and other infotainment driven solutions.

### Flexible, high speed and better connectivity

ADLINK Mini-ITX boards support the latest Intel and AMD processors to deliver a high performance and space-saving platform for a wide array of embedded computing applications. Along with its compact footprint, this product line supports high processing speeds and high-bandwidth network connectivity with PCI Express®-based Gigabit Ethernet. Coupled with ample memory, diverse I/O, storage, and audio interfaces, ADLINK Mini-ITX boards are suitable for multimedia, automation control, and gaming applications requiring a compact, easy-to deploy, and cost-effective mainboard.

#### Rich I/O

- Vertical onboard USB interface

#### Easy Development and Maintenance

- Dual fail-safe BIOS
- BMC onboard
- SEMA and SEMA Cloud support IoT deployment

#### Excellent Graphics Performance

- HDMI
- LVDS onboard
- Multi DisplayPort
- PCIe slot for external graphics

#### Others

- SATADOM support
- +5VDC DC/DC converter
- TPM onboard
- ATX or 12VDC-only power input

## SEMA Cloud IoT Solution based on ADLINK Mini-ITX Platform


### SEMA - Intelligent Middleware to Monitor your Device



Today's Embedded PC Systems need to provide both optimal performance and low power consumption. This can be difficult to accomplish without adequate control and system management tools to detect potential problems before they get out of hand. To meet these requirements, a tool is needed which is able to monitor and gather performance and status necessary information from the hardware in a timely, flexible and precise manner. ADLINK's Smart Embedded Management Agent (SEMA) accomplishes these goals for you, the developer and end user.

Time-to-Market (TTM) and Total-Costs-of-Ownership (TCO) are key aspects to producing competitive products. To combine TTM and TCO in a reliable manner, a solid and reliable platform is fundamental. To assist in this endeavor, every new ADLINK computer-on-module (COM) is equipped with a Board Management Controller (BMC) device supporting SEMA.

Initially designed for power sequencing tasks, the BMC has evolved to include many new and useful features through the years. Measuring the supply current to get a snapshot of the system's power consumption is only one of the new capabilities. Being compatible with the latest Embedded Application Programming Interface specification (EAPI) reduces your effort to port existing calls to SEMA to nearly zero!



Interfacing the hardware to the operating system is one of SEMA's most important functions. The BMC first collects all relevant information from the chipset and other sources. Using the System Management Bus driver, the application layer fetches the data and presents it to the user.

## An Intelligent Cloud Solution for Remote Monitoring, Management and Control


### Configure, Control and Manage - Anywhere, Anytime




ADLINK's SEMA Cloud takes today's intelligent middleware a step further than previous generations of remote management technology. By employing cloud server architecture and a machine-to-machine (M2M) stack on top of the intelligent middleware, embedded devices can be connected to the cloud without additional design requirements. ADLINK's SEMA Cloud solution provides the entire infrastructure, from gathering local data on the device and pushing it securely to the cloud, to the cloud server which stores and processes the data, to the user interface that lets operators remotely monitor, control and configure devices. With SEMA Cloud, users can remotely access power supply voltage, CPU temperature, fan rotation speed and other critical data to push data to the cloud. It enables operators to verify, monitor and manage system performance from a single, central location – improving reliability and reducing management costs.

ADLINK's SEMA Cloud solution provides customers with a one-stop shopping model for bringing device data into the cloud rapidly and effectively. ADLINK offers all parts of a cloud solution:

- Client application for fetching and pushing data to the cloud
- Cloud server infrastructure for hosting and processing data
- End application to monitor, control and configure devices








## Infotainment Applications in Retail, Medical and Digital Signage

ADLINK Infotainment solution for Gaming and Retail services include ATMs, floor plan guides, lottery & slot machines and supermarket self-service kiosks. ADLINK Mini-ITX industrial motherboards provide flexible connection possibilities for system integrators to link and manage multiple peripherals to meet application needs. Video lottery terminal and slot machines must sustain continuous operation; thus, hardware stability and ease of maintenance become essential. ADLINK extensive experience and capabilities in hardware design and software development combined with our self-owned manufacturing base allows us to provide reliable products of superior quality for different solutions.

In the retail environment, multimedia digital signage that combines entertainment and information is one of the best ways to communicate with consumers. Intelligent display panels powered by ADLINK Mini-ITX motherboards can be installed above checkout counters or in other suitable locations. Supermarket self-service kiosks are stand-alone terminals which integrate environment information, promotional products, membership management and other relevant data through interactive multimedia communication.

Medical environments require highly accurate video images with low latency during surgical procedures, such as X-ray, ultrasound, and endoscopy. This market presents diverse opportunities for embedded designers, fueled by demand for real-time data processing and sharing, high definition imaging and graphics displays, and creative, compact solutions that enable healthcare anywhere. ADLINK expertly solves these medical design challenges, offering intelligent embedded platforms that help OEMs/ODMs innovate, reduce risk and accelerate time-to-market with solutions validated for high performance and complex regulatory requirements. For medical device developers and manufacturers, ADLINK is your complete supplier of Mini-ITX industrial motherboards that provide robust, fault-free connectivity, as well as the wide range of high-speed I/O required to support the broad and growing spectrum of imaging and diagnostics applications. Development time is reduced, and medical device manufacturers can focus on their core competencies in creating competitive, high performance healthcare applications.

## Mini-ITX Applications

	Retail	Medical	Digital Signage
			
Requirements	<ul style="list-style-type: none"> <li>• TTM</li> <li>• Processing performance</li> </ul>	<ul style="list-style-type: none"> <li>• High performance HD graphics</li> <li>• Quality product and service</li> </ul>	<ul style="list-style-type: none"> <li>• High performance HD graphics</li> <li>• Multi DisplayPort/HDMI/LVDS outputs</li> </ul>
Applications	<ul style="list-style-type: none"> <li>• Kiosk (e.g. ATM, POS)</li> <li>• Vending machine</li> </ul>	<ul style="list-style-type: none"> <li>• Ultrasound</li> <li>• MRI</li> <li>• Point-of-care terminal</li> <li>• Patient's bedside terminal</li> </ul>	<ul style="list-style-type: none"> <li>• Flight information display</li> <li>• Out of home advertising</li> </ul>

## Mini-ITX boards




Product Number	AmITX-BE-G	AmITX-BT-I
CPU	AMD® RX-427BB/425BB/225FB	Intel® Atom™ Processors E3800 series SoC Intel® Celeron® N2930/J1900
Memory	non-ECC 1333/1666 MHz DDR3L memory up to 16 GB	non-ECC 1333/1066 MHz DDR3L memory up to 8 GB
SATA	3x SATA 6.0	2x SATA 3.0
USB	4x USB 3.0 11x USB 2.0	4x USB 3.0 6x USB 2.0
Expansion Slots	1x PCIe x16 1x PCIe x1 1x full size Mini PCIe 1x half size Mini PCIe 1x SPI header for external BIOS	1x PCIe x1 1x Mini-PCIe 1x mSATA
Serial Port	1x RS-232/422/485 3x RS-232	1x RS-232 2x RS-232/422/485 2x RS-232/422/485
Display	AMD® Radeon HD 9000 4 DisplayPort, LVDS	Intel® Gen7 graphics core VGA, HDMI, LVDS
Ethernet	2x GbE	2x GbE
Operating Temperature	0°C to 60°C	0°C to 60°C



Product Number	AmITX-HL-G	AmITX-IB-I
CPU	Intel® Core™ Processors i7-4700S/4770TE, i5-4570S/4570TE, i3-4330/4330TE Pentium® Processors G3420/G3320TE Celeron® Processors G1820/G1820TE	Intel® Xeon® Processors E3-1275v2/1224v2 Intel® Core™ Processors i7-3770, i5-3550S, i3-3220 Intel® Pentium® Processor G2120 Intel® Celeron® G1620
Memory	non-ECC 1333/1666 MHz DDR3L memory up to 16 GB	non-ECC 1333/1066 MHz DDR3L memory up to 16 GB
SATA	3x SATA 6.0	2x SATA 3.0
USB	4x USB 3.0 11x USB 2.0	2x USB3.0 7x USB2.0
Expansion Slots	1x PCIe x16 1x PCIe x1 1x full size Mini PCIe 1x half size Mini PCIe 1x SPI header for external BIOS	1x PCI Express x4 1x Mini-PCIe
Serial Port	1x RS-232/422/485 3x RS-232	5x RS-232 1x RS-232/422/485
Display	Intel® Generation 7.5 3 DisplayPort, LVDS	Intel® HD Graphics VGA, DVI, HDMI, Dual Display VGA+DVI-D, VGA+HDMI, DVI+HDMI
Ethernet	2x GbE	2x GbE
Operating Temperature	0°C to 60°C -40°C to + 85°C (optional)	0°C to 60°C





# Headquarters

## ADLINK Technology, Inc.

9F., No.166, Jian 1st Rd., Zhonghe Dist.,  
New Taipei City 235, Taiwan  
新北市中和區建一路166號9樓  
Tel: +886-2-8226-5877  
Fax: +886-2-8226-5729  
Email: service@adlinktech.com

## Worldwide Offices

### Ampro ADLINK Technology, Inc.

5215 Hellyer Avenue, #110, San Jose, CA 95138, USA  
Tel: +1-408-360-0200  
Toll Free: +1-800-966-5200 (USA only)  
Fax: +1-408-360-0222  
Email: info@adlinktech.com

### ADLINK Technology Singapore Pte. Ltd.

84 Genting Lane #07-02A, Cityneon Design Centre,  
Singapore 349584  
Tel: +65-6844-2261  
Fax: +65-6844-2263  
Email: singapore@adlinktech.com

### ADLINK Technology Singapore Pte. Ltd. (Indian Liaison Office)

#50-56, First Floor, Spearhead Towers  
Margosa Main Road (between 16th/17th Cross),  
Malleswaram, Bangalore - 560 055, India  
Tel: +91-80-65605817, +91-80-42246107  
Fax: +91-80-23464606  
Email: india@adlinktech.com

### ADLINK Technology Japan Corporation

〒101-0045 東京都千代田区神田鍛冶町3-7-4  
神田374ビル4F  
Tel: +81-3-4455-3722  
Fax: +81-3-5209-6013  
Email: japan@adlinktech.com

### ADLINK Technology, Inc. (Korean Liaison Office)

137-881 서울시 서초구 서초대로 326, 802 (서초동, 모인터빌딩)  
Tel: +82-2-2057-0565  
Fax: +82-2-2057-0563  
Email: korea@adlinktech.com

### ADLINK Technology (China) Co., Ltd.

上海市浦东新区张江高科技园区芳春路300号 (201203)  
Tel: +86-21-5132-8988  
Fax: +86-21-5192-3588  
Email: market@adlinktech.com

### ADLINK Technology Beijing

北京市海淀区上地东路1号盈创动力大厦E座801室(100085)  
Tel: +86-10-5885-8666  
Fax: +86-10-5885-8626  
Email: market@adlinktech.com

### ADLINK Technology Shenzhen

深圳市南山区科技园南区高新南七道数字技术园  
A1栋2楼C区 (518057)  
Tel: +86-755-2643-4858  
Fax: +86-755-2664-6353  
Email: market@adlinktech.com

### LiPPERT ADLINK Technology GmbH

Hans-Thoma-Strasse 11, D-68163, Mannheim, Germany  
Tel: +49 621 43214-0  
Fax: +49 621 43214-30  
Email: emea@adlinktech.com

### ADLINK Technology, Inc. (French Liaison Office)

6 allée de Londres, Immeuble Ceylan 91940 Les Ulis, France  
Tel: +33 (0) 1 60 12 35 66  
Fax: +33 (0) 1 60 12 35 66  
Email: france@adlinktech.com

### ADLINK Technology, Inc. (Israeli Liaison Office)

27 Maskit St., Corex Building PO Box 12777 Herzliya 4673300, Israeli  
Tel: +972-54-632-5251  
Fax: +972-77-208-0230  
Email: israel@adlinktech.com



**ADLINK**  
TECHNOLOGY INC.

[www.adlinktech.com](http://www.adlinktech.com)

All products and company names listed are trademarks or trade names of their respective companies.  
All specifications are subject to change without further notice.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.